Canon

Canon imageFORMULA DR-G2110 Sheet-fed scanner 600 x 600 DPI A3 Black, White

Brand : Canon

Product family: imageFORMULA

Product code: 3150C003

Product name : DR-G2110

- Ultra-fast scanner - Up to 220 images per minute
- Highly efficient - 50,000 Scans per day
- Durable - Robust design
- Network connectivity - connect directly to the network via a wired LAN connection
- Capture on touch - Powerful touch with easy operation
- Easy connectivity and integration - ISIS/TWAIN/WIA and KOFAX VRS Drivers enable integration into various scanning applications
- Reliable and versatile feeding - Scan mixed documents together with pages being reliably fed into the scanner
- Energy Efficient - Consume low energy while scanning
- Superior Image quality - Enhanced image processing with Active Thresholding
A3, CIS, 600 dpi, RGB LED, 500 sheets, RJ-45, USB 3.1

Canon imageFORMULA DR-G2110 Sheet-fed scanner 600 x 600 DPI A3 Black, White:

Fast and durable A3 production scanner

Optimised for customers who demand exceptional high-speed productivity, superior image quality and dependable feeding performance, this A3 scanner is robust, simple to use and performs quietly

Scanning	
Maximum scan size *	305 x 432 mm
Optical scanning resolution *	600 x 600 DPI
Colour scanning	✔
Duplex scanning *	✔
ADF scan speed (b/w, A3)	120 ppm
ADF scan speed (colour, A3)	120 ppm
Duplex ADF scan speed (b/w, A4)	240 ipm
Duplex ADF scan speed (colour, A4)	240 ipm

Design	
Scanner type *	Sheet-fed scanner
Product colour *	Black, White
Built-in display *	✔

Performance	
Sensor type *	CIS
Light source	RGB LED
Daily duty cycle (max) *	50000 pages
Scanning noise level	54 dB

Input capacity	
Standard input capacity	500 sheets

Paper handling	
Long-paper mode	✔
Maximum ISO A-series paper size *	A3

Paper handling	
Auto Document Feeder (ADF) media weight	20 - 209 g/m²

Ports & interfaces	
USB port *	✔
USB version	3.2 Gen 2 (3.1 Gen 2)
Standard interfaces	RJ-45, USB 3.2 Gen 1 (3.1 Gen 1)

Network	
Ethernet LAN	✔

Power	
Power supply type *	AC
Power consumption (typical)	66.5 W
Power consumption (standby)	3.5 W
AC input frequency	50 - 60 Hz
Input voltage	220 - 240 V

Weight & dimensions	
Width	480 mm
Depth	569 mm
Height	315 mm
Weight	25 kg

Operational conditions	
Operating temperature (T-T)	10 - 35 °C
Operating relative humidity (H-H)	20 - 80%
Operating temperature (T-T)	50 - 95 °F

Logistics data	
Harmonized System (HS) code	84716070

4528472108216

0013803308938

013803308938

Catalog Object Cloud