

ASUS WS C621E SAGE (BMC) Intel® C621 LGA 3647 (Socket P) EEB

Brand : ASUS

Product code: 90SW0021-M0EAY0


Product name : WS C621E SAGE (BMC)

Intel C621, 12 x DIMM, Max. 768GB, DDR4, EEB, SLI, CrossFireX, SATA III
ASUS WS C621E SAGE (BMC). Processor manufacturer: Intel, Processor socket: LGA 3647 (Socket P), Compatible processor series: Intel® Xeon®. Supported memory types: DDR4-SDRAM, Maximum internal memory: 768 GB, Memory slots type: DIMM. Supported storage drive interfaces: M.2, SATA III, U.2, RAID levels: 0, 1, 5, 10. Parallel processing technology support: 4-Way CrossFireX, 4-Way SLI, Graphics card family: ASPEED, Graphics card: AST2500. Ethernet interface type: Gigabit Ethernet, LAN controller: Intel® I210-AT



Processor		Rear panel I/O ports	
Processor manufacturer *	Intel	USB 2.0 ports quantity *	4
Processor socket *	LGA 3647 (Socket P)	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	4
Compatible processor series *	Intel® Xeon®	USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity *	1
Memory		USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity *	1
Supported memory types *	DDR4-SDRAM	Ethernet LAN (RJ-45) ports *	2
Number of memory slots *	12	PS/2 ports quantity	1
Memory slots type	DIMM	S/PDIF out port	✓
Supported memory clock speeds	2400,2666 MHz	Network	
Maximum internal memory *	768 GB	Ethernet LAN	✓
Storage controllers		Ethernet interface type	Gigabit Ethernet
Supported storage drive interfaces *	M.2, SATA III, U.2	LAN controller	Intel® I210-AT
RAID levels	0, 1, 5, 10	Features	
Graphics		Motherboard chipset *	Intel® C621
Parallel processing technology support *	4-Way CrossFireX, 4-Way SLI	Audio chip	Realtek S1220A
Graphics card family	ASPEED	Audio output channels *	7.1 channels
Graphics card	AST2500	Component for *	PC
Internal I/O		Motherboard form factor *	EEB
USB 2.0 connectors *	1	Motherboard chipset family *	Intel
USB 3.2 Gen 1 (3.1 Gen 1) connectors *	2	Power source type	ATX
Number of SATA III connectors *	10	Expansion slots	
Front panel audio connector	✓	PCI Express x16 (Gen 3.x) slots	7
Number of EATX power connectors	4	Number of M.2 (M) slots	1
CPU fan connector	✓	Logistics data	
Number of chassis fan connectors	7	Harmonized System (HS) code	84733020
Number of COM connectors	1		

Weight & dimensions	
Width	305 mm
Depth	330 mm
Other features	
Supported RDIMM clock speeds	2400,2666 MHz
VGA connectors	1



4712900910377

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.