## **PHILIPS**

## Philips P Line LCD monitor with USB-C Dock 329P9H/00

Brand : Philips Product family: P Line Product code: 329P9H/00

**Product name :** LCD monitor with USB-C Dock 329P9H/00

- P Line
- 32 (31.5"/80 cm diag.)
- 4K UHD (3840 x 2160)

Brilliance 329P9H LCD monitor with USB-C docking

## Philips P Line LCD monitor with USB-C Dock 329P9H/00:

When every detail matters, Philips Brilliance 32" 4K display delivers crisp visuals with accurate color. Convenient features like USB-C docking and a secure pop-up webcam increase your productivity. Philips P Line LCD monitor with USB-C Dock 329P9H/00. Display diagonal: 80 cm (31.5"), Display resolution: 3840 x 2160 pixels, HD type: 4K Ultra HD, Display technology: LED, Response time: 5 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub. VESA mounting, Height adjustment. Product colour: Black





Display		Ergonomics	
Display diagonal * Display resolution * HD type * Native aspect ratio * Display technology * Panel type * Backlight type Touchscreen * Display brightness (typical) Response time * Anti-glare screen	80 cm (31.5") 3840 x 2160 pixels 4K Ultra HD 16:9 LED IPS W-LED  X 350 cd/m² 5 ms	Swivelling Swivel angle range Tilt adjustment Tilt angle range Picture-in-Picture On Screen Display (OSD) On Screen Display (OSD) languages	-175 - 175°  -5 - 25°  Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Screen shape *	Flat	Number of OSD languages	20
Aspect ratio	16:9	Plug and Play	1
Contrast ratio (typical) *	1300:1	LED indicators	Operation, Stand-by
Contrast ratio (dynamic)	50000000:1	Power	
Dynamic contrast ratio marketing name	SmartContrast	Energy efficiency class (SDR) *	G
Maximum refresh rate * Viewing angle, horizontal	60 Hz 178°	Energy consumption (SDR) per 1000 hours *	51 kWh
Viewing angle, vertical	178°	Power consumption (typical) *	33.95 W
Display number of colours *	1.07 billion colours	Power consumption (standby) *	0.5 W
Pixel pitch	0.182 x 0.182 mm	Power consumption (off)	0 W
Pixel density	140 ppi	Power consumption (PowerSave)	30.8 W
Horizontal scan range	30 - 160 kHz	AC input voltage	100 - 240 V
Vertical scan range	23 - 80 Hz	AC input frequency	50 - 60 Hz
Viewable size, horizontal	69.7 cm	Power supply type	Internal
Viewable size, vertical	39.2 cm	Energy efficiency scale	A to G
Digital horizontal frequency Digital vertical frequency	30 - 160 kHz 23 - 80 Hz	European Product Registry for Energy Labelling (EPREL) code	413600

Syn. Con green (SOG)         V         Operating lemperature (T.T.)         0.40 °C           Display dagoral (metric)         80 cm         St07age temperature (T.T.)         -20 °C           DOCCI         V         Operating relative humidity (H+)         20 ·80%           Haze rate         25%         Operating relative humidity (H+)         0 ·3658 m           Solar candines         3H         Non-operating unitude         0 ·21219 m           SOLour gamut standard         6KGB         Weight 6 dimensions         215 mm           SOLOur gamut standard         188%         Depth (with stand)         215 mm           8GG coverage (typical)         90%         Held)(t (with stand)         0 5k mm           Adobe RGB coverage         87%         With (with stand)         10 kg mm           Adobe RGB coverage         87%         With (with stand)         12 mm           Adob RGB coverage         87%         With (with stand)         12 mm           Performance         V         Height (without stand)         12 mm           Performance         Y         Package weight         73 mm           NVIDIA C-SYNC*         X         Package weight         178 mm           Kickerfee setchnology         V         Package weight         178 mm <th>Diamlass</th> <th></th> <th>On a making all and disking a</th> <th></th>	Diamlass		On a making all and disking a	
DSDP All Subgrand (metric)         80 cm         Storage temperature (T-T)         20-60 °C         20-80 °C         24-80 °C	Display (SOC)		Operational conditions	0.40%
DOCICI         25%         Operating relative humidity (H+H)         20 - 80%           Haze rate         25%         Operating slittude         0 - 2129 zm           Surface hardnames         3H         Non-operating slittude         0 - 1219 zm           Colour gamut standard         6RG8         Weight 6 dimensions           SKGE coverage (typical)         90%         Width (with stand)         215 mm           AGDe RGB coverage         87%         Weight (with stand)         10.6 kg           AGD RGB coverage         87%         Weight (with stand)         10.6 kg           AGD RGB coverage         87%         Weight (with stand)         11.6 kg           AGD RGB coverage         87%         Weight (with stand)         11.6 kg           AGD RGB coverage         7         Weight (with stand)         71.5 mm           AGD Spage RGB         7         Package (with 10.6 kg)         72.5 mm           Display SpRGB         7         Package (with 10.6 kg)         72.5 mm           Performance         X         Package (with 10.6 kg)         72.3 kg           Performance         X         Package (with 10.6 kg)         72.3 kg           Performance         X         Package (with 10.6 kg)         72.3 kg         72.5 kg	· ·			
Human   Fate   Package			•	
Surface hardness         2 Miss         Non-operating altitude         0 - 1219 2 m           Colour gamut standard         90%         Weight & dimensions         715 mm           5KGS coverage (typical)         100%         Width (with stand)         715 mm           5KGS coverage (typical)         90%         Height (with stand)         246 mm           NYSC coverage (typical)         90%         Height (with stand)         715 mm           Adobe Rold Coverage         87%         Weight (without stand)         715 mm           Separate HV sync         -         Depth (without stand)         715 mm           Performance         -         Weight (without stand)         715 mm           Performance         -         Package width         733 kg           Performance         -         Package width         73 mm           Pickier-free technology         -         Package width         73 mm           Component video sync         Separate sync, Sync-on-green (SOG)         Package height         73 mm           Cikker-free technology         -         Package width         73 mm           Likker-free technology         -         Package type         80x           Low Bur of Speakers         2         Stand included         - <td>·</td> <td></td> <td></td> <td></td>	·			
Color gamut         90%         Width (with stand)         71.5 mm           AGB coverage (typical)         90%         Bethy (with stand)         24.6 mm           NTSC coverage (typical)         90%         Height (with stand)         10.6 kg           3D         X         Weight (with stand)         10.6 kg           Separate MY syrc         Y         Depth (without stand)         51.5 mm           Display 98GB         Y         Height (without stand)         412 mm           Performance         Weight (without stand)         7.33 kg           Performance         Y         Packaging data           Performance         Y         Package poth         166 mm           Component video sync         Separate sync, sync-on-green         Package petight         167 mm           Cilicker-free technology         Y         Package petight         14.4 kg           Liller Spakers         2         Stand included         Y           Number of spakers         2         Stand included         Y           Built-in spaker(s)         4         Amanual         Y           Very Spaker         4         Amanual         Y           Design         4         Mm         Mm           Built-in spake				0 12132 111
shGB coverage (typical)         108%         Depth (with stand)         246 mm           NTSC coverage (typical)         98%         Height (with stand)         35 mm           Adobe RGE coverage         57%         Width (without stand)         715 mm           3D         X         Width (without stand)         51 mm           Claylay RGB         -         Helpit (without stand)         51 mm           Portranace         -         Package width (without stand)         12 mm           AMD FreeSync*         X         Package width (without stand)         12 mm           AMD FreeSync*         X         Package width         733 mm           AMD FreeSync*         X         Package depth         136 mm           Component video sync         Separate sync, Sync-on-green (SoG)         Package depth         136 mm           Mortineda         -         Package elepith         14 kg           Low Blue Light technology         -         Package elepith         14 kg           William Spackers         2         Package elepith         14 kg           William Spackers         2         Package elepith         14 kg           William Spackers         2         Package elepith         14 kg           William Spackers	•			
NTSC coverage (typical)         90%         Height (with stand)         636 mm           Adobe RGB coverage         87%         Weight (with stand)         1.0 kg           3D         X         Width (without stand)         715 mm           Separate HV sync         Y         Depth (without stand)         41 mm           Display sRGB         Y         Height (without stand)         41 mm           Performance         Weight (without stand)         412 mm           Portionance         Y         Package width         733 kg           WID AG SYNC *         X         Package width         793 mm           AMD FreeSync **         X         Package weight         613 mm           Component video sync         Separate sync, Sync-on-green (SOG)         Package weight         144 kg           Ficker-free technology         Y         Package weight         144 kg           Low Biue Light technology         Y         Package weight         144 kg           Low Biue Light technology         Y         Package weight         144 kg           Number of speakers         2         Stand included         Y           Number of speakers         2         Stand included         Y           Built-in smear         Y <td< td=""><td><del>-</del></td><td></td><td>•</td><td></td></td<>	<del>-</del>		•	
Adobe RGB coverage         87%         Weight (with stand)         10.6 kg           3D         X         Width (without stand)         7.5 mm           Separate HV sync         /         Depth (without stand)         5.1 mm           Display sRGB         /         Height (without stand)         4.2 mm           WorlDIA GSYNC*         X         Packaging data         7.3 3 kg           AMD FreeSync*         X         Package width         7.93 mm           AMD FreeSync*         X         Package depth         1.6 mm           Component video sync         Separate sync, Sync-on-green         Package weight         1.4 kg           Package weight         1.4 kg         7.3 mm           Hull standing         Y         Package weight         1.4 kg           Hull standing         Y         Package weight         1.4 kg           Multimedia         Y         Stand included         W           Multimedia         Y         Stand included         W           Multimedia         Y         Y         W           Multimedia         Y         Y         W           Multimedia         Y         Y         W         W           Sulli-in standing         Y	- · · ·			
3D         X         Wildth (without stand)         715 mm           Separate H/V sync         V         Oepth (without stand)         51 mm           Separate H/V sync         V         Depth (without stand)         51 mm           Displays xRG         V         Height (without stand)         412 mm           Performance         Weight (without stand)         7.33 kg           NVDIA G-SYNC*         X         Package width         793 mm           AMD FreeSync*         X         Package depth         168 mm           Component video sync         Separate sync, Sync-on-green (SOG)         Package weight         168 mm           Flicker-free technology         V         Package weight         168 mm           Low Blue Light technology         V         Package weight         144 kg           Williamedia         V         Package weight         144 kg           Number of speakers         2         Stand included         V           RNS rated power         6 W         Cables included         V           Built-in speaker(s)*         Weep Manual         V           Built-in speaker(s)*         Weep Manual         V           Built-in microphone         V Manual         V           Built-in micropho	• • • • • • • • • • • • • • • • • • • •		<b>3</b> ', ,	
Separate NV sync         4 (months)         5 mm           Display sRGB         4 (months)         41 mm         42 mm           Performance         Weight (without stand)         43 mm         73 mm           MVDIA G-SYNC*         X         Package width         793 mm         793 mm           Component video sync         Separate sync, Sync-on-green         Package depth         166 mm         73 mm           Cilicker-free technology         V         Package weight         14 kg         73 mm           Flicker-free technology         V         Package weight         16 mm         73 mm           Will tembol         V         Package weight         14 kg         70 mm           Will tembol         V         Package weight         14 kg         70 mm           Multimedia         V         Package weight         14 kg         70 mm         70 mm<		×	• •	•
Display sRGB         4.12 mm         4.12 mm         7.3 kg           Performance         Velight (without stand)         7.3 kg         7.3 kg           NVDIA G-SYNC*         X         Package gridth         793 mm           AMD FreeSync*         Separate sync, Sync-on-green (SGG)         Package depth         166 mm         793 mm           Component video sync         Separate sync, Sync-on-green (SGG)         Package height         167 mm         793 mm           Flicker-free technology         ✓         Package height         167 mm         793 mm           Low Blue Light technology         ✓         Package height         14.4 kg           I will many technology         ✓         Package weight         14.4 kg           Number of speakers         2         Stand included         ✓           Number of speakers         2         Stand included         ✓           RNS rated power         6         W         Aunual         ✓           Built-in microphone         2         MP         Aunual         ✓         Many Countril         SmartControl         SmartControl         Mp         Many Countril         Many Countril         Mp         Mp         Mp         Mp         Mp         Mp         Mp         Mp	Separate H/V sync	<b>✓</b>	,	
Performance         Weight (without stand)         7.33 kg           NVIDIA G-SYNC*         X         Packagin data           AMD FreeSync*         X         Package width         793 mm           Component video sync         Separate sync, Sync-on-green (500)         Package depth         166 mm           Flicker-free technology         A         Package weight         144 kg           Low Blue Light technology         A         Package weight         144 kg           Low Blue Light technology         A         Package weight         144 kg           Low Blue Light technology         A         Package weight         144 kg           Low Blue Light technology         A         Package weight         144 kg           Mumber of speakers         2         A         Wall technology         Wall technology           Built micro of speakers         2         As a din cluded         VBR Technology         Wall technology         Yeight (MSP) (USB Type-C, USB Type-C to USB Type-C, USB Type-C, USB Type-C to USB Type-C, USB Type-C to USB Type-C, USB Type-C, USB Type-C to USB Power Delivery revision         A         A Cadapter included         ✓           Freet colour         Black         AC adapter included	•	<b>,</b>		412 mm
NIDIA G-SYNC*	. ,	•	Weight (without stand)	7.33 kg
AMD FreeSync*         X         Package width (Social package depth (Social package depth)         793 mm           Component video sync         Searate sync, Sync-on-green (Social package depth)         673 mm           Flicker-free technology         Y         Package weight         14.4 kg           Low Blue Light technology         Y         Package type         80x           Low Blue Light technology         Y         Packaging content         ************************************			Packaging data	
AMD FreeSpyc.*         X         Package depth         186 mm           Component video sync         Separate sync, Sync-on-green (SOG)         Package height         673 mm           Flicker-free technology         Y         Package weight         14.4 kg           Low Blue Light technology         Y         Package type         80x           Multimedia           Stand included         Y           Number of Speakers         2         Stand included         HDMI, DisplayPort, USB Type-C to USB Type-C to USB Type-C and Call Separate (Soff				793 mm
Component video sync         Separate sync, Sync-on-green (SOG)         Package weight         14.4 kg         14.4 kg               Flicker-free technology             V             Package type             14.4 kg             14.4 kg               Low Blue Light technology             V             Package type             15.0 kg             14.4 kg               William dia             V             Stand included             V               Mumber of speakers             2             Stand included             V               Megapixel (approx.)             2 MP             Manual             V               Built-in microphone             4 Manual             V             Sustainability               Design             V             Sustainability certificates             ENERGY STAR, TCO               Market positioning *             Home             Doesn't contain             VC/BFK, Mercury               Product colour *             Black             Other features               Front bezel colour             Black             AC adapter included             V               Feet colour             Black             V             Rotating               Built-in USB rub*             V             Tuter integrated	AMD FreeSync *		•	
Filicker-free technology         ✓         Package weight         14.4 kg           Low Blue Light technology         ✓         Package type         Box           Muttimedia         Packaging content           Mumber of speakers         2         Stand included         ✓           MS rated power         6 W         Cables included         ✓         HDMI, DisplayPort, USB Type-C to USB Type-C to USB Type-C to USB Type-C to USB Type-C, USB Type-C to USB Type	Component video sync			673 mm
Low Blue Light technology         Package type         Box           Multimedia         Packaging content           Mumber of speakers         2         Stand included         /           RMS rated power         6 W         Cables included         // USB Type-C, USB Type-C to USB Type-C to USB Type-C to USB Type-C to USB Type-C, USB Type-C to USB Type-C, USB Typ	Flicker-free technology		Package weight	14.4 kg
Multimedia         Packaging content           Number of speakers         2           RMS rated power         6 W         Abliculuded         IHDMI, DisplayPort, USB Type-C to USB Type-C, USB Type-C to USB Type-C.           Built-in microphone         2 MP         Manual         7           Built-in camera*         2 MP         Sustainability           Built-in camera*         4 More         Sustainability certificates         ENERGY STAR, TCO           Market positioning*         Home         Doesn't contain         PVC/BFR, Mercury           Product colour*         Black         Other features         Front bezel colour         Black         PVC/BFR, Mercury           Front bezel colour         Black         Cadapter included         7         PVC/BFR, Mercury           Front bezel colour         Black         WES Power Delivery revision         2.0         PVC/BFR, Mercury           Front bezel colour         Black         TV uner integrated         7         X           Built-in USB hub*         Y         TV uner integrated         X         X           USB uitter am port type         USB			Package type	Box
Number of speakers 2 RMS rated power 6 W 6 W 6 W 6 W 6 W 6 W 6 W 6 W 6 W 6	3 3,	-	Packaging content	
RMS rated power Built-in speaker(s) *		2	Stand included	✓
Bullt-in speaker(s)*	•			
Megapixel (approx.)         2 MP         Manual         ✓           Built-in microphone         ✓         Burdled software         SmartControl           Built-in microphone         ✓         Sustainability           Built-in camera*         ✓         Sustainability certificates         ENERGY STAR, TCO           Market positioning *         Home         Doesn't contain         PVC/BFR, Mercury           Product colour *         Black         WEV/BFR, Mercury           Front bezel colour         Black         AC adapter included         ✓           Feet colour         Black         USB Power Delivery revision         2.0           Ports & interfaces         Rotating         X           Built-in USB hub *         ✓         Y tuner integrated         X           USB systeam port type         USB Type-C         Picture ephancemet         Smarttnage           USB Type-A downstream ports quantity         4         Picture enhancement         Smarttnage           USB Type-C DisiplayPort Alternate Mode         ✓         MultiView         PIP/PBP mode, 2 x devices           USB Power Delivery (USB PD)         ✓         Heavy metals free         Hg (mercury)           USB Power Delivery (USB PD)         ✓         Light sensor         ✓ <t< td=""><td>·</td><td></td><td>Cables included</td><td></td></t<>	·		Cables included	
Built-in microphone         Y         Sustainability         SurartControl           Design         Home         Desent contain         PYC/BFR, Mercury           Market positioning *         Home         Doesn't contain         PYC/BFR, Mercury           Product colour *         Black         Other features         ***           Front bezel colour         Black         AC adapter included         *           Feet colour         Black         USB Power Delivery revision         2.0           Ports & interfaces         Rotating         *           Built-in USB hub *         *         TV tuner integrated         *           USB upstream port type         USB Type-C         Picture-by-Picture (PbP)         *           Number of upstream ports         1         Exterior finish type         Textured           USB Type-A downstream ports         4         Recyclable packaging material         100%           USB Type-C DisplayPort Alternate         *         MultiView         HIP/PBP mode, 2 x devices           Mode         MultiView         Hip/PBP mode, 2 x devices           MOSB Power Delivery (USB PD)         *         Light sensor         *           USB Power Delivery up to         65 W         Light sensor         *	·		Manual	
Built-in camera *				
Design         Sustainability certificates         ENERGY STAR, TCO           Market positioning *         Home         Doesn't contain         PVC/BFR, Mercury           Product colour *         Black         Other features           Front bezel colour         Black         AC adapter included         ✓           Feet colour         Black         USB Power Delivery revision         2.0           Ports & interfaces         Rotating         X           Built-in USB hub *         ✓         TV tuner integrated         X           USB upstream port type         USB Type-C         Picture-by-Picture (PbP)         ✓           USB Type-A downstream ports         1         Exterior finish type         Textured           USB Type-C DisplayPort Alternate quantity         4         Picture enhancement packaging material plus (PiPPBP mode, 2 x devices)           USB Power Delivery (USB PD)         ✓         Heavy metals free         Hg (mercury)           USB Power Delivery (USB PD)         ✓         Light sensor         ✓           USB Power Delivery up to         65 W         EasyRead mode         ✓           HDMI or squantity         2         Compliance certificates         WEEE, RoHS           HDMI yersion         2.0         Regulatory Approvals         <	•			Situateonicol
Market positioning * Home Doesn't contain PVC/BFR, Mercury Product colour * Black Other features Front bezel colour Black AC adapter included		•		ENERGY STAR TOO
Product colour* Black Front bezel colour Black Black CUSB Power Delivery revision CUSB Upstream port type Number of upstream ports Quantity CUSB Type-C DisplayPort Alternate Mode CUSB Power Delivery up to CUSB Power Delivery CUSB Power Delivery CUSB Upstream ports CUSB Upstream ports CUSB Type-C DisplayPort Alternate Mode CUSB Power Delivery CUSB Type-C DisplayPort Alternate Mode CUSB Power Delivery CUSB Type-C DisplayPort Alternate Mode CUSB Power Delivery CUSB Power Cusb Rotation Cusb Cusb Cusb Cube Cusb Cusb Cusb Cube Cusb Cusb Cusb Cube Cusb Cusb Cube Cusb Cusb Cube Cube Cube Cube Cube Cube Cube Cube			· ·	
Front bezel colour Feet colour  Black Blac	·			r ve/bi it, Mercury
Feet colour Black USB Power Delivery revision 2.0  Ports & interfaces				
Ports & interfaces  Built-in USB hub*  V USB Type-C VISB Type-C VISB Type-A downstream ports Quantity USB Type-C DisplayPort Alternate Mode  USB Type-C DisplayPort Alternate Mode  USB Power Delivery (USB PD) V USB Power Delivery up to DISP W DVI port  HDMI *  ** ** ** ** ** ** ** ** ** ** ** **			·	
Built-in USB hub *		Bideix	ŕ	
Number of upstream port type  Number of upstream ports  1 Exterior finish type  Ficture enhancement USB Type-A downstream ports quantity  USB Type-C DisplayPort Alternate Mode  USB Type-C DisplayPort Alternate Mode  USB Power Delivery (USB PD)  V  USB Power Delivery up to  65 W  EasyRead mode  USB Power Delivery up to  DVI port  HDMI *  V  HDMI ports quantity  2 Compliance certificates  HDMI version  DisplayPorts quantity  2 Cemmended resolution  DisplayPorts quantity  1 2  Delta E  Headphone out *  Headphone out puts  HDCP  V  Exterior finish type  Textured		_	-	
Number of upstream ports  USB Type-A downstream ports quantity  USB Type-C DisplayPort Alternate Mode  USB Type-C DisplayPort Alternate Mode  USB Power Delivery (USB PD)  USB Power Delivery up to  65 W  Light sensor  V  HDMI *  HDMI ports quantity  LowBlue mode  LowBlue mode  Compliance certificates  HUMI version  DisplayPorts quantity  LowBlue mode  LowBlue mode  Recommended resolution  DisplayPorts quantity  LowBlue mode  Recommended resolution  DisplayPort version  Audio input  X  Headphone out *  Headphone out tytes  Headphone outputs  HDDCP  Light sensor  MultiView  PIP/PBP mode, 2 x devices  Hg (mercury)  Full (mercury)  Full (mercury)  WEEL, ROHS  Recommended resolution  Recommended resolution  Sa40 x 2160 @ 60 Hz  CE Mark; FCC Class B; China ROHS; CLE AC; CETLus; TUV Ergo; TUV/GS; SEMKO; EPA  Headphone out *  Headphone out *  Headphone outputs  HDCP  Mean time between failures (MTBF)  Too000 h			•	
USB Type-A downstream ports quantity  USB Type-C DisplayPort Alternate Mode  USB Type-C DisplayPort Alternate Mode  USB Power Delivery (USB PD)  USB Power Delivery up to  65 W  Light sensor  EasyRead mode  USB Power Delivery up to  DVI port  HDMI *  **  **  **  **  **  **  **  **  **				
quantity  USB Type-C DisplayPort Alternate Mode  WaltiView  WaltiView  WaltiView  WaltiView  WaltiView  WaltiView  PIP/PBP mode, 2 x devices  Hg (mercury)  WSB Power Delivery (USB PD)  WSB Power Delivery up to  65 W  DVI port  X  HDMI*  HDMI *  **  **  **  **  **  **  **  **  **	• •		<b>,</b> ,	
USB Type-C DisplayPort Alternate Mode  USB Power Delivery (USB PD)  USB Power Delivery up to 65 W  DVI port  HDMI *  HDMI ports quantity  DisplayPorts quantity  DisplayPorts quantity  DisplayPort version  Audio input  Headphone out *  Headphone outputs  Headphone outputs  HDMI *  MultiView  MultiView  Heavy metals free  Heavy metals free  Hg (mercury)  Heavy metals free  Hg (mercury)  Hg (mercury)  Heavy metals free  Heavy metals free  Hg (mercury)  Hg (mercury)  Heavy metals free  Hg (mercury)		4		•
Wode  USB Power Delivery (USB PD)  USB Power Delivery up to  65 W  Light sensor  EasyRead mode  LowBlue mode  HDMI *  **  **  **  **  **  **  **  **  **		<b>✓</b>		
USB Power Delivery up to 65 W Light sensor   DVI port   HDMI *  HDMI ports quantity  2 Compliance certificates  HDMI version  2.0 Recommended resolution  3840 x 2160 @ 60 Hz  CE Mark; FCC Class B; China RoHS; UKRAINIAN; ICES-003; CU-EAC; CETLus; TUV Ergo; TUV/GS; SEMKO; EPA  Headphone out *  Headphone outputs  1 Philips SmartUniformity  Mean time between failures (MTBF)  70000 h				
DVI port X EasyRead mode   HDMI * LowBlue mode   HDMI ports quantity   HDMI version   DisplayPorts quantity   DisplayPort version   Audio input   Headphone out *   Headphone out pubs   Headphone out pubs   HDMI ports quantity   Headphone out pubs   Headphone out pubs   HDMI version   HEEAR A   HEADPH   HEADP		•	•	• • • • • • • • • • • • • • • • • • • •
HDMI *  HDMI ports quantity  2  Compliance certificates  Recommended resolution  3840 x 2160 @ 60 Hz  CE Mark; FCC Class B; China RoHS;  UKRAINIAN; ICES-003; CU-EAC;  CETLus; TUV Ergo; TUV/GS; SEMKO;  EPA  Headphone out *  Headphone outputs  HDCP  LowBlue mode  Delta E  Philips SmartUniformity  97 - 102%  Mean time between failures (MTBF)  70000 h			<u> </u>	
HDMI ports quantity  4 Compliance certificates  5 Compliance certificates  6 Compliance certificates  7 Compliance certificates  8 WEEE, RoHS  8 Recommended resolution  8 Recommended resolution  8 Regulatory Approvals  8 Regulatory Approvals  9 CE Mark; FCC Class B; China RoHS; UKRAINIAN; ICES-003; CU-EAC; CETLus; TUV Ergo; TUV/GS; SEMKO; EPA  9 Readphone out *  9 Philips SmartUniformity	•		•	
HDMI version 2.0 Recommended resolution 3840 x 2160 @ 60 Hz  DisplayPorts quantity 2 DisplayPort version 1.2 Regulatory Approvals  Audio input x  Headphone out * ✓ Delta E  Headphone outputs 1 HDCP ✓ Mean time between failures (MTBF) 70000 h				
DisplayPorts quantity DisplayPort version 1.2 Audio input Headphone out * Headphone outputs HDCP  DisplayPorts quantity 2 Regulatory Approvals  Regulatory Approvals  CE Mark; FCC Class B; China RoHS; UKRAINIAN; ICES-003; CU-EAC; CETLus; TUV Ergo; TUV/GS; SEMKO; EPA  Delta E Philips SmartUniformity 97 - 102%  Mean time between failures (MTBF) 70000 h				
DisplayPort version  1.2  Regulatory Approvals  UKRAINIAN; ICES-003; CU-EAC; CETLus; TUV Ergo; TUV/GS; SEMKO; EPA  Headphone out *  Headphone outputs  HDCP  Regulatory Approvals  UKRAINIAN; ICES-003; CU-EAC; CETLus; TUV Ergo; TUV/GS; SEMKO; EPA  Philips SmartUniformity 97 - 102%  Mean time between failures (MTBF)  70000 h				•
Audio input X EPA  Headphone out * Delta E  Headphone outputs 1  HDCP Mean time between failures (MTBF)  CETCUS; TOV Erg0; TOV/GS; SEMKO; EPA  EPA  2  Philips SmartUniformity 97 - 102%  Mean time between failures (MTBF)  70000 h			Regulatory Approvals	
Headphone out * ✓ Delta E 2 Headphone outputs 1 Philips SmartUniformity 97 - 102% HDCP ✓ Mean time between failures (MTBF) 70000 h	• •			
Headphone outputs 1 Philips SmartUniformity 97 - 102% Mean time between failures (MTBF) 70000 h	·		Delta E	2
HDCP Mean time between failures (MTBF) 70000 h	•			97 - 102%
	·			
HDCP version 2.2		2.2	Ethernet LAN data rates	10,100,1000 Mbit/s
Ethernet LAN (RJ-45) ports 1			Etnernet LAN (RJ-45) ports	
Ethernet LAN  Compliance industry standards  CE, FCC Class B, China RoHS, UKRAINIAN, ICES-003, CU-EAC, cETLus, TUV Ergo, TUV/GS, SEMKO, EPA		•	Compliance industry standards	UKRAINIAN, ICES-003, CU-EAC, cETLus, TUV Ergo, TUV/GS, SEMKO,

Ergonomics		Other features	
VESA mounting * Panel mounting interface Cable lock slot *	el mounting interface 100 x 100 mm	Certification	CE Mark, FCC Class B, China RoHS, UKRAINIAN, ICES-003, CU-EAC, CETLus, TUV Ergo, TUV/GS, SEMKO, EPA
Cable lock slot type	t type Kensington	Recycling data	
Height adjustment *	✓	Total amount of recyclable	85%
Adjustable height (max)	18 cm	materials	
Pivot	✓	Post-consumer recycled plastic	85%
Pivot angle	-90 - 90°	Logistics data	
		Harmonized System (HS) code	85285210



8712581756826

## **Catalog Object Cloud**



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.