APC

APC Back-UPS Pro, 1600VA/960W, Tower, 230V, 8x IEC C13 outlets, Sine Wave, AVR, USB Type A + C ports, LCD, User Replaceable Battery

Brand : APC

Product code: BR1600SI

Product name : Back-UPS Pro, 1600VA/960W, Tower, 230V, 8x IEC C13 outlets, Sine Wave, AVR, USB Type A + C ports, LCD, User Replaceable Battery

Back-UPS Pro, 1600VA/960W, Tower, 230V, 8x IEC C13 outlets, Sine Wave, AVR, USB Type A + C ports, LCD, User Replaceable Battery
APC Back-UPS Pro, 1600VA/960W, Tower, 230V, 8x IEC C13 outlets, Sine Wave, AVR, USB Type A + C ports, LCD, User Replaceable Battery. UPS topology: Line-Interactive, Output power capacity: 1.6 kVA, Output power: 960 W. AC outlet types: C13 coupler, Power plug: C14 coupler, AC outlets quantity: 8 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 260 Ah, Battery life (max): 5 year(s). Form factor: Mini Tower, Product colour: Black, Display type: LCD. Compliance certificates: RoHS, Certification: A-tick, C-tick, CE, EAC, GS Mark, RCM, TISI, REACH

Features

UPS topology *	Line-Interactive
Output power capacity *	1.6 kVA
Output power *	960 W
Waveform *	Sine
Input operation voltage (min) *	176 V
Input operation voltage (max) *	294 V
Input frequency *	50/60 Hz
Output operation voltage (max)	230 V
Output frequency	50/60 Hz
Automatic Voltage Regulation (AVR)	✔
Maximum current	10 A
Surge energy rating	509 J
Noise level	45 dB
Power protection features	Overload
Audible alarm(s)	✔
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm

Ports & interfaces

AC outlet types	C13 coupler
Power plug	C14 coupler
AC outlets quantity	8 AC outlet(s)
USB port	✔
USB 2.0 ports quantity	2
Ethernet LAN (RJ-45) ports	1

Battery

Hot-swap battery	✔
Automatic battery test	✔
Cold start	✔

Design

Form factor *	Mini Tower
Product colour *	Black
Display type	LCD

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m

Certificates

Compliance certificates	RoHS
Certification	A-tick, C-tick, CE, EAC, GS Mark, RCM, TISI, REACH

Sustainability

Sustainability certificates	Green Premium

Weight & dimensions

Width	100 mm
Depth	368 mm
Height	260 mm

Battery

Battery technology	Sealed Lead Acid (VRLA)
Battery capacity	260 Ah
Number of batteries supported	1
Battery life (max)	5 year(s)
Battery recharge time	16 h

Weight & dimensions

Weight	12.1 kg

Packaging data

Package width	223 mm
Package depth	482 mm
Package height	359 mm
Package weight	13.8 kg

Logistics data

Harmonized System (HS) code	85078000

0731304346920

731304346920

Catalog Object Cloud