Canon

Canon imageFORMULA DR-G2140 Sheet-fed scanner 600×600 DPI A3 Black, White

Brand : Canon Product family: Product code: 3149C003

imageFORMULA

Product name: DR-G2140

A3, CIS, 600 dpi, RGB LED, 500 sheets, RJ-45, USB 3.1

Canon imageFORMULA DR-G2140 Sheet-fed scanner 600 x 600 DPI A3 Black, White:

Ultra-fast model takes production scanning to the next level

Optimised for customers who require exceptional high-speed productivity, superior image quality and dependable feeding performance, this A3 scanner has been created to excel in demanding environments

Productivity

Ultra-efficient scanner outputs up to 280 images per minute

Reliability

Robust, durable paper feed and transport rollers can deliver up to 70,000 scans per day

Image quality


Advanced image-processing tools deliver consistently crisp, clear, high-quality images

Scanning		Paper handling	
Maximum scan size * Optical scanning resolution *	305 x 432 mm 600 x 600 DPI	Auto Document Feeder (ADF) media weight	20 - 209 g/m²
Colour scanning	✓	Ports & interfaces	
Duplex scanning *	✓	USB port *	✓
Output colour depth	24 bit	USB version	3.2 Gen 2 (3.1 Gen 2)
ADF scan speed (b/w, A3) ADF scan speed (colour, A3) Duplex ADF scan speed (b/w, A4) Duplex ADF scan speed (colour, A4)	145 ppm 145 ppm 290 ipm 290 ipm	Standard interfaces	RJ-45, USB 3.2 Gen 1 (3.1 Gen 1)
		Network	
		Ethernet LAN	✓
Design		Power	
Scanner type * Product colour * Built-in display *	Sheet-fed scanner Black, White	Power supply type * Power consumption (typical) Power consumption (standby) AC input frequency	AC 66.5 W 3.5 W 50 - 60 Hz
Performance		Input voltage	220 - 240 V
Sensor type *	CIS	Weight & dimensions	
Light source Daily duty cycle (max) * Scanning noise level	RGB LED 70000 pages 54 dB	Width Depth Height	480 mm 569 mm 315 mm
Input capacity		Weight	25 kg
Standard input capacity	500 sheets	Operational conditions	
Paper handling		Operating temperature (T-T)	10 - 35 °C
Long-paper mode	/	Operating relative humidity (H-H)	20 - 80%
Maximum ISO A-series paper size *	A3	Operating temperature (T-T)	50 - 95 °F
		Logistics data	
		Harmonized System (HS) code	84716070









4528472108131

0013803308303



013803308303

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.