**EPSON**

# Epson TM-T20III 203 x 203 DPI Wired Thermal POS printer

**Brand :** Epson

**Product code:** C31CH51012

**Product name :** TM-T20III

- Economical: Automatic paper reduction function
- Reliable: Mechanism life of 15 million lines
- Fast print speed: Print speed of 250mm/sec
- Flexible connectivity: Two models: 1) USB + Serial 2) Ethernet
- Peace of mind: Epson is Europe's number one POS printer manufacturer
Themal Line, 250 mm/sec, 80 mm, 203 dpi, Ethernet, 55 dB, 1.7 kg
Epson TM-T20III. Print technology: Thermal, Type: POS printer, Maximum resolution: 203 x 203 DPI.
Maximum roll diameter: 8.3 cm, Supported paper width: 48, 64, 80 mm. Connectivity technology: Wired,
Standard interfaces: Ethernet. Sound pressure level (printing): 55 dB, Mean time between failures
(MTBF): 360000 h, Autocutter durability: 1.5 million cuts. Product colour: Black

## Printing

| | |
|---|---|
| Maximum resolution | 203 x 203 DPI |
| Print speed | 250 mm/sec |
| Character density | 22.6 cpi |
| Character sets | ANK |
| Print technology * | Thermal |
| Type * | POS printer |

## Paper handling

| | |
|---|---|
| Maximum roll diameter | 8.3 cm |
| Supported paper width | 48, 64, 80 mm |

## Ports & interfaces

| | |
|---|---|
| Connectivity technology * | Wired |
| Standard interfaces | Ethernet |

## Network

| | |
|---|---|
| Ethernet LAN * | ✔ |
| Wi-Fi * | ✘ |

## Features

| | |
|---|---|
| Sound pressure level (printing) | 55 dB |
| Mean time between failures (MTBF) | 360000 h |
| Cutter | ✔ |
| Autocutter durability | 1.5 million cuts |
| Print head life | 150 km |
| Country of origin | Philippines |
| Built-in sensors details | Roll paper cover open sensor, Paper End Sensor, Paper Near End Sensor |
| Certification | FCC class A, CE marking, EN55022 Class A, UL, CSA, TÜV |

## Design

| | |
|---|---|
| Product colour * | Black |

## Operational conditions

| | |
|---|---|
| Storage relative humidity (H-H) | 10 - 90% |

## Weight & dimensions

| | |
|---|---|
| Width | 140 mm |
| Depth | 199 mm |
| Height | 146 mm |
| Weight | 1.7 kg |

## Packaging data

| | |
|---|---|
| Cables included | AC |
| Quantity per pack | 1 pc(s) |
| Package width | 192 mm |
| Package depth | 235 mm |
| Package height | 280 mm |
| Package weight | 2.49 kg |

## Packaging content

| | |
|---|---|
| Drivers included | ✔ |
| Quick start guide | ✔ |
| AC adapter included | ✔ |

## Logistics data

| | |
|---|---|
| Pallet weight (UK) | 0 g |
| Harmonized System (HS) code | 84433210 |
| Products per master (outer) case | 4 pc(s) |
| Master (outer) case width | 400 mm |
| Master (outer) case length | 490 mm |
| Master (outer) case height | 295 mm |
| Master (outer) case gross weight | 0 g |
| Products per pallet | 112 pc(s) |
| Products per pallet layer | 16 pc(s) |
| Pallet gross weight | 0 g |
| Products per pallet (UK) | 168 pc(s) |

## Power

| | |
|---|---|
| Power source type * | AC |
| AC input voltage | 24 V |

## Operational conditions

| | |
|---|---|
| Operating temperature (T-T) | 5 - 45 °C |
| Storage temperature (T-T) | -10 - 50 °C |
| Operating relative humidity (H-H) | 10 - 90% |

## Logistics data

| | |
|---|---|
| Products per pallet layer (UK) | 24 pc(s) |

## Other features

| | |
|---|---|
| Buffer size | 45 KB |
| Mean cycles between failures (MCBF) | 60000000 |
| Print head life | 150 million characters |

8715946669656

**Catalog Object Cloud**