EPSON

# Epson WorkForce DS-6500

Brand : Epson   **Product family:** WorkForce   **Product code:** B11B205231

Product name : Epson
WorkForce DS-6500

A4, 1200 x 1200 dpi, ReadyScan LED, 25 ppm, 50 - 128 gsm, USB 2.0, 44.5 W, 9800 g, White
Epson WorkForce DS-6500. Maximum scan size: 215.9 x 1016 mm, Optical scanning resolution: 1200 x
1200 DPI, Input colour depth: 48 bit. Scanner type: Flatbed & ADF scanner, Product colour: White. Daily
duty cycle (max): 3000 pages, Light source: ReadyScan LED, Scan file formats: JPG, PDF, TIFF. Maximum
ISO A-series paper size: A4, Scanning media types supported: Plain paper, ISO A-series sizes (A0...A9):
A4, A5, A6. Standard interfaces: USB 2.0

Scanning

Maximum scan size *	215.9 x 1016 mm
Optical scanning resolution *	1200 x 1200 DPI
Colour scanning	✔
Duplex scanning *	✔
Input colour depth	48 bit
Output colour depth	24 bit

Design

Scanner type *	Flatbed & ADF scanner
Product colour *	White
Built-in display *	✘

Performance

Light source	ReadyScan LED
Scan file formats	JPG, PDF, TIFF
Daily duty cycle (max) *	3000 pages
Scan to	E-mail, FTP
Scan drivers	ISIS, TWAIN, WIA

Paper handling

Scanning media types supported	Plain paper
Maximum ISO A-series paper size *	A4
ISO A-series sizes (A0...A9)	A4, A5, A6
ISO B-series sizes (B0...B9)	B5
Letter	✔
Legal	✔

Ports & interfaces

USB port *	✔
USB version	2.0
Standard interfaces	USB 2.0

Power

Power supply type *	AC
Power consumption (typical)	44.5 W

Packaging data

Quantity per pack	1 pc(s)
Package width	325 mm
Package depth	595 mm
Package height	495 mm
Package weight	12.4 g

Sustainability

Sustainability certificates	ENERGY STAR

System requirements

Compatible operating systems	Mac OS 10.4.11+ Presentation Server 4.5 Terminal Service Windows 7 (32/64-bit) Windows Server 2003 (32/64-bit) Windows Server 2008 (32/64-bit) Windows Server 2008 R2 Windows Vista (32/64-bit) Windows XP (32/64-bit) Windows server 2003 R2 XenApp 5.0 XenApp 6.0
Windows operating systems supported	✔
Mac operating systems supported	✔
USB required	✔

Operational conditions

Operating temperature (T-T)	5 - 35 °C
Storage temperature (T-T)	-25 - 60 °C
Operating relative humidity (H-H)	10 - 80%
Storage relative humidity (H-H)	10 - 85%

Other features

Simplex scan speed (colour)	25 ppm

Logistics data

Products per pallet	12 pc(s)
Country of origin	China
Pallet gross length	120 cm
Pallet gross width	80 cm

Power

Power consumption (standby)	1.6 W
AC input frequency	50 - 60 Hz
Input voltage	100-240 V

Weight & dimensions

Width	495 mm
Depth	360 mm
Height	217 mm
Weight	9.8 kg

Logistics data

Pallet gross height	157.8 cm
Products per pallet layer	2 pc(s)
Products per pallet layer (UK)	4 pc(s)
Products per pallet (UK)	24 pc(s)
Pallet length (UK)	120 cm
Pallet width (UK)	100 cm
Pallet height (UK)	157.8 cm
Harmonized System (HS) code	84716070

8715946499215

Catalog Object Cloud