PHILIPS

Philips 279P1/00 LED display 68.6 cm (27") 3840 x 2160 pixels 4K Ultra HD Black

Brand : Philips

Product code: 279P1/00

Product name : 279P1/00

Monitor 279P1 LCD monitor with USB-C docking

Philips 279P1/00 LED display 68.6 cm (27") 3840 x 2160 pixels 4K Ultra HD Black:

This Philips monitor offers 90W power delivery and a simple laptop docking solution. View UHD image, re-charge a laptop and Ethernet, all at the same time with a single USB-C cable. Eye comfort with TUV certification to reduce eye fatigue.
Philips 279P1/00. Display diagonal: 68.6 cm (27"), Display resolution: 3840 x 2160 pixels, HD type: 4K Ultra HD, Display technology: LED, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 2 (3.1 Gen 2). VESA mounting, Height adjustment. Product colour: Black

Display

Display diagonal *	68.6 cm (27")
Display resolution *	3840 x 2160 pixels
HD type *	4K Ultra HD
Native aspect ratio *	16:9
Display technology *	LED
Panel type *	IPS
Backlight type	W-LED
Touchscreen *	✘
Display brightness (typical)	350 cd/m²
Response time *	4 ms
Anti-glare screen	✔
Screen shape *	Flat
Supported graphics resolutions	3840 x 2160
Aspect ratio	16:9
Contrast ratio (typical) *	1000:1
Contrast ratio (dynamic)	50000000:1
Dynamic contrast ratio marketing name	SmartContrast
Maximum refresh rate *	60 Hz
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours *	1.07 billion colours
SmartResponse	4 ms
Pixel pitch	0.1554 x 0.1554 mm
Pixel density	163 ppi
Horizontal scan range	30 - 140 kHz
Vertical scan range	23 - 60 Hz
Viewable size, horizontal	59.7 cm
Viewable size, vertical	33.6 cm
Digital horizontal frequency	30 - 140 kHz
Digital vertical frequency	23 - 60 Hz
Display diagonal (metric)	68.6 cm

Ergonomics

Adjustable height (max)	15 cm
Pivot	✔
Pivot angle	-90 - 90°
Swivelling	✔
Swivel angle range	-180 - 180°
Tilt adjustment	✔
Tilt angle range	-5 - 35°
On Screen Display (OSD)	✔
On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Plug and Play	✔
LED indicators	Operation, Stand-by

Power

Energy efficiency class (SDR) *	G
Energy consumption (SDR) per 1000 hours *	30 kWh
Power consumption (typical) *	25.9 W
Power consumption (standby) *	0.3 W
Power consumption (off)	0 W
Power consumption (PowerSave)	20.9 W
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Power supply type	Internal
Energy efficiency scale	A to G
European Product Registry for Energy Labelling (EPREL) code	416782

Operational conditions

Operating temperature (T-T)	0 - 40 °C

Display

DDC/CI	✔
Haze rate	25%
Surface hardness	3H
Colour gamut standard	sRGB
Colour gamut	103%
sRGB coverage (typical)	112%
NTSC coverage (typical)	93%
Display sRGB	✔

Performance

NVIDIA G-SYNC *	✘
AMD FreeSync *	✘
Component video sync	Separate sync
Flicker-free technology	✔
Low Blue Light technology	✔

Multimedia

Number of speakers	2
RMS rated power	6 W
Built-in speaker(s) *	✔
Built-in camera *	✘

Design

Market positioning *	Home
Product colour *	Black
Front bezel colour	Black
Feet colour	Black

Ports & interfaces

Built-in USB hub *	✔
USB hub version	3.2 Gen 2 (3.1 Gen 2)
USB upstream port type	USB Type-C
Number of upstream ports	1
Number of USB Type-C upstream ports quantity	1
USB Type-C DisplayPort Alternate Mode	✔
USB Power Delivery (USB PD)	✔
USB Power Delivery up to	90 W
DVI port	✘
HDMI *	✔
HDMI ports quantity	2
HDMI version	2.0
DisplayPorts quantity	1
DisplayPort version	1.4
Audio output	✔
HDCP	✔
HDCP version	2.2

Network

Ethernet LAN	✔

Ergonomics

VESA mounting *	✔
Panel mounting interface	100 x 100 mm
Cable lock slot *	✔
Cable lock slot type	Kensington
Height adjustment *	✔

Operational conditions

Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 80%
Operating altitude	0 - 3658 m
Non-operating altitude	0 - 12192 m

Weight & dimensions

Width (with stand)	613 mm
Depth (with stand)	225 mm
Height (with stand)	537 mm
Weight (with stand)	7.52 kg
Width (without stand)	613 mm
Depth (without stand)	54 mm
Height (without stand)	366 mm
Weight (without stand)	5.73 kg

Packaging data

Package width	730 mm
Package depth	193 mm
Package height	471 mm
Package weight	11.2 kg
Package type	Box

Packaging content

Stand included	✔
Cables included	HDMI, DisplayPort, USB Type-C, AC
Manual	✔
Bundled software	SmartControl

Sustainability

Sustainability certificates	ENERGY STAR, TCO
Doesn't contain	Mercury, PVC/BFR

Other features

HBR3 support	✔
USB Power Delivery revision	3.0
Exterior finish type	Textured
Recyclable packaging material	100%
Heavy metals free	Hg (mercury), Pb (lead)
Light sensor	✔
EasyRead mode	✔
LowBlue mode	✔
Philips SmartUniformity	97 - 102%
Picture enhancement	SmartImage
Regulatory Approvals	cETLus; CB; TUV/GS; TUV Ergo; SEMKO; CU-EAC; EAEU RoHS; CE Mark; UKRAINIAN; FCC Class B; ICES-003; TUV Eye Comfort certified
Delta E	2
Compliance certificates	RoHS
Mean time between failures (MTBF)	70000 h
Ethernet LAN data rates	10,100,1000 Mbit/s
Wake-on-LAN	✔
Certification	cETLus, CB, TUV/GS, TUV Ergo, SEMKO, CU-EAC, EAEU RoHS, CE Mark, UKRAINIAN, FCC Class B, ICES-003, TUV Eye Comfort certified

Recycling data

Post-consumer recycled plastic	85%

Logistics data

Harmonized System (HS) code	85285210

8712581764371

Catalog Object Cloud