



APC Smart-UPS On-Line SRT1500RMXLI-NC - 1500VA, 6x C13 output, rack mountable, NMC

Brand : APC

Product code: SRT1500RMXLI-NC

Product name : APC Smart-UPS On-Line SRT1500RMXLI-NC - 1500VA, 6x C13 output, rack mountable, NMC



APC Smart-UPS On-Line SRT1500RMXLI-NC - 1500VA, 6x C13 output, rack mountable, NMC
APC Smart-UPS On-Line SRT1500RMXLI-NC - 1500VA, 6x C13 output, rack mountable, NMC. UPS topology: Double-conversion (Online), Output power capacity: 1.5 kVA, Output power: 1500 W. Serial interface type: RJ-45. Battery technology: Sealed Lead Acid (VRLA), Battery voltage: 48 V, Battery life (max): 5 year(s). Form factor: Rackmount, Product colour: Black, Cable length: 1.83 m. Compliance certificates: RoHS, Certification: CE, EAC




Features		Design	
UPS topology *	Double-conversion (Online)	Product colour *	Black
Output power capacity *	1.5 kVA	Display type	LCD
Output power *	1500 W	LED indicators	Status
Waveform *	Sine	International Protection (IP) code	IP20
Input operation voltage (min) *	50 V	Operational conditions	
Input operation voltage (max) *	150 V	Operating temperature (T-T)	0 - 40 °C
Input frequency *	40/70 Hz	Storage temperature (T-T)	-20 - 50 °C
Output operation voltage (min)	220 V	Operating relative humidity (H-H)	0 - 95%
Output operation voltage (max)	240 V	Storage relative humidity (H-H)	0 - 95%
Output frequency	50/60 Hz	Certificates	
Surge energy rating	432 J	Compliance certificates	RoHS
Crest factor	3:1	Certification	CE, EAC
Emergency Power Off (EPO)	✓	Packaging content	
Noise level	50 dB	Manual	✓
Audible alarm(s)	✓	Sustainability	
Ports & interfaces		Sustainability certificates	Green Premium
USB port	✓	Weight & dimensions	
Serial interface	✓	Width	432 mm
Serial interface type	RJ-45	Depth	505 mm
SmartSlot	✓	Height	85 mm
Battery		Weight	21 kg
Battery technology	Sealed Lead Acid (VRLA)	Packaging data	
Battery voltage	48 V	Package width	594 mm
Battery life (max)	5 year(s)	Package depth	749 mm
Battery recharge time	3 h	Package height	246 mm
Hot-swap battery	✓	Package weight	29.6 kg

Design		Logistics data	
Form factor *	Rackmount	Products per pallet	12 pc(s)
Cable length	1.83 m	Harmonized System (HS) code	85078000
		Total carbon footprint (kg of CO2e)	2577.53



0731304340294



731304340294

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.