



APC SRV2KI uninterruptible power supply (UPS) Double-conversion (Online) 2 kVA 1600 W 4 AC outlet(s)

Brand : APC

Product code: SRV2KI

Product name : SRV2KI

SRV2KI, 1.6kW, 230V, 50/60Hz, 4x IEC 320 C13, IEC-320 C14, USB, 145x400x238 mm
APC SRV2KI. UPS topology: Double-conversion (Online), Output power capacity: 2 kVA, Output power: 1600 W. AC outlet types: C13 coupler, AC outlets quantity: 4 AC outlet(s), USB port type: USB Type-B. Battery technology: Sealed Lead Acid (VRLA), Battery recharge time: 4 h. Form factor: Tower, Product colour: Black, Display type: LCD. Compliance certificates: RoHS, Certification: CE, IEC 62040-1-1, IEC 62040-1-2, REACH



Features		Battery	
UPS topology *	Double-conversion (Online)	Battery technology	Sealed Lead Acid (VRLA)
Output power capacity *	2 kVA	Battery recharge time	4 h
Output power *	1600 W	Design	
Waveform *	Sine	Form factor *	Tower
Input operation voltage (min) *	160 V	Product colour *	Black
Input operation voltage (max) *	280 V	Display type	LCD
Input frequency *	40 - 70 Hz	Operational conditions	
Output operation voltage (min)	220 V	Operating temperature (T-T)	0 - 40 °C
Output operation voltage (max)	240 V	Storage temperature (T-T)	-20 - 50 °C
Output frequency	50/60 Hz	Operating relative humidity (H-H)	0 - 95%
Surge energy rating	600 J	Storage relative humidity (H-H)	0 - 95%
Crest factor	3:1	Operating altitude	0 - 3000 m
ECO mode	✓	Non-operating altitude	0 - 14763.6 m
Output voltage Total Harmonic Distortion (THD)	3%	Certificates	
Surge protection	✓	Compliance certificates	RoHS
Audible alarm(s)	✓	Certification	CE, IEC 62040-1-1, IEC 62040-1-2, REACH
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm	Packaging content	
Ports & interfaces		Cables included	USB cable
AC outlet types	C13 coupler	Manual	✓
AC outlets quantity	4 AC outlet(s)	Weight & dimensions	
USB port	✓	Width	145 mm
USB 2.0 ports quantity	1	Depth	400 mm
USB port type	USB Type-B		

Ports & interfaces		Weight & dimensions	
Serial interface	✓	Height	238 mm
Serial interface type	RS-232	Weight	16.8 kg
RS-232 ports	1	Packaging data	
		Package width	235 mm
		Package depth	525 mm
		Package height	355 mm
		Package weight	18.1 kg
		Logistics data	
		Harmonized System (HS) code	85078000



0731304339243



731304339243

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.