

Epson DFX-9000

Brand : Epson

Product code: C11C605011BZ

Product name : DFX-9000

DFX-9000, Matrix Printer, 1550cps, A4

Epson DFX-9000. Maximum print speed: 1550 cps, Maximum resolution: 240 x 144 DPI, Maximum print speed (draft): 1320 cps. Maximum print size: A4 (210 x 297 mm), Paper tray media types: Labels. Buffer size: 128 KB, Sound pressure level (printing): 58 dB, Page description languages: ESC P, PPDS. Standard interfaces: Parallel, RS-232, USB 2.0, Optional connectivity: Ethernet. Print head: 9-pin, Print direction: Bidirectional, Print head life: 200 million characters



Printing		Operational conditions	
Maximum resolution *	240 x 144 DPI	Operating temperature (T-T)	5 - 35 °C
Maximum printing width (columns) *	136	Operating relative humidity (H-H)	10 - 80%
Colour *	×	System requirements	
Maximum print speed *	1550 cps	Windows operating systems supported	Windows 2000, Windows 7, Windows 8, Windows 98, Windows XP
Maximum print speed (draft)	1320 cps	Bundled software	Epson Status Monitor
Maximum print speed (LQ)	330 cps	Weight & dimensions	
Character pitch	10,12 cpi	Width	700 mm
Maximum number of copies	10 copies	Depth	378 mm
Built-in barcodes	Code 39, POSTNET, UPC-A, UPC-E	Height	363 mm
Paper handling		Weight	34 kg
Maximum print size	A4 (210 x 297 mm)	Packaging data	
Paper tray media types	Labels	Quantity per pack	1 pc(s)
Features		Package width	485 mm
Buffer size *	128 KB	Package depth	840 mm
Sound pressure level (printing) *	58 dB	Package height	505 mm
Page description languages *	ESC P, PPDS	Package weight	35.5 g
Country of origin	Japan	Other features	
Ports & interfaces		Connectivity technology	Wired
Standard interfaces *	Parallel, RS-232, USB 2.0	Print technology	Dot matrix
Optional connectivity	Ethernet	Needles	36 (4 x 9)
Endurance		Logistics data	
Print head *	9-pin	Products per pallet	4 pc(s)
Print direction	Bidirectional	Pallet gross width	120 cm
Print head life	200 million characters	Pallet gross height	100 cm
Ribbon life (black, draft)	15 million characters	Products per pallet layer	1 pc(s)
Mean time between failures (MTBF)	20000 h	Products per pallet layer (UK)	2 pc(s)
Power		Products per pallet (UK)	8 pc(s)
Power consumption (typical)	185 W	Pallet length (UK)	120 cm
Power consumption (standby)	75 W	Pallet width (UK)	100 cm
		Pallet height (UK)	2.1 m
		Harmonized System (HS) code	84433210



8715946275987

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.