Epson WorkForce Pro RIPS WF-C879R Inkjet A3 4800 x 1200 DPI 35 ppm Wi-Fi

Brand: Epson Product family: WorkForce Pro Product code: C11CH35401

Product name: RIPS WF-

C879R

- High ink yield: Print 86,000 pages mono or 50,000 colour without changing supplies
- Less waste: With high capacity ink packs, reduce the need for supplies and reduce waste
- Low power consumption: Epson's Heat-Free technology uses no heat, reducing energy consumption
- Powerful scanning capability: Thin paper support and improved scanning quality
- Works with Epson Remote Services: Cloud-based, advanced diagnosis of Epson printers and MFPs PrecisionCore printhead, 4800×1200 dpi, 800 nozzles, 53 dB, 54 W, 100 240 V, 50 60 Hz, $621 \times 751 \times 711$ mm, 79.3 kg

Epson WorkForce Pro RIPS WF-C879R. Print technology: Inkjet, Printing: Colour printing, Maximum resolution: 4800 x 1200 DPI, Print speed (colour, normal quality, A4/US Letter): 35 ppm. Copying: Colour copying, Maximum copy resolution: 600 x 1200 DPI. Scanning: Colour scanning, Optical scanning resolution: 600 x 600 DPI. Faxing: Mono faxing. Maximum ISO A-series paper size: A3. Wi-Fi. Direct printing. Product colour: White





| Printing | | Input & output capacity | |
|---|-----------------|---|---|
| Duplex printing mode | Auto | Multi-Purpose tray input capacity | 150 sheets |
| Print technology * | Inkjet | Auto document feeder (ADF) | ✓ |
| Printing * | Colour printing | Auto document feeder (ADF) input | 150 sheets |
| Duplex printing * | ✓ | capacity | |
| Maximum resolution * | 4800 x 1200 DPI | Maximum input capacity | 1900 sheets |
| Print speed (black, normal quality, A4/US Letter) * | 35 ppm | Paper handling | A.2. |
| Print speed (colour, normal quality, A4/US Letter) | 35 ppm | Maximum ISO A-series paper size * | A3 Plain paper, Recycled paper, Art |
| Print speed (black, normal quality, A3) | 13 ppm | Paper tray media types * | paper, Letterhead, Glossy paper, Photo paper |
| Print speed (colour, normal quality, A3) | 13 ppm | ISO A-series sizes (A0A9) * ISO B-series sizes (B0B9) | A3, A3+, A4, A5, A6 B4, B5, B6 |
| Print speed (ISO/IEC 24734) black | 26 ppm | ISO C-series sizes (C0C9) | C4, C5, C6 |
| Print speed (ISO/IEC 24734) colour | 25 ppm | Custom media width | 55 - 127 mm |
| Duplex print speed (black, normal quality, A4/US Letter) | 11 ppm | Custom media length Paper tray media weight | 330 - 1200 mm 64 - 300 g/m² |
| Duplex print speed (colour, normal quality, A4/US Letter) | 11 ppm | Ports & interfaces | |
| Duplex print speed (ISO/IEC 24734) | 100 ipm | Direct printing * | / |
| Duplex print speed (ISO/IEC 24734) colour | 100 ipm | USB port Network | • |
| Duplex print speed (ISO/IEC 24734, | 18 ppm | Wi-Fi * | ✓ |
| A4) black | • • | Ethernet LAN * | ✓ |
| Duplex print speed (ISO/IEC 24734, A4) colour | 17 ppm | Cabling technology | 10/100Base-T(X) |
| Duplex print speed (ISO/IEC 24734, | 11 ppm | Ethernet LAN data rates | 10,100 Mbit/s |
| A3) black | | Wi-Fi standards | 802.11b, 802.11g, Wi-Fi 4 (802.11n) |
| Duplex print speed (ISO/IEC 24734, A3) colour | 11 ppm | Security algorithms | 64-bit WEP, 128-bit WEP, WPA-PSK, WPA-TKIP, WPA2-PSK, WPA2-AES, |
| Time to first page (black, normal) | 5.5 s | | WPA2-Enterprise |
| Time to first page (colour, normal) | 5.5 s | Supported network protocols (IPv4) | TCP, UDP, HTTP, HTTPS, IPv4, IPv6, IPSEC, SSL / TLS |
| Secure printing | ✓ | | SNMP, HTTP, DHCP, BOOTP, APIPA, |
| Copying | | Management protocols | DDNS, mDNS, SNTP, SLP, WSD, LLTD, Ping, SNMP 2.0c, SNMP 3.0, |
| Duplex copying * | × | | SNMP Trap |

| Copying | | Network | |
|---|---|---------------------------------------|--|
| Copying * Maximum copy resolution * Maximum copy size | aximum copy resolution * 600 x 1200 DPI | Mobile printing technologies | Epson Connect, Epson iPrint, Epson Email Print, Epson Remote Print, Apple AirPrint, Google Cloud Print |
| Maximum number of copies | 999 copies | Performance | |
| Copier resize | 25 - 400% | Internal storage capacity | 320 GB |
| Scanning | | Sound pressure level (printing) | 53 dB |
| | | Sound power level (printing) | 6.9 dB |
| Duplex scanning * Scanning * | ✓ Colour scanning | Design | |
| Optical scanning resolution * | Colour scanning 600 x 600 DPI | Product colour * | White |
| Maximum scan resolution | 600 x 600 DPI | Built-in display * | ✓ |
| Scanner type * | ADF scanner | Display | LCD |
| Scan technology | CIS | Display diagonal | 12.7 cm (5") |
| Scan to | E-mail, FTP, Network folder, PC, | Touchscreen | ✓ |
| | Software, USB | Control type | Touch |
| Scan speed (black) | 50 inch/min | Colour display | ✓ |
| Scan speed (colour) | 50 inch/min | Power | |
| Image formats supported Document formats supported | JPEG, TIFF PDF | | |
| | FUI | Power consumption (average operating) | 54 W |
| Fax | | Power consumption (copying) | 54 W |
| Faxing * | Mono faxing | Power consumption (ready) | 25 W |
| Fax transmission speed | 3 sec/page | Power consumption (off) | 0.15 W |
| Modem speed | 33.6 Kbit/s | AC input voltage | 100 - 240 V |
| Fax memory | 550 pages | AC input frequency | 50 - 60 Hz |
| Auto-redialing | ✓ | System requirements | |
| Speed dialling | 2000 | | Windows 10, Windows 10 |
| Fax speed dialing (max numbers) Fax forwarding to | 2000 E-mail, Folder, PC | | Education, Windows 10 Education x64, Windows 10 Enterprise, |
| Error Correction Mode (ECM) | ∠-mail, rolder, r∈ | | Windows 10 Enterprise, Windows 10 Enterprise x64, |
| | • | | Windows 10 Home, Windows 10 |
| Features | | | Home x64, Windows 10 IOT Core, Windows 10 IoT Enterprise, |
| Recommended duty cycle | 2000 - 10000 pages per month | | Windows 10 Pro, Windows 10 Pro |
| Maximum duty cycle * | 75000 pages per month | | x64, Windows 10 x64, Windows 7, Windows 7 Enterprise, Windows 7 |
| Printing colours * | Black, Cyan, Yellow, Magenta | | Enterprise x64, Windows 7 Home |
| Page description languages | PCL 5c, PCL 5e, ESC/P-R, PostScript 3, PDF 1.7, PCL 6 | | Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, |
| Country of origin | Indonesia | | Windows 7 Home Premium x64, |
| Input & output capacity | | | Windows 7 Professional, Windows 7 Professional x64, Windows 7 |
| Total number of input trays * | 2 | | Starter, Windows 7 Starter x64, |
| Total input capacity * | 250 sheets | | Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, |
| Total output capacity * | 250 sheets | Windows operating systems | Windows 8, Windows 8 Enterprise, |
| Multi-Purpose tray | / | supported | Windows 8 Enterprise x64, Windows |
| | | | 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 |
| | | | Enterprise, Windows 8.1 Enterprise |
| | | | x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows |
| | | | Vista, Windows Vista Business, |
| | | | Windows Vista Business x64, |
| | | | Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista |
| | | | Home Basic, Windows Vista Home |
| | | | Basic x64, Windows Vista Home Premium, Windows Vista Home |
| | | | Premium x64, Windows Vista |
| | | | Ultimate, Windows Vista Ultimate |
| | | | x64, Windows Vista x64, Windows XP, Windows XP Home, Windows XP |
| | | | Home x64, Windows XP |
| | | | Professional, Windows XP Professional x64 |
| | | | Mac OS X 10.11 El Capitan, Mac OS |
| | | Mac operating systems supported | X 10.6 Snow Leopard, Mac OS X |
| | | | 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks |
| | | | 2.511, Fide 05 A 1015 FidVericks |

| System requirements | |
|---|---|
| Server operating systems supported | Windows Server 2003 R2, Windows Server 2003 x64, Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016 |
| Weight & dimensions | |
| Width Depth Height Weight | 621 mm 751 mm 711 mm 79.3 kg |
| Packaging data | |
| Package width Package depth Package height Package weight Quantity per pack | 715 mm 840 mm 1086 mm 94 kg 1 pc(s) |
| Packaging content | |
| Cables included Manual Warranty card | AC ✓ |
| Other features | |
| Printing method Ink drop | Epson PrecisionCore 4.6 |
| Print head nozzles | 800 nozzles black, 800 nozzles per colour |
| Other network protocols supported | NetBIOS over TCP/IP, WSD-Scan, Bonjour/Airprint, FTP |
| Supported network protocols | TCP, UDP, HTTP, HTTPS, IPv4, IPv6, IPSEC, SSL/TLS |
| Noise level | 53 dB |



8715946670706

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.