

Brother DCP-1610W multifunction printer Laser A4 2400 x 600 DPI 20 ppm Wi-Fi

Brand : Brother Product code: DCP-1610W

Product name: DCP-1610W

DCP-1610W - Print/Copy/Scan, A4, 2400x600 dpi, USB 2.0, 802.11b/g/n, GDI, 32MB, 7.2kg

Brother DCP-1610W multifunction printer Laser A4 2400 x 600 DPI 20 ppm Wi-Fi:

Effortless printing with no complications

The Brother DCP-1610W is stylishly designed and compact enough to fit onto a shelf or workstation. It produces outputs with the speed and quality you would expect from a more expensive machine. Installation is very easy – connect using wireless or the USB cable, and you will be printing in no time. Plus innovative Anti-Jam technology allows you to print wirelessly with no hassle. You will also be able to print at speeds of up to 20 pages per minute (ppm), and your first page will come out in less than 10 seconds.

- Print, copy and scan
- Up to 20ppm print speed
- Wireless ready
- 2,400 x 600dpi resolution
- 150-sheet paper tray
- Innovative anti-jam technology.





Printing		Performance	
Print technology * Printing * Duplex printing *	Laser Mono printing	Built-in processor Processor frequency Sound pressure level (printing)	✓ 200 MHz 52 dB
Maximum resolution *	2400 x 600 DPI	Design	
Print speed (black, normal quality, A4/US Letter) * Time to first page (black, normal)	20 ppm 10 s	Product colour * Market positioning * Built-in display *	Black, White Home & office ✓
Copying * Copying * Maximum copy resolution *	X Mono copying 600 x 600 DPI	Display Display number of lines Display number of characters	LCD 2 lines 16
Copy speed (black, normal quality,		Power	
A4)	20 cpm	Power consumption (max)	1080 W
Maximum number of copies Copier resize N-in-1 copy function (N=)	99 copies 25 - 400% 2, 4	Power consumption (average operating) Power consumption (PowerSave)	390 W 0.9 W
Scanning		Power consumption (ready)	50 W
Duplex scanning * Scanning * Optical scanning resolution * Maximum scan resolution Maximum scan area Scan technology Scan to Scan drivers	Colour scanning 600 x 1200 DPI 19200 x 19200 DPI A4 (210 x 297) CIS E-mail, File, Image ICA, TWAIN, WIA	Power consumption (off) AC input voltage AC input frequency	0.28 W 220 - 240 V 50 - 60 Hz
Fax			
Duplex faxing	×		

Fav		System requirements	
Fax		System requirements	Windows 7 Homo Pasis Windows 7
Faxing *	×		Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home
Recommended duty cycle Number of print cartridges * Printing colours * Page description languages	250 - 1800 pages per month 1 Black GDI		Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows
Country of origin	Vietnam		8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro
Input & output capacity			x64, Windows 8 x64, Windows 8.1,
Total input capacity * Total output capacity *	150 sheets 50 sheets	Windows operating systems 8.1 Enterprise x64, Windows supported Pro, Windows 8.1 Pro x64, W	Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows
Paper handling			8.1 x64, Windows Vista Business, Windows Vista Business x64,
Maximum ISO A-series paper size * Paper tray media types * ISO A-series sizes (A0A9) * ISO B-series sizes (B0B9) Non-ISO print media sizes Custom media length Paper tray media weight	A4 Plain paper, Recycled paper A4, A5, A6 B5 Executive, Folio, Legal, Letter 148 - 355.6 mm 65 - 105 g/m²		Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP
Ports & interfaces			Professional, Windows XP Professional x64
Standard interfaces USB port USB 1.1 ports quantity	USB 1.1, USB 2.0, Wireless LAN ✓ 1	Mac operating systems supported	Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
USB 2.0 ports quantity	1	Linux operating systems supported	✓
Network			Windows Server 2003, Windows Server 2003 x64, Windows Server
Wi-Fi *	✓	Server operating systems supported	2008, Windows Server 2008 R2, Windows Server 2008 x64, Windows
Ethernet LAN *	×		Server 2012, Windows Server 2012
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)		R2 x64
Socurity algorithms	128-bit WEP, 64-bit WEP, SMTP-	Onerational conditions	
Security algorithms		Operational conditions	
Security algorithms	AUTH, WPA-AES, WPA-PSK, WPA-TKIP, WPA2-AES, WPA2-PSK, WPS	Operating relative humidity (H-H)	20 - 80% 0 - 40 °C
Security algorithms	AUTH, WPA-AES, WPA-PSK, WPA- TKIP, WPA2-AES, WPA2-PSK, WPS ARP, RARP, BOOTP, DHCP,	Operating relative humidity (H-H) Storage temperature (T-T)	20 - 80% 0 - 40 °C 10 - 32 °C
	AUTH, WPA-AES, WPA-PSK, WPA- TKIP, WPA2-AES, WPA2-PSK, WPS ARP, RARP, BOOTP, DHCP, APIPA(Auto IP), WINS/NetBIOS, DNS resolver, mDNS, LLMNR responder,	Operating relative humidity (H-H)	0 - 40 °C
Security algorithms Supported network protocols (IPv4)	AUTH, WPA-AES, WPA-PSK, WPA-TKIP, WPA2-AES, WPA2-PSK, WPS ARP, RARP, BOOTP, DHCP, APIPA(Auto IP), WINS/NetBIOS, DNS resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/Port	Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T)	0 - 40 °C 10 - 32 °C
	AUTH, WPA-AES, WPA-PSK, WPA-TKIP, WPA2-AES, WPA2-PSK, WPS ARP, RARP, BOOTP, DHCP, APIPA(Auto IP), WINS/NetBIOS, DNS resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, SNMPv1/v2c, HTTP Server, TFTP Client/Server,	Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H)	0 - 40 °C 10 - 32 °C
	AUTH, WPA-AES, WPA-PSK, WPA-TKIP, WPA2-AES, WPA2-PSK, WPS ARP, RARP, BOOTP, DHCP, APIPA(Auto IP), WINS/NetBIOS, DNS resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, SNMPv1/v2c, HTTP Server, TFTP Client/Server, SMTP Client, ICMP, Web Services	Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Sustainability	0 - 40 °C 10 - 32 °C 35 - 85%
	AUTH, WPA-AES, WPA-PSK, WPA-TKIP, WPA2-AES, WPA2-PSK, WPS ARP, RARP, BOOTP, DHCP, APIPA(Auto IP), WINS/NetBIOS, DNS resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, SNMPv1/v2c, HTTP Server, TFTP Client/Server, SMTP Client, ICMP, Web Services NDP, RA, DNS Resolver, mDNS, LLMNR responder, LPR/LPD, Custom	Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Sustainability Sustainability certificates	0 - 40 °C 10 - 32 °C 35 - 85%
	AUTH, WPA-AES, WPA-PSK, WPA-TKIP, WPA2-AES, WPA2-PSK, WPS ARP, RARP, BOOTP, DHCP, APIPA(Auto IP), WINS/NetBIOS, DNS resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, SNMPv1/v2c, HTTP Server, TFTP Client/Server, SMTP Client, ICMP, Web Services NDP, RA, DNS Resolver, mDNS,	Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Sustainability Sustainability certificates Weight & dimensions	0 - 40 °C 10 - 32 °C 35 - 85% ENERGY STAR
Supported network protocols (IPv4)	AUTH, WPA-AES, WPA-PSK, WPA-TKIP, WPA2-AES, WPA2-PSK, WPS ARP, RARP, BOOTP, DHCP, APIPA(Auto IP), WINS/NetBIOS, DNS resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, SNMPv1/v2c, HTTP Server, TFTP Client/Server, SMTP Client, ICMP, Web Services NDP, RA, DNS Resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/ Port 9100, IPP, FTP Server, SNMPv1/v2c, HTTP Server, TFTP Client/Server, SMTP Client,	Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Sustainability Sustainability certificates Weight & dimensions Width Depth Height	0 - 40 °C 10 - 32 °C 35 - 85% ENERGY STAR 438 mm 410 mm 478 mm
Supported network protocols (IPv4)	AUTH, WPA-AES, WPA-PSK, WPA-TKIP, WPA2-AES, WPA2-PSK, WPS ARP, RARP, BOOTP, DHCP, APIPA(Auto IP), WINS/NetBIOS, DNS resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, SNMPv1/v2c, HTTP Server, TFTP Client/Server, SMTP Client, ICMP, Web Services NDP, RA, DNS Resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/ Port 9100, IPP, FTP Server, SNMPv1/v2c, HTTP Server,	Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Sustainability Sustainability certificates Weight & dimensions Width Depth Height Weight	0 - 40 °C 10 - 32 °C 35 - 85% ENERGY STAR 438 mm 410 mm
Supported network protocols (IPv4) Supported network protocols (IPv6)	AUTH, WPA-AES, WPA-PSK, WPA-TKIP, WPA2-AES, WPA2-PSK, WPS ARP, RARP, BOOTP, DHCP, APIPA(Auto IP), WINS/NetBIOS, DNS resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, SNMPv1/v2c, HTTP Server, TFTP Client/Server, SMTP Client, ICMP, Web Services NDP, RA, DNS Resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/ Port 9100, IPP, FTP Server, SNMPv1/v2c, HTTP Server, TFTP Client/Server, SMTP Client, ICMPv6, Web Services	Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Sustainability Sustainability certificates Weight & dimensions Width Depth Height Weight Packaging data	0 - 40 °C 10 - 32 °C 35 - 85% ENERGY STAR 438 mm 410 mm 478 mm 7.13 kg
Supported network protocols (IPv4) Supported network protocols (IPv6) Mobile printing technologies Performance	AUTH, WPA-AES, WPA-PSK, WPA-TKIP, WPA2-AES, WPA2-PSK, WPS ARP, RARP, BOOTP, DHCP, APIPA(Auto IP), WINS/NetBIOS, DNS resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, SNMPv1/v2c, HTTP Server, TFTP Client/Server, SMTP Client, ICMP, Web Services NDP, RA, DNS Resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/ Port 9100, IPP, FTP Server, SNMPv1/v2c, HTTP Server, TFTP Client/Server, SMTP Client, ICMPv6, Web Services Brother iPrint & Scan	Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Sustainability Sustainability certificates Weight & dimensions Width Depth Height Weight Packaging data Package width	0 - 40 °C 10 - 32 °C 35 - 85% ENERGY STAR 438 mm 410 mm 478 mm 7.13 kg
Supported network protocols (IPv4) Supported network protocols (IPv6) Mobile printing technologies	AUTH, WPA-AES, WPA-PSK, WPA-TKIP, WPA2-AES, WPA2-PSK, WPS ARP, RARP, BOOTP, DHCP, APIPA(Auto IP), WINS/NetBIOS, DNS resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, SNMPv1/v2c, HTTP Server, TFTP Client/Server, SMTP Client, ICMP, Web Services NDP, RA, DNS Resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/ Port 9100, IPP, FTP Server, SNMPv1/v2c, HTTP Server, TFTP Client/Server, SMTP Client, ICMPv6, Web Services	Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Sustainability Sustainability certificates Weight & dimensions Width Depth Height Weight Packaging data Package width Package depth	0 - 40 °C 10 - 32 °C 35 - 85% ENERGY STAR 438 mm 410 mm 478 mm 7.13 kg
Supported network protocols (IPv4) Supported network protocols (IPv6) Mobile printing technologies Performance Card reader integrated	AUTH, WPA-AES, WPA-PSK, WPA-TKIP, WPA2-AES, WPA2-PSK, WPS ARP, RARP, BOOTP, DHCP, APIPA(Auto IP), WINS/NetBIOS, DNS resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, SNMPv1/v2c, HTTP Server, TFTP Client/Server, SMTP Client, ICMP, Web Services NDP, RA, DNS Resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/ Port 9100, IPP, FTP Server, SNMPv1/v2c, HTTP Server, TFTP Client/Server, SMTP Client, ICMPv6, Web Services Brother iPrint & Scan	Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Sustainability Sustainability certificates Weight & dimensions Width Depth Height Weight Packaging data Package width	0 - 40 °C 10 - 32 °C 35 - 85% ENERGY STAR 438 mm 410 mm 478 mm 7.13 kg
Supported network protocols (IPv4) Supported network protocols (IPv6) Mobile printing technologies Performance Card reader integrated	AUTH, WPA-AES, WPA-PSK, WPA-TKIP, WPA2-AES, WPA2-PSK, WPS ARP, RARP, BOOTP, DHCP, APIPA(Auto IP), WINS/NetBIOS, DNS resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, SNMPv1/v2c, HTTP Server, TFTP Client/Server, SMTP Client, ICMP, Web Services NDP, RA, DNS Resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/ Port 9100, IPP, FTP Server, SNMPv1/v2c, HTTP Server, TFTP Client/Server, SMTP Client, ICMPv6, Web Services Brother iPrint & Scan	Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Sustainability Sustainability Sustainability certificates Weight & dimensions Width Depth Height Weight Packaging data Package width Package depth Package height	0 - 40 °C 10 - 32 °C 35 - 85% ENERGY STAR 438 mm 410 mm 478 mm 7.13 kg 481 mm 436 mm 406 mm
Supported network protocols (IPv4) Supported network protocols (IPv6) Mobile printing technologies Performance Card reader integrated	AUTH, WPA-AES, WPA-PSK, WPA-TKIP, WPA2-AES, WPA2-PSK, WPS ARP, RARP, BOOTP, DHCP, APIPA(Auto IP), WINS/NetBIOS, DNS resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, SNMPv1/v2c, HTTP Server, TFTP Client/Server, SMTP Client, ICMP, Web Services NDP, RA, DNS Resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/ Port 9100, IPP, FTP Server, SNMPv1/v2c, HTTP Server, TFTP Client/Server, SMTP Client, ICMPv6, Web Services Brother iPrint & Scan	Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Sustainability Sustainability Sustainability certificates Weight & dimensions Width Depth Height Weight Packaging data Package width Package depth Package height Package weight	0 - 40 °C 10 - 32 °C 35 - 85% ENERGY STAR 438 mm 410 mm 478 mm 7.13 kg 481 mm 436 mm 406 mm
Supported network protocols (IPv4) Supported network protocols (IPv6) Mobile printing technologies Performance Card reader integrated	AUTH, WPA-AES, WPA-PSK, WPA-TKIP, WPA2-AES, WPA2-PSK, WPS ARP, RARP, BOOTP, DHCP, APIPA(Auto IP), WINS/NetBIOS, DNS resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, SNMPv1/v2c, HTTP Server, TFTP Client/Server, SMTP Client, ICMP, Web Services NDP, RA, DNS Resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/ Port 9100, IPP, FTP Server, SNMPv1/v2c, HTTP Server, TFTP Client/Server, SMTP Client, ICMPv6, Web Services Brother iPrint & Scan	Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Sustainability Sustainability certificates Weight & dimensions Width Depth Height Weight Packaging data Package width Package depth Package height Package weight Packaging content	0 - 40 °C 10 - 32 °C 35 - 85% ENERGY STAR 438 mm 410 mm 478 mm 7.13 kg 481 mm 436 mm 406 mm 8.8 kg
Supported network protocols (IPv4) Supported network protocols (IPv6) Mobile printing technologies Performance Card reader integrated	AUTH, WPA-AES, WPA-PSK, WPA-TKIP, WPA2-AES, WPA2-PSK, WPS ARP, RARP, BOOTP, DHCP, APIPA(Auto IP), WINS/NetBIOS, DNS resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, SNMPv1/v2c, HTTP Server, TFTP Client/Server, SMTP Client, ICMP, Web Services NDP, RA, DNS Resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/ Port 9100, IPP, FTP Server, SNMPv1/v2c, HTTP Server, TFTP Client/Server, SMTP Client, ICMPv6, Web Services Brother iPrint & Scan	Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Sustainability Sustainability Sustainability certificates Weight & dimensions Width Depth Height Weight Packaging data Package width Package depth Package depth Package weight Packaging content Bundled software	0 - 40 °C 10 - 32 °C 35 - 85% ENERGY STAR 438 mm 410 mm 478 mm 7.13 kg 481 mm 436 mm 406 mm 8.8 kg
Supported network protocols (IPv4) Supported network protocols (IPv6) Mobile printing technologies Performance Card reader integrated	AUTH, WPA-AES, WPA-PSK, WPA-TKIP, WPA2-AES, WPA2-PSK, WPS ARP, RARP, BOOTP, DHCP, APIPA(Auto IP), WINS/NetBIOS, DNS resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, SNMPv1/v2c, HTTP Server, TFTP Client/Server, SMTP Client, ICMP, Web Services NDP, RA, DNS Resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/ Port 9100, IPP, FTP Server, SNMPv1/v2c, HTTP Server, TFTP Client/Server, SMTP Client, ICMPv6, Web Services Brother iPrint & Scan	Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Sustainability Sustainability Sustainability certificates Weight & dimensions Width Depth Height Weight Packaging data Package width Package depth Package height Package weight Packaging content Bundled software Logistics data Harmonized System (HS) code Pallet gross height	0 - 40 °C 10 - 32 °C 35 - 85% ENERGY STAR 438 mm 410 mm 478 mm 7.13 kg 481 mm 436 mm 406 mm 8.8 kg Brother BRAdmin Light Network Management 84433100 17.7 cm
Supported network protocols (IPv4) Supported network protocols (IPv6) Mobile printing technologies Performance Card reader integrated	AUTH, WPA-AES, WPA-PSK, WPA-TKIP, WPA2-AES, WPA2-PSK, WPS ARP, RARP, BOOTP, DHCP, APIPA(Auto IP), WINS/NetBIOS, DNS resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, SNMPv1/v2c, HTTP Server, TFTP Client/Server, SMTP Client, ICMP, Web Services NDP, RA, DNS Resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/ Port 9100, IPP, FTP Server, SNMPv1/v2c, HTTP Server, TFTP Client/Server, SMTP Client, ICMPv6, Web Services Brother iPrint & Scan	Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Sustainability Sustainability Sustainability certificates Weight & dimensions Width Depth Height Weight Packaging data Package width Package depth Package height Package weight Packaging content Bundled software Logistics data Harmonized System (HS) code Pallet gross weight	0 - 40 °C 10 - 32 °C 35 - 85% ENERGY STAR 438 mm 410 mm 478 mm 7.13 kg 481 mm 436 mm 406 mm 8.8 kg Brother BRAdmin Light Network Management 84433100 17.7 cm 162 kg
Supported network protocols (IPv4) Supported network protocols (IPv6) Mobile printing technologies Performance Card reader integrated	AUTH, WPA-AES, WPA-PSK, WPA-TKIP, WPA2-AES, WPA2-PSK, WPS ARP, RARP, BOOTP, DHCP, APIPA(Auto IP), WINS/NetBIOS, DNS resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, SNMPv1/v2c, HTTP Server, TFTP Client/Server, SMTP Client, ICMP, Web Services NDP, RA, DNS Resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/ Port 9100, IPP, FTP Server, SNMPv1/v2c, HTTP Server, TFTP Client/Server, SMTP Client, ICMPv6, Web Services Brother iPrint & Scan	Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Sustainability Sustainability Sustainability certificates Weight & dimensions Width Depth Height Weight Packaging data Package width Package depth Package height Package weight Packaging content Bundled software Logistics data Harmonized System (HS) code Pallet gross height	0 - 40 °C 10 - 32 °C 35 - 85% ENERGY STAR 438 mm 410 mm 478 mm 7.13 kg 481 mm 436 mm 406 mm 8.8 kg Brother BRAdmin Light Network Management 84433100 17.7 cm

Technical details

Master (outer) cases per pallet layer 4 pc(s)

Pallet type 1200 x 1000 mm

Other features

Energy saving mode

Spare part retention 5 year(s)














Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.