



APC Power Cord Kit (6 ea), Locking, C13 to C14, 1.2m

Brand : APCProduct code: AP8704S-WW

Product name : Power Cord Kit (6 ea), Locking, C13 to C14, 1.2m



Power Cord Kit (6 ea), Locking, C13 to C14, 1.2m

APC Power Cord Kit (6 ea), Locking, C13 to C14, 1.2m:

This Series of Rack Power Distribution Units (PDU) comes with Locking IEC Receptacles. The output and input connections are C13 to C14. The cord length is 1.2m. Locking IEC system allows the use of optional locking IEC power cords for added power cord security and enhanced reliability. No tools are required to disengage the locking feature and remove the plug from the locking receptacle.  
APC Power Cord Kit (6 ea), Locking, C13 to C14, 1.2m. Cable length: 1.2 m, Connector 1: C13 coupler, Connector 2: C14 coupler. Input current: 10 A

| Features                          |             | Operational conditions              |            |
|-----------------------------------|-------------|-------------------------------------|------------|
| Product colour *                  | Black       | Storage relative humidity (H-H)     | 20 - 80%   |
| Connector 1 gender *              | Female      | Operating altitude                  | 0 - 3000 m |
| Connector 2 gender *              | Male        | Certificates                        |            |
| Cable length *                    | 1.2 m       | Compliance certificates             | RoHS       |
| Connector 1 *                     | C13 coupler | Weight & dimensions                 |            |
| Connector 2 *                     | C14 coupler | Width                               | 70 mm      |
| Power                             |             | Depth                               | 45 mm      |
| Input current                     | 10 A        | Height                              | 240 mm     |
| Operational conditions            |             | Weight                              | 1.01 kg    |
| Operating temperature (T-T)       | 0 - 70 °C   | Logistics data                      |            |
| Storage temperature (T-T)         | -25 - 75 °C | Harmonized System (HS) code         | 84733080   |
| Operating relative humidity (H-H) | 20 - 80%    | Total carbon footprint (kg of CO2e) | 317.74     |



0731304296478



731304296478

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.