
## D-Link

## D-Link DES-1005D Unmanaged Fast Ethernet (10/100) Black

**Brand :** D-Link **Product code:** DES-1005D/E

**Product name:** DES-1005D







Management features		Operational conditions	
Switch type *  Ports & interfaces	Unmanaged	Storage temperature (T-T) Operating relative humidity (H-H)	-10 - 70 °C 10 - 90%
Basic switching RJ-45 Ethernet ports		Storage relative humidity (H-H)	5 - 90%
quantity *	5	Heat dissipation	8.528 BTU/h
Basic switching RJ-45 Ethernet ports type *	Fast Ethernet (10/100)	Weight & dimensions	
Power connector	DC-in jack	Width	125.3 mm
Network		Depth Height	83.4 mm 29.1 mm
Networking standards *	IEEE 802.3, IEEE 802.3u, IEEE 802.3x	Packaging content	
10G support *	X	Cables included	AC
Copper ethernet cabling technology	100Base-TX, 10Base-T	User guide	✓
Cable types supported	Cat3, Cat4, Cat5, Cat5e	Manual	✓
Full duplex	✓	Packaging data	
Flow control support	✓	Package width	65 mm
Auto MDI/MDI-X	✓	Package depth	105 mm
Auto-negotiation	✓	Package height	98 mm
MAC address auto-learning	/	Package weight	170 g
supported	·	Technical details	
Data transmission		Shipping (inner) case height	23 cm
Supported data transfer rates	10/20/100/200 Mb/s	Shipping (inner) case width	35 cm
Switching capacity *	1 Gbit/s	Shipping (inner) case length	51.5 cm
Forwarding rate	0.1488 Mpps	Shipping (inner) case net weight	8.5 kg
MAC address table *	2000 entries	Products per shipping (inner) case	50 pc(s)
Store-and-forward	<b>✓</b>	Pallet gross weight (air)	465.2 kg
Maximum data transfer rate	0.2 Gbit/s	Master (outer) cases per pallet (air)	48 pc(s)
Packet buffer memory	0.046875 MB	Products per pallet (air) Pallet gross length	2400 pc(s) 110 cm
Design		Pallet gross width	120 cm
Rack mounting *	×	Pallet height (air)	197.5 cm
Stackable *	×	Pallet gross weight (sea)	465.2 kg
Product colour	Black	Master (outer) cases per pallet (sea)	•
LED indicators	LAN, Power	Products per pallet (sea)	2400 pc(s)
Performance		Pallet height (sea)	197.5 cm
Plug and Play	✓	Shipping (inner) case gross weight	9.25 kg
Power		Certificates	
Power consumption (typical)	2.5 W	Certification	RoHS, FCC, CE

Power over Ethernet (PoE)		Logistics data	
Power over Ethernet (PoE) *	×	Harmonized System (HS) code	85176990
Other features			
Packet transfer speed	14880 - 148800 p/s		
Power LED	✓		
Operational conditions			
Operating temperature (T-T)	0 - 50 °C		





7612758090764

0790069217524



790069217524

## **Catalog Object Cloud**



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.