Epson WorkForce DS-70000

Product code: B11B204331 **Brand**: Epson **Product family:** WorkForce

Product name : Epson WorkForce DS-70000



ReadyScan LED, 600 DPI, A3, 70 ppm, USB 2.0 Type B Epson WorkForce DS-70000. Maximum scan size: 297 x 2540 mm, Optical scanning resolution: 600 x 600 DPI, Input colour depth: 48 bit. Scanner type: Flatbed & ADF scanner, Product colour: Grey. Daily duty cycle (max): 8000 pages, Scan file formats: JPG, PDF, TIFF, Scan to: E-mail, FTP. Standard input capacity: 200 sheets. Maximum ISO A-series paper size: A3, ISO A-series sizes (A0...A9): A3, A4, A5, A6, ISO B-series sizes (B0...B9): B4, B5, B6

| Scanning | | Packaging content | |
|--|--|---|---|
| Maximum scan size * Optical scanning resolution * Colour scanning Duplex scanning * Input colour depth Output colour depth | 297 x 2540 mm 600 x 600 DPI 48 bit 24 bit | Bundled software | EpsonNet Config, Epson Document Capture Pro Server (on free download), Epson Document Capture Pro, ABBYY FineReader Sprint 9.0 (Windows), ABBYY FineReader Sprint 8.0 (MacOS), Epson Scan, Epson Event Manager (Mac Only) |
| Film scanning | x | Sustainability | |
| ADF scan speed (b/w, A4) | 70 ppm | Sustainability certificates | ENERGY STAR |
| ADF scan speed (colour, A4) | 70 ppm | System requirements | |
| Design | | Mac compatibility | 1 |
| Scanner type * Product colour * Display Built-in display * | Flatbed & ADF scanner Grey X | Compatible operating systems | XenApp 6.0, XenApp 5.0, Windows server 2003 R2, Windows XP x64, Windows XP, Windows Vista x64, Windows Vista, Windows Server 2008 R2, Windows Server 2008 (32/64bit), Windows 7 x64, Windows 7, Terminal Service, Presentation Server 4.5, Mac OS 10.6+, Mac OS 10.5+, Mac OS 10.4+ |
| Performance Scan file formats Daily duty cycle (max) * | JPG, PDF, TIFF 8000 pages | | |
| Scan to | E-mail, FTP | Windows operating systems | ✓ |
| Input capacity | · | Mac operating systems supported | ✓ |
| Standard input capacity | 200 sheets | , , , , , , , , | • |
| Paper handling | | Operational conditions | |
| Maximum ISO A-series paper size * ISO A-series sizes (A0A9) ISO B-series sizes (B0B9) Letter | A3 A3, A4, A5, A6 B4, B5, B6 | Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) | 5 - 35 °C -25 - 60 °C 10 - 80% 10 - 85% |
| Legal | ✓ | Other features | |
| Auto Document Feeder (ADF) media | 35 - 128 g/m² | Network ready | × |
| weight Ports & interfaces | 33 120 g/m | Standard media sizes | B6, B5, B4, A6, A5, A4, A3, Letter, Legal, Executive |
| USB port * USB version Standard interfaces | 2.0 USB 2.0 | Box contents | Main unit, Power cable, Setup guide, Software (CD), USB cable, Warranty document |
| Power | | | |
| Power supply type * Power consumption (typical) Power consumption (standby) Input voltage | AC 79 W 1.5 W 100-240 V | | |
| Weight & dimensions | | | |
| Width | 640 mm | | |

| Weight & dimensions | | Other features | |
|---|--|--|--|
| Depth Height Weight | 522 mm 289 mm 26.9 kg | Special features | Zonal OCR A & B support, Barcode Recognition, Automatic Folder Creation, Book spine correction, Descreening, Unsharp Mask (USM), Advanced cropping feature for Auto size, Edge enhancement, Text enhancement, Auto-rotation, Dual Image Output (Windows only), RGB colour enhance, Automatic multidocument recognition, Automatic de-skew, Automatic area segmentation, Pre-defined scanning settings, Punch holes removal, Skip blank page, RGB colour dropout, |
| Packaging data Quantity per pack Package width Package depth Package height Package weight | 1 pc(s) 534 mm 875 mm 745 mm 35 kg | | |
| | | Media weight (tray 1) | One keypress Auto loading:35 - 128 g/m ² |
| | | Logistics data | |
| | | Products per pallet Country of origin Pallet gross length Pallet gross width Pallet gross height Products per pallet layer Products per pallet layer (UK) Products per pallet (UK) Pallet length (UK) Pallet width (UK) Pallet height (UK) Harmonized System (HS) code | 3 pc(s) China 120 cm 80 cm 180 cm 1 pc(s) 1 pc(s) 3 pc(s) 120 cm 100 cm 180 cm 84716070 |



8715946499239

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.