Canon

Canon imageFORMULA DR-M160II Sheet-fed scanner 600 x 600 DPI A4 Black

Brand : Canon

Product family: imageFORMULA

Product code: 9725B003

Product name : DR-M160II

CMOS CIS, 600 dpi, RGB LED, 60ppm, USB 2.0, RoHS, Energy Star

Canon imageFORMULA DR-M160II Sheet-fed scanner 600 x 600 DPI A4 Black:

Productive, ultra-compact scanner ideal for reliable paper-intensive scanning.

The imageFORMULA DR-M160II is a productivity-boosting desktop scanner. With a robust design, fast speed and reliable media handling, it is ideal for paper-intensive scanning.

Benefits

- Class-leading colour scanning speeds of up to 120ipm
- Robust design to handle up to 7,000 scans/day
- Windows, Mac and Linux compatible
- Compactly built and highly productive
- Supreme paper-handling reliability includes paper separation retry

Canon imageFORMULA DR-M160II. Maximum scan size: 216 x 3000 mm, Optical scanning resolution: 600 x 600 DPI, Output colour depth: 24 bit. Scanner type: Sheet-fed scanner, Product colour: Black. Sensor type: CMOS CIS, Daily duty cycle (max): 7000 pages, Light source: RGB LED. Standard input capacity: 60 sheets. Maximum ISO A-series paper size: A4

Scanning

Maximum scan size *	216 x 3000 mm
Optical scanning resolution *	600 x 600 DPI
Colour scanning	✔
Duplex scanning *	✔
Output colour depth	24 bit
Output greyscale depth	8 bit
Film scanning	✘
Greyscale levels	256
ADF scan speed (b/w, A4)	60 ppm
ADF scan speed (colour, A4)	60 ppm
Duplex ADF scan speed (b/w, A4)	120 ipm
Duplex ADF scan speed (colour, A4)	120 ipm
Black/white scanning colour modes	Grayscale

Design

Scanner type *	Sheet-fed scanner
Product colour *	Black
Built-in display *	✘

Performance

Sensor type *	CMOS CIS
Light source	RGB LED
Daily duty cycle (max) *	7000 pages
Scan drivers	ISIS, TWAIN

Input capacity

Standard input capacity	60 sheets

Paper handling

Maximum ISO A-series paper size *	A4

Ports & interfaces

USB port *	✔
USB version	2.0
Standard interfaces	USB 2.0

Power

Power supply type *	AC
Power consumption (typical)	27 W
Power consumption (standby)	1.8 W
Power consumption (off)	0.5 W
AC input frequency	50 - 60 Hz
Input voltage	100-240 V

Weight & dimensions

Width	280 mm
Depth	606 mm
Height	366.4 mm
Weight	3.2 kg

Packaging content

Drivers included	✔
Bundled software	CapturePerfect CaptureOnTouch eCopy PDF Pro Office Kofax VRS (with AIPE) Plug-in: EMC Captiva Cloud Runtime Controls

Sustainability

Sustainability certificates	ENERGY STAR

System requirements

Windows operating systems supported	✔
Mac operating systems supported	✔

Other features

Other features	
Compliance certificates	RoHS
Logistics data	
Harmonized System (HS) code	84716070

Catalog Object Cloud