



D-Link Wireless AC1300 Wave 2 Outdoor IP67 Cloud Managed Access Point

Brand : D-Link


Product code: DBA-3621P

Product name : D-Link Wireless AC1300 Wave 2 Outdoor IP67 Cloud Managed Access Point

- Centralized cloud-based management, with intuitive web and app-based interface
 - Slice through congestion with better handling of multiple connections thanks to IEEE 802.11ac Wave 2 wireless
 - 2 x 2 MU-MIMO Antenna with two spatial streams handles simultaneous connections more efficiently
 - Supports WPA3™ - the latest WiFi security for more protection
 - Band Steering pushes 5 GHz capable devices onto the faster band
 - Beamforming tracks devices, giving better connectivity while on the move
 - Create a secure guest network with social login amongst other authentication options
 - Supports Power over Ethernet for simpler installation with less cable clutter
 - With Zero Touch Deployment, deployment is flexible and fast: get online in no time
 - IP67-rated water-resistant and dust-resistant housing
- Nuclias Cloud-Managed AC1300 Wave 2 Outdoor Access Point, 2 x 2 MU-MIMO, Dual-band



Features		Design	
2.4 GHz *	✓	International Protection (IP) code	IP67
5 GHz *	✓	Antenna	
Maximum data transfer rate *	1267 Mbit/s	Antenna type *	External
Maximum data transfer rate (2.4 GHz)	400 Mbit/s	Antennas quantity	2
Maximum data transfer rate (5 GHz)	867 Mbit/s	Antenna gain level (max)	5 dBi
Ethernet LAN data rates	10,100,1000 Mbit/s	Antenna connector type	N-type
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3az, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x	Certificates	
		Certification	CE Class B FCC Class B UL IC Class B
Cabling technology	10/100/1000Base-T(X)	Weight & dimensions	
Flow control support	✓	Width	160 mm
Security		Depth	79.5 mm
Security algorithms *	AES, SSID	Height	460 mm
MAC address filtering	✓	Weight	1.38 kg
Ports & interfaces		Operational conditions	
Ethernet LAN (RJ-45) ports *	1	Operating relative humidity (H-H)	10 - 90%
Power		Operating temperature (T-T)	-40 - 50 °C
Power over Ethernet (PoE) *	✓	Storage temperature (T-T)	-40 - 65 °C
Power consumption (typical)	13.5 W	Storage relative humidity (H-H)	5 - 90%
Design		Logistics data	
Placement *	In-wall, Pole	Harmonized System (HS) code	85176990
Product colour *	White		



0790069454448



790069454448

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.