Viewsonic TD2760 computer monitor 68.6 cm (27") 1920 x 1080 pixels Full HD LED Touchscreen Multi-user Black

Brand : Viewsonic

Product code: TD2760

Product name : TD2760

27", 1920x1080, 16:9, MVA, 3000:1, 12ms, 230 cd/m2, 16.7M, 2xUSB 3.1 Typw-A, 1xUSB 3.1 Typw-B, 3.5mm Audio in, 3.5mm Audio out, VGA, HDMI 1.4, RS232, Display Port, 32W, VESA 100 x 100, 660x443x239 mm, 17400g

Viewsonic TD2760. Display diagonal: 68.6 cm (27"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LED, Response time: 6 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting. Product colour: Black

Display

Display diagonal *	68.6 cm (27")
Display resolution *	1920 x 1080 pixels
HD type *	Full HD
Native aspect ratio *	16:9
Display technology *	LED
Panel type *	VA
LED backlight	✔
Backlight type	LED
Touchscreen *	✔
Touchscreen type	Multi-user
Touchscreen technology	Projected capacitive system
Touch technology	Multi-touch
Number of simultaneous touchpoints	10
Display brightness	300 cd/m²
Response time *	6 ms
Anti-glare screen	✔
Screen shape *	Flat
Aspect ratio	16:9
Contrast ratio (typical) *	3000:1
Contrast ratio (dynamic)	50000000:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours *	16.78 million colours
Pixel pitch	0.311 x 0.311 mm
Horizontal scan range	15 - 90 kHz
Vertical scan range	50 - 76 Hz
Viewable size, horizontal	59.8 cm
Viewable size, vertical	33.6 cm
Display diagonal (metric)	68.58 cm
Surface hardness	6H
Separate H/V sync	✔

Ports & interfaces

DisplayPorts quantity	1
DisplayPort version	1.2
Audio input	1
Audio output	1
HDCP	✔
RS-232 ports	1

Ergonomics

VESA mounting *	✔
Panel mounting interface	100 x 100 mm
Wall mountable	✔
Cable lock slot *	✔
Cable lock slot type	Kensington
Tilt adjustment	✔
Tilt angle range	-4 - 90°
On Screen Display (OSD)	✔
Number of OSD languages	14

Power

Energy efficiency class (SDR) *	F
Energy consumption (SDR) per 1000 hours *	19 kWh
Power consumption (typical) *	26 W
Power consumption (standby) *	0.3 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Power supply type	AC
European Product Registry for Energy Labelling (EPREL) code	384384

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	20 - 90%

Performance

NVIDIA G-SYNC *	✘
AMD FreeSync *	✘

Multimedia

Number of speakers	2
RMS rated power	4 W
Built-in speaker(s) *	✔
Built-in microphone	✘
Built-in camera *	✘

Design

Product colour *	Black
Glass thickness	1.88 mm

Ports & interfaces

Built-in USB hub *	✔
USB hub version	3.2 Gen 1 (3.1 Gen 1)
USB upstream port type	USB Type-B
Number of upstream ports	1
Number of USB Type-B upstream ports quantity	1
USB Type-A downstream ports quantity	2
VGA (D-Sub) ports quantity	1
HDMI *	✔
HDMI ports quantity	1
HDMI version	1.4

Weight & dimensions

Width (with stand)	660 mm
Depth (with stand)	239 mm
Height (with stand)	443 mm
Weight (with stand)	7.9 kg
Width (without stand)	660 mm
Depth (without stand)	58 mm
Height (without stand)	410 mm
Weight (without stand)	5.5 kg

Packaging data

Package width	753 mm
Package depth	204 mm
Package height	525 mm
Package weight	10.2 kg

Packaging content

Quick start guide	✔

Other features

Connection to PC	✔
Accessories included	Power Cable, VGA Cable, HDMI Cable, USB Cable, Audio Cable
Mean time between failures (MTBF)	30000 h
Certification	MX-CoC, Mexico Energy, CE, CE EMC, CB

Logistics data

Harmonized System (HS) code	85285210

0766907002775

766907002775

Catalog Object Cloud