



## APC Smart-UPS SMT750IC - 6x C13, USB, SmartConnect, 750VA

**Brand :** APC

**Product code:** SMT750IC

**Product name :** APC Smart-UPS SMT750IC - 6x C13, USB, SmartConnect, 750VA



- Intelligent and efficient network power protection from entry level to scaleable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices

- Includes: CD with software, Documentation CD, USB cable

APC Smart-UPS SMT750IC - 6x C13, USB, SmartConnect, 750VA

APC Smart-UPS SMT750IC - 6x C13, USB, SmartConnect, 750VA. UPS topology: Line-Interactive, Output power capacity: 0.75 kVA, Output power: 500 W. AC outlet types: C13 coupler, Power plug: C14 coupler, AC outlets quantity: 6 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Typical backup time at full load: 4.6 min, Typical backup time at half load: 15.8 min. Form factor: Tower, Product colour: Black, Cable length: 1.83 m. Compliance certificates: RoHS, Certification: CE, CSA, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, UL 1778, VDE, REACH, PEP, EOL

### Features

UPS topology *	Line-Interactive
Output power capacity *	0.75 kVA
Output power *	500 W
Waveform *	Sine
Input operation voltage (min) *	151 V
Input operation voltage (max) *	302 V
Input frequency *	50/60 Hz
Output operation voltage (min)	220 V
Output operation voltage (max)	240 V
Automatic Voltage Regulation (AVR)	✓
Surge energy rating	540 J
Efficiency	98%
Noise level	40 dB
Audible alarm(s)	✓
Auto-restart	✓

### Ports & interfaces

AC outlet types	C13 coupler
Power plug	C14 coupler
AC outlets quantity	6 AC outlet(s)
Number of output IEC jumpers	2
USB port	✓
Ethernet LAN (RJ-45) ports	1
SmartSlot	✓

### Battery

Battery technology	Sealed Lead Acid (VRLA)
Typical backup time at full load	4.6 min
Typical backup time at half load	15.8 min

### Design

Form factor *	Tower
Cable length	1.83 m
Product colour *	Black
Display type	LCD
LED indicators	Status

### Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	5 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m

### Certificates

Compliance certificates	RoHS
Certification	CE, CSA, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, UL 1778, VDE, REACH, PEP, EOL

### Packaging content

Cables included	USB cable
Manual	✓
Quick installation guide	✓

### Sustainability

Sustainability certificates	Green Premium
-----------------------------	---------------

### Weight & dimensions

Width	138 mm
Depth	358 mm
Height	157 mm

Battery		Weight & dimensions	
Battery life (max)	5 year(s)	Weight	13.2 kg
Battery recharge time	3 h	Packaging data	
Hot-swap battery	✓	Bundled software	Powershute Serial Edition
Automatic battery test	✓	Package width	278 mm
Cold start	✓	Package depth	499 mm
		Package height	301 mm
		Package weight	14.2 kg
		Logistics data	
		Products per pallet	24 pc(s)
		Harmonized System (HS) code	85078000
		Total carbon footprint (kg of CO2e)	639.93



0731304340317



731304340317

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.