StarTech.com 3-Port PCI Express USB 3.0 Card + Gigabit Ethernet

Brand : StarTech.com

Product name : 3-Port PCI Express USB 3.0 Card + Gigabit Ethernet

Product code: PEXUSB3S3GE

StarTech.com 3 Port PCI Express USB 3.0 Card + Gigabit Ethernet - Fits Standard & Low-Profile PCs - UASP Supported - Optional SATA Power
StarTech.com 3-Port PCI Express USB 3.0 Card + Gigabit Ethernet. Internal. Connectivity technology: Wired, Host interface: PCI Express, Interface: Ethernet. Maximum data transfer rate: 5000 Mbit/s. Product colour: Metallic, Red

Ports & interfaces

Connectivity technology *	Wired
Host interface *	PCI Express
Interface *	Ethernet
Ethernet LAN (RJ-45) ports	1
USB 3.2 Gen 1 (3.1 Gen 1) Type-A hub ports quantity	3
USB version	3.2 Gen 1 (3.1 Gen 1)
PCI version	2.0
PCI Card form factor	Full-height (low-profile)

Network

Maximum data transfer rate *	5000 Mbit/s
Networking standards *	IEEE 802.1p, IEEE 802.1Q, IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x
Ethernet LAN	✔
Ethernet LAN data rates	10,100,1000 Mbit/s
Cabling technology	10/100/1000BaseT(X)
Wake-on-LAN ready	✔
Auto MDIX IEEE	✔
Full duplex	✔
Jumbo frames support	✔
Auto-negotiation	✔
Jumbo frames	9000
VLAN tagging	✔

Design

Product colour	Metallic, Red
Internal *	✔

System requirements

Windows operating systems supported	Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 Pro, Windows 10 Pro x64, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Linux operating systems supported	✔
Server operating systems supported	Windows Server 2008 R2, Windows Server 2012

Design

Chipset	Renesas / NEC - µPD720201, Realtek - RTL8153
LED indicators	Activity, Link
Mean time between failures (MTBF)	1920042 h
Certification	CE, FCC

Operational conditions

Operating temperature (T-T)	5 - 50 °C
Storage temperature (T-T)	-25 - 70 °C
Operating relative humidity (H-H)	20 - 80%

Weight & dimensions

Width	18 mm
Depth	77 mm
Height	120 mm
Weight	60 g

Packaging data

Drivers included	✔
Quantity per pack	1 pc(s)
Package width	144 mm
Package depth	176 mm
Package height	33 mm
Package weight	150 g

Packaging content

Mounting brackets included	✔
Manual	✔

Technical details

Compliance certificates	RoHS

Logistics data

Harmonized System (HS) code	85176990

Other features

Flow control support	✔
USB data transfer rates	5000 Mbit/s
UASP support	✔

0065030860796

065030860796

Catalog Object Cloud