

Epson EB-L520U Standard throw projector 5200 ANSI lumens 3LCD WUXGA (1920x1200) White

Brand : Epson

Product code: V11HA30040

Product name : EB-L520U

Epson EB-L520U. Projector brightness: 5200 ANSI lumens, Projection technology: 3LCD, Projector native resolution: WUXGA (1920x1200). Light source type: Laser, Service life of light source: 20000 h, Service life of light source (economic mode): 30000 h. Focus: Manual, Focal length range: 20 - 31.8 mm, Aperture range (F-F): 1.5 - 1.7. Video processing: 10 bit, Video colour modes: Cinema, Dynamic, Presentation, sRGB, DICOM simulation mode. Serial interface type: RS-232C



| Projector | | Multimedia | |
|--|--|--|-------------------------------|
| Screen size compatibility * | 1270 - 12700 mm (50 - 500") | Built-in speaker(s) * | ✓ |
| Projector brightness * | 5200 ANSI lumens | RMS rated power | 10 W |
| Projection technology * | 3LCD | Number of built-in speakers | 1 |
| Projector native resolution * | WUXGA (1920x1200) | Design | |
| Contrast ratio (typical) * | 2500000:1 | Market positioning * | Presentation |
| Native aspect ratio * | 16:10 | Product type * | Standard throw projector |
| Number of colours | 1.07 billion colours | Product colour * | White |
| Projector brightness (economic mode) | 3640 ANSI lumens | Placement | Ceiling, Desktop, Floor, Wall |
| Vertical scan range | 192 - 240 Hz | Cable lock slot | ✓ |
| Keystone correction, horizontal | -30 - 30° | Cable lock slot type | Kensington |
| Keystone correction, vertical | -30 - 30° | Display | |
| Matrix size | 1.7 cm (0.67") | Built-in display * | ✗ |
| Light source | | Power | |
| Light source type * | Laser | Power source * | AC |
| Service life of light source * | 20000 h | Power consumption (typical) * | 293 W |
| Service life of light source (economic mode) | 30000 h | Power consumption (standby) * | 0.3 W |
| Lens system | | Power consumption (economy mode) | 223 W |
| Focus * | Manual | AC input voltage | 100-240 V |
| Focal length range | 20 - 31.8 mm | AC input frequency | 50 - 60 Hz |
| Aperture range (F-F) | 1.5 - 1.7 | Software | |
| Zoom capability | ✓ | Software support | |
| Zoom type | Manual | | |
| Zoom ratio | 1.6:1 | via: AMX, Crestron (Network), Control4, Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX Device Discovery, Control4 Simple Device Discovery Protocol | |
| Throw ratio | 1.35 - 2.2:1 | | |
| Video | | Operational conditions | |
| Analog signal format system * | Not supported | Storage temperature (T-T) | -10 - 60 °C |
| Full HD * | ✓ | Operating relative humidity (H-H) | 20 - 80% |
| 3D * | ✗ | Storage relative humidity (H-H) | 10 - 90% |
| Video processing | 10 bit | Weight & dimensions | |
| Video colour modes | Cinema, Dynamic, Presentation, sRGB, DICOM simulation mode | Width | 440 mm |
| Ports & interfaces | | Depth | 122 mm |
| USB 2.0 ports quantity | 2 | Height | 304 mm |
| USB 2.0 Type-B ports quantity | 1 | Weight * | 7.7 kg |
| | | Package width | 540 mm |

| Ports & interfaces | | Weight & dimensions | |
|------------------------------|----------------------------|-----------------------------|-------------------------------|
| Audio (L/R) in * | 1 | Package depth | 530 mm |
| Serial interface type * | RS-232C | Package height | 210 mm |
| VGA (D-Sub) ports quantity * | 3 | Package weight | 10.4 kg |
| HDMI ports quantity * | 2 | Packaging content | |
| DVI port * | ✗ | Remote control included * | ✓ |
| Network | | Batteries included | ✓ |
| Ethernet LAN * | ✓ | Cables included | AC, HDMI |
| Wi-Fi * | ✓ | Warranty card | ✓ |
| Wi-Fi standards | 802.11a, Wi-Fi 4 (802.11n) | Bundled software | EasyMP Multi PC Projection |
| Storage | | Technical details | |
| Card reader integrated * | ✗ | USB display function | 3 in 1: Image / Mouse / Sound |
| Features | | Sustainability certificates | TCO |
| Noise level (economic mode) | 23 dB | Logistics data | |
| Noise level * | 31 dB | Quantity per pack | 1 pc(s) |
| Country of origin | Philippines | Products per pallet | 14 pc(s) |
| | | Pallet gross weight | 0 g |
| | | Products per pallet (UK) | 14 pc(s) |
| | | Pallet weight (UK) | 0 g |
| | | Harmonized System (HS) code | 85286200 |



8715946695563

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.