

## HP Intel Pentium G3440T processor 2.8 GHz 3 MB Smart Cache

Brand: HP Product code: 773233-001

Product name: Intel Pentium G3440T

Intel Pentium G3440T, 3M Cache, 2.8 GHz, 5 GT/s DMI2

## HP Intel Pentium G3440T processor 2.8 GHz 3 MB Smart Cache:

Options, accessories, services and support for all your HP and Compaq products. HP Intel Pentium G3440T. Processor family: Intel Pentium G, Processor socket: LGA 1150 (Socket H3), Processor lithography: 22 nm. Memory channels: Dual-channel, Maximum internal memory supported by processor: 32 GB, Memory types supported by processor: DDR3-SDRAM, DDR3L. On-board graphics card model: Intel® HD Graphics, Maximum on-board graphics card memory: 1.7 GB, On-board graphics card outputs supported: DVI, DisplayPort, Embedded DisplayPort (eDP), HDMI, VGA (D-Sub). Market segment: Desktop, PCI Express configurations: 1x16, 1x8+2x4, 2x8, Supported instruction sets: SSE4.1, SSE4.2. Compatibility: EliteDesk 800 G1

Processor		Graphics	
Processor model *	G3440T	On-board graphics card refresh rate	CO.11-
Processor base frequency *	2.8 GHz	at maximum resolution (eDP - Integrated Flat Panel)	60 Hz
Processor family *	Intel Pentium G	On-board graphics card refresh rate	
Processor cores *	2	at maximum resolution (HDMI)	60 Hz
Processor socket *	LGA 1150 (Socket H3)	On-board graphics card refresh rate	60 Hz
Component for	PC	at maximum resolution (VGA)	30112
Processor lithography *	22 nm	Features	
Processor series	Intel Pentium G3000 series for Desktop	Execute Disable Bit	✓
Processor threads	2	Idle States	✓
System bus rate	5 GT/s	Thermal Monitoring Technologies	<b>✓</b>
Processor operating modes *	64-bit	Market segment	Desktop
Processor cache	3 MB	Maximum number of PCI Express	16
Processor cache type	Smart Cache	lanes	
Thermal Design Power (TDP)	35 W	PCI Express slots version	3.0
Stepping	C0	PCI Express configurations	1x16, 1x8+2x4, 2x8
Bus type	DMI2	Supported instruction sets	SSE4.1, SSE4.2
Memory bandwidth supported by processor (max)	25.6 GB/s	Scalability	1S
		CPU configuration (max)	1
Memory		Embedded options available	X
Maximum internal memory supported by processor	32 GB	Graphics & IMC lithography Thermal solution specification	22 nm PCG 2013A
Memory types supported by processor	DDR3-SDRAM, DDR3L	Processor special features	
Memory clock speeds supported by processor	1333,1600 MHz	Intel® Hyper Threading Technology (Intel® HT Technology)	×
Memory voltage supported by	1.5 V	Intel® Turbo Boost Technology	×
processor		Intel® Quick Sync Video Technology	<b>✓</b>
Memory channels * ECC	Dual-channel	Intel® Wireless Display (Intel® WiDi)	<b>✓</b>
Graphics	•	Intel® Clear Video HD Technology	,
•	/	(Intel® CVT HD)	-
On-board graphics card * On-board graphics card model *	Intel® HD Graphics	Intel® AES New Instructions (Intel® AES-NI)	×
Maximum on-board graphics card memory	1.7 GB	Enhanced Intel SpeedStep Technology	1
On-board graphics card outputs	DVI, DisplayPort, Embedded	Intel Trusted Execution Technology	×
supported	DisplayPort (eDP), HDMI, VGA (D- Sub)	Intel VT-x with Extended Page Tables (EPT)	<b>✓</b>
On-board graphics card base frequency	200 MHz	Intel TSX-NI	×

Graphics		Processor special features	
On-board graphics card dynamic frequency (max)	1100 MHz	Intel Stable Image Platform Program (SIPP)	×
Number of displays supported (on- board graphics)	3	Intel 64	✓
On-board graphics card DirectX version	11.1/12	Intel Virtualization Technology (VT-x)	<b>✓</b>
On-board graphics card OpenGL version	4.3	Intel Virtualization Technology for Directed I/O (VT-d)	X
On-hoard graphics card maximum	2560 x 1600 pixels	Conflict-Free processor	✓
		Intel® vPro™ Platform Eligibility	×
On-board graphics card maximum resolution (eDP - Integrated Flat Panel)	2560 x 1600 pixels	Operational conditions	
		Tcase	66.4 °C
On-board graphics card maximum resolution (HDMI)	1920 x 1080 pixels	Other features	
On-board graphics card maximum resolution (VGA)	1920 x 1200 pixels	Compatibility	EliteDesk 800 G1
On-board graphics card refresh rate at maximum resolution (DisplayPort)	60 Hz		

