Keep Learning or Start Over?

Plasticity-Preserving Updates for Bearing Vibration Forecasting

Elissa Ephrem eee19@mail.aub.edu
Galia Akl gra16@mail.aub.edu
Karim Bteish krb05@mail.aub.edu

Project proposal | 20 October 2026

1. Problem and motivation

As a bearing degrades, a vibration forecaster may need updating. However, continued training can reduce a neural network's ability to learn new patterns, a phenomenon called *loss of plasticity* [1]. We ask: **do simple plasticity-preserving updates improve one-hour-ahead vibration forecasting relative to ordinary continual training and periodic retraining, at comparable computational cost?** A secondary question is whether internal diagnostics predict *when an intervention helps*, rather than merely tracking current error.

We will predict $y_t = \log_{10}[\mathrm{RMS}(t+1\,\mathrm{h})/(1\,g)]$ from current and past vibration features. This is a regression task, not a remaining-useful-life (RUL) estimator or failure alarm. Our measurable objective is positive forecasting skill, $1 - \mathrm{MAE}_m/\mathrm{MAE}_b > 0$, against both ordinary updating and a validation-selected periodic-retraining baseline on the evaluation run. We also require comparison with persistence and inspection of late-life errors; success is not assumed.

2. Impact

The practical decision is whether a monitoring model should retain its weights, refresh a small part of them, or restart. A useful result identifies an accuracy–computation trade-off that maintenance analysts can examine before adopting costly adaptation. A negative result is also informative: resets may harm useful representations, or improved trainability may not improve forecasting. Underprediction during degradation is especially concerning, so we report directional and late-life errors. One laboratory rig and few failures cannot establish industrial safety or generalization. No maintenance decisions will be automated.

3. Related work and positioning

Warm starts. Ash and Adams [2] found that warm-starting can generalize worse than fresh initialization despite similar training losses, and introduced shrink-and-perturb. We reuse that lightweight intervention, but evaluate chronological vibration forecasting rather than assume its gains transfer.

Sustained learning. Dohare et al. [1] demonstrated plasticity loss in continual image-learning and reinforcement-learning settings; continual backpropagation recycles low-utility units. Their evidence motivates equal-budget trainability comparisons. We do not assume their phenomenon must appear in every bearing history.

Selective resets. Sokar et al. [3] linked increasing neuron dormancy to reduced expressivity in reinforcement learning and proposed ReDo. We test a documented ReDo-style intervention in regression, keeping architecture and data access fixed.

Interpreting diagnostics. Lyle et al. [4] connected plasticity loss to loss-landscape curvature, including cases without saturated units. Thus, neuron inactivity alone will not be treated as proof of the mechanism. In a recent preprint, Wang et al. [5] showed that rank-based diagnostics can fail to predict trainability and proposed optimization readiness. We distinguish trainability from the subsequent forecasting benefit of a specific intervention; implementing their full diagnostic is outside the core scope.

Closest bearing application. Yang et al. [6] combine BiGRU–Informer fusion with utility-based selective reinitialization for RUL prediction. Their XJTU-SY ablations report lower errors with the plasticity mechanism; supplementary FEMTO-ST experiments extend evaluation. They use successive groups of bearing histories. We found no explicit matched-budget periodic-retraining comparison or evaluation of diagnostics as predictors of future intervention benefit. Our contribution is that controlled comparison for a small chronological RMS forecaster, building on established bearing-plasticity work. We claim neither a new reset algorithm nor the first bearing application.

4. Data and preliminary exploration

Source and access. The IMS Bearing Data Set was collected by the University of Cincinnati's Center for Intelligent Maintenance Systems with Rexnord and distributed through NASA [7, 9]. The official entry is `https://data.nasa.gov/dataset/ims-bearings`. It labels the license `other-license-specified` and links U.S. government-work guidance; we preserve source acknowledgements and do not infer that third-party code licensing licenses the raw data.

Our starting point is six processed CSVs from the public `nasa-bearing-anomaly` repository [8]. All supplied files were byte-matched to commit `f8a40f9` on 20 October 2026; the repository's code is MIT-licensed. This verifies the feature-table source, not the original extraction. Week 1 includes checking representative early/late




Figure 1: Recomputed exploration of Tests 1–2. Left: unsmoothed RMS histories; * marks a documented failed bearing, gray marks the first 200 calibration observations, and lines break at irregular intervals. Right: target distributions after filtering. These are vibration forecasts, not failure-class labels. Source: supplied IMS-derived feature tables [7, 8]; figure generated by the accompanying baseline script.

Table 1: Recomputed development-data audit. Forecast counts include all four bearings; zero missing entries were found.

Quantity	Test 1	Test 2
Original / live snapshots	2,156 / 2,156	984 / 982
Eligible forecast pairs	6,428	3,104
Gaps $>$ 15 min	24	0
Target mean / SD	-0.813 / 0.035	-1.046 / 0.138
Late failed-bearing pairs	558	99

raw recordings and acquisition metadata before relying on spectral interpretations.

The rig records four bearings at 2,000 rpm under a 6,000-lb radial load, with 20,480-sample accelerometer snapshots at nominal 20 kHz [8, 9]. Tests 1–3 provide 2,156, 984 and 6,324 acquisition rows; Test 1 has two channels per bearing and the others one. We use channel 1 throughout. There are 12 bearing histories but only three runs and four documented failures; co-mounted bearings and adjacent rows are dependent.

Inputs and preprocessing. Twenty continuous features comprise RMS/std/peak (g), four shape ratios, PSD mean/std and six defect-band sums (upstream PSD units, g^2/Hz), three shape statistics, spectral entropy and a high-frequency ratio (dimensionless). Six-observation trailing means give 40 inputs. Positive scale features are log-transformed; signed shape statistics use a signed logarithm. Each bearing's first 200 observations calibrate the mean/std; an asinh transform compresses extremes. Calibration observations are excluded from fitting and scoring. Rolling windows restart at gaps. We retain six-step pairs only when intervening intervals are 9–11 min and elapsed horizon is 60 ± 1 min, with a complete trailing history.

Only the trailing acquisitions where *all four* channels fall below 20% of their calibration-median RMS are removed (two in Test 2). Test 1 has a 6.18-day gap. Snapshot noise, few failures, one operating condition and shared-shaft vibration limit conclusions; a bearing without a documented failure is not an independently certified healthy control. Figure 1 shows concentrated targets with a degradation tail. No interpolation or future-derived failure label is used as an input.

Table 2: Executed baselines: log-RMS MAE (lower is better). Train error is in-sample; validation error is out of run.

Model	Train	Validation	Val. late
Last-value persistence	0.00379	0.01128	0.06936
Moving-average persistence	0.00336	0.01124	0.07699
Ridge residual	0.00338	0.01115	0.07594
Static MLP (seed 42)	0.00336	0.01110	0.07616

5. Models and preliminary baseline

Simple baselines. Last-value and moving-average persistence encode short-horizon continuity. Ridge regression [10] predicts the residual from the trailing mean of log-RMS, testing whether the 40 features add linear predictive information. Training uses Test 1; seven ridge penalties 10^0–10^6 were compared on Test 2, selecting $\lambda = 100$ for the unnormalized squared-error objective. Table 2 reports the reproduced baseline results. Late means target time within the final 10% of elapsed live-run time, on documented failed bearings only.

Ridge and the static MLP offer small overall validation-MAE gains; last-value persistence is better late in life. The MLP has slightly worse validation RMSE than ridge (0.02585 versus 0.02567). One selected seed does not establish superiority or plasticity loss.

One neural architecture. We implemented a 40–64–64–1 ReLU MLP (6,849 parameters) in NumPy [11], including backpropagation and Adam [12]; all 49 parameters of a small version passed a finite-difference gradient check. It predicts the same residual, scaled by its training-only standard deviation, using MSE, batch size 64 and learning rate 10^{-3}. Test-2 MAE selected epoch 1; patience 25 stopped training at epoch 26. Further training lowered training error but raised validation error. These scores were reproduced on a teammate's laptop. The planned adaptive methods start from independent source-model copies for each bearing.

Four update strategies. (i) ordinary continual updates; (ii) periodic full reinitialization followed by retraining; (iii) shrink-and-perturb, $\theta \leftarrow \alpha\theta + \sigma\theta_0$ [2]; and (iv) ReDo-style resets of low relative-activation units [3], reinitializing incoming weights, zeroing outgoing weights and clearing affected optimizer state. Strategy (ii) continues updating between restarts. It tests whether preserving old weights is useful; (iii)–(iv) test gentler alternatives.

Causal updates and cost. At six-hour update times, each model uses at most the latest 200 eligible examples whose targets have already arrived; its buffer is cleared at acquisition gaps. All adaptive strategies receive the same examples, batch size and step allowance (25 or 100 steps/update). Test 2 selects restart/intervention frequency from 24 or 48 h and a small strength grid, with at most eight configurations per strategy. Initialization, optimizer resets, data access and timing will be logged. An additional retraining run with four times the step allowance checks whether strict budget limits unfairly handicap restarts; it is compared on an accuracy–cost curve, not called equal-cost.

6. Evaluation and diagnostic study

Split and reporting. Test 1 trains the source models; Test 2 selects settings; Test 3 is evaluated after settings are frozen. Test 3 has been inspected descriptively, so it is not a pristine blind dataset; no Test-3 model scores are used here. Online Test-3 updates are allowed only after labels mature, with predictions saved first. We report macro-average per-bearing MAE, pooled MAE/RMSE, late-life MAE and mean underprediction $\max(y - \hat{y}, 0)$, plus runtime, update count and reset count. Log-space errors will not be mislabeled as percentage errors.

Five paired seeds share initial weights and minibatch schedules where applicable. We will report each bearing and seed, paired error differences, and descriptive 95% moving-block bootstrap intervals (24-h blocks, 48-h sensitivity) within each run; co-mounted bearings stay grouped. These intervals describe this record, not population-level reliability. All methods use identical preprocessing; published RUL/classification scores are not numerical benchmarks for this target. Ablations include a 400-example buffer, 12-h updates and removing the range-compression transform, varied one at a time.

Secondary: predict intervention benefit. Every 24 h, copies of an ordinary continual checkpoint branch into continue, selected intervention, and fresh retraining. Each receives the same matured buffer and update budget; the branches remain frozen while forecasting the next non-overlapping 24 h. We define $\Delta = \mathrm{MAE}_{\mathrm{continue}} - \mathrm{MAE}_{\mathrm{intervention}}$. Before branching, we record dormant fraction and normalized effective rank [13]; we compare their ability to rank Δ with recent matured-label error and cumulative update count. Directions/thresholds are selected on Test 2, then evaluated on Test 3 using Spearman correlation and AUROC for $\Delta > 0$ (undefined if only one outcome class occurs). Future scores never trigger a past action.

Interpretation and fallback. A controlled probe on copies, with matched output initialization, reset optimizer state, identical targets and budget, will compare warm/fresh learning curves. A small synthetic changing-target stream checks that the implementation can expose plasticity loss. Neither random-target fit nor rank alone proves useful adaptation or causality. If the real stream shows little loss, that negative result will be reported without repeated data recycling. The core forecasting comparison remains the deliverable; a learned intervention policy and second dataset are optional.

7. Resources and code

The laptop-first implementation uses Python, NumPy, pandas [14] and Matplotlib [15]. The accompanying code includes the loader, simple and neural baselines, checksums, compact results and setup README; running it regenerates per-example predictions. The reproduced static MLP run took 1.36 s excluding plotting; this does not predict the full grid's cost. We initially budget 10–30 CPU-hours and will profile before expanding. AUB HPC and GPU computation are not required for the core scope. All members will commit regularly, review generated code and disclose AI assistance. Continual-update and plasticity experiments remain planned.

Code repository: `https://github.com/karimbteish/plasticity-bearing-forecasting`

8. Timeline and responsibilities

Elissa Ephrem leads data/provenance; Galia Akl leads models/updates; Karim Bteish leads evaluation/diagnostics. All three contribute code and writing.

Week	Milestone and owner
Oct 19	Proposal Oct 20; audit, baseline, repository (all).
Oct 26	Raw-data spot-check; timestamp/unit audit (Elissa); static MLP seed and learning-rate checks (Galia).
Nov 2	Causal stream, retraining and two interventions (Galia); paired logging and cost profiling (Karim).
Nov 9	Test-2 tuning; freeze primary protocol (Galia/Karim); checkpoint-branch pilot and data review (Elissa/Karim).
Nov 16	Progress report Nov 17 (all); five-seed development results and selected ablations (Galia/Karim).
Nov 23	Frozen Test-3 evaluation; uncertainty and diagnostic analysis (Elissa/Karim); finalize scope (all).
Nov 30	Figures, poster and rehearsal; poster session Dec 4 (all).
Dec 7	Final report, limitations and reproducibility; submit Dec 10 (all).

References

[1] Shibhansh Dohare, J. Fernando Hernandez-Garcia, Qingfeng Lan, Parash Rahman, A. Rupam Mahmood, and Richard S. Sutton. Loss of plasticity in deep continual learning. *Nature*, 632:768–774, 2024. doi: 10.1038/s41586-024-07711-7.

[2] Jordan T. Ash and Ryan P. Adams. On warm-starting neural network training. In *Advances in Neural Information Processing Systems*, volume 33, 2020. URL https://proceedings.neurips.cc/paper/2020/hash/288cd2567953f06e460a33951f55daaf-Abstract.html.

[3] Ghada Sokar, Rishabh Agarwal, Pablo Samuel Castro, and Utku Evci. The dormant neuron phenomenon in deep reinforcement learning. In *Proceedings of ICML*, volume 202 of *Proceedings of Machine Learning Research*, pages 32145–32168, 2023. URL https://proceedings.mlr.press/v202/sokar23a.html.

[4] Clare Lyle, Zeyu Zheng, Evgenii Nikishin, Bernardo Avila Pires, Razvan Pascanu, and Will Dabney. Understanding plasticity in neural networks. In *Proceedings of ICML*, volume 202 of *Proceedings of Machine Learning Research*, pages 23190–23211, 2023. URL https://proceedings.mlr.press/v202/lyle23b.html.

[5] Jiuqi Wang, Jayanth Srinivasa, Claire Chen, Shuze Daniel Liu, Ali Payani, and Shangtong Zhang. Predicting plasticity in deep continual learning: A theoretical perspective. arXiv preprint 2605.09044, 2026. Version 1, 9 May 2026.

[6] Haonan Yang, Jianchao Tang, and Shaowu Yang. TFGI: a continual learning framework for remaining useful life prediction based on temporal fusion model. *The Journal of Supercomputing*, 82:529, 2026. doi: 10.1007/s11227-026-08667-3. Published 24 June 2026.

[7] J. Lee, H. Qiu, G. Yu, J. Lin, and Rexnord Technical Services. IMS bearing data set. NASA Ames Prognostics Data Repository; data from IMS, University of Cincinnati, 2007. URL https://data.nasa.gov/dataset/ims-bearings. Accessed 20 October 2026; catalog license: other-license-specified, linking U.S. government-work guidance.

[8] fatemeh-studio. nasa-bearing-anomaly: processed IMS feature tables and data documentation. GitHub repository, 2026. URL https://github.com/fatemeh-studio/nasa-bearing-anomaly/tree/f8a40f9ec0b47aac027e69f631c1deb79c7bef66. Accessed 20 October 2026. Commit f8a40f9. Code: MIT; data terms documented separately.

[9] Hai Qiu, Jay Lee, Jing Lin, and Gang Yu. Wavelet filter-based weak signature detection method and its application on rolling element bearing prognostics. *Journal of Sound and Vibration*, 289(4–5):1066–1090, 2006. doi: 10.1016/j.jsv.2005.03.007.

[10] Arthur E. Hoerl and Robert W. Kennard. Ridge regression: Biased estimation for nonorthogonal problems. *Technometrics*, 12(1):55–67, 1970. doi: 10.1080/00401706.1970.10488634.

[11] Charles R. Harris, K. Jarrod Millman, Stéfan J. van der Walt, et al. Array programming with NumPy. *Nature*, 585:357–362, 2020. doi: 10.1038/s41586-020-2649-2.

[12] Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *International Conference on Learning Representations*, 2015. URL https://arxiv.org/abs/1412.6980.

[13] Olivier Roy and Martin Vetterli. The effective rank: A measure of effective dimensionality. In *European Signal Processing Conference (EUSIPCO)*, pages 606–610, 2007. doi: 10.5281/zenodo.40328.

[14] Wes McKinney. Data structures for statistical computing in Python. In *Proceedings of the 9th Python in Science Conference*, pages 56–61, 2010. doi: 10.25080/Majora-92bf1922-00a.

[15] John D. Hunter. Matplotlib: A 2D graphics environment. *Computing in Science & Engineering*, 9(3):90–95, 2007. doi: 10.1109/MCSE.2007.55.