

```

1 package com.example.coach.ouils;
2
3 import android.content.Context;
4 import android.database.sqlite.SQLiteDatabase;
5 import android.database.sqlite.SQLiteOpenHelper;
6
7 import androidx.annotation.Nullable;
8
9 public class MySQLiteOpenHelper extends SQLiteOpenHelper {
10     // proprietes
11     private String creation = "CREATE TABLE T_Profil("
12         + "dateMesure TEXT PRIMARY KEY,"
13         + "Poids INTEGER NOT NULL,"
14         + "Taille INTEGER NOT NULL,"
15         + "Age INTEGER NOT NULL,"
16         + "Sexe INTEGER NOT NULL)";
17
18     /**
19      *
20      * @param context
21      * @param name
22      * @param factory
23      * @param version
24      */
25     public MySQLiteOpenHelper(@Nullable Context context, @
26         Nullable String name, @Nullable SQLiteDatabase.CursorFactory
27         factory, int version) {
28         super(context, name, factory, version);
29     }
30
31     /**
32      * si changement de BD
33      * @param sqLiteDatabase
34      */
35     @Override
36     public void onCreate(SQLiteDatabase sqLiteDatabase) {
37         sqLiteDatabase.execSQL(creation);
38     }
39
40     /**
41      * si changement de version
42      * @param sqLiteDatabase
43      * @param i
44      * @param i1
45      */
46     @Override
47     public void onUpgrade(SQLiteDatabase sqLiteDatabase, int i
48         , int i1) {
49     }

```

```
48 }
```

```
49
```