

Reconstruction Metric - GPU Optimized

2026-05-19

Table of contents

0.1	1. Setup e Imports	1
0.2	2. Cargar Datos	3
0.3	3. Cargar SAE y Extraer Features	4
0.4	4. Split Train/Test y Filtrar BSPs de Piezas	5
0.5	5. Funciones GPU-Optimizadas	6
0.6	6. Fase 1: Identificar Features de Alta Precisión (GPU)	7
0.7	7. Fase 2: Reconstruir Tableros en Test Set (GPU)	10
0.8	8. Análisis de Resultados	12
0.9	9. Guardar Resultados	14
0.10	10. Generar PDF con Quarto	15

0.1 1. Setup e Imports

```
import numpy as np
import pandas as pd
import sys
import os
import subprocess
import time
import torch
import torch.nn as nn
import torch.nn.functional as F
import matplotlib.pyplot as plt

from pathlib import Path
from tqdm import tqdm
from sae.tools.experiment_utils import get_experiment_dir, get_metrics_dir, get_report_name
from sae.tools.naming_utils import get_checkpoint_dir, get_model_name, get_extras_id

project_root = Path('.../.../...').resolve()
sys.path.insert(0, str(project_root))

device = torch.device('cuda' if torch.cuda.is_available() else 'cpu')
print(f"Device: {device}")
if torch.cuda.is_available():
    print(f"GPU: {torch.cuda.get_device_name(0)}")
    print(f"Memoria: {torch.cuda.get_device_properties(0).total_memory / 1e9:.2f} GB")
```

Device: cuda
GPU: NVIDIA GeForce RTX 5060
Memoria: 8.55 GB

```
# Configuración para visualización en PDF
pd.set_option('display.max_colwidth', None)
pd.set_option('display.max_columns', None)
pd.set_option('display.width', 100)
```

```

np.set_printoptions(linewidth=100, edgeitems=3)

os.environ['COLUMNS'] = '100'

print(" Configuración para PDF lista")

```

Configuración para PDF lista

```

NAMING_META = {
    'variante': 'topk',
    'tecnica': 'batch-topk',
    'capa': 6,
    'juegos': 5000,
    'base_path': 'C:\\Users\\Esposa\\Documents\\Repos\\sae-othello-gpt',
    'experiment_base_path': os.path.abspath('../../../experiments'),
    'extras': {
        'expansion': 16,
        'k': 81,
        'epochs': 1000,
        'patience': 20,
        'batch_size_tokens': 1024,
    }
}

print('\n Metadata de naming:')
for key, value in NAMING_META.items():
    print(f' {key}: {value}')

```

Metadata de naming:

```

variante: topk
tecnica: batch-topk
capa: 6
juegos: 5000
base_path: C:\Users\Esposa\Documents\Repos\sae-othello-gpt
experiment_base_path: c:\Users\Esposa\Documents\Repos\othello_world\sae\experiments
extras: {'expansion': 16, 'k': 81, 'epochs': 1000, 'patience': 20, 'batch_size_tokens': 1024}

```

```

class BatchTopKSAE(nn.Module):
    def __init__(self, d_in: int, d_sae: int, k: int, k_aux: int = 512):
        super().__init__()
        self.d_in = d_in
        self.d_sae = d_sae
        self.k = k
        self.k_aux = k_aux

        self.W_enc = nn.Parameter(torch.empty(d_in, d_sae))
        self.W_dec = nn.Parameter(torch.empty(d_sae, d_in))
        self.b_dec = nn.Parameter(torch.zeros(d_in))

        nn.init.kaiming_uniform_(self.W_enc)
        nn.init.kaiming_uniform_(self.W_dec)
        self.W_dec.data = self.W_dec.data / self.W_dec.data.norm(dim=-1, keepdim=True)
        self.register_buffer('num_batches_not_active', torch.zeros(d_sae))

    def encode(self, x: torch.Tensor, threshold=None) -> torch.Tensor:
        x_norm, _, _ = self.preprocess_input(x)
        x_cent = x_norm - self.b_dec
        pre_acts = F.relu(x_cent @ self.W_enc)
        return self._topk_activation(pre_acts, threshold=threshold)

```

```

def _topk_activation(self, x: torch.Tensor, threshold=None) -> torch.Tensor:
    if threshold is None:
        acts_topk = torch.topk(x.flatten(), self.k * x.shape[0], dim=-1)
        return (
            torch.zeros_like(x.flatten())
            .scatter(-1, acts_topk.indices, acts_topk.values)
            .reshape(x.shape)
        )
    return torch.where(x > threshold, x, torch.zeros_like(x))

def decode(self, hidden: torch.Tensor) -> torch.Tensor:
    return hidden @ self.W_dec + self.b_dec

def preprocess_input(self, x: torch.Tensor):
    x_mean = x.mean(dim=-1, keepdim=True)
    x = x - x_mean
    x_std = x.std(dim=-1, keepdim=True)
    x = x / (x_std + 1e-5)
    return x, x_mean, x_std

def postprocess_output(self, x_reconstruct, x_mean, x_std):
    return x_reconstruct * x_std + x_mean

def forward(self, x: torch.Tensor, threshold=None):
    x_norm, x_mean, x_std = self.preprocess_input(x)
    x_cent = x_norm - self.b_dec
    pre_acts = F.relu(x_cent @ self.W_enc)
    hidden = self._topk_activation(pre_acts, threshold=threshold)
    recon = self.postprocess_output(self.decode(hidden), x_mean, x_std)
    return recon, hidden, pre_acts

print("BatchTopKSAE definida")

```

BatchTopKSAE definida

0.2 2. Cargar Datos

```

# Cargar activaciones
activations_path = project_root / "activations" / "data" / "layer6_2000games.npy"
activations = np.load(activations_path)

print(f"Activaciones del modelo:")
print(f" Shape: {activations.shape}")
print(f" Memoria: {activations.nbytes / (1024**2):.2f} MB")

```

Activaciones del modelo:

```

Shape: (118000, 512)
Memoria: 230.47 MB

```

```

# Cargar ground truth de BSPs
bsp_gt_path = project_root / "metrics" / "02_data" / "bsp_ground_truth_2000games.npy"
bsp_names_path = project_root / "metrics" / "02_data" / "bsp_ground_truth_2000games.names.npy"

bsp_ground_truth = np.load(bsp_gt_path)
bsp_names = np.load(bsp_names_path, allow_pickle=True)

print(f"\nGround truth BSPs:")
print(f" Shape: {bsp_ground_truth.shape}")
print(f" Total BSPs: {len(bsp_names)}")

```

Ground truth BSPs:
Shape: (118000, 326)
Total BSPs: 326

0.3 3. Cargar SAE y Extraer Features

```
# Configuración del SAE
input_dim = 512
hidden_dim = 8192

# Construir ruta del modelo usando naming_utils
checkpoint_dir = get_checkpoint_dir(
    NAMING_META['base_path'],
    NAMING_META['variante'],
    NAMING_META['tecnica'],
    NAMING_META['capa'],
    NAMING_META['juegos']
)
extras_id = get_extras_id(checkpoint_dir, NAMING_META['extras']) if NAMING_META.get('extras') else None

model_filename = get_model_name(
    NAMING_META['variante'],
    NAMING_META['tecnica'],
    NAMING_META['capa'],
    NAMING_META['juegos'],
    'best',
    extras_id=extras_id
)
model_path = checkpoint_dir / model_filename

# Cargar modelo BatchTopK
sae = BatchTopKSAE(d_in=input_dim, d_sae=hidden_dim, k=NAMING_META['extras']['k']).to(device)

checkpoint = torch.load(model_path, map_location=device, weights_only=False)
sae.load_state_dict(checkpoint['model_state_dict'])
sae.eval()

print(f"SAE cargado:")
print(f"  Path: {model_path}")
print(f"  Input: {input_dim}, Hidden: {hidden_dim}, k: {NAMING_META['extras']['k']}")
print(f"  Expansion: {hidden_dim/input_dim}x")
```

SAE cargado:

Path: C:\Users\Esposa\Documents\Repos\sae-othello-gpt\layer_06\models\sae_topk\sae_batch-topk_topk\5000games\sae_topk_topk_l6_5000g_ex2_best.pt
Input: 512, Hidden: 8192, k: 81
Expansion: 16.0x

```
# Extraer features del SAE en GPU
print("Extrayendo features del SAE...")
activations_tensor = torch.from_numpy(activations).float().to(device)

# Estimar threshold con mini-batch
with torch.no_grad():
    sample = activations_tensor[:4096]
    x_s, _, _ = sae.preprocess_input(sample)
    pre_s = F.relu(x_s - sae.b_dec) @ sae.W_enc
    threshold = torch.topk(pre_s.flatten(), sae.k * 4096).values.min().item()
print(f"Threshold estimado: {threshold:.6f}")
```

```
# Encoding completo con operación in-place
with torch.no_grad():
    x_norm, _, _ = sae.preprocess_input(activations_tensor)
    x_cent = x_norm - sae.b_dec
    pre_acts = F.relu(x_cent @ sae.W_enc)
    pre_acts.mul_(pre_acts > threshold)
    sae_features = pre_acts

del activations_tensor, x_norm, x_cent
torch.cuda.empty_cache()

print(f"\nFeatures SAE:")
print(f"  Shape: {sae_features.shape}")
print(f"  Device: {sae_features.device}")
print(f"  Sparsity: {(sae_features == 0).float().mean():.2%}")
print(f"  Activaciones promedio: {(sae_features > 0).sum(dim=1).float().mean():.1f}")
```

Extrayendo features del SAE...
Threshold estimado: 0.719861

Features SAE:
Shape: torch.Size([118000, 8192])
Device: cuda:0
Sparsity: 99.02%
Activaciones promedio: 80.6

0.4 4. Split Train/Test y Filtrar BSPs de Piezas

```
# Split 50/50:
n_moves = 59
n_games = 2000 # número de partidas para prueba de métricas
train_games = n_games // 2
split_idx = train_games * n_moves

sae_features_train = sae_features[:split_idx]
sae_features_test = sae_features[split_idx:]

print(f"Total partidas: {n_games}")
print(f"Train: {train_games} partidas ({split_idx} activaciones)")
print(f"Test: {n_games - train_games} partidas ({len(activations) - split_idx} activaciones)")
print(f"Train set: {sae_features_train.shape}")
print(f"Test set: {sae_features_test.shape}")
```

Total partidas: 2000
Train: 1000 partidas (59000 activaciones)
Test: 1000 partidas (59000 activaciones)
Train set: torch.Size([59000, 8192])
Test set: torch.Size([59000, 8192])

```
# =====
# CONFIGURACIÓN DE FILTRADO DE BSPs
# =====
USE_PLAYER = True # BSPs perspectiva del jugador (1 y 2)
USE_ABSOLUTE = False # BSPs absolutas negro/blanco (B y W)
USE_STRATEGIC = False # BSPs especiales (BSP_)

bsp_pieces_indices = []
bsp_pieces_names = []
```

```

for i, name in enumerate(bsp_names):
    include = False
    if USE_PLAYER and len(name) == 6 and name.startswith('BSP') and (name.endswith('1') or name.endswith('2')):
        include = True
    if USE_ABSOLUTE and (name.endswith('B') or name.endswith('W')):
        include = True
    if USE_STRATEGIC and name.startswith('BSP_'):
        include = True
    if include:
        bsp_pieces_indices.append(i)
        bsp_pieces_names.append(name)

bsp_pieces_indices = np.array(bsp_pieces_indices)

# Para reconstruction necesitas split train/test
bsp_gt_train_pieces = torch.from_numpy(bsp_ground_truth[:split_idx, bsp_pieces_indices]).bool().to(device)
bsp_gt_test_pieces = torch.from_numpy(bsp_ground_truth[split_idx:, bsp_pieces_indices]).bool().to(device)

# Convertir a tensor en GPU
# Identificador del filtrado (para naming de archivos de salida)
parts = []
if USE_PLAYER: parts.append("player")
if USE_ABSOLUTE: parts.append("absolute")
if USE_STRATEGIC: parts.append("strategic")
filter_suffix = "_".join(parts) if parts else "none"

print(f"BSPs seleccionadas para Reconstruction:")
print(f" Player: {USE_PLAYER} | Absolute: {USE_ABSOLUTE} | Strategic: {USE_STRATEGIC}")
print(f" Total: {len(bsp_pieces_indices)}")
print(f" Train shape: {bsp_gt_train_pieces.shape}")
print(f" Test shape: {bsp_gt_test_pieces.shape}")
print(f" Device: {bsp_gt_train_pieces.device}")
print(f" Primeras 5: {'', '.join(bsp_pieces_names[:5])}")
print(f" Últimas 5: {'', '.join(bsp_pieces_names[-5:])}")
print(f" Filter suffix: {filter_suffix}")

```

```

BSPs seleccionadas para Reconstruction:
Player: True | Absolute: False | Strategic: False
Total: 128
Train shape: torch.Size([59000, 128])
Test shape: torch.Size([59000, 128])
Device: cuda:0
Primeras 5: BSPA11, BSPA12, BSPA21, BSPA22, BSPA31
Últimas 5: BSPH62, BSPH71, BSPH72, BSPH81, BSPH82
Filter suffix: player

```

0.5 5. Funciones GPU-Optimizadas

```

def fast_precision_score_gpu(y_true, y_pred, eps=1e-8):
    """
    Precisión vectorizada en GPU.

    Args:
        y_true: Tensor (n_positions,) booleano
        y_pred: Tensor (n_positions, n_candidates) booleano

    Returns:
        precision_scores: Tensor (n_candidates,)
    """
    y_true_expanded = y_true.unsqueeze(1)

```

```

tp = (y_true_expanded & y_pred).sum(dim=0).float()
fp = (~y_true_expanded & y_pred).sum(dim=0).float()

precision = tp / (tp + fp + eps)

return precision

def fast_f1_score_gpu(y_true, y_pred, eps=1e-8):
    """
    F1 score vectorizado en GPU.

    Args:
        y_true: Tensor (n_positions,) booleano
        y_pred: Tensor (n_positions,) booleano

    Returns:
        f1: Float
    """
    tp = (y_true & y_pred).sum().float()
    fp = (~y_true & y_pred).sum().float()
    fn = (y_true & ~y_pred).sum().float()

    precision = tp / (tp + fp + eps)
    recall = tp / (tp + fn + eps)

    f1 = 2 * (precision * recall) / (precision + recall + eps)

    return f1.item()

print(" Funciones GPU definidas")

```

Funciones GPU definidas

0.6 6. Fase 1: Identificar Features de Alta Precisión (GPU)

Para cada BSP, encontrar features con precisión 0.95 en el train set.

```

def identify_high_precision_features_gpu(
    sae_features_train,
    bsp_gt_train,
    f_max,
    precision_threshold=0.95,
    significance_threshold=1,
    thresholds=[0.0, 0.1, 0.2, 0.3, 0.4, 0.5, 0.6, 0.7, 0.8, 0.9],
    feature_batch_size=512,
    verbose=True
):
    """
    Para cada (threshold t, feature f, BSP b): determina si f es clasificador
    de alta precisión para b al threshold t.

    Criterios (igual que implementación oficial):
        - precision(f, b, t) >= precision_threshold (default 0.95)
        - on_count(f, t) >= significance_threshold (default 10)

    Args:
        sae_features_train: Tensor (P, n_features) GPU
        bsp_gt_train: Tensor (P, n_bsps) GPU, bool
        f_max: Tensor (n_features,) GPU - calculado FUERA para
    """

```

```

        garantizar identidad exacta con Fase 2
precision_threshold: float, default 0.95
significance_threshold: int, mín. activaciones requeridas (default 10)
thresholds: lista de fracciones t [0, 1)
feature_batch_size: int, features por mini-batch interno

Returns:
    hp_mask_TFB: BoolTensor (T, n_active, n_bsps)
    active_feature_indices: LongTensor (n_active,)
"""
n_positions, n_features = sae_features_train.shape
n_bsps = bsp_gt_train.shape[1]
device = sae_features_train.device

thresholds_T = torch.tensor(thresholds, device=device)
n_thresholds = len(thresholds_T)

# Features vivas (f_max > 0)
active_feature_indices = (f_max > 0).nonzero(as_tuple=True)[0]
n_active = len(active_feature_indices)

if verbose:
    print("=" * 60)
    print("FASE 1: IDENTIFICAR FEATURES DE ALTA PRECISIÓN")
    print("=" * 60)
    print(f"Precision threshold: {precision_threshold}")
    print(f"Significance threshold: >= {significance_threshold} activaciones")
    print(f"Features activas: {n_active}/{n_features} ({n_active/n_features*100:.1f}%)")
    print(f"BSPs: {n_bsps}")
    print(f"Thresholds: {thresholds}")
    print("=" * 60)

# Thresholds absolutos: thresh_TF[t, f] = t * f_max[f]
active_f_max = f_max[active_feature_indices] # (n_active,)
thresholds_TF = thresholds_T[:, None] * active_f_max # (T, n_active)

# Acumuladores sobre todo el train set
on_count_TF = torch.zeros(n_thresholds, n_active, device=device)
tp_count_TFB = torch.zeros(n_thresholds, n_active, n_bsps, device=device)

bsp_float_PB = bsp_gt_train.float() # (P, B)

n_iters = (n_active + feature_batch_size - 1) // feature_batch_size

for fi in tqdm(range(n_iters), desc="Fase 1"):
    f_start = fi * feature_batch_size
    f_end = min(f_start + feature_batch_size, n_active)

    global_idx = active_feature_indices[f_start:f_end]
    acts_PF = sae_features_train[:, global_idx] # (P, bs)
    thresh_TF = thresholds_TF[:, f_start:f_end] # (T, bs)

    # active_TFP[t, f, p] = True si acts[p,f] > thresh[t,f]
    active_TFP = acts_PF.T.unsqueeze(0) > thresh_TF.unsqueeze(2) # (T, bs, P)

    # Conteo de activaciones por (threshold, feature)
    on_count_TF[:, f_start:f_end] += active_TFP.sum(dim=2).float()

    # True positives: f activa Y BSP verdadera
    # tp[t, f, b] = Σ_p active[t,f,p] * bsp[p,b]
    tp_count_TFB[:, f_start:f_end, :] += torch.einsum(
        'tfp,pb->tfb', active_TFP.float(), bsp_float_PB

```



```

    )

    # Precisión: tp / on_count
    eps = 1e-8
    precision_TFB = tp_count_TFB / (on_count_TF.unsqueeze(2) + eps) # (T, F, B)

    # Máscara: alta precisión AND significancia suficiente
    sig_mask_TF1 = (on_count_TF >= significance_threshold).unsqueeze(2) # (T, F, 1)
    hp_mask_TFB = (precision_TFB >= precision_threshold) & sig_mask_TF1 # (T, F, B)

    if verbose:
        hp_per_t = hp_mask_TFB.sum(dim=(1, 2)) # (T,)
        hp_per_b = hp_mask_TFB.sum(dim=1) # (T, B)
        best_t = hp_per_t.argmax().item()
        print(f"\nPares (feature, BSP) de alta precisión por threshold:")
        for i, t in enumerate(thresholds):
            marker = " ← más pares" if i == best_t else ""
            print(f" t={t:.1f}: {hp_per_t[i].item():5d} pares{marker}")
        print(f"\nFeatures HP por BSP en t={thresholds[best_t]:.1f}:")
        print(f" Media: {hp_per_b[best_t].float().mean():.1f}")
        print(f" Máx: {hp_per_b[best_t].max().item()}")
        print(f" BSPs sin features: {(hp_per_b[best_t] == 0).sum().item()}")

    return hp_mask_TFB, active_feature_indices

print(" Fase 1 rediseñada: umbral de significancia (10) + estructura (T, F, B)")

```

Fase 1 rediseñada: umbral de significancia (10) + estructura (T, F, B)

```

THRESHOLDS = [0.0, 0.1, 0.2, 0.3, 0.4, 0.5, 0.6, 0.7, 0.8, 0.9]

# f_max calculado UNA SOLA VEZ aquí - se pasa a Fase 1 y Fase 2
f_max = sae_features_train.max(dim=0)[0] # (n_features,)
print(f"f_max calculado: {(f_max > 0).sum().item()} features activas de {f_max.shape[0]}")

start_time = time.time()

hp_mask_TFB, active_feature_indices = identify_high_precision_features_gpu(
    sae_features_train,
    bsp_gt_train_pieces,
    f_max,
    precision_threshold=0.95,
    significance_threshold=1,
    thresholds=THRESHOLDS,
    feature_batch_size=512,
    verbose=True
)

phase1_time = time.time() - start_time

print(f"\nTiempo Fase 1: {phase1_time:.2f} seg")
print(f"hp_mask_TFB shape: {hp_mask_TFB.shape} (T, n_active, n_bsps)")

```

f_max calculado: 8192 features activas de 8192

```

=====
FASE 1: IDENTIFICAR FEATURES DE ALTA PRECISIÓN
=====
Precision threshold:      0.95
Significance threshold:   >= 1 activaciones
Features activas:        8192/8192 (100.0%)
BSPs:                    128

```

Thresholds: [0.0, 0.1, 0.2, 0.3, 0.4, 0.5, 0.6, 0.7, 0.8, 0.9]

Fase 1: 100% | 16/16 [00:00<00:00, 1087.52it/s]

Pares (feature, BSP) de alta precisión por threshold:

t=0.0: 314 pares
t=0.1: 373 pares
t=0.2: 1363 pares
t=0.3: 2703 pares
t=0.4: 4071 pares
t=0.5: 5933 pares
t=0.6: 9921 pares
t=0.7: 22086 pares
t=0.8: 54113 pares
t=0.9: 120223 pares ← más pares

Features HP por BSP en t=0.9:

Media: 939.2
Máx: 3072
BSPs sin features: 0

Tiempo Fase 1: 0.89 seg

hp_mask_TFB shape: torch.Size([10, 8192, 128]) (T, n_active, n_bsps)

0.7 7. Fase 2: Reconstruir Tableros en Test Set (GPU)

```
def reconstruct_boards_gpu(
    sae_features_test,
    bsp_gt_test,
    hp_mask_TFB,
    active_feature_indices,
    f_max,
    thresholds=[0.0, 0.1, 0.2, 0.3, 0.4, 0.5, 0.6, 0.7, 0.8, 0.9],
    verbose=True
):
    """
    Fase 2: barrido simultáneo de thresholds T → toma el mejor F1.

    Para cada threshold t:
    1. Binarizar features de test: active[p, f] = acts[p, f] > t * f_max[f]
    2. Predicción por (posición, BSP):
        predict[p, b] = OR_f ( active[p,f] AND hp_mask[t, f, b] )
        implementado como: (active_PF @ hp_FB) > 0
    3. F1 global micro-averaged (acumula TP/FP/FN sobre todas las posiciones y BSPs)

    Retorna el max F1 sobre todos los thresholds (Eq. 5 del paper: max_t).

    Args:
        sae_features_test: Tensor (P, n_features) GPU
        bsp_gt_test: Tensor (P, n_bsps) GPU, bool
        hp_mask_TFB: BoolTensor (T, n_active, n_bsps) de Fase 1
        active_feature_indices: LongTensor (n_active,) de Fase 1
        f_max: Tensor (n_features,) GPU - MISMO objeto que Fase 1
        thresholds: lista de fracciones (debe coincidir con Fase 1)

    Returns:
        best_f1: float, max F1 sobre thresholds
        best_threshold: float, threshold óptimo
```

```

    f1_per_threshold: np.array (T,), F1 por threshold
"""
device = sae_features_test.device
n_thresholds = len(thresholds)
thresholds_T = torch.tensor(thresholds, device=device)

# Activaciones del test solo para features activas
test_active_PF = sae_features_test[:, active_feature_indices] # (P, n_active)
active_f_max = f_max[active_feature_indices] # (n_active,)

gt_PB = bsp_gt_test.bool() # (P, B)
eps = 1e-8

f1_scores = torch.zeros(n_thresholds, device=device)
precision_T = torch.zeros(n_thresholds, device=device)
recall_T = torch.zeros(n_thresholds, device=device)

if verbose:
    print("=" * 60)
    print("FASE 2: RECONSTRUCCIÓN - BARRIDO DE THRESHOLDS")
    print("=" * 60)
    print(f"{'t':>5} {'F1':>8} {'P':>8} {'R':>8} {'TP':>8} {'FP':>8} {'FN':>8}")
    print("-" * 60)

for t_idx in range(n_thresholds):
    t = thresholds[t_idx]

    # Threshold absoluto por feature: t * f_max[f]
    abs_thresh_F = thresholds_T[t_idx] * active_f_max # (n_active,)

    # Binarizar features en test
    active_PF = test_active_PF > abs_thresh_F.unsqueeze(0) # (P, n_active)

    # predict[p, b] = any( active[p,f] AND hp[t,f,b] )
    # = (active_PF.float() @ hp_mask[t].float()) > 0
    hp_FB = hp_mask_TFB[t_idx].float() # (n_active, B)
    predictions_PB = (active_PF.float() @ hp_FB) > 0 # (P, B)

    # Métricas globales micro-averaged
    tp = (predictions_PB & gt_PB).sum().float()
    fp = (predictions_PB & ~gt_PB).sum().float()
    fn = (~predictions_PB & gt_PB).sum().float()

    p = tp / (tp + fp + eps)
    r = tp / (tp + fn + eps)
    f1 = 2 * p * r / (p + r + eps)

    f1_scores[t_idx] = f1
    precision_T[t_idx] = p
    recall_T[t_idx] = r

    if verbose:
        print(f"{'t':>5.1f} {'f1.item():>8.4f} {'p.item():>8.4f} {'r.item():>8.4f}"
              f" {'tp.item():>8.0f} {'fp.item():>8.0f} {'fn.item():>8.0f}")

best_idx = f1_scores.argmax().item()
best_f1 = f1_scores[best_idx].item()
best_threshold = thresholds[best_idx]

if verbose:
    print("=" * 60)
    print(f"Mejor threshold: t={best_threshold:.1f}")

```

```

        print(f"Reconstruction Score (max_t F1): {best_f1:.4f}")
        print("=" * 60)

    return best_f1, best_threshold, f1_scores.cpu().numpy()

print(" Fase 2 rediseñada: barrido T simultáneo + F1 global micro-averaged + max_t")

```

Fase 2 rediseñada: barrido T simultáneo + F1 global micro-averaged + max_t

```

start_time = time.time()

reconstruction_score, best_threshold, f1_per_threshold = reconstruct_boards_gpu(
    sae_features_test,
    bsp_gt_test_pieces,
    hp_mask_TFB,
    active_feature_indices,
    f_max,          # mismo tensor calculado antes de Fase 1
    thresholds=THRESHOLDS,
    verbose=True
)

phase2_time = time.time() - start_time
total_time = phase1_time + phase2_time

print(f"\nTiempo Fase 2: {phase2_time:.2f} seg")
print(f"Tiempo total: {total_time:.2f} seg ({total_time/60:.2f} min)")

```

```

=====
FASE 2: RECONSTRUCCIÓN - BARRIDO DE THRESHOLDS
=====

```

t	F1	P	R	TP	FP	FN
0.0	0.0165	0.9324	0.0083	16711	1212	1989289
0.1	0.0180	0.9307	0.0091	18189	1354	1987811
0.2	0.0831	0.9542	0.0434	87110	4185	1918890
0.3	0.1473	0.9653	0.0797	159922	5750	1846078
0.4	0.1804	0.9744	0.0994	199439	5230	1806561
0.5	0.1593	0.9698	0.0868	174091	5415	1831909
0.6	0.1172	0.9297	0.0625	125470	9484	1880530
0.7	0.0893	0.7931	0.0473	94861	24754	1911139
0.8	0.0840	0.6019	0.0452	90603	59926	1915397
0.9	0.0926	0.4892	0.0511	102560	107093	1903440

```

=====

```

```

Mejor threshold: t=0.4
Reconstruction Score (max_t F1): 0.1804
=====

```

Tiempo Fase 2: 4.70 seg
Tiempo total: 5.58 seg (0.09 min)

0.8 8. Análisis de Resultados

```

print("=" * 60)
print("BARRIDO DE THRESHOLDS - F1 POR THRESHOLD")
print("=" * 60)
for i, (t, f1) in enumerate(zip(THRESHOLDS, f1_per_threshold)):
    marker = " ← MEJOR" if i == f1_per_threshold.argmax() else ""
    print(f"t={t:.1f}: F1={f1:.4f}{marker}")
print("=" * 60)

```

```

plt.figure(figsize=(10, 6))
plt.plot(THRESHOLDS, f1_per_threshold, marker='o', linewidth=2, markersize=8)
plt.axhline(y=reconstruction_score, color='r', linestyle='--',
            label=f'Best F1={reconstruction_score:.4f} (t={best_threshold:.1f})')
plt.axhline(y=0.95, color='g', linestyle=':', label='Target Othello SAE (paper)=0.95')
plt.xlabel('Threshold t', fontsize=12)
plt.ylabel('F1 Score (micro-averaged global)', fontsize=12)
plt.title('Board Reconstruction: F1 por Threshold', fontsize=14, fontweight='bold')
plt.grid(True, alpha=0.3)
plt.legend()
plt.tight_layout()
plt.show()


print(f"\n Threshold óptimo: t={best_threshold:.1f}")
print(f" Reconstruction Score: {reconstruction_score:.4f}")

```

```

=====
BARRIDO DE THRESHOLDS - F1 POR THRESHOLD
=====
t=0.0: F1=0.0165
t=0.1: F1=0.0180
t=0.2: F1=0.0831
t=0.3: F1=0.1473
t=0.4: F1=0.1804 ← MEJOR
t=0.5: F1=0.1593
t=0.6: F1=0.1172
t=0.7: F1=0.0893
t=0.8: F1=0.0840
t=0.9: F1=0.0926
=====

```



```
Threshold óptimo: t=0.4
Reconstruction Score: 0.1804
```

```
# Estadísticas sobre features de alta precisión por BSP
hp_per_bsp = hp_mask_TFB.sum(dim=1) # (T, n_bsps)
best_t_idx = torch.tensor(f1_per_threshold).argmax().item()
n_features_per_bsp = hp_per_bsp[best_t_idx].cpu().numpy()

print("="*60)
print("ESTADÍSTICAS - FEATURES POR BSP")
print("="*60)
print(f"Total BSPs: {len(n_features_per_bsp)}")
print(f"Features promedio por BSP: {np.mean(n_features_per_bsp):.1f}")
print(f"Features mediana por BSP: {np.median(n_features_per_bsp):.1f}")
print(f"BSPs con 0 features: {np.sum(n_features_per_bsp == 0)}")
print(f"BSPs con 1+ features: {np.sum(n_features_per_bsp > 0)}")
print(f"BSPs con 5+ features: {np.sum(n_features_per_bsp >= 5)}")
print(f"BSPs con 10+ features: {np.sum(n_features_per_bsp >= 10)}")
print(f"Max features en una BSP: {np.max(n_features_per_bsp)}")
print("="*60)
```

```
=====
ESTADÍSTICAS - FEATURES POR BSP
=====
```

```
Total BSPs: 128
Features promedio por BSP: 31.8
Features mediana por BSP: 9.0
BSPs con 0 features: 3
BSPs con 1+ features: 125
BSPs con 5+ features: 88
BSPs con 10+ features: 60
Max features en una BSP: 287
=====
```

0.9 9. Guardar Resultados

```
results = {
    'reconstruction_score': reconstruction_score,
    'best_threshold': best_threshold,
    'f1_per_threshold': f1_per_threshold,
    'thresholds': np.array(THRESHOLDS),
    'phase1_time_seconds': phase1_time,
    'phase2_time_seconds': phase2_time,
    'total_time_seconds': total_time,
    'bsp_names': bsp_pieces_names,
}

metrics_dir = get_metrics_dir(
    NAMING_META['experiment_base_path'],
    NAMING_META['variante'],
    NAMING_META['tecnica'],
    NAMING_META['capa'],
    NAMING_META['juegos'],
    extras_id=extras_id
)

output_path = metrics_dir / f"reconstruction_results_{filter_suffix}.npz"
np.savez(output_path, **results)

print(f" Resultados guardados en: {output_path}")
print(f"\nContenido:")
```

```

print(f"   reconstruction_score: {reconstruction_score:.4f}")
print(f"   best_threshold:         {best_threshold:.1f}")
print(f"   f1_per_threshold:         {f1_per_threshold}")

# Comparación con el paper
print()
print("=" * 60)
print("COMPARACIÓN CON PAPER (Karvonen et al., NeurIPS 2024)")
print("=" * 60)
print(f"{'Modelo':<25} {'Reconstruction':>14}")
print("-" * 40)
print(f"{'SAE trained (paper)':<25} {'0.95':>14} ← Objetivo Othello")
print(f"{'Nuestro SAE':<25} {reconstruction_score:>14.4f} ← Resultado")
print("=" * 60)

if reconstruction_score >= 0.90:
    print("\n Excelente: Muy cercano al objetivo del paper")
elif reconstruction_score >= 0.50:
    print("\n~ Moderado: Por encima de random, revisar SAE")
else:
    print("\n Bajo: Revisar entrenamiento del SAE o calidad de las activaciones")

```

Resultados guardados en: c:\Users\Esposa\Documents\Repos\othello_world\sae\experiments\layer_06\sae_topk\sae_batch-topk_topk\5000games\ex2\metrics\reconstruction_results_player.npz

Contenido:

```

reconstruction_score: 0.1804
best_threshold:       0.4
f1_per_threshold:     [0.01651347 0.01795963 0.08306891 0.14728005 0.18043315 0.15931414 0.11720943 0.08925511 0.0840
0.09257768]

```

```

=====
COMPARACIÓN CON PAPER (Karvonen et al., NeurIPS 2024)
=====
Modelo                Reconstruction
-----
SAE trained (paper)           0.95  ← Objetivo Othello
Nuestro SAE                  0.1804 ← Resultado
=====

```

Bajo: Revisar entrenamiento del SAE o calidad de las activaciones

0.10 10. Generar PDF con Quarto

```

output_dir = get_metrics_dir(
    NAMING_META['experiment_base_path'],
    NAMING_META['variante'],
    NAMING_META['tecnica'],
    NAMING_META['capa'],
    NAMING_META['juegos'],
    extras_id=extras_id
)

pdf_name = get_report_name(
    NAMING_META['variante'],
    NAMING_META['tecnica'],
    NAMING_META['capa'],
    NAMING_META['juegos'],
    f'reconstruction_{filter_suffix}',
    extras_id=extras_id
)

```

```

)

notebook_name = 'reconstruction_sae_batchtopk.ipynb'
output_path = output_dir / pdf_name

print(f' Generando PDF con Quarto...')
print(f' Archivo de salida: {output_path}')

result = subprocess.run(
    f'quarto render {notebook_name} --to pdf --output-dir "{output_dir}" --output {pdf_name}',
    shell=True,
    capture_output=True,
    text=True
)

if result.returncode == 0:
    print(f' PDF generado exitosamente: {output_path}')
else:
    print(f' Error al generar PDF:')
    print(result.stderr)

```

```

Generando PDF con Quarto...
Archivo de salida: c:\Users\Esposa\Documents\Repos\othello_world\sae\experiments\layer_06\sae_topk\sae_batch-
topk_topk\5000games\ex2\metrics\sae_topk_batch-topk_l6_5000g_ex2_reconstruction_player.pdf
PDF generado exitosamente: c:\Users\Esposa\Documents\Repos\othello_world\sae\experiments\layer_06\sae_topk\sae_batch-
topk_topk\5000games\ex2\metrics\sae_topk_batch-topk_l6_5000g_ex2_reconstruction_player.pdf

```