

Prior_production_IM

karine Durand

9 novembre 2018

production des priors IM

mon_script

```
library(stats)
library("KSCorrect", lib.loc=~R/x86_64-pc-linux-gnu-library/3.3")
#####partie locus
#variables locus
#-L=taille du gène
#-t=theta
#-r=rho
#-delta=taille du track recombinant
#boucle de 10 000 iterations(10 000 tirages demographique)
demo<-NULL
locus<-NULL
tbs<-NULL
#####TIRER un prior locus dans une distribution uniforme de bornes
L<-scan("/home/kadurand/partage_windows/Xylella/analyses_genomiques/ABC/msms/lenght")#bound_taille du g
t<-runif(997,0, 0.001 )#bound_theta=[0-0.0003]bornes vrai pour 13pauca_multiplex augmenter la borne sup
r<-runif(997,0,0.001)#bound_rho=[0-0.0003]bornes vrai pour 13pauca_multiplex augmenter la borne sup à 0
#delta<-round(runif(997,10, 1000))#bound=[10-1000]
#print(L,t,r,delta)
m_locus=matrix(c(L,t*L,r*L),ncol=3)
m_locus=as.data.frame(m_locus)

for (i in 1:1000){#tirage des priors demographiques
  #variables demographique modèle SI
  ##Param_demo (5) = Ts N1, N2, M12, M21
  Ts<-runif(1,0,20)#bound=[1,100,1E+7] Ts/4N0
  N1<-runif(1,0,30)#bound=[100,1E+6] X=N1/N0
  N2<-runif(1,0,30)#bound=[100,1E+6]
  Na<-runif(1,0,60)#Bound=[100,1E+6]
  M12<-runif(1,0.01,5)#bound=[0.01-30]
  M21<-runif(1,0.01,5)#bound=[0.01-30]

  #print( Ts N1, N2, M12, M21)
  m_demo=matrix(c(Ts,N1,N2,Na,M12,M21),ncol=6)
  m_demo=as.data.frame(m_demo)
  locus<-cbind(m_locus,m_demo)

  path <- "/home//kadurand/partage_windows/Xylella/analyses_genomiques/ABC/msms/Priors_IM_ms_9/IM"
  write.table(locus,file= paste(path,i, sep="-"),col.names=FALSE,row.names =FALSE)
}
```