

Max-Planck-Institut für Gravitationsphysik
Albert Einstein Institut
Ms.Kruuse
Callinstraße 38
30167 Hannover

Pfeiffer Vacuum Components & Solutions GmbH

Anna-Vandenhoeck-Ring 44
37081 Göttingen
T +49 551 999630
F +49 551 999633010
info-cs@pfeiffer-vacuum.com
www.pfeiffer-vacuum.de

Angebot

Belegnummer: AN-25-35326
Kundennummer: D90493
Bearbeiter: Meyer, Katharina
T +49 551 99963-3023
Betreff: Karin Kruuse
Datum: 05.09.2025
Gültig bis: 05.10.2025
Vertrieb: Dziechciejewski, Dr.
Wojciech (306)
Telefon: +49 (0) 172 77 69 455
EUUstId: DE129517720

Projektnummer: P48209
Version 2

Vielen Dank für Ihre Anfrage. Gemäß unseren allgemeinen Geschäftsbedingungen unterbreiten wir Ihnen folgendes Angebot:

Pos.	Artikel	Bezeichnung	Menge	ME	Einzelpreis	Gesamtpreis
------	---------	-------------	-------	----	-------------	-------------

This is a guide price for orientation and information only and does not represent an orderable offer.

This price information is for guidance and information only and does not constitute an offer ready for order. Due to certain circumstances adjustments to the pricing may become necessary (e.g. material availability, changes in customer specifications or mandatory design changes). We therefore reserve the right to adjust the stated price taking into account these circumstances until the conclusion of the contract.

Your technical support for this quote:

Patrick-Norbert David
Pre-Sales
T +49 551 999 63 -3173
M +49 151 54393168
Patrick-Norbert.David@Pfeiffer-Vacuum.com



Belegnummer: AN-25-35326

Pos.	Artikel	Bezeichnung	Menge	ME	Einzelpreis	Gesamtpreis
1	TR-8880-08977	Vakuumkammer DN500 CF mit Abgaengen	1	Stk	24.480,00	24.480,00

Description:

- Incl. drawing for approval based on your sketch „Screenshot 2025-08-21 143558" and „Screenshot 2025-08-21 143609" and information in your request
- *Notice:*
The transfer of drawing sets (except for release drawings) and 3D data models (format-independent) is not provided.
We reserve all copyrights for the drawings and 3D data provided by us.
They remain our intellectual property and may not be reproduced or made available to third parties without our express prior consent.
- Vacuum chamber DN500 with welded base plate and height of 500 mm
- Cover flange as DN500 CF blind flange
- Main tube Ø508x4mm
- 4x DN40 CF flange for viewport --> Positioning is carried out during the design phase in consultation with you
- 1x DN63 CF flange for HiPace 80, reinforced design
- 1x DN63 CF, flange for UHV gate valve
- 1x DN40 CF, flange for PKR 360
- All flanges fixed
- Includes:
- 4x viewport with anti-reflective coating 1064 nm and free view of 35 mm
 - Materials:
 - Flange: Stainless Steel (304)
 - Weld Ring: Stainless Steel (304)
 - Glass: Fused Silica
 - Glass-Metal-Sealing: Brazed
 - Surface quality: 20/10 scratch/dig
 - Flatness: < $\lambda/4$ @ 632 nm
 - Parallelism: < 10 Arc Seconds
 - Homogeneity Grade: A
 - Inclusion Class: 0
 - Coating:
 - Antireflective
 - 1064 nm
 - Both sides
 - Coated Ø vacuumside: 27 mm
 - R < 0,25% per surface
 - Laser Damage Threshold: 10 J/cm² for 10 ns pulse

(note: varies with wavelength, laser type and cleanliness of optic)

Always use washers for installation.

Please use annealed copper gaskets or elastomer seals to minimize stress inside the glass.



Belegnummer: AN-25-35326

Pos.	Artikel	Bezeichnung	Menge	ME	Einzelpreis	Gesamtpreis
		1x HiPace 80 promo package 1x HiScroll 6 promo package 1x UHV gate valve (GVM-S06500) 1x PKR 360 (PT T02 350 010) 1x Measurement cable, 3 m for PKR 360 - Includes screws, washers, nuts, and copper gaskets 3x copper seal DN500 CF as spare part 3x O-ring screws as lifting equipment for DN500 CF blind flange - Excluded: - Two cavities (glass cylinders with lengths of 25 and 30 cm) - Breadboard and 2x cylindrical thermal shields made of aluminum				

General welding information:

- General quality requirements according DIN EN ISO 3834 -2
- Applied welding processes:
 - TIG-welding (EN4063-141)
 - Laser beam welding (EN4063 -52)
- Welds performed to meet vacuum requirement
 - Vacuum side circumferentially welded and atmosphere side reinforced with stitch welds
 - Alternatively full penetration welds (opposite side formed with argon)

Tolerances:

- General tolerances: ISO 2768 -1 mK
- General tolerances for welded designs: EN ISO 13920 BF
- CF-Flanges up to DN 250: ISO 3669:2020

Materials:

- CF-Flanges 1.4307 (304L)
- Glass: Fused Silica
- Tubes 1.4301 (304) or higher valued
- Sheet and bar material 1.4301 (304) or higher valued
- Magnetic permeability not specified

Surfaces:

- Vacuum side: glass bead blasted
- Atmosphere side: glass bead blasted
- Sealing surfaces free of scratches / protected while manufacturing
- Edges:
 - Deburred according DIN ISO 13715 "free of burrs"

Cleaning:

- According Pfeiffer Vacuum standard procedure for UHV chambers and components
- No cooling lubricants based on silicone or sulfur are used



Belegnummer: AN-25-35326

Pos.	Artikel	Bezeichnung	Menge	ME	Einzelpreis	Gesamtpreis
------	---------	-------------	-------	----	-------------	-------------

Operating parameters:

- Pressure range:
 - 0 hPa (mbar) to ambient pressure
- Temperature range according sealing material:
 - (-15)°C to 150°C with FKM seals (temporarily up to 200°C)
 - (-196)°C to 200°C with Cu -gaskets (silver plated up to 450°C)
- Temperature range according material:
 - 1.4301/1.4307 (304/304L): (-110)°C to 300°C
 - Fused silica: (-100)°C to 200°C
 - Thermal gradient: 20°C per minute
 - *Please note the specific length expansion and modification of the mechanical properties with temperature changes*

Scope of testing:

- Helium leak test according to vacuum procedure local
 - Based on DIN EN 1779:1999 -10
 - Tightness < 1·E -10 Pa·m³/s (< 1·E -9 mbar·l/s), excl. gas permeation

Technical documentation:

- Helium leak test report

Condition as supplied to customer

- Chamber ports not blanked off / sealing surfaces protected with PE foil or protection caps
- Viewports DN40 CF and blind flange DN500 CF mounted
- Component labelled with article number, manufacturer and date of manufacture (detailed clarification after order)
- Packaged to meet vacuum demands
- Additional components such as HiPace, HiScroll, PKR, etc. will be shipped separately in their original packaging

Options:

- *Non-destructive weld inspection according to customer requirements*
- *Dimensional report of agreed check dimensions*
- *Material certificates according to DIN EN 10204 -3.1*
- *Finite element analysis (FEA)*
- *Surface treatments (e.g. e -polishing, grinding)*
- *Residual gas analysis (RGA) and bake -out*
- *Support frame*
- *Access guard/safety mesh for your turbopump*
- *Factory acceptance test (FAT)*
- *Accessories like electrical feedthroughs, valves, viewports etc. can be found in our catalogue or on our website www.pfeiffer-vacuum.com*

Please note that within the terms of the Product Safety Act / Machinery Directive, additional accessories such as access guards / safety screens may be required for your turbopump.



Belegnummer: AN-25-35326

Pos.	Artikel	Bezeichnung	Menge	ME	Einzelpreis	Gesamtpreis
		Herkunftsland: DE				

Delivery time:

Approx. 2 weeks for preparation of drawings / review of technical details

Approx. 6 weeks for material procurement after drawing approval and clarification of technical details

Approx. 9 weeks for manufacturing after material receipt

(Please note that the actual delivery times will depend on raw material availability and production capacity at the time of order confirmation.)

Incl. freight, insurance and packing

Zwischensumme EUR	24.480,00
zzgl. MwSt 19,00 % aus EUR 24.480,00	4.651,20
Endsumme EUR	29.131,20

Zahlung erfolgt über Rechnung

30 Tage ohne Abzug 29.131,20 EUR

Lieferbedingung: DAP (Incoterms 2020) DE -37081 Göttingen, Anna -Vandenhoeck-Ring 44

Für weitere Fragen stehen wir Ihnen gern zur Verfügung.

Es gelten unsere Allgemeinen Geschäftsbedingungen, Allgemeine Datenschutzerklärung und Allgemeinen Qualitätsanforderungen, die Sie unter:

- Deutsch: vacuum-shop.de - Impressum

- Englisch: vacuum-shop.com - Legal Notice
einsehen können.

Mit freundlichen Grüßen

i. A. Katharina Meyer
Sales Support

T +49 551 99963 -3023

F +49 551 99963 -3010

katharina.meyer@pfeiffer-vacuum.com

