

Admin Portal API Reference

This document defines the admin-facing endpoints delivered in Sprint 4: staff oversight, admin self-service and oversight, adopter oversight, shelter management, and org-wide analytics. It follows the same conventions established in 07-Public API Reference — see that document for base URL, standard response structure, and error code definitions, which are not repeated here. All endpoints below require Admin role auth (Bearer token) unless otherwise noted.

1. Staff Management

1.1 GET /api/v1/staff

Returns a paginated, org-wide staff list, ordered by staffName ascending.

Request

Field	Value
Method	GET
Auth required	Yes — Admin only
Query params	page (int, optional, default 1), limit (int, optional, default 20), shelterID (int, optional filter), staffDesignation (optional — one of Manager/Senior/Associate), accountStatus (optional — one of Pending/Active/Deactivated — Pending means awaiting admin approval)

Response

```
200 OK
{
  "success": true,
  "message": "Staff retrieved successfully",
  "data": [
    {
      "userID": 5,
      "avatarSeed": "a1b2c3d4-...",
      "staffName": "...",
      "staffPhone": "...",
      "shelterID": 3,
      "staffDOB": "1990-04-12",
      "staffSex": "F",
      "staffDOJ": "2024-01-15",
      "staffDOS": null,
      "staffDesignation": "Manager",
      "accountStatus": "Active",
      "onboardingComplete": true,
      "governmentIdStatus": "Verified",
      "user": { "userEmail": "..." }
    }
  ],
  "pagination": { "page": 1, "limit": 20, "total": 12, "totalPages": 1 }
```

```
}
```

governmentIdStatus is Pending/Verified/Rejected, or null if none submitted — only the status is exposed.

Error Cases

Scenario	Error Code	HTTP Status
Invalid page or limit	BAD_REQUEST	400
Invalid shelterID	BAD_REQUEST	400
Invalid staffDesignation or accountStatus value	BAD_REQUEST	400

1.2 GET /api/v1/staff/:id

Returns full detail for one staff member — the same fields as a list item (1.1), plus managedShelters: the shelter(s) this person currently manages, if any.

Request

Field	Value
Method	GET
Auth required	Yes — Admin only
Path params	id (int, required) — userID

Response

```
200 OK
{
  "success": true,
  "message": "Staff member retrieved successfully",
  "data": {
    "userID": 5,
    "avatarSeed": "a1b2c3d4-...",
    "staffName": "...",
    "staffPhone": "...",
    "shelterID": 3,
    "staffDOB": "1990-04-12",
    "staffSex": "F",
    "staffDOJ": "2024-01-15",
    "staffDOS": null,
    "staffDesignation": "Manager",
    "accountStatus": "Active",
    "onboardingComplete": true,
    "governmentIdStatus": "Verified",
    "user": { "userEmail": "..." },
    "managedShelters": [ { "shelterID": 3, "shelterName": "..." } ]
  }
}
```

Error Cases

Scenario	Error Code	HTTP Status
----------	------------	-------------

id is not a positive integer	BAD_REQUEST	400
Staff member does not exist	NOT_FOUND	404

1.3 PATCH /api/v1/staff/:id

Partial update to a staff member's profile. staffDesignation and/or shelterID may be updated (account activation is a separate endpoint, 1.4).

Request

Field	Value
Method	PATCH
Auth required	Yes — Admin only
Path params	id (int, required) — userID
Body fields	Any subset of: shelterID (int), staffDesignation (one of Manager/Senior/Associate), and other updatable staff profile fields

Manager sync, two directions: (a) if shelterID changes and this staff member currently manages their old shelter, that shelter's managerStaffID is cleared automatically — a manager can't be reassigned to a new branch while still listed as managing the old one. (b) staffDesignation and Shelter.managerStaffID are kept in sync: setting designation to 'Manager' makes this person the managerStaffID of their (possibly new) shelter, overwriting any existing manager there; moving away from 'Manager' (or away from that shelter) clears managerStaffID on the shelter they were managing.

Response

200 OK, same shape as the detail response in 1.2.

Error Cases

Scenario	Error Code	HTTP Status
No updatable fields provided	BAD_REQUEST	400
Invalid staffDesignation value	BAD_REQUEST	400
shelterID is not a positive integer	BAD_REQUEST	400
shelterID doesn't reference an existing shelter	NOT_FOUND	404
Staff member does not exist	NOT_FOUND	404

1.4 PATCH /api/v1/staff/:id/status

Activates or deactivates a staff account.

Request

Field	Value
Method	PATCH
Auth required	Yes — Admin only
Path params	id (int, required) — userID
Body fields	accountStatus (string, required — "Active" or "Deactivated"; Pending is never an accepted target — there is no manual revert-to-Pending workflow)

Admins approve Pending Manager sign-ups here; other Pending staff are approved by their shelter's Manager (PATCH /staff/me/team/:id/status). Deactivating clears managerStaffID on every shelter this staff member currently

manages. A Deactivated (or still-Pending) staff member is rejected on their next login attempt, and an already-issued access token is separately invalidated immediately by live account-status enforcement on every protected request — not just at next login.

Approving a Pending Manager sign-up requires their onboarding to be complete AND their government ID Verified; otherwise 409 naming what's missing. Declining is allowed at any time.

Response

200 OK, same detail shape as 1.2.

Error Cases

Scenario	Error Code	HTTP Status
accountStatus missing or invalid	BAD_REQUEST	400
Staff member does not exist	NOT_FOUND	404
Approving a Pending Manager before onboarding is complete and the government ID is Verified (message names what's missing)	CONFLICT	409

2. Admin Management

2.1 GET /api/v1/admins

Returns a paginated list of admins, ordered by adminName ascending, including self-registered accounts awaiting approval.

Request

Field	Value
Method	GET
Auth required	Yes — Admin only
Query params	page (int, optional, default 1), limit (int, optional, default 20), accountStatus (optional — Pending/Active/Deactivated)

Response

```
200 OK
{
  "success": true,
  "message": "Admins retrieved successfully",
  "data": [
    {
      "userID": 2,
      "avatarSeed": "a1b2c3d4-...",
      "adminName": "...",
      "adminPhone": "...",
      "addressLine1": "...",
      "addressLine2": null,
      "city": "...",
      "state": "...",
      "zip": "...",
    }
  ]
}
```

```
    "country": "...",
    "adminDOB": "1988-03-02",
    "adminSex": "M",
    "createdAt": "2026-01-10T09:00:00Z",
    "lastLoginAt": "2026-09-01T08:30:00Z",
    "accountStatus": "Active",
    "statusChangedAt": "2026-01-10T09:05:00Z",
    "statusChangedBy": { "userID": 1, "adminName": "..." }
  }
],
"pagination": { "page": 1, "limit": 20, "total": 4, "totalPages": 1 }
}
```

statusChangedBy records who last changed this admin's status, and is null if it has never been changed — an audit trail of the most recent change only, not full history.

lastLoginAt comes from *USERS*, not the *ADMIN* table.

Error Cases

Scenario	Error Code	HTTP Status
Invalid page, limit, or accountStatus	BAD_REQUEST	400

2.2 GET /api/v1/admins/me

Returns the logged-in admin's own profile, same shape as one list item in 2.1.

Request

Field	Value
Method	GET
Auth required	Yes — Admin only
Path/Body fields	None — admin identified via req.user.userID

Response

200 OK, same shape as one item in 2.1's response list.

Error Cases

Scenario	Error Code	HTTP Status
No/invalid token	UNAUTHORIZED	401

2.3 PUT /api/v1/admins/me

Self-service update to the logged-in admin's own profile.

Request

Field	Value
Method	PUT
Auth required	Yes — Admin only

Body fields	avatarSeed (≤64 chars), adminName (≤45 chars), adminPhone (normalized to E.164 server-side), addressLine1 (≤100 chars), addressLine2 (≤100 chars), city (≤45 chars), state (≤45 chars), zip (≤10 chars), country (≤45 chars), adminDOB (valid date), adminSex (one of M/F/O). adminPhone/addressLine2/adminDOB/adminSex may be explicitly set to null to clear them; adminName/avatarSeed cannot be null/empty.
-------------	---

accountStatus is explicitly rejected here — that's admin-approval-only, via the 1.4-style endpoint (2.7). Providing it returns 400 listing the rejected field(s), before any write occurs.

Response

200 OK, updated profile, same shape as 2.2.

Error Cases

Scenario	Error Code	HTTP Status
Rejected field (accountStatus) present	BAD_REQUEST	400
A provided field is null but not nullable	BAD_REQUEST	400
String field too long	BAD_REQUEST	400
Invalid adminSex or adminDOB	BAD_REQUEST	400
No updatable fields provided	BAD_REQUEST	400

2.4 DELETE /api/v1/admins/me

Self-service account closure for the logged-in admin.

Request

Field	Value
Method	DELETE
Auth required	Yes — Admin only
Body fields	mode (string, required — "deactivate" or "delete")

deactivate sets accountStatus to Deactivated and clears the refresh token (self-service, no “last active admin” guard — unlike 2.7 below, this is only ever your own account). delete removes the admin's government ID (including its stored Storage file), the Admin row, and the Users row.

Response

```
200 OK
{
  "success": true,
  "message": "Account deleted",
  "data": null
}
```

(or "Account deactivated" depending on mode)

Error Cases

Scenario	Error Code	HTTP Status
mode missing or invalid	VALIDATION_ERROR	422

2.5 GET & POST /api/v1/admins/me/government-id

Identical contract to the Adopter Portal's government-ID endpoints (see 09-Adopter_API, Section 2), scoped to userType "Admin" instead of "Adopter": same multipart upload (idType, idNumber ≤45 chars, file ≤5MB), same one-per-admin uniqueness (a Rejected record can be resubmitted, overwriting the prior one), same idNumber masking (e.g. *****4567) on the POST response, same 404/409 error cases. Self-only — never exposed via GET /admins/:id.

2.6 GET /api/v1/admins/:id

Returns full detail for one admin, same shape as a list item (2.1).

Request

Field	Value
Method	GET
Auth required	Yes — Admin only
Path params	id (int, required) — userID

Response

200 OK, same shape as one item in 2.1's response list.

Error Cases

Scenario	Error Code	HTTP Status
id is not a positive integer	BAD_REQUEST	400
Admin does not exist	NOT_FOUND	404

2.7 PATCH /api/v1/admins/:id/status

Activates or deactivates another admin's account.

Request

Field	Value
Method	PATCH
Auth required	Yes — Admin only
Path params	id (int, required) — userID
Body fields	accountStatus (string, required — "Active" or "Deactivated")

This is also how a self-registered Pending admin is approved or declined; it records the acting admin's userID and the current timestamp as statusChangedAt (shown as statusChangedBy in the response) — an audit trail of the last change only, not full history. An admin cannot deactivate their own account this way (guards against the last active admin locking themselves out with no one left to reverse it) — use 2.4 instead for self-service.

Response

200 OK, updated detail, same shape as 2.6.

Error Cases

Scenario	Error Code	HTTP Status
accountStatus missing or invalid	BAD_REQUEST	400
Self-deactivation attempt	BAD_REQUEST	400
Admin does not exist	NOT_FOUND	404

3. Adopter Oversight

3.1 GET /api/v1/adopters

Returns a paginated, org-wide adopter list for admin oversight, ordered by adopterName ascending. Never includes governmentID or stripeCustomerID.

Request

Field	Value
Method	GET
Auth required	Yes — Admin only
Query params	page (int, optional, default 1), limit (int, optional, default 20), accountStatus (optional — Active/Banned/Deactivated), adopterRiskFlag (optional boolean — only the exact string "true" filters to flagged adopters)

Response

```
200 OK
{
  "success": true,
  "message": "Adopters retrieved successfully",
  "data": [
    {
      "userID": 12,
      "avatarSeed": "a1b2c3d4-...",
      "adopterName": "...",
      "adopterPhone": "...",
      "accountStatus": "Active",
      "adopterRiskFlag": false,
      "preQualifyFlag": true,
      "createdAt": "2026-02-01T10:00:00Z",
      "city": "...",
      "state": "...",
      "country": "..."
    }
  ],
  "pagination": { "page": 1, "limit": 20, "total": 340, "totalPages": 17 }
}
```

Error Cases

Scenario	Error Code	HTTP Status
Invalid page, limit, or accountStatus	BAD_REQUEST	400

3.2 GET /api/v1/adopters/:id

Returns full detail for one adopter — the same fields as a list item (3.1), plus profile and household fields. Never includes governmentID or stripeCustomerID.

Request

Field	Value
Method	GET
Auth required	Yes — Admin only
Path params	id (int, required) — userID

Response

```
200 OK
{
  "success": true,
  "message": "Adopter retrieved successfully",
  "data": {
    "userID": 12,
    "avatarSeed": "a1b2c3d4-...",
    "adopterName": "...",
    "adopterPhone": "...",
    "accountStatus": "Active",
    "adopterRiskFlag": false,
    "preQualifyFlag": true,
    "createdAt": "2026-02-01T10:00:00Z",
    "city": "...",
    "state": "...",
    "country": "...",
    "adopterDOB": "1992-06-18",
    "adopterSex": "F",
    "addressLine1": "...",
    "addressLine2": null,
    "zip": "...",
    "housingType": "House",
    "ownsOrRents": "Owns",
    "householdSize": 3,
    "numChildren": 1,
    "employmentStatus": "Employed",
    "activityLevel": "Active",
    "petExperience": "Some",
    "...": "...other profile/household fields"
  }
}
```

Error Cases

Scenario	Error Code	HTTP Status
----------	------------	-------------

id is not a positive integer	BAD_REQUEST	400
Adopter does not exist	NOT_FOUND	404

3.3 PATCH /api/v1/adopters/:id/status

Bans, deactivates, or reactivates an adopter.

Request

Field	Value
Method	PATCH
Auth required	Yes — Admin only
Path params	id (int, required) — userID
Body fields	accountStatus (string, required — "Active", "Banned", or "Deactivated")

Banned and Deactivated adopters are rejected on their next login, and transitioning to either of those statuses nulls the adopter's stored refresh token immediately (the same helper the adopter's own self-deactivate flow uses) — this closes the window where an already-issued refresh token could otherwise keep minting fresh access tokens for up to its remaining 7-day life.

Response

200 OK, updated adopter summary, same shape as one item in 3.1's response list.

Error Cases

Scenario	Error Code	HTTP Status
accountStatus missing or invalid	BAD_REQUEST	400
Adopter does not exist	NOT_FOUND	404

4. Shelter Management

4.1 POST /api/v1/shelters

Creates a new shelter. This is the only supported way to add a shelter to the network — no other creation path exists.

Request

Field	Value
Method	POST
Auth required	Yes — Admin only
Body fields	shelterName (≤45 chars, required), shelterAddress (≤45 chars, required), shelterPhone (required, normalized to E.164), shelterEmail (valid email, ≤45 chars, required), shelterZIP (required), shelterSize (positive integer, required)

shelterStatus is never accepted here — it always starts as the schema default ("Open"). shelterZIP is geocoded server-side (offline US zip → coords) into a PostGIS point, the same column the public /shelters/nearby search reads; an unresolvable ZIP fails the whole request before any row is written.

Response

```
201 Created
{
  "success": true,
  "message": "Shelter created successfully",
  "data": {
    "shelterID": 6,
    "shelterName": "...",
    "shelterAddress": "...",
    "shelterPhone": "...",
    "shelterEmail": "...",
    "shelterZIP": "...",
    "shelterSize": 40,
    "shelterStatus": "Open",
    "managerStaffID": null,
    "lat": 40.7128,
    "lng": -74.006
  }
}
```

Error Cases

Scenario	Error Code	HTTP Status
A required field is missing	BAD_REQUEST	400
Field fails validation (bad email format, non-positive ZIP/size, unparseable phone)	BAD_REQUEST	400
shelterZIP can't be geocoded	BAD_REQUEST	400

4.2 PUT /api/v1/shelters/:id

Partial update to a shelter; only fields present in the body are changed, using the same field set and validation as 4.1.

Request

Field	Value
Method	PUT
Auth required	Yes — Admin only
Path params	id (int, required) — shelterID
Body fields	Any subset of the fields listed in 4.1

shelterLocation is re-geocoded when shelterAddress or shelterZIP is present in the body (using the new ZIP if provided, otherwise the shelter's existing one) — both the geocode and the DB write share one transaction, so a bad geocode fails cleanly with nothing partially applied.

Response

200 OK, same shape as 4.1's response.

Error Cases

Scenario	Error Code	HTTP Status
No updatable fields provided	BAD_REQUEST	400

A provided field fails validation	BAD_REQUEST	400
ZIP can't be geocoded	BAD_REQUEST	400
Shelter does not exist	NOT_FOUND	404

4.3 PATCH /api/v1/shelters/:id/status

Changes a shelter's shelterStatus.

Request

Field	Value
Method	PATCH
Auth required	Yes — Admin only
Path params	id (int, required) — shelterID
Body fields	shelterStatus (string, required — "Open", "Full", or "Closed")

Response

200 OK, same shape as 4.1's response.

Error Cases

Scenario	Error Code	HTTP Status
shelterStatus missing or invalid	BAD_REQUEST	400
Shelter does not exist	NOT_FOUND	404

4.4 PATCH /api/v1/shelters/:id/manager

(Re)assigns the staff member who manages a shelter.

Request

Field	Value
Method	PATCH
Auth required	Yes — Admin only
Path params	id (int, required) — shelterID
Body fields	managerStaffID (int, required)

managerStaffID must belong to a staff member already assigned to THIS shelter — a staff member who exists but works elsewhere is treated as not-found (404), identical to a nonexistent ID. A Deactivated staff member at the right shelter is rejected with 409 rather than being silently accepted.

Response

200 OK, same shape as 4.1's response.

Error Cases

Scenario	Error Code	HTTP Status
managerStaffID missing or not a positive integer	BAD_REQUEST	400
Shelter doesn't exist, or managerStaffID doesn't	NOT_FOUND	404

belong to a staff member at this shelter		
Staff member is Deactivated	CONFLICT	409

5. Analytics

5.1 GET /api/v1/analytics/overview

Returns an org-wide KPI summary. No params. Computed as four grouped-count queries (shelters by shelterStatus, pets by adoptionStatus, adopters by accountStatus, applications by applicationStatus) — O(1) queries regardless of data volume, no per-row loops.

Request

Field	Value
Method	GET
Auth required	Yes — Admin only
Path/Body fields	None

Response

```
200 OK
{
  "success": true,
  "message": "Overview retrieved successfully",
  "data": {
    "shelters": { "total": 6, "byStatus": { "Open": 5, "Full": 1, "Closed":
0 } },
    "pets": { "total": 210, "byStatus": { "available": 140, "...": "..." } },
    "adopters": { "total": 340, "byStatus": { "Active": 330, "Banned": 2,
"Deactivated": 8 } },
    "applications": {
      "total": 95,
      "byStatus": { "Pending": 20, "Accepted": 60, "Rejected": 10, "Withdrawn": 5
    },
    "adoptionRate": 0.42
  }
}
```

adoptionRate is Accepted ÷ total applications, rounded to 2 decimal places — null (not 0) when there are no applications yet, since 0% would misleadingly imply every application was rejected rather than none existing.

Error Cases

Scenario	Error Code	HTTP Status
No/invalid token	UNAUTHORIZED	401

5.2 GET /api/v1/analytics/shelters

Returns per-shelter stats, not paginated (this list is also what backs the Admin Shelters tab's list and edit-form pre-fill, not just an analytics view). Ordered by shelterName ascending by default.

Request

Field	Value
Method	GET
Auth required	Yes — Admin only
Query params	sortBy (optional — "utilization" or "petCount" — ranks highest-first instead of alphabetical; shelters with no computable utilization sort last)

Response

```
200 OK
{
  "success": true,
  "message": "Shelter analytics retrieved successfully",
  "data": [
    {
      "shelterID": 3,
      "shelterName": "...",
      "shelterAddress": "...",
      "shelterPhone": "...",
      "shelterEmail": "...",
      "shelterZIP": "...",
      "shelterSize": 40,
      "shelterStatus": "Open",
      "managerStaffID": 5,
      "petCount": 28,
      "petsByStatus": { "available": 20, "adopted": 5, "fostered": 3 },
      "openApplicationCount": 6,
      "staffCount": 4,
      "utilization": 70.0
    }
  ]
}
```

openApplicationCount counts Pending applications only. staffCount counts Active staff only. utilization is pet count ÷ shelterSize as a PERCENTAGE, 2dp — null, not 0, for a zero-capacity shelter. Note this is a percentage, unlike adoptionRate's 0–1 fraction above.

Error Cases

Scenario	Error Code	HTTP Status
sortBy not one of the two allowed values	BAD_REQUEST	400

5.3 GET /api/v1/analytics/monthly-stats

Returns Jan–Dec monthly stats for one calendar year, for the Admin Overview chart.

Request

Field	Value
Method	GET
Auth required	Yes — Admin only
Query params	year (optional int, min 2000, default the current year)

Response

```
200 OK
{
  "success": true,
  "message": "Monthly stats retrieved successfully",
  "data": [
    { "month": "Jan", "year": 2026, "intake": 12, "adoptions": 8 },
    { "month": "Feb", "year": 2026, "intake": 9, "adoptions": 6 }
  ]
}
```

Array of 12 objects in Jan→Dec order. Intake counts pets by Pet.intakeDate; Adoptions counts applications with applicationStatus 'Accepted' by their submission month (createdAt) — the schema has no separate “accepted on” timestamp, the same approximation adoptionRate already makes. All bucketing uses UTC month/year, so results don't shift based on where the server process happens to run.

Error Cases

Scenario	Error Code	HTTP Status
year is not an integer between 2000 and the current year	BAD_REQUEST	400

6. Government ID Review

6.1 GET /api/v1/government-ids

Returns the government ID submissions an admin can review — shelter Managers' and other Admins' IDs.

Request

Field	Value
Method	GET
Auth required	Yes — Admin only
Query params	section (optional — pending or reviewed), userType (optional filter), name (optional — search by name)

Response

200 OK, list of government ID submissions matching the filters.

Error Cases

Scenario	Error Code	HTTP Status
No/invalid token	UNAUTHORIZED	401

6.2 GET /api/v1/government-ids/:id

Returns full detail for one submission, including the full idNumber, a signed documentURL that expires after 5 minutes, and documentKind (image, pdf, or file) so the frontend knows how to render the document.

Request

Field	Value
Method	GET
Auth required	Yes — Admin only
Path params	id (int, required) — governmentIDID

Response

```
200 OK
{
  "success": true,
  "message": "Government ID retrieved successfully",
  "data": {
    "governmentIDID": 7,
    "userID": 5,
    "userType": "Staff",
    "idType": "Driver's License",
    "idNumber": "D1234567",
    "verificationStatus": "Pending",
    "documentURL": "https://... (signed, expires in 5 minutes)",
    "documentKind": "pdf"
  }
}
```

Error Cases

Scenario	Error Code	HTTP Status
id is not a positive integer	BAD_REQUEST	400
Submission does not exist	NOT_FOUND	404

6.3 PATCH /api/v1/government-ids/:id/status

Verifies or rejects a government ID submission.

Request

Field	Value
Method	PATCH
Auth required	Yes — Admin only
Path params	id (int, required) — governmentIDID
Body fields	verificationStatus (string, required — "Verified" or "Rejected")

Only a Pending submission can be reviewed. An admin can't review their own government ID — that returns 403.

Response

200 OK, the updated submission, same shape as 6.2.

Error Cases

Scenario	Error Code	HTTP Status
verificationStatus missing or invalid	BAD_REQUEST	400
Reviewing your own government ID	FORBIDDEN	403
Submission does not exist	NOT_FOUND	404
Submission is not Pending	CONFLICT	409