

PetPals [Animal Adoption Management System] – Staff Portal API Reference

This document defines the shelter-staff endpoints — pet management, applications, visits, appointments, transfers, tasks, events, volunteers, donations, government ID review, team management and staff self-service. It follows the conventions in 07-Public API Reference (base URL, response envelope, error codes), which are not repeated here. All endpoints require a Bearer token; roles are listed per endpoint. Staff are always scoped to their own shelter (re-fetched from the STAFF table on every request, never taken from the token or request body).

1. Pets & Photos

1.1 GET /api/v1/staff/me/pets

Returns every pet at the staff member's shelter, regardless of adoption status, optionally filtered.

Request

Field	Value
Method	GET
Auth required	Yes — Staff only
Query params	adoptionStatus (optional — incoming / available / adopted / fostered / transferred / deceased), species (repeatable speciesID), breed (repeatable breedName), size (repeatable — Small / Medium / Large), minAge / maxAge (int, months, inclusive), sort (optional — "newest" orders by intakeDate descending; default is petID descending), page (int, optional, default 1), limit (int, optional, default 20)

Response

```
200 OK
{
  "success": true,
  "message": "Pets retrieved successfully",
  "data": [
    {
      "petID": 9,
      "petName": "Buddy",
      "petAge": "2 yr",
      "petSex": "M",
      "petPhoto": "...",
      "breed": { "...": "..."},
      "adoptionStatus": "incoming"
    }
  ],
  "pagination": { "page": 1, "limit": 20, "total": 42, "totalPages": 3 }
}
```

Error Cases

Scenario	Error Code	HTTP Status
----------	------------	-------------

Invalid adoptionStatus value	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Role not permitted	FORBIDDEN	403
The staff member has no shelter assigned yet	CONFLICT	409

1.2 GET /api/v1/staff/me/pets/:id

Returns full detail for one pet at the staff member's shelter — richer than public GET /pets/:id.

Request

Field	Value
Method	GET
Auth required	Yes — Staff only
Path params	id (int, required) — petID

Response

```
200 OK
{
  "success": true,
  "message": "Pet retrieved successfully",
  "data": {
    "petID": 9,
    "petCode": "PE000009",
    "petName": "Buddy",
    "petDOB": "2024-02-14",
    "petAge": "2 yr",
    "petSize": "Medium",
    "petBGroup": "N/A",
    "microchipID": "982000123456789",
    "intakeDate": "2026-05-02",
    "intakeType": "stray",
    "featuredFlag": false,
    "...": "...same fields as public GET /pets/:id"
  }
}
```

Error Cases

Scenario	Error Code	HTTP Status
id is not a positive integer	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Pet is at another shelter	FORBIDDEN	403
Pet does not exist	NOT_FOUND	404

1.3 GET /api/v1/staff/me/pets/:id/health-passport

Returns a pet's full health passport: its detail plus health records, vaccinations and transfer history.

Request

Field	Value
Method	GET
Auth required	Yes — Staff only
Path params	id (int, required) — petID

transferHistory is not scoped to the caller's shelter — the passport shows the pet's full network-wide history. Each vaccination's status (Overdue / Due Soon / Up to Date) is computed from how close its dueDate is.

Response

```
200 OK
{
  "success": true,
  "message": "Health passport retrieved successfully",
  "data": {
    "pet": { "...": "same shape as 1.2" },
    "healthRecords": [
      { "recordID": 4, "createdAt": "2026-06-10T10:00:00Z", "recordDesc": "...",
        "vetName": "...", "shelterName": "..." }
    ],
    "vaccinations": [
      { "recordID": 15, "vaccineName": "Rabies", "administeredDate": "2026-01-10T00:00:00Z", "dueDate": "2027-01-10T00:00:00Z", "status": "Up to Date" }
    ],
    "transferHistory": [
      { "recordID": 2, "transferDate": "2026-03-02T09:00:00Z", "transferReason": "...", "transferStatus": "Completed", "fromShelterName": "...", "toShelterName": "...", "fromStaffName": "...", "toStaffName": "..." }
    ]
  }
}
```

Error Cases

Scenario	Error Code	HTTP Status
id is not a positive integer	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Pet is at another shelter	FORBIDDEN	403
Pet does not exist	NOT_FOUND	404

1.4 POST /api/v1/pets

Creates a new pet profile.

Request

Field	Value
Method	POST

Auth required	Yes — Staff, Admin
Body fields	breedID, petName (≤45), petDOB (date), petSex (M/F), petColor (≤45), petSize (Small / Medium / Large), intakeDate (date), petWeight, petHeight — all required; petBGroup (optional, ≤5, defaults to 'N/A'), intakeType (optional — stray / surrendered / transferred), adoptionStatus (optional, defaults to 'incoming'), shelterID (Admin only — required for Admin, ignored for Staff)

shelterID is never read from the body for Staff. petPhoto starts as a placeholder — POST /pets/:id/photos supplies the real one. The default adoptionStatus 'incoming' keeps the pet out of the public catalog until staff mark it 'available'.

Response

201 Created

```
{
  "success": true,
  "message": "Pet created successfully",
  "data": {
    "petID": 21,
    "petName": "Luna",
    "petAge": "1 yr",
    "petSex": "F",
    "petPhoto": "...",
    "petColor": "Black",
    "petHeight": 30.5,
    "petWeight": 8.2,
    "petDesc": null,
    "breed": { "breedID": 3, "breedName": "...", "speciesName": "..." },
    "shelter": { "shelterID": 3, "shelterName": "...", "shelterAddress": "..." },
    "compatibleWithChildren": false,
    "compatibleWithPets": false,
    "specialNeeds": false
  }
}
```

Error Cases

Scenario	Error Code	HTTP Status
Missing/invalid field, breedID doesn't reference an existing breed, or (Admin) shelterID doesn't reference an existing shelter	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Role not permitted	FORBIDDEN	403
Staff caller has no shelter assigned yet	CONFLICT	409

1.5 PUT /api/v1/pets/:id

Partially updates a pet's profile, optionally replacing its photo in the same request.

Request

Field	Value
Method	PUT

Auth required	Yes — Staff, Admin
Path params	id (int, required) — petID
Content-Type	multipart/form-data
Body fields	Any subset of: breedID, petName, petDOB, petSex, petColor, petSize, intakeDate, intakeType, petWeight, petHeight, petBGroup, petDesc (≤500), microchipID (≤45), featuredFlag, compatibleWithChildren, compatibleWithPets, specialNeeds, adoptionStatus; file (optional — replaces the pet's photo)

Staff may only edit pets at their own shelter; Admin may edit any. shelterID can't change here (that's a transfer). adoptionStatus 'adopted'/'transferred' are set only by the adoption/transfer workflows. A pet mid-transfer is read-only; an adopted pet may only have its adoptionStatus changed. v1 holds one photo per pet.

Response

```
200 OK
{
  "success": true,
  "message": "Pet updated successfully",
  "data": { "...": "same shape as 1.4" }
}
```

Error Cases

Scenario	Error Code	HTTP Status
No updatable fields, invalid field (including adoptionStatus 'adopted'/'transferred'), unsupported photo file type, or unknown breedID	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Pet is at another shelter	FORBIDDEN	403
Pet does not exist	NOT_FOUND	404
Pet is mid-transfer, or adopted and the update touches more than adoptionStatus	CONFLICT	409

1.6 DELETE /api/v1/pets/:id

Deletes a pet profile and its stored photos.

Request

Field	Value
Method	DELETE
Auth required	Yes — Shelter Manager, Admin
Path params	id (int, required) — petID

Staff must be the manager of the pet's shelter (Shelter.managerStaffID); Admin may delete any pet. Photos are removed from the pet-images Storage bucket before the row.

Response

```
200 OK
{
  "success": true,
  "message": "Pet deleted successfully",
}
```

```
"data": null
}
```

Error Cases

Scenario	Error Code	HTTP Status
No/invalid token	UNAUTHORIZED	401
Pet is at another shelter, or the caller isn't that shelter's manager	FORBIDDEN	403
Pet does not exist	NOT_FOUND	404
Pet has a Pending or Accepted adoption application, or is adopted/mid-transfer	CONFLICT	409

1.7 GET /api/v1/pets/:id/photos

Returns a pet's current photos.

Request

Field	Value
Method	GET
Auth required	Yes — Staff, Admin
Path params	id (int, required) — petID

Response

```
200 OK
{
  "success": true,
  "message": "Photos retrieved successfully",
  "data": [
    {
      "photoID": 31,
      "photoURL": "...",
      "uploadedAt": "2026-09-01T10:00:00Z",
      "isPrimary": true
    }
  ]
}
```

Error Cases

Scenario	Error Code	HTTP Status
No/invalid token	UNAUTHORIZED	401
Pet is at another shelter	FORBIDDEN	403
Pet does not exist	NOT_FOUND	404

1.8 POST /api/v1/pets/:id/photos

Uploads a pet's photo, replacing the existing one.

Request

Field	Value
Method	POST
Auth required	Yes — Staff, Admin
Path params	id (int, required) — petID
Content-Type	multipart/form-data
Body fields	file (required — JPEG / PNG / WebP)

v1 supports one photo per pet: an upload replaces the previous photo, whose Storage object and PetPhoto row are removed only once the new one is committed. Only JPEG, PNG and WebP are accepted.

Response

```
201 Created
{
  "success": true,
  "message": "Photo uploaded successfully",
  "data": [
    {
      "photoID": 31,
      "photoURL": "...",
      "uploadedAt": "2026-09-01T10:00:00Z",
      "isPrimary": true
    }
  ]
}
```

Error Cases

Scenario	Error Code	HTTP Status
Missing file or unsupported file type	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Pet is at another shelter	FORBIDDEN	403
Pet does not exist	NOT_FOUND	404
Pet is adopted or mid-transfer (read-only)	CONFLICT	409

1.9 DELETE /api/v1/pets/:id/photos/:photoId

Removes a pet's photo from Storage and the database.

Request

Field	Value
Method	DELETE
Auth required	Yes — Staff, Admin
Path params	id (int, required) — petID; photoId (int, required) — photoID

If the removed photo was primary, the earliest remaining photo (if any) becomes primary.

Response

```
200 OK
{
  "success": true,
  "message": "Photo removed successfully",
  "data": []
}
```

Error Cases

Scenario	Error Code	HTTP Status
No/invalid token	UNAUTHORIZED	401
Pet is at another shelter	FORBIDDEN	403
Pet doesn't exist, or the photo doesn't exist/belong to this pet	NOT_FOUND	404
Pet is adopted or mid-transfer (read-only)	CONFLICT	409

1.10 POST /api/v1/species

Adds a species.

Request

Field	Value
Method	POST
Auth required	Yes — Staff, Admin
Body fields	speciesName (string, required, ≤45)

speciesName is trimmed and must be unique, compared case-insensitively.

Response

```
201 Created
{
  "success": true,
  "message": "Species created successfully",
  "data": { "speciesID": 4, "speciesName": "Rabbit" }
}
```

Error Cases

Scenario	Error Code	HTTP Status
speciesName missing, blank, or longer than 45 characters	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Role not permitted	FORBIDDEN	403
A species with that name already exists	CONFLICT	409

1.11 POST /api/v1/breeds

Adds a breed to a species.

Request

Field	Value
Method	POST
Auth required	Yes — Staff, Admin
Body fields	speciesID (int, required), breedName (string, required, ≤45)

breedName is trimmed and must be unique within its species, compared case-insensitively.

Response

```
201 Created
{
  "success": true,
  "message": "Breed created successfully",
  "data": { "breedID": 12, "breedName": "Beagle", "speciesName": "Dog" }
}
```

Error Cases

Scenario	Error Code	HTTP Status
Invalid speciesID, or breedName missing, blank, or longer than 45 characters	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Role not permitted	FORBIDDEN	403
Species does not exist	NOT_FOUND	404
That species already has a breed with that name	CONFLICT	409

2. Adoption Applications

2.1 GET /api/v1/adoption-applications

Returns the shelter's paginated application queue, split into active and past sections.

Request

Field	Value
Method	GET
Auth required	Yes — Staff, Admin (queue branch)
Query params	section (required — "active" = Pending; "past" = Accepted / Rejected / Withdrawn), species (repeatable speciesID), adopterName (contains match), petName (contains match), shelterID (Admin only), page (int, optional, default 1), limit (int, optional, 1–100, default 20)

The same path serves the Adopter's checkoutSessionId lookup (see 09-Adopter API Reference). Admin sees all shelters, optionally filtered by shelterID.

Response

```
200 OK
{
  "success": true,
```

```
"message": "Applications retrieved successfully",
"data": [
  {
    "...": "..."
  }
],
"pagination": { "page": 1, "limit": 20, "total": 42, "totalPages": 3 }
```

Error Cases

Scenario	Error Code	HTTP Status
Invalid or missing input	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Staff/Admin sending checkoutSessionId, or an Adopter omitting it	FORBIDDEN	403

2.2 PATCH /api/v1/adoption-applications/:id/status

Accepts or rejects a Pending adoption application.

Request

Field	Value
Method	PATCH
Auth required	Yes — Staff, Admin (Adopters use this endpoint to withdraw)
Path params	id (int, required) — applicationID
Body fields	status (string, required — "Accepted" or "Rejected"; "Withdrawn" is Adopter-only), staffRemark (string, optional, ≤500, nullable)

Staff/Admin may move only a Pending application to Accepted or Rejected. Accepting sets staffID to the acting Staff member (never for an Admin) and the pet's adoptionStatus to 'adopted'; Rejecting leaves the pet available to other applicants and lets the adopter re-apply for it.

A pet goes to one applicant. Accepting marks the pet adopted and moves the pet's OTHER Pending applications to Rejected with an automatic staffRemark ('Another applicant was approved for this pet...'). Accepting when the pet is no longer available returns 409 ('<pet> is no longer available — another application has already been accepted'). A one-Accepted-per-pet unique index also stops two simultaneous acceptances.

Response

```
200 OK
{
  "success": true,
  "message": "Application updated successfully",
  "data": {
    "applicationID": 44,
    "petID": 9,
    "adopterID": 12,
    "shelterID": 3,
    "staffID": 5,
    "applicationStatus": "Accepted",
```

```

    "applicationType": "Adopt",
    "shelterMessage": "...",
    "paymentStatus": "Paid",
    "amountPaid": 15.00,
    "createdAt": "2026-08-03T09:00:00Z",
    "pet": { "petName": "Buddy" },
    "shelter": { "shelterName": "..." }
  }
}

```

Error Cases

Scenario	Error Code	HTTP Status
Invalid or missing input	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Role not permitted, or Staff acting on another shelter's application	FORBIDDEN	403
Application does not exist	NOT_FOUND	404
The application isn't in a status the transition allows	CONFLICT	409
Accepting when the pet is no longer available — another application has already been accepted	CONFLICT	409

2.3 PATCH /api/v1/adoption-applications/:id

Assigns the staff member handling an application.

Request

Field	Value
Method	PATCH
Auth required	Yes — Shelter Manager, Admin
Path params	id (int, required) — applicationID
Body fields	staffID (int, required)

staffID is the only editable field. Only the application's shelter manager (Shelter.managerStaffID) or an Admin may set it, only while the application is Pending, and only to an Active staff member at that shelter.

Response

```

200 OK
{
  "success": true,
  "message": "Application updated successfully",
  "data": {
    "applicationID": 44,
    "applicationCode": "APP-00044",
    "staffID": 6,
    "applicationStatus": "Pending",
    "assignedStaffName": "...",
    "pet": { "petName": "Buddy", "petPhoto": "...", "breedName": "...",
    "speciesName": "..." },
  }
}

```

```

    "shelter": { "shelterName": "..."},
    "adopter": { "adopterName": "...", "adopterEmail": "...", "...":
"...contact/household fields" },
    "governmentIdStatus": "Verified",
    "otherPendingCount": 1,
    "canAssignStaff": true,
    "...": "...other application fields"
  }
}

```

otherPendingCount — Staff/Admin only: how many other Pending applications this pet has — accepting this one declines them all.

Error Cases

Scenario	Error Code	HTTP Status
Invalid id/staffID, or the staff member isn't active at the application's shelter	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Caller isn't the application's shelter manager	FORBIDDEN	403
Application does not exist	NOT_FOUND	404
Application is no longer Pending	CONFLICT	409

3. Visits

3.1 GET /api/v1/visits

Returns the shelter's paginated visit queue.

Request

Field	Value
Method	GET
Auth required	Yes — Staff, Admin
Query params	upcoming ("true" — future, non-Cancelled, soonest first), past ("true" — past or Cancelled, newest first; can't combine with upcoming), status (Unconfirmed / Confirmed / Completed / Cancelled — Unconfirmed = no visitStatus yet), name (adopter or assigned staff name, case-insensitive), shelterID (Admin only), page (int, optional, default 1), limit (int, optional, 1–100, default 20)

Response

```

200 OK
{
  "success": true,
  "message": "Visits retrieved successfully",
  "data": [
    {
      "visitID": 21,
      "adopterID": 12,
      "petID": 9,

```

```

      "staffID": null,
      "shelterID": 3,
      "visitTime": "2026-10-10T14:00:00Z",
      "remarks": "...",
      "visitStatus": null,
      "pet": { "petName": "Buddy" },
      "adopter": { "adopterName": "...", "user": { "userEmail": "..." } },
      "staff": null
    }
  ],
  "pagination": { "page": 1, "limit": 20, "total": 42, "totalPages": 3 }
}

```

Error Cases

Scenario	Error Code	HTTP Status
Invalid or missing input	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Role not permitted	FORBIDDEN	403

3.2 PATCH /api/v1/visits/:id

Confirms or completes a visit.

Request

Field	Value
Method	PATCH
Auth required	Yes — Staff, Admin (Adopters use this endpoint to cancel)
Path params	id (int, required) — visitID
Body fields	visitStatus (string, required — "Confirmed" or "Completed"; "Cancelled" is Adopter-only)

Staff/Admin may confirm an unconfirmed (null-status) visit, then complete a Confirmed one. Confirming or completing sets staffID to the acting Staff member (never for an Admin).

Response

```

200 OK
{
  "success": true,
  "message": "Visit updated successfully",
  "data": {
    "visitID": 21,
    "adopterID": 12,
    "petID": 9,
    "staffID": 5,
    "shelterID": 3,
    "visitTime": "2026-10-10T14:00:00Z",
    "remarks": "...",
    "visitStatus": "Confirmed",
  }
}

```

```
    "shelter": { "shelterName": "... " },
    "pet": { "petName": "Buddy" }
  }
}
```

Error Cases

Scenario	Error Code	HTTP Status
Invalid or missing input	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Role not permitted, or Staff acting on another shelter's visit	FORBIDDEN	403
Visit does not exist	NOT_FOUND	404
The visit isn't in a status the transition allows	CONFLICT	409

4. Appointments

4.1 GET /api/v1/appointments

Returns the shelter's paginated appointments, upcoming or past.

Request

Field	Value
Method	GET
Auth required	Yes — Staff, Admin
Query params	upcoming (boolean, optional, default false — true: Scheduled with a future date; false: past-dated or Cancelled), vetID (int), petName, shelterID (Admin only — omit for network-wide), page (int, optional, default 1), limit (int, optional, max 100, default 20)

Response

```
200 OK
{
  "success": true,
  "message": "Appointments retrieved successfully",
  "data": [
    {
      "appointmentID": 8,
      "appointmentDate": "2026-10-05T10:00:00Z",
      "appointmentReason": "Annual checkup",
      "status": "Scheduled",
      "pet": { "petID": 9, "petName": "Buddy", "petPhoto": "...", "breedName": "...", "speciesName": "... " },
      "vetName": "..."
    }
  ],
  "pagination": { "page": 1, "limit": 20, "total": 42, "totalPages": 3 }
}
```

Error Cases

Scenario	Error Code	HTTP Status
Missing/invalid query param	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Role not permitted	FORBIDDEN	403

4.2 POST /api/v1/appointments

Creates a vet appointment at the shelter.

Request

Field	Value
Method	POST
Auth required	Yes — Staff, Admin
Body fields	petID (int, required), vetID (int, required), appointmentDate (date-time, required, not in the past), appointmentReason (string, required, ≤300), volunteerID (int, optional), staffID (int, optional — defaults to the acting Staff member), shelterID (Admin only — required for Admin)

petID must belong to the resolved shelter, vetID must be an Active vet there, volunteerID a volunteer there, and staffID an Active staff member there. staffID is null when an Admin creates without one.

Response

```
201 Created
{
  "success": true,
  "message": "Appointment created successfully",
  "data": {
    "appointmentID": 8,
    "appointmentCode": "APT-00008",
    "appointmentDate": "2026-10-05T10:00:00Z",
    "appointmentReason": "Annual checkup",
    "pet": { "petID": 9, "petName": "Buddy", "petPhoto": "...", "breedName": "...", "speciesName": "..."},
    "vetName": "...",
    "shelterName": "...",
    "shelterAddress": "...",
    "vaccinesAdministered": []
  }
}
```

Error Cases

Scenario	Error Code	HTTP Status
Missing/invalid field, or petID/vetID/volunteerID/staffID don't belong to the resolved shelter	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Role not permitted	FORBIDDEN	403

Referenced resource does not exist	NOT_FOUND	404
Staff caller has no shelter assigned yet	CONFLICT	409

4.3 GET /api/v1/appointments/:id

Returns one appointment's full detail, including the vaccines administered at it.

Request

Field	Value
Method	GET
Auth required	Yes — Staff, Admin
Path params	id (int, required) — appointmentID

Response

```
200 OK
{
  "success": true,
  "message": "Appointment retrieved successfully",
  "data": {
    "appointmentID": 8,
    "appointmentCode": "APT-00008",
    "appointmentDate": "2026-10-05T10:00:00Z",
    "appointmentReason": "Annual checkup",
    "pet": { "petID": 9, "petName": "Buddy", "petPhoto": "...", "breedName": "...", "speciesName": "..."},
    "vetName": "...",
    "shelterName": "...",
    "shelterAddress": "...",
    "vaccinesAdministered": [
      { "recordID": 15, "vaccineName": "Rabies", "dueDate": "2027-10-05T00:00:00Z" }
    ]
  }
}
```

Error Cases

Scenario	Error Code	HTTP Status
id is not a positive integer	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Appointment is at another shelter	FORBIDDEN	403
Appointment does not exist	NOT_FOUND	404

4.4 PATCH /api/v1/appointments/:id

Edits a Scheduled, upcoming appointment.

Request

Field	Value
Method	PATCH
Auth required	Yes — Staff, Admin
Path params	id (int, required) — appointmentID
Body fields	Any subset of: vetID, staffID, volunteerID (null to unassign), appointmentDate, appointmentReason (≤300)

Only a Scheduled appointment whose date hasn't passed can be edited. petID, shelterID and status can't be sent (400). vetID/staffID must be active at the appointment's shelter. The pet + vet + time double-booking guard applies, excluding this appointment.

Response

```
200 OK
{
  "success": true,
  "message": "Appointment updated successfully",
  "data": { "...": "same shape as 4.3" }
}
```

Error Cases

Scenario	Error Code	HTTP Status
Invalid/locked/no fields, past date, or a vet/staff/volunteer not at this shelter	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Appointment is at another shelter	FORBIDDEN	403
Appointment does not exist	NOT_FOUND	404
No longer Scheduled/upcoming, or the new slot is already booked	CONFLICT	409

4.5 PATCH /api/v1/appointments/:id/cancel

Cancels a Scheduled, upcoming appointment.

Request

Field	Value
Method	PATCH
Auth required	Yes — Staff, Admin
Path params	id (int, required) — appointmentID

Only a Scheduled appointment whose date hasn't passed can be cancelled.

Response

```
200 OK
{
  "success": true,
  "message": "Appointment cancelled successfully",
  "data": { "...": "same shape as 4.3" }
}
```

```
}
```

Error Cases

Scenario	Error Code	HTTP Status
id is not a positive integer	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Appointment is at another shelter	FORBIDDEN	403
Appointment does not exist	NOT_FOUND	404
Appointment is no longer Scheduled/upcoming	CONFLICT	409

4.6 GET /api/v1/appointments/vets

Lists the shelter's active vets for the appointment form's dropdowns.

Request

Field	Value
Method	GET
Auth required	Yes — Staff, Admin
Query params	shelterID (int — required for Admin; Staff is scoped automatically)

Response

```
200 OK
{
  "success": true,
  "message": "Vets retrieved successfully",
  "data": [
    {
      "...": "..."
    }
  ]
}
```

Error Cases

Scenario	Error Code	HTTP Status
shelterID missing/invalid (Admin)	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Role not permitted	FORBIDDEN	403

4.7 GET /api/v1/appointments/volunteers

Lists the shelter's active volunteers for the appointment form's dropdowns.

Request

Field	Value
Method	GET

Auth required	Yes — Staff, Admin
Query params	shelterID (int — required for Admin; Staff is scoped automatically)

Response

```
200 OK
{
  "success": true,
  "message": "Volunteers retrieved successfully",
  "data": [
    {
      "...": "..."
    }
  ]
}
```

Error Cases

Scenario	Error Code	HTTP Status
shelterID missing/invalid (Admin)	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Role not permitted	FORBIDDEN	403

4.8 GET /api/v1/appointments/staff

Lists the shelter's active staff for the appointment form's dropdowns.

Request

Field	Value
Method	GET
Auth required	Yes — Staff, Admin
Query params	shelterID (int — required for Admin; Staff is scoped automatically)

Response

```
200 OK
{
  "success": true,
  "message": "Staff retrieved successfully",
  "data": [
    {
      "...": "..."
    }
  ]
}
```

Error Cases

Scenario	Error Code	HTTP Status
shelterID missing/invalid (Admin)	BAD_REQUEST	400

No/invalid token	UNAUTHORIZED	401
Role not permitted	FORBIDDEN	403

5. Transfers

5.1 GET /api/v1/transfers

Returns the shelter's paginated incoming or outgoing transfers.

Request

Field	Value
Method	GET
Auth required	Yes — Staff, Admin
Query params	direction (required — "incoming" = this shelter is the destination; "outgoing" = this shelter sent it), status (In_Progress / Completed / Rejected / Cancelled), shelterName (matches the other shelter's name), petName, shelterID (Admin only — omit for network-wide), page (int, optional, default 1), limit (int, optional, max 100, default 20)

Response

```
200 OK
{
  "success": true,
  "message": "Transfers retrieved successfully",
  "data": [
    {
      "recordID": 3,
      "petID": 9,
      "transferDate": "2026-09-20T09:00:00Z",
      "fromShelterID": 3,
      "toShelterID": 5,
      "transferStatus": "In_Progress",
      "transferReason": "...",
      "pet": { "petName": "Buddy", "petPhoto": "...", "breedName": "...",
      "speciesName": "... },
      "fromShelter": { "shelterName": "... },
      "toShelter": { "shelterName": "... }
    }
  ],
  "pagination": { "page": 1, "limit": 20, "total": 42, "totalPages": 3 }
}
```

Error Cases

Scenario	Error Code	HTTP Status
Missing/invalid direction, status, or pagination param	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Role not permitted	FORBIDDEN	403

5.2 POST /api/v1/transfers

Initiates an inter-shelter pet transfer.

Request

Field	Value
Method	POST
Auth required	Yes — Staff, Admin
Body fields	petID (int, required), toShelterID (int, required — must differ from the origin), transferReason (string, required, ≤300), fromShelterID (Admin only — required for Admin)

Only a pet currently 'available' at the origin shelter can be transferred. On success its adoptionStatus becomes 'transferred' until the transfer is approved, declined or cancelled.

Response

```
201 Created
{
  "success": true,
  "message": "Transfer created successfully",
  "data": {
    "recordID": 3,
    "petID": 9,
    "transferDate": "2026-09-20T09:00:00Z",
    "fromShelterID": 3,
    "toShelterID": 5,
    "transferStatus": "In_Progress",
    "transferReason": "...",
    "fromShelterStaff": 5,
    "toShelterStaff": 11,
    "fromStaff": { "staffName": "..." },
    "toStaff": { "staffName": "..." },
    "canReassignToShelterStaff": false,
    "pet": { "petName": "Buddy", "petPhoto": "...", "breedName": "...",
    "speciesName": "...", "petAge": "~4 yrs", "petSex": "M", "petColor": "Brown" },
    "fromShelter": { "shelterName": "..." },
    "toShelter": { "shelterName": "..." }
  }
}
```

Error Cases

Scenario	Error Code	HTTP Status
Missing/invalid field, toShelterID doesn't reference an existing shelter, or a shelter mismatch	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Pet is at another shelter	FORBIDDEN	403
Referenced resource does not exist	NOT_FOUND	404
Pet isn't available for transfer, or Staff has no shelter	CONFLICT	409

assigned yet		
--------------	--	--

5.3 GET /api/v1/transfers/assignees

Previews the staff a new transfer will be assigned.

Request

Field	Value
Method	GET
Auth required	Yes — Staff, Admin
Query params	toShelterID (int, optional)

Resolves exactly what POST /transfers assigns: fromShelterStaff is the acting staff member (null for Admin); toShelterStaff is the destination shelter's manager (null if it has none, or if toShelterID is omitted).

Response

```
200 OK
{
  "success": true,
  "message": "Assignees retrieved successfully",
  "data": {
    "fromShelterStaff": { "staffID": 5, "staffName": "..."},
    "toShelterStaff": { "staffID": 11, "staffName": "..."}
  }
}
```

Error Cases

Scenario	Error Code	HTTP Status
toShelterID is not a positive integer	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Role not permitted	FORBIDDEN	403
Shelter does not exist	NOT_FOUND	404

5.4 GET /api/v1/transfers/:id

Returns one transfer's full detail.

Request

Field	Value
Method	GET
Auth required	Yes — Staff, Admin
Path params	id (int, required) — recordID

Staff may view a transfer touching their shelter on either side (origin or destination).

Response

```
200 OK
```

```
{
  "success": true,
  "message": "Transfer retrieved successfully",
  "data": { "...": "same shape as 5.2" }
}
```

Error Cases

Scenario	Error Code	HTTP Status
id is not a positive integer	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Transfer doesn't touch the caller's shelter	FORBIDDEN	403
Transfer does not exist	NOT_FOUND	404

5.5 PATCH /api/v1/transfers/:id

Reassigns a transfer's destination staff member.

Request

Field	Value
Method	PATCH
Auth required	Yes — Destination shelter Manager, Admin
Path params	id (int, required) — recordID
Body fields	toShelterStaff (int, required)

toShelterStaff is the only editable field. Only the destination shelter's manager (Shelter.managerStaffID) or an Admin may set it, only while the transfer is In_Progress, and only to an Active staff member at the destination shelter.

Response

```
200 OK
{
  "success": true,
  "message": "Transfer updated successfully",
  "data": { "...": "same shape as 5.2" }
}
```

Error Cases

Scenario	Error Code	HTTP Status
Invalid id/toShelterStaff, or the staff member isn't active at the destination shelter	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Caller isn't the destination shelter's manager	FORBIDDEN	403
Transfer does not exist	NOT_FOUND	404
Transfer is no longer In_Progress	CONFLICT	409

5.6 PATCH /api/v1/transfers/:id/status

Approves, declines, or cancels an in-progress transfer.

Request

Field	Value
Method	PATCH
Auth required	Yes — Staff, Admin
Path params	id (int, required) — recordID
Body fields	status (string, required — "Completed", "Rejected", or "Cancelled")

Completed (approve) and Rejected (decline) may only be set by the destination shelter; Cancelled only by the origin shelter. Only an In_Progress transfer can move. Completed moves the pet to the new shelter, clears its assigned staff and sets it back to 'available'; Rejected/Cancelled leave it at the origin, back to 'available'.

Response

```
200 OK
{
  "success": true,
  "message": "Transfer updated successfully",
  "data": { "...": "same shape as 5.2" }
}
```

Error Cases

Scenario	Error Code	HTTP Status
Missing/invalid status or id	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Acting from the wrong side, or on another shelter's transfer	FORBIDDEN	403
Transfer does not exist	NOT_FOUND	404
Transfer is no longer In_Progress	CONFLICT	409

6. Tasks

6.1 GET /api/v1/tasks

Returns the shelter's paginated volunteer tasks, sorted by due date.

Request

Field	Value
Method	GET
Auth required	Yes — Staff, Admin
Query params	taskStatus (In_progress / Completed / Cancelled), dueFrom / dueTo (date-time bounds on taskDue), overdue (boolean — only In_progress tasks past due; overrides dueFrom/dueTo), volunteerName (matches any assigned volunteer), shelterID (Admin only), page (int, optional, default 1), limit (int, optional, max 100, default 20)

Each item's status is its taskStatus, or "Overdue" for an In_progress task past due.

Response

```
200 OK
{
  "success": true,
  "message": "Tasks retrieved successfully",
  "data": [
    {
      "taskID": 14,
      "taskName": "Feeding",
      "taskDesc": "...",
      "taskDate": "2026-09-25T08:00:00Z",
      "taskDue": "2026-09-30T17:00:00Z",
      "taskStatus": "In_progress",
      "status": "In_progress",
      "staffName": "...",
      "volunteers": [ { "volunteerID": 21, "volunteerName": "..." } ]
    }
  ],
  "pagination": { "page": 1, "limit": 20, "total": 42, "totalPages": 3 }
}
```

Error Cases

Scenario	Error Code	HTTP Status
Invalid taskStatus, date, shelterID, or pagination param	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Role not permitted	FORBIDDEN	403

6.2 POST /api/v1/tasks

Creates a task and assigns it to volunteers.

Request

Field	Value
Method	POST
Auth required	Yes — Staff, Admin
Body fields	taskName (required — Animal_Care / Vet_Assistance / Cleaning / Feeding / Events / Admin / Other), taskDesc (string, required, ≤300), taskDue (date-time, required, not in the past), volunteerIDs (int array, required), shelterID (Admin only — required for Admin)

Every volunteer must be Active at the task's shelter. taskDate is set to now and staffID to the acting staff member.

Response

```
201 Created
{
  "success": true,
  "message": "Task created successfully",
}
```

```
"data": {
  "taskID": 14,
  "taskName": "Feeding",
  "taskDesc": "...",
  "taskDate": "2026-09-25T08:00:00Z",
  "taskDue": "2026-09-30T17:00:00Z",
  "taskStatus": "In_progress",
  "status": "In_progress",
  "staffName": "...",
  "volunteers": [ { "volunteerID": 21, "volunteerName": "..." } ]
}
```

Error Cases

Scenario	Error Code	HTTP Status
Missing/invalid field, past due date, or a volunteer not active at this shelter	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Role not permitted	FORBIDDEN	403
Staff has no shelter assigned yet	CONFLICT	409

6.3 GET /api/v1/tasks/:id

Returns one task.

Request

Field	Value
Method	GET
Auth required	Yes — Staff, Admin
Path params	id (int, required) — taskID

Response

```
200 OK
{
  "success": true,
  "message": "Task retrieved successfully",
  "data": { "...": "same shape as 6.2" }
}
```

Error Cases

Scenario	Error Code	HTTP Status
id is not a positive integer	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Task is at another shelter	FORBIDDEN	403
Task does not exist	NOT_FOUND	404

6.4 PATCH /api/v1/tasks/:id

Edits an open task, including its volunteer assignment.

Request

Field	Value
Method	PATCH
Auth required	Yes — Staff, Admin
Path params	id (int, required) — taskID
Body fields	Any subset of: taskName, taskDesc (≤ 300), taskDue (not in the past), volunteerIDs (int array)

Only In_progress tasks can be edited. volunteerIDs replaces the whole assignee set.

Response

```
200 OK
{
  "success": true,
  "message": "Task updated successfully",
  "data": { "...": "same shape as 6.2" }
}
```

Error Cases

Scenario	Error Code	HTTP Status
Invalid/no fields, past due date, or a volunteer not active at this shelter	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Task is at another shelter	FORBIDDEN	403
Task does not exist	NOT_FOUND	404
Task is already Completed or Cancelled	CONFLICT	409

6.5 PATCH /api/v1/tasks/:id/status

Completes or cancels an open task.

Request

Field	Value
Method	PATCH
Auth required	Yes — Staff, Admin
Path params	id (int, required) — taskID
Body fields	taskStatus (string, required — "Completed" or "Cancelled")

Only In_progress tasks can change status.

Response

```
200 OK
{
  "success": true,
```

```

    "message": "Task updated successfully",
    "data": { "...": "same shape as 6.2" }
  }

```

Error Cases

Scenario	Error Code	HTTP Status
Missing/invalid taskStatus or id	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Task is at another shelter	FORBIDDEN	403
Task does not exist	NOT_FOUND	404
Task is already Completed or Cancelled	CONFLICT	409

7. Events

7.1 POST /api/v1/events

Creates a shelter event.

Request

Field	Value
Method	POST
Auth required	Yes — Staff, Admin
Body fields	eventName (string, required, ≤45), eventDesc (string, required, ≤300), eventCategory (required — Adoption_Event / Fundraiser / Volunteer_Orientation / Vaccination_Clinic / Community_Outreach / Workshop / Donation_Drive / Other), eventDate (date-time, required, not in the past), volunteerIDs (int array, optional — Active volunteers at the event's shelter), shelterID (Admin only — required for Admin)

Response

```

201 Created
{
  "success": true,
  "message": "Event created successfully",
  "data": {
    "eventID": 7,
    "eventName": "...",
    "eventDate": "2026-10-12T11:00:00Z",
    "eventDesc": "...",
    "eventCategory": "Adoption_Event",
    "shelter": { "shelterID": 3, "shelterName": "...", "shelterAddress": "..." }
  }
}

```

Error Cases

Scenario	Error Code	HTTP Status
Missing/invalid field, eventDate in the past, or (Admin) shelterID doesn't reference an existing	BAD_REQUEST	400

shelter		
No/invalid token	UNAUTHORIZED	401
Role not permitted	FORBIDDEN	403
Staff caller has no shelter assigned yet	CONFLICT	409

7.2 PUT /api/v1/events/:id

Partially updates an event; its shelter can't be changed.

Request

Field	Value
Method	PUT
Auth required	Yes — Staff, Admin
Path params	id (int, required) — eventId
Body fields	Any subset of: eventName (≤45), eventDesc (≤300), eventCategory, eventDate, volunteerIDs (replaces the assigned set; empty array = none)

Response

```
200 OK
{
  "success": true,
  "message": "Event updated successfully",
  "data": { "...": "same shape as 7.1" }
}
```

Error Cases

Scenario	Error Code	HTTP Status
No updatable fields provided, or an invalid field	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Event is at another shelter	FORBIDDEN	403
Event does not exist	NOT_FOUND	404

7.3 DELETE /api/v1/events/:id

Deletes an event along with its volunteer signups.

Request

Field	Value
Method	DELETE
Auth required	Yes — Staff, Admin
Path params	id (int, required) — eventId

Response

```
200 OK
{
```

```
"success": true,
"message": "Event deleted successfully",
"data": null
}
```

Error Cases

Scenario	Error Code	HTTP Status
id is not a positive integer	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Event is at another shelter	FORBIDDEN	403
Event does not exist	NOT_FOUND	404

7.4 GET /api/v1/events/:id/volunteers

Lists the volunteers assigned to an event, sorted by name (kept out of public GET /events/:id).

Request

Field	Value
Method	GET
Auth required	Yes — Staff, Admin
Path params	id (int, required) — eventId

Response

```
200 OK
{
  "success": true,
  "message": "Event volunteers retrieved successfully",
  "data": [
    { "volunteerID": 21, "volunteerName": "..." }
  ]
}
```

Error Cases

Scenario	Error Code	HTTP Status
id is not a positive integer	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Event is at another shelter	FORBIDDEN	403
Event does not exist	NOT_FOUND	404

8. Volunteers

8.1 GET /api/v1/volunteers

Returns the shelter's paginated volunteers.

Request

Field	Value
Method	GET
Auth required	Yes — Staff, Admin
Query params	accountStatus (Pending / Active / Banned / Deactivated), name (case-insensitive contains match on volunteerName), shelterID (Admin only — omit for network-wide), page (int, optional, default 1), limit (int, optional, max 100, default 20)

Response

```
200 OK
{
  "success": true,
  "message": "Volunteers retrieved successfully",
  "data": [
    {
      "userID": 21,
      "volunteerName": "...",
      "volunteerPhone": "...",
      "volunteerEmail": "...",
      "accountStatus": "Pending"
    }
  ],
  "pagination": { "page": 1, "limit": 20, "total": 42, "totalPages": 3 }
}
```

Error Cases

Scenario	Error Code	HTTP Status
Invalid accountStatus, shelterID, or pagination param	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Role not permitted	FORBIDDEN	403

8.2 GET /api/v1/volunteers/:id

Returns one volunteer's full profile, including login email and government ID type/number (null if none submitted).

Request

Field	Value
Method	GET
Auth required	Yes — Staff, Admin
Path params	id (int, required) — userID

Response

```
200 OK
{
  "success": true,
  "message": "Volunteer retrieved successfully",

```

```
"data": {
  "userID": 21,
  "volunteerCode": "VOL-00021",
  "avatarSeed": "a1b2c3d4-...",
  "volunteerName": "...",
  "addressLine1": "...",
  "addressLine2": null,
  "city": "...",
  "state": "...",
  "zip": "...",
  "country": "...",
  "volunteerPhone": "...",
  "volunteerDOB": "1998-07-21T00:00:00Z",
  "volunteerSex": "F",
  "volunteerSchedule": "...",
  "shelterID": 3,
  "shelterName": "...",
  "createdAt": "2026-08-01T10:00:00Z",
  "accountStatus": "Active",
  "volunteerEmail": "...",
  "governmentID": { "idType": "Passport", "idNumber": "..." }
}
```

Error Cases

Scenario	Error Code	HTTP Status
id is not a positive integer	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Volunteer is at another shelter	FORBIDDEN	403
Volunteer does not exist	NOT_FOUND	404

8.3 PATCH /api/v1/volunteers/:id/status

Approves, declines, or deactivates a volunteer.

Request

Field	Value
Method	PATCH
Auth required	Yes — Staff, Admin
Path params	id (int, required) — userID
Body fields	accountStatus (string, required — "Active" or "Deactivated")

Allowed transitions: Pending → Active (approve), Pending → Deactivated (decline), Active → Deactivated (deactivate). Anything else is 409.

Response

200 OK

```
{
  "success": true,
  "message": "Volunteer updated successfully",
  "data": { "...": "same shape as 8.2" }
}
```

Error Cases

Scenario	Error Code	HTTP Status
Missing/invalid accountStatus or id	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Volunteer is at another shelter	FORBIDDEN	403
Volunteer does not exist	NOT_FOUND	404
Transition isn't allowed from the volunteer's current status	CONFLICT	409

9. Donations

9.1 GET /api/v1/donations

Returns donations received at the shelter, newest first.

Request

Field	Value
Method	GET
Auth required	Yes — Staff, Admin
Query params	dateFrom / dateTo (date-time bounds on donationDate), donorName (case-insensitive contains match), shelterID (Admin only — omit for network-wide), page (int, optional, default 1), limit (int, optional, max 100, default 20)

Response

```
200 OK
{
  "success": true,
  "message": "Donations retrieved successfully",
  "data": [
    {
      "donationID": 12,
      "donationCode": "DON-00012",
      "donationDate": "2026-09-14T16:20:00Z",
      "donationAmt": 50.00,
      "donorName": "..."
    }
  ],
  "pagination": { "page": 1, "limit": 20, "total": 42, "totalPages": 3 }
}
```

Error Cases

Scenario	Error Code	HTTP Status
Invalid date, shelterID, or pagination param	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Role not permitted	FORBIDDEN	403

9.2 GET /api/v1/donations/stats

Returns donation totals over all of the shelter's donations (not the list's filters).

Request

Field	Value
Method	GET
Auth required	Yes — Staff, Admin
Query params	monthStart (date-time, required — the client's local start of the current month), shelterID (Admin only)

Response

```
200 OK
{
  "success": true,
  "message": "Donation stats retrieved successfully",
  "data": { "totalAmount": 4250.00, "totalDonors": 37, "thisMonthAmount":
600.00 }
}
```

Error Cases

Scenario	Error Code	HTTP Status
Missing/invalid monthStart, or invalid shelterID	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Role not permitted	FORBIDDEN	403

9.3 GET /api/v1/donations/:id

Returns one donation with its donor's contact details; the donor's Stripe customer ID is never included.

Request

Field	Value
Method	GET
Auth required	Yes — Staff, Admin
Path params	id (int, required) — donationID

Response

```
200 OK
{
  "success": true,
```

```

    "message": "Donation retrieved successfully",
    "data": {
      "donationID": 12,
      "donationCode": "DON-00012",
      "donationDate": "2026-09-14T16:20:00Z",
      "donationAmt": 50.00,
      "donationDesc": null,
      "donor": { "donorName": "...", "donorEmail": "...", "donorPhone": "..." }
    }
  }
}

```

Error Cases

Scenario	Error Code	HTTP Status
id is not a positive integer	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Donation is at another shelter	FORBIDDEN	403
Donation does not exist	NOT_FOUND	404

10. Government ID Review

10.1 GET /api/v1/government-ids

Returns the government ID records the caller reviews, pending or already reviewed.

Request

Field	Value
Method	GET
Auth required	Yes — Staff, Admin
Query params	section (required — "pending" = Pending; "reviewed" = Verified or Rejected), userType (Adopter / Volunteer / Staff / Veterinarian / Admin), name, shelterID (Admin only), page (int, optional, default 1), limit (int, optional, max 100, default 20)

Who reviews whom: a shelter's manager → its Staff, Veterinarians, Volunteers and Adopters; any other staff member → Adopters and Volunteers; Admin → shelter Managers and other Admins. Staff lists cover people connected to the caller's shelter (an Adopter with at least one application there; anyone else by their shelterID). A userType the caller doesn't review returns an empty page, and the caller's own ID is never listed.

Response

```

200 OK
{
  "success": true,
  "message": "Government IDs retrieved successfully",
  "data": [
    {
      "governmentIDID": 7,
      "userID": 12,
      "userType": "Adopter",

```

```
    "personName": "...",
    "personEmail": "...",
    "personAvatarSeed": "a1b2c3d4-...",
    "idType": "Passport",
    "verificationStatus": "Pending"
  },
  ],
  "pagination": { "page": 1, "limit": 20, "total": 42, "totalPages": 3 }
}
```

Error Cases

Scenario	Error Code	HTTP Status
Missing/invalid query param	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Role not permitted	FORBIDDEN	403

10.2 GET /api/v1/government-ids/:id

Returns one record's full detail, including the unmasked idNumber and a signed document URL.

Request

Field	Value
Method	GET
Auth required	Yes — Staff, Admin
Path params	id (int, required) — governmentIDID

documentURL is a 5-minute signed URL generated fresh on every read, never cached or persisted. *documentKind* is image (JPEG/PNG/WebP), pdf, or file (HEIC or unrecognised — link only), and null when there's no document. Same *who-reviews-whom* rules as 10.1; never the caller's own record.

Response

```
200 OK
{
  "success": true,
  "message": "Government ID retrieved successfully",
  "data": {
    "governmentIDID": 7,
    "userID": 12,
    "userType": "Adopter",
    "personName": "...",
    "personEmail": "...",
    "personAvatarSeed": "a1b2c3d4-...",
    "idType": "Passport",
    "verificationStatus": "Pending",
    "idNumber": "D1234567",
    "documentURL": "https://...",
    "documentKind": "image"
  }
}
```

```
}
```

Error Cases

Scenario	Error Code	HTTP Status
id is not a positive integer	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Record is outside the caller's shelter	FORBIDDEN	403
No such record, or it belongs to a Staff/Veterinarian/Admin user	NOT_FOUND	404

10.3 PATCH /api/v1/government-ids/:id/status

Verifies or rejects a Pending government ID record.

Request

Field	Value
Method	PATCH
Auth required	Yes — Staff, Admin
Path params	id (int, required) — governmentIDID
Body fields	verificationStatus (string, required — "Verified" or "Rejected")

Only a Pending record can be reviewed. Same who-reviews-whom rules as 10.1; never the caller's own record.

Response

```
200 OK
{
  "success": true,
  "message": "Government ID updated successfully",
  "data": { "...": "same shape as 10.2" }
}
```

Error Cases

Scenario	Error Code	HTTP Status
Missing/invalid verificationStatus	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Record is outside the caller's shelter	FORBIDDEN	403
Record does not exist	NOT_FOUND	404
Record is no longer Pending	CONFLICT	409

11. Team & Vets (Shelter Manager)

11.1 GET /api/v1/staff/me/team

Returns the staff at the shelter the caller manages, ordered by name.

Request

Field	Value
Method	GET
Auth required	Yes — Shelter Manager only
Query params	section (required — "pending" = registrations awaiting approval; "all" = approved Active/Deactivated staff, the manager included), staffDesignation (Manager / Senior / Associate), name (case-insensitive match on staffName), page (int, optional, default 1), limit (int, optional, max 100, default 20)

Response

```
200 OK
{
  "success": true,
  "message": "Team retrieved successfully",
  "data": [
    {
      "userID": 6,
      "avatarSeed": "a1b2c3d4-...",
      "staffName": "...",
      "staffEmail": "...",
      "staffPhone": "...",
      "staffDOB": "1994-03-08",
      "staffSex": "F",
      "staffDesignation": "Associate",
      "staffDOJ": "2026-06-01T09:00:00Z",
      "staffDOS": null,
      "accountStatus": "Active",
      "addressLine1": "...",
      "addressLine2": null,
      "city": "...",
      "state": "...",
      "zip": "...",
      "country": "...",
      "onboardingComplete": true,
      "governmentIdStatus": "Verified"
    }
  ],
  "pagination": { "page": 1, "limit": 20, "total": 42, "totalPages": 3 }
}
```

Error Cases

Scenario	Error Code	HTTP Status
Missing/invalid section, designation, or pagination param	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Caller isn't a shelter's manager	FORBIDDEN	403

11.2 PATCH /api/v1/staff/me/team/:id

Changes a staff member's designation.

Request

Field	Value
Method	PATCH
Auth required	Yes — Shelter Manager only
Path params	id (int, required) — userID
Body fields	staffDesignation (string, required — "Senior" or "Associate")

Designation is the only editable field; Manager is Admin-controlled. The target must be an Active staff member at the caller's shelter, not the caller.

Response

```
200 OK
{
  "success": true,
  "message": "Staff member updated successfully",
  "data": { "...": "same shape as 11.1 (one item)" }
}
```

Error Cases

Scenario	Error Code	HTTP Status
Invalid id or designation	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Not a manager, another shelter's staff, the caller themselves, or a Manager target	FORBIDDEN	403
Staff member does not exist	NOT_FOUND	404
Staff member isn't Active	CONFLICT	409

11.3 PATCH /api/v1/staff/me/team/:id/status

Approves, declines, or deactivates a staff member.

Request

Field	Value
Method	PATCH
Auth required	Yes — Shelter Manager only
Path params	id (int, required) — userID
Body fields	accountStatus (string, required — "Active" or "Deactivated"), staffDesignation (string — "Senior" or "Associate"; required when approving a Pending member)

Allowed transitions: Pending → Active (approve), Pending → Deactivated (decline), Active → Deactivated (deactivate); anything else is 409. The target must be at the caller's shelter and not the caller. staffDOJ is stamped on first approval; staffDOS on deactivation (cleared on reactivation). A Pending Manager sign-up is approved by an Admin, not here (403).

Approving (Pending → Active) requires the member's onboarding to be complete AND their government ID Verified; otherwise 409 naming what's missing (e.g. 'This staff member can't be approved yet — their government ID is Pending, not Verified'). Declining is allowed at any time.

Response

```
200 OK
{
  "success": true,
  "message": "Staff member updated successfully",
  "data": { "...": "same shape as 11.1 (one item)" }
}
```

Error Cases

Scenario	Error Code	HTTP Status
Invalid id or accountStatus, or staffDesignation missing when approving	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Not a manager, another shelter's staff, or the caller themselves	FORBIDDEN	403
Staff member does not exist	NOT_FOUND	404
Transition not allowed from the current status	CONFLICT	409
Approving before onboarding is complete and the government ID is Verified (message names what's missing)	CONFLICT	409

11.4 GET /api/v1/staff/me/vets

Returns the veterinarians at the caller's shelter.

Request

Field	Value
Method	GET
Auth required	Yes — Shelter Manager only
Query params	section (required — "pending" = awaiting approval; "all" = approved vets), accountStatus (Active/Deactivated — section=all only), name (case-insensitive contains match), page (int, optional, default 1), limit (int, optional, 1–100, default 20)

Response

```
200 OK
{
  "success": true,
  "message": "Vets retrieved successfully",
  "data": [
    {
      "userID": 7,
      "avatarSeed": "a1b2c3d4-...",
      "vetName": "...",
      "vetEmail": "...",
      "vetPhone": "...",

```

```

    "addressLine1": "...",
    "addressLine2": null,
    "city": "...",
    "state": "...",
    "zip": "...",
    "country": "...",
    "vetDOB": "1985-11-02",
    "vetSex": "M",
    "createdAt": "2026-07-14T10:00:00Z",
    "accountStatus": "Active"
  }
]
}

```

Error Cases

Scenario	Error Code	HTTP Status
Missing/invalid section, or invalid accountStatus/page/limit	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Caller isn't a shelter manager	FORBIDDEN	403

11.5 PATCH /api/v1/staff/me/vets/:id/status

Approves, declines, or deactivates a veterinarian.

Request

Field	Value
Method	PATCH
Auth required	Yes — Shelter Manager only
Path params	id (int, required) — userID
Body fields	accountStatus (string, required — "Active" or "Deactivated")

Allowed transitions: Pending → Active (approve), Pending → Deactivated (decline), Active → Deactivated (deactivate); anything else is 409. The vet must be at the caller's shelter.

Response

```

200 OK
{
  "success": true,
  "message": "Vet updated successfully",
  "data": { "...": "same shape as 11.4 (one item)" }
}

```

Error Cases

Scenario	Error Code	HTTP Status
Invalid id or accountStatus	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401

Not a manager, or the vet is at another shelter	FORBIDDEN	403
Vet does not exist	NOT_FOUND	404
Transition not allowed from the current status	CONFLICT	409

12. Staff Self-Service

A new staff member onboards while still Pending, before approval (wizard: 2 Personal, 3 Address, 4 Identity, 5 Review). A Pending staff member can call only 12.1, 12.2, 12.4, 12.5, 12.6 and 12.7 (and log out); every other endpoint returns 401 until they're approved.

12.1 GET /api/v1/staff/me

Returns the logged-in staff member's own profile.

Request

Field	Value
Method	GET
Auth required	Yes — Staff only
Path/Body fields	None — staff member identified via req.user.userID

Response

```
200 OK
{
  "success": true,
  "message": "Profile retrieved successfully",
  "data": {
    "avatarSeed": "a1b2c3d4-...",
    "staffName": "...",
    "staffPhone": "...",
    "staffDOB": "1990-04-12",
    "staffSex": "F",
    "...": "...other staff profile fields"
  }
}
```

Error Cases

Scenario	Error Code	HTTP Status
No/invalid token	UNAUTHORIZED	401
Role not permitted	FORBIDDEN	403
Staff record does not exist	NOT_FOUND	404

12.2 PUT /api/v1/staff/me

Partially updates the logged-in staff member's own profile.

Request

Field	Value
Method	PUT
Auth required	Yes — Staff only
Body fields	Any subset of: avatarSeed (≤64), staffName (≤45), staffPhone (nullable), staffDOB (date, nullable), staffSex (M / F / O, nullable)

shelterID, staffDesignation and accountStatus are rejected with 400 — they are Admin-controlled via PATCH /staff/:id and PATCH /staff/:id/status.

Response

```
200 OK
{
  "success": true,
  "message": "Profile updated successfully",
  "data": { "...": "same shape as 12.1" }
}
```

Error Cases

Scenario	Error Code	HTTP Status
Invalid input, or a rejected field (shelterID, staffDesignation, accountStatus)	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Role not permitted	FORBIDDEN	403
Staff record does not exist	NOT_FOUND	404

12.3 DELETE /api/v1/staff/me

Deactivates or permanently deletes the logged-in staff member's own account.

Request

Field	Value
Method	DELETE
Auth required	Yes — Staff only
Body fields	mode (string, required — "deactivate" or "delete")

'deactivate' keeps the row (accountStatus → Deactivated, refresh token cleared); 'delete' removes the Staff and Users rows. Either mode clears managerStaffID on every shelter this staff member manages, and is blocked while a Pending application is assigned to them.

Response

```
200 OK
{
  "success": true,
  "message": "Account deactivated",
  "data": null
}
```

Error Cases

Scenario	Error Code	HTTP Status
No/invalid token	UNAUTHORIZED	401
Role not permitted	FORBIDDEN	403
A Pending application is still assigned to this staff member	CONFLICT	409
mode missing or not 'deactivate'/'delete'	VALIDATION_ERROR	422

12.4 GET /api/v1/staff/me/government-id

Returns the logged-in staff member's submitted government ID.

Request

Field	Value
Method	GET
Auth required	Yes — Staff only
Path/Body fields	None — staff member identified via req.user.userID

*idNumber is masked (e.g. *****6789) on this and the POST response — never returned in full.*

Response

```
200 OK
{
  "success": true,
  "message": "Government ID retrieved successfully",
  "data": {
    "governmentIDID": 9,
    "userID": 5,
    "userType": "Staff",
    "idType": "Passport",
    "idNumber": "*****6789",
    "verificationStatus": "Pending",
    "documentURL": "..."
  }
}
```

Error Cases

Scenario	Error Code	HTTP Status
No/invalid token	UNAUTHORIZED	401
Role not permitted	FORBIDDEN	403
No government ID has been submitted yet	NOT_FOUND	404

12.5 POST /api/v1/staff/me/government-id

Submits a government ID for identity verification.

Request

Field	Value
Method	POST
Auth required	Yes — Staff only
Content-Type	multipart/form-data
Body fields	idType (string, required, ≤45), idNumber (string, required, ≤45), file (required)

One per staff member (`@@unique([userID, userType])`): a second submission is 409, except a Rejected record, which can be resubmitted — overwriting the row and resetting it to Pending.

Response

```
201 Created
{
  "success": true,
  "message": "Government ID submitted successfully",
  "data": { "...": "same shape as 12.4" }
}
```

Error Cases

Scenario	Error Code	HTTP Status
Invalid or missing input	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Role not permitted	FORBIDDEN	403
A government ID already exists for this staff member	CONFLICT	409

12.6 PATCH /api/v1/staff/me/onboarding-step

Advances the logged-in staff member's onboarding progress.

Request

Field	Value
Method	PATCH
Auth required	Yes — Staff only
Body fields	step (int, required, 2–5) — the wizard step just completed

Called after a wizard step's own data has been saved (Step 2 Personal, 3 Address, 4 Identity, 5 Review). The server sets `onboardingStep = min(max(current, step + 1), 5)`, so it only ever advances. Available to Pending staff: onboarding happens before approval.

Response

```
200 OK
{
  "success": true,
  "message": "Onboarding step updated successfully",
  "data": { "...": "same shape as 12.1" }
}
```

Error Cases

Scenario	Error Code	HTTP Status
Invalid or missing input	BAD_REQUEST	400
No/invalid token	UNAUTHORIZED	401
Role not permitted	FORBIDDEN	403
Staff record does not exist	NOT_FOUND	404

12.7 PATCH /api/v1/staff/me/onboarding-complete

Marks the logged-in staff member's onboarding as complete — the final submit of the wizard's Review step.

Request

Field	Value
Method	PATCH
Auth required	Yes — Staff only
Path/Body fields	None — staff member identified via req.user.userID

Requires staffPhone, staffDOB, staffSex, addressLine1, city, state, zip, country and a submitted government ID — 409 lists whatever is missing. Sets onboardingComplete = true and onboardingStep = 5. A Pending staff member then waits for approval, which also requires their government ID to be Verified.

Response

```
200 OK
{
  "success": true,
  "message": "Onboarding completed successfully",
  "data": { "...": "same shape as 12.1" }
}
```

Error Cases

Scenario	Error Code	HTTP Status
No/invalid token	UNAUTHORIZED	401
Role not permitted	FORBIDDEN	403
Staff record does not exist	NOT_FOUND	404
Required profile fields or a submitted government ID are missing	CONFLICT	409