

CST8276 Lab 7: Query Optimizer

Purpose: To provide you with the opportunity to gain additional insight into aspects of query performance.

Deliverables: Provide the specified answers and results in a file named *Lab7_yourName*. Submit the file using BrightSpace, and demonstrate your work to your lab professor before the end of next week's lab session. The lab exercise is worth 2 marks towards your lab grade if correct and submitted on-time or early.

Activities:

1. Logon to your general user account and use the supplied script to create a sequence, create two tables, and to populate both tables with several rows of data. (Note: neither table has a primary key or an index). Think of the *lab7_parent* table as a strong entity (e.g., *Employees*) and the *lab7child* table as a weak entity (e.g., *Dependents* of the employee). You may recall a weak entity inherits its parent's primary key and adds this inherited key to a local partial key to create a composite primary key. In our situation the *lab7_child* table will eventually (i.e., several steps later) have a composite primary key of (ee#, fname). Note: If you are unable to create a sequence then from SYS, *grant create sequence to* your general user.
 - a. From your general user account:
 - i. Enter: **EXPLAIN PLAN FOR**
Select ee#
From lab7_parent
Where ee# = 123456;

Enter: **SELECT PLAN TABLE OUTPUT**
FROM TABLE(DBMS_XPLAN.DISPLAY());
 - ii. Paste a screen snapshot of the Explain Plan query and the Plan_Table_Output into the area below .

CST8276 Lab 7: Query Optimizer

```
SQL Plus

SQL> SELECT PLAN_TABLE_OUTPUT
       2 FROM TABLE(DBMS_XPLAN.DISPLAY());

PLAN_TABLE_OUTPUT
-----
Plan hash value: 1893668631
-----

| Id | Operation          | Name          | Rows  | Bytes | Cost (%CPU)| Time | |
|---|---|---|---|---|---|---|---|
|    |          |          |      |      |          |      |      |
|----|-----|-----|-----|-----|-----|-----|-----|

PLAN_TABLE_OUTPUT
-----
| 0 | SELECT STATEMENT |          | 1 | 13 | 3 (0)| 00:00:01 | |
|  |          |          |   |    |      |      |      |
| * 1 | TABLE ACCESS FULL| LAB7_PARENT | 1 | 13 | 3 (0)| 00:00:01 |
|  |          |          |   |    |      |      |      |
|----|-----|-----|-----|-----|-----|-----|-----|
```

- b. Change the WHERE clause in *l*ai** so that the query returns a range of approximately 25 ee#s. Copy your Explain Plan and Plan_Table_Output to your submission document.(below)

CST8276 Lab 7: Query Optimizer

SQL Plus

```
SQL>
SQL> EXPLAIN PLAN FOR
  2  Select ee#
  3  From lab7_parent
  4  Where ee# >= 500 OR ee# <= 525;
```

Explained.

```
SQL>
SQL> SELECT PLAN_TABLE_OUTPUT
  2  FROM TABLE(DBMS_XPLAN.DISPLAY());
```

PLAN_TABLE_OUTPUT

Plan hash value: 1893668631

Id	Operation	Name	Rows	Bytes	Cost (%CPU)	Time
----	-----------	------	------	-------	-------------	------

PLAN_TABLE_OUTPUT

0	SELECT STATEMENT		1000	13000	3 (0)	00:00:01
1	TABLE ACCESS FULL	LAB7_PARENT	1000	13000	3 (0)	00:00:01

Note

PLAN_TABLE_OUTPUT

- dynamic statistics used: dynamic sampling (level=2)

12 rows selected.

CST8276 Lab 7: Query Optimizer

- c. Write an Explain Plan for a query that displays Parent.EE#, Parent.Lname, Child.EE# and Child.Lname. Take a screenshot of the Explain_plan and the Plan_Table_Output**

CST8276 Lab 7: Query Optimizer

SQL Plus

```
SQL> EXPLAIN PLAN FOR
  2 Select lab7_parent.ee#, lab7_parent.Lname, lab7_child.EE#, lab7_child.Lname
  3 From lab7_parent JOIN lab7_child ON lab7_parent.EE# = lab7_child.ee#
  4 Where lab7_parent.ee# = 1;
```

Explained.

```
SQL>
SQL> SELECT PLAN_TABLE_OUTPUT
  2 FROM TABLE(DBMS_XPLAN.DISPLAY());
```

PLAN_TABLE_OUTPUT

Plan hash value: 1027991852

--

Id	Operation	Name	Rows	Bytes	Cost (%CPU)	Time
----	-----------	------	------	-------	-------------	------

--

PLAN_TABLE_OUTPUT

0	SELECT STATEMENT		1	46	13 (0)	00:00:01
*	1	HASH JOIN		1	46	13 (0)
*	2	TABLE ACCESS FULL	LAB7_PARENT	1	30	3 (0)
*	3	TABLE ACCESS FULL	LAB7_CHILD	2	32	10 (0)

--

PLAN_TABLE_OUTPUT

--
Predicate Information (identified by operation id):

1 - access("LAB7_PARENT" "EE#"="LAB7_CHILD" "EE#")

CST8276 Lab 7: Query Optimizer

- d. The main purpose of the preceding activities was to reinforce the idea that a certain type of retrieval – generally considered relatively slow - will be the default approach to retrieving data.
2. Add a primary key to the parent table (ee#) and the child table (ee#, fname). Rerun *lai*. If you obtain the same result as *lai*, then connect to sys as sysdba and enter: ***ALTER SYSTEM FLUSH SHARED_POOL;*** and bounce the database (shutdown, startup), reconnect to your general user and rerun the EXPLAIN PLAN query.
 - a. Your Plan_Table_Output should now be significantly different from the non-indexed version. Take a screenshot of the Explain Plan query and the Plan_Table _Output and add it to your submission document.

CST8276 Lab 7: Query Optimizer

```
SQL>
SQL> ALTER TABLE lab7_parent ADD CONSTRAINT EE# PRIMARY KEY (EE#);

Table altered.

SQL>
SQL> EXPLAIN PLAN FOR
  2 Select ee#
  3 From lab7_parent
  4 Where ee# = 1;

Explained.

SQL> SELECT PLAN_TABLE_OUTPUT
  2 FROM TABLE(DBMS_XPLAN.DISPLAY());

PLAN_TABLE_OUTPUT
-----
Plan hash value: 646621475

-----
| Id | Operation          | Name | Rows  | Bytes | Cost (%CPU)| Time     |
-----+-----+-----+-----+-----+-----+-----+
|  0 | SELECT STATEMENT   |      |    1  |    13 |    1   (0)| 00:00:01 |
|*  1 |  INDEX UNIQUE SCAN | EE#  |    1  |    13 |    1   (0)| 00:00:01 |
-----

Predicate Information (identified by operation id):
-----

PLAN_TABLE_OUTPUT
-----

      1 - access("EE#"=1)

13 rows selected.

SQL> _
```

Explain how your actions in 2 changed the query plan (if your plan doesn't change, explain what you would expect to occur). _

Table access is not full anymore, there's an index instead. I suppose the row is accessed directly as it has a primary key now instead of searching all the rows and filtering them

- b. Now that you have added primary keys to both tables, revisit each of the scenarios (i.e., a single ee#, a range of ee#, a table join

CST8276 Lab 7: Query Optimizer

on ee#) in Question 1. Include a screenshot of the explain plan and plan table output.

```
SQL> EXPLAIN PLAN FOR
  2 Select ee#
  3 From lab7_parent
  4 Where ee# >= 500 OR ee# <= 525;

Explained.

SQL>
SQL> SELECT PLAN_TABLE_OUTPUT
  2 FROM TABLE(DBMS_XPLAN.DISPLAY());

PLAN_TABLE_OUTPUT
-----
Plan hash value: 2859652636

-----
| Id | Operation                | Name | Rows  | Bytes | Cost (%CPU)| Time     |
-----+-----+-----+-----+-----+-----+-----+
|  0 | SELECT STATEMENT         |      |  1000 | 13000 |    3   (0)| 00:00:01 |
|  1 |  INDEX FAST FULL SCAN    | EE#  |  1000 | 13000 |    3   (0)| 00:00:01 |
-----+-----+-----+-----+-----+

Note
-----
PLAN_TABLE_OUTPUT
-----
- dynamic statistics used: dynamic sampling (level=2)

12 rows selected.

SQL> _
```


CST8276 Lab 7: Query Optimizer

SQL Plus

```
SQL>
SQL> SELECT PLAN_TABLE_OUTPUT
       2 FROM TABLE(DBMS_XPLAN.DISPLAY());
```

PLAN_TABLE_OUTPUT

Plan hash value: 3498815431

| Id | Operation | Name | Rows | Bytes | Cost (%CPU)
Time

PLAN_TABLE_OUTPUT

| 0 | SELECT STATEMENT | | 2 | 92 | 12 (0)
| 00:00:01 |

| 1 | NESTED LOOPS | | 2 | 92 | 12 (0)
| 00:00:01 |

| 2 | TABLE ACCESS BY INDEX ROWID | LAB7_PARENT | 1 | 30 | 2 (0)
| 00:00:01 |

|* 3 | INDEX UNIQUE SCAN | EE# | 1 | | 1 (0)
| 00:00:01 |

PLAN_TABLE_OUTPUT

|* 4 | TABLE ACCESS FULL | LAB7_CHILD | 2 | 32 | 10 (0)
00:00:01

Predicate Information (identified by operation id):

PLAN_TABLE_OUTPUT

3 - access("LAB7_PARENT"."EE#"=1)
4 - filter("LAB7_CHILD"."EE#"=1)

CST8276 Lab 7: Query Optimizer

3. Add a foreign key to the child table referencing the parent table. Rerun the table join case. If your results did not change from the pre-foreign key table join results then, from SYS, bounce the database and retry. Include a screenshot of the explain plan and the resulting plan table output. IF there is still no difference, try changing the where clause to include multiple criteria.

Describe what you expected to happen (and why) and show your actual results below.

```
SQL>
SQL> SELECT PLAN_TABLE_OUTPUT
      2  FROM TABLE(DBMS_XPLAN.DISPLAY());

PLAN_TABLE_OUTPUT
-----
Plan hash value: 646621475

-----
| Id | Operation          | Name | Rows  | Bytes | Cost (%CPU)| Time     |
-----
|  0 | SELECT STATEMENT   |      |    1  |    13 |    1   (0)| 00:00:01 |
|*  1 |  INDEX UNIQUE SCAN | EE#  |    1  |    13 |    1   (0)| 00:00:01 |
-----

Predicate Information (identified by operation id):
-----

PLAN_TABLE_OUTPUT
-----

      1 - access("EE#=1)

13 rows selected.

SQL> _
```

4. Write an Explain Plan query that contains a child ee# range and a child lname range selection criteria.
 - a. Copy the explain plan and plan table output.

CST8276 Lab 7: Query Optimizer

```
SQL>
SQL> EXPLAIN PLAN FOR
  2 Select ee#, lname
  3 From lab7_child
  4 Where ee# >= 500 OR ee# <= 525;

Explained.

SQL> SELECT PLAN_TABLE_OUTPUT
  2 FROM TABLE(DBMS_XPLAN.DISPLAY());

PLAN_TABLE_OUTPUT
-----
Plan hash value: 36428831

-----
| Id | Operation          | Name      | Rows  | Bytes | Cost (%CPU)| Time     |
-----
|  0 | SELECT STATEMENT   |           | 10000 | 156K  | 10  (0)    | 00:00:01 |
|  1 |  TABLE ACCESS FULL| LAB7_CHILD | 10000 | 156K  | 10  (0)    | 00:00:01 |
-----

Note
-----
PLAN_TABLE_OUTPUT
-----
- dynamic statistics used: dynamic sampling (level=2)

12 rows selected.

SQL>
```

- b. Add an index to child.lname. Rerun the previous child ee# and child lname range query. Copy the explain plan and plan table output. Again, if you don't see any change in results, bounce the instance and rerun.

CST8276 Lab 7: Query Optimizer

```
SQL> CREATE INDEX lname_index
  2  ON lab7_child (lname);

Index created.

SQL>
SQL> EXPLAIN PLAN FOR
  2  Select ee#, lname
  3  From lab7_child
  4  Where ee# >= 500 OR ee# <= 525;

Explained.

SQL> SELECT PLAN_TABLE_OUTPUT
  2  FROM TABLE(DBMS_XPLAN.DISPLAY());

PLAN_TABLE_OUTPUT
-----
Plan hash value: 36428831

-----
| Id | Operation          | Name       | Rows  | Bytes | Cost (%CPU)| Time     |
-----
|  0 | SELECT STATEMENT   |            | 10000 | 156K |    10  (0)| 00:00:01 |
|  1 |  TABLE ACCESS FULL| LAB7_CHILD | 10000 | 156K |    10  (0)| 00:00:01 |
-----

Note
-----

PLAN_TABLE_OUTPUT
-----
- dynamic statistics used: dynamic sampling (level=2)

12 rows selected.
```

5. Write an Explain Plan query that contains parent ee#, count(lname) and ee# range selection criteria and an ordering of the results by ee#. Copy the explain plan and plan table output.

CST8276 Lab 7: Query Optimizer

SQL Plus

```
SQL> EXPLAIN PLAN FOR
  2 SELECT ee#, COUNT(lname)
  3 FROM lab7_parent
  4 WHERE ee# >= 500 OR ee# <= 525
  5 GROUP BY EE#
  6 ORDER BY ee#;
```

Explained.

```
SQL>
SQL> SELECT PLAN_TABLE_OUTPUT
  2 FROM TABLE(DBMS_XPLAN.DISPLAY());
```

PLAN_TABLE_OUTPUT

Plan hash value: 3121998291

--

Id	Operation	Name	Rows	Bytes	Cost (%CPU)	Time
----	-----------	------	------	-------	-------------	------

PLAN_TABLE_OUTPUT

0	SELECT STATEMENT		1000	30000	4 (25)	00:00:01
1	SORT GROUP BY		1000	30000	4 (25)	00:00:01
2	TABLE ACCESS FULL	LAB7_PARENT	1000	30000	3 (0)	00:00:01

PLAN_TABLE_OUTPUT

Note

- dynamic statistics used: dynamic sampling (level=2)

13 rows selected.

CST8276 Lab 7: Query Optimizer

6. Materialized views are very important performance enhancing objects in large databases and/or data warehouses that either need to join multiple tables or perform significant aggregation from remote instances. The Oracle Data Warehousing Guide, located here, <http://docs.oracle.com/database/121/DWHSG/basicmv.htm#DWHSG008>, provides a good description of this feature.

What does a materialized view contain that a regular view does not?

Normal views don't have a physical component whereas materialized views are stored on the disc

7. Connect to SYS as SYSDBA and grant your generalized user the privilege of being able to *create materialized view*. Return to your general user and create a materialize view on parent ee#, count(fname) and count(lname). Re-run the query from Q5 using the newly created materialized view. Copy the explain plan and plan table output.

CST8276 Lab 7: Query Optimizer

SQL Plus

```
SQL> CREATE MATERIALIZED VIEW MView AS
  2 SELECT ee#, COUNT(fname), COUNT(lname)
  3 FROM lab7_child
  4 GROUP BY ee#;
```

Materialized view created.

SQL>

```
SQL> EXPLAIN PLAN FOR
  2 SELECT ee#, COUNT(lname)
  3 FROM lab7_parent
  4 WHERE ee# >= 500 OR ee# <= 525
  5 GROUP BY EE#
  6 ORDER BY ee#;
```

Explained.

SQL>

```
SQL> SELECT PLAN_TABLE_OUTPUT
  2 FROM TABLE(DBMS_XPLAN.DISPLAY());
```

PLAN_TABLE_OUTPUT

Plan hash value: 3121998291

--

Id	Operation	Name	Rows	Bytes	Cost (%CPU)	Time
----	-----------	------	------	-------	-------------	------

--

PLAN_TABLE_OUTPUT

0	SELECT STATEMENT		1000	30000	4 (25)	00:00:01
1	SORT GROUP BY		1000	30000	4 (25)	00:00:01
2	TABLE ACCESS FULL	LAB7_PARENT	1000	30000	3 (0)	00:00:01

--

PLAN_TABLE_OUTPUT

CST8276 Lab 7: Query Optimizer

You're finished. Please submit.