



v.0.0.1

itadOS

Guides

Karl-Markus Oismann
7-15-2025

Contents

Create itadOS ISO	2
Prerequisites:	2
Helpful links for live-build:	2
Step 1 – Create a directory	3
Step 2 – Create live-build config directory	3
Step 3 – Insert itadOS into live-build	4
Step 4 – Give itadOS execution permission	4
Step 5 – Add the dependencies	5
Step 6 – Start itadOS on boot	6
Step 7 – Allow laptop lid to be closed.....	7
Step 8 – Legacy boot support	8
Step 9 – UEFI boot support.....	10
Step 10. – Build ISO	11
Modify itadOS	12
Step 1 – Clean config.....	12
Step 2 – Modify itadOS settings.....	13
Step 3 – Issue config command.....	14
Step 4 – Build ISO	14
Create itadOS USB disk.....	16
Step 1 – Get flashing utility.	16
Step 2 – Get itadOS ISO.....	16
Step 3 – Flash USB disk with itadOS	17

Create itadOS ISO

Prerequisites:

- Computer or virtual machine with Debian operating system.
 - The following packages installed:
 - nvme-cli
 - lshw
 - dd (coreutils)
 - hdparm
 - rtcwake (util-linux)
 - mmc-utils
 - whiptail
 - shred (coreutils)
 - smartmontools
 - pciutils
 - fop
 - xsltrpoc
 - live-build
 - isolinux

Helpful links for live-build:

<https://debian-install-notes.pages.dev/netinstall/live-build#3>

https://manpages.debian.org/testing/live-build/lb_config.1.en.html

Step 1 – Create a directory

- Create a directory and change directory to it, as an in an example shown in figure 1.1.

```
mkdir itadOS && cd itadOS
```




Figure 1.1. Directory created for live-build and directory changed to it.

Step 2 – Create live-build config directory

- Enter the following command, as shown in figure 1.2:

```
sudo lb config --distribution bookworm --architectures amd64 --archive-areas "main contrib non-free non-free-firmware" --binary-images iso-hybrid --bootloader grub-efi --debian-installer none --bootappend-live "boot=live components username=root toram quiet splash"
```




Figure 1.2. Live-build config command issued.

Step 3 – Insert itadOS into live-build

- **Insert itadOS to config/includes.chroot, as shown in figure 1.3.**

(in this example itadOS was downloaded from github: <https://github.com/karloismann/itadOS>)

```
sudo mkdir -p config/includes.chroot && sudo mv ~/Downloads/itadOS-main/itadOSv.0.0.1/ config/includes.chroot
```




Figure 1.3. Directory made for itadOS and it is being moved into it.

Step 4 – Give itadOS execution permission

- **Issue chmod command, as shown in figure 1.4.**

```
sudo chmod +x config/includes.chroot/itadOSv.0.0.1/main.sh
```




Figure 1.4. ItadOS given execution permissions using chmod command.

Step 5 – Add the dependencies

- Create a file, as shown in figure 1.5.

```
sudo nano config/package-lists/my.list.chroot
```




Figure 1.5. File for packages is created.

- Insert the following to my.list.chroot, as shown in figure 1.6:

```
nvme-cli  
lshw  
hdparm  
mmc-utils  
fop  
xsltproc  
smartmontools  
pciutils
```




Figure 1.5. my.list.chroot filled with required packages.

Step 6 – Start itadOS on boot

- **Create path and file '.bashrc' and start editing it, as shown in figure 1.6.**

```
sudo mkdir -p config/includes.chroot/root/ && sudo nano .bashrc
```




Figure 1.6. Path for .bashrc created and nano command issued.

- **Insert the following line into .bashrc, as shown in figure 1.7:**

```
/itadOSv.0.0.1/main.sh
```





Figure 1.7. Bashrc contents.

Step 7 – Allow laptop lid to be closed

- Create path and file 'logind.conf' and start editing it, as shown in figure 1.8.

```
Sudo mkdir -p config/includes.chroot/etc/systemd && sudo nano  
config/includes.chroot/etc/systemd/logind.conf
```




A terminal window titled 'karl@debian: ~/itadOS' showing the command: `karl@debian:~/itadOS$ sudo mkdir -p config/includes.chroot/etc/systemd && \> sudo nano config/includes.chroot/etc/systemd/logind.conf`. The cursor is at the end of the second line.

Figure 1.8. Path for logind.conf created and nano command issued.

- Add the following to logind.conf, as shown in figure 1.9:

```
[Login]  
HandleLidSwitch=ignore  
HandleLidSwitchDocked=ignore  
HandleLidSwitchExternalPower=ignore
```




A terminal window titled 'karl@debian: ~/itadOS' showing the nano editor editing 'logind.conf'. The header bar says 'GNU nano 7.2 logind.conf *'. The content is: `[Login]
HandleLidSwitch=ignore
HandleLidSwitchDocked=ignore
HandleLidSwitchExternalPower=ignore`. The cursor is at the end of the last line.

Figure 1.9. Logind.conf contents.

Step 8 – Legacy boot support

- **Create path and file, as shown in figure 1.10:**

```
sudo mkdir -p config/includes.chroot/isolinux && sudo nano
config/includes.chroot/isolinux/isolinux.cfg
```



A terminal window titled 'karl@debian: ~/itadOS' showing the command: `karl@debian:~/itadOS$ sudo mkdir -p config/includes.binary/isolinux && \> sudo nano config/includes.binary/isolinux/isolinux.cfg`. The cursor is at the end of the second line.

Figure 1.10. Path for `isolinux.cfg` created and `nano` command issued.

- **Insert the following to `isolinux.cfg`, as shown in figure 1.11:**

```
UI vesamenu.c32
PROMPT 0
MENU TITLE itadOS Boot Menu
TIMEOUT 50
DEFAULT live

LABEL live
    MENU LABEL Boot itadOS (Live)
    KERNEL /live/vmlinuz-6.1.0-37-amd64
    APPEND initrd=/live/initrd.img-6.1.0-37-amd64 boot=live components
username=root toram quiet splash
```




A terminal window titled 'karl@debian: ~/itadOS/config/includes.binary/isolinux' showing the contents of the `isolinux.cfg` file in nano editor. The text matches the code block above. The window title bar includes 'GNU nano 7.2' and 'isolinux.cfg'.

Figure 1.11. `isolinux.cfg` contents.

- Also add required binaries from syslinux, as shown in figure 1.12:

```
cp /usr/lib/syslinux/modules/bios/*.c32  
config/includes.binary/isolinux/
```



A terminal window titled 'karl@debian: ~/itadOS' with search and menu icons in the top right. It contains two tabs: 'karl@debian: ~/itadOS' (active) and 'karl@debian: ~'. The active tab shows the command 'karl@debian:~/itadOS\$ sudo cp /usr/lib/syslinux/modules/bios/*.c32 config/includes.binary/isolinux/' being entered.

Figure 1.12. COM32 modules copied to the destination.

Step 9 – UEFI boot support

- **Create path and file, as shown in figure 1.13:**

```
sudo mkdir -p config/includes.binary/boot/grub && sudo nano  
config/includes.binary/boot/grub/grub.cfg
```




Figure 1.13. Path for grub.cfg created and nano command issued.

- **Insert the following to grub.cfg, as shown in figure 1.14:**

```
set default=0  
set timeout=5  
  
menuentry "itadOS (Live)" {  
    linux /live/vmlinuz-6.1.0-37-amd64 boot=live components  
    username=root toram quiet splash  
    initrd /live/Initrd.img-6.1.0-37-amd64  
}
```




Figure 1.14. grub.cfg contents.

Step 10. – Build ISO

- Enter the following command, as shown in figure 1.15:

```
sudo lb build
```




Figure 1.15. Sudo lb build command issued.

- ISO file is now created as shown in figure 1.16.




Figure 1.16. ItadOS ISO file is highlighted.

Modify itadOS

!!! Must complete ‘[Create ISO file](#)’ before continuing. !!!

Step 1 – Clean config

- Go into the directory created [here](#) and insert the following command, as shown in figure 2.1:

```
sudo lb clean --purge
```




Figure 1.2. *sudo lb clean --purge* command issued.

Step 2 – Modify itadOS settings

- **Modify settings in config.sh, as shown in figure 2.2.**

```
sudo nano config/includes.chroot/itadOSv.0.0.1/config.sh
```




Figure 2.2. Nano command issued for config.sh

- **In this example, I am setting default technician's name to 'Karl', as shown in figure 2.3.**





Figure 2.3. ItadOS default technician changed to 'Karl'.

Step 3 – Issue config command

- Enter the following command, as shown in figure 2.4:

```
sudo lb config --distribution bookworm --architectures amd64 --archive-areas "main contrib non-free non-free-firmware" --binary-images iso-hybrid --bootloader grub-efi --debian-installer none --bootappend-live "boot=live components username=root toram quiet splash"
```

A terminal window titled 'karl@debian: ~/itadOS' with two tabs. The active tab shows the command 'sudo lb config' being entered line by line. The command is: 'sudo lb config \', followed by ' > --distribution bookworm \', ' > --architectures amd64 \', ' > --archive-areas "main contrib non-free non-free-firmware" \', ' > --binary-images iso-hybrid \', ' > --bootloader grub-efi \', ' > --debian-installer none \', and finally ' > --bootappend-live "boot=live components username=root toram quiet splash"'.


```
karl@debian: ~/itadOS$ sudo lb config \  
> --distribution bookworm \  
> --architectures amd64 \  
> --archive-areas "main contrib non-free non-free-firmware" \  
> --binary-images iso-hybrid \  
> --bootloader grub-efi \  
> --debian-installer none \  
> --bootappend-live "boot=live components username=root toram quiet splash"
```

Figure 2.4. Live-build config command issued.

Step 4 – Build ISO

- Enter the following command, as shown in figure 2.5:


```
sudo lb build
```

A terminal window titled 'karl@debian: ~/itadOS' with two tabs. The active tab shows the command 'sudo lb build' being entered. The command is: 'sudo lb build'.

```
karl@debian: ~/itadOS$ sudo lb build
```

Figure 2.5. Sudo lb build command issued.

- ISO file is now created as shown in figure 2.6.



```
karl@debian: ~/itadOS
[2025-08-06 16:32:17] lb chroot_proc remove
P: Begin unmounting /proc...
[2025-08-06 16:32:17] lb chroot_devpts remove
P: Begin unmounting /dev/pts...
P: Binary stage completed
P: Begin unmounting filesystems...
P: Saving caches...
Reading package lists... Done
Building dependency tree... Done
Reading state information... Done
[2025-08-06 16:32:17] lb source
P: Source stage disabled, skipping
P: Build completed successfully
karl@debian:~/itadOS$ ls
auto                config
binary              live-image-amd64.contents
binary.modified_timestamps live-image-amd64.files
cache                live-image-amd64.hybrid.iso
chroot               live-image-amd64.hybrid.iso.zsync
chroot.files         live-image-amd64.packages
chroot.packages.install local
chroot.packages.live
karl@debian:~/itadOS$
```

Figure 1.16. ItadOS ISO file is highlighted.

Create itadOS USB disk

This guide is utilising rufus on Windows PC.

Step 1 – Get flashing utility.

- **Install Rufus (windows) or other alternative software.**

Rufus : <https://rufus.ie/en/>

Step 2 – Get itadOS ISO

- **Download itadOS ISO from [here](#) OR create ISO [here](#).**

Step 3 – Flash USB disk with itadOS

- Insert the USB drive into the PC and choose it from the list highlighted in figure 3.1.




Figure 3.1. Rufus' USB drive list highlighted.

- Click on the highlighted button in figure 3.2 and select itadOS ISO.




Figure 3.2. ISO selection button in Rufus.

- Name the volume label as 'ITADOS' as highlighted in figure 3.3, and press 'START'.
 - This helps itadOS to identify boot disk.




Figure 3.3. Volume label named as 'ITADOS' in Rufus.