

# <algorithm>

Karl Solomon

December 27, 2024

## Contents

1	batchOperations	2
2	Search Operations	2
3	Fold Operations	7
4	Copy Operations	7
5	Swap Operations	8
6	Transform Operations	9
7	Generation Operations	10
8	Removing Operations	12
9	Order-Changing Operations	12
10	Sampling Operations	12
11	Random Number Generation	13
12	Partitioning Operations	13
13	Sorting Operations	13
14	Binary Search Operations (on partitioned ranges)	14
15	Set Operation (on sorted ranges)	14
16	Merge Operations (on sorted ranges)	14
17	Heap Operations	15
18	Min/Max Operations	17
19	Lexicographical Operations	19
20	Permutation Operations	19
21	Numeric Operations	20
22	Uninitialized Memory Operations	22

## 1 batchOperations

- `for_each`
- `ranges::for_each`
- `for_each_n`
- `ranges::for_each_n`

```
1 std::vector<int> numbers = {1, 2, 3, 4, 5};
2
3 // Use std::for_each to print each element
4 std::for_each(numbers.begin(), numbers.end(), [](int n) { std::cout << n << " "; });
5
6 // Use std::for_each_n to print the first 3 elements
7 std::for_each_n(numbers.begin(), 3, [](int n) { std::cout << n << " "; });
8
9 // Use std::ranges::for_each to print each element
10 std::ranges::for_each(numbers, [](int n) { std::cout << n << " "; });
11
12 // Use std::ranges::for_each_n to print the first 3 elements
13 std::ranges::for_each_n(numbers.begin(), 3, [](int n) { std::cout << n << " "; });
```

## 2 Search Operations

- `all_of`
- `any_of`
- `none_of`

```
1 std::vector<int> numbers = {1, 2, 3, 4, 5};
2 // Use std::all_of to check if all elements are positive
3 bool allPositive = std::all_of(numbers.begin(), numbers.end(), [](int n) { return n > 0; });
4 // Use std::any_of to check if any element is greater than 4
5 bool anyGreaterThanFour = std::any_of(numbers.begin(), numbers.end(), [](int n) { return n > 4; });
6 // Use std::none_of to check if no elements are negative
7 bool noneNegative = std::none_of(numbers.begin(), numbers.end(), [](int n) { return n < 0; });
```

- `ranges::contains`
- `ranges::contains_subrange`

```
1 std::vector<int> numbers = {1, 2, 3, 4, 5, 6, 7, 8, 9, 10};
2
3 // Check if the range contains the value 5
4 bool containsFive = std::ranges::contains(numbers, 5);
5 // Check if the range contains the value 11
6 bool containsEleven = std::ranges::contains(numbers, 11);
7 // Define a subrange to check
8 std::vector<int> subrange = {4, 5, 6};
9 // Check if the range contains the subrange
```

```

10 bool containsSubrange = std::ranges::contains_subrange(numbers,
    subrange);
11 // Define another subrange to check
12 std::vector<int> nonExistentSubrange = {7, 8, 11};
13 // Check if the range contains the non-existent subrange
14 bool containsNonExistentSubrange = std::ranges::contains_subrange(
    numbers, nonExistentSubrange);

```

- find
- find\_if
- find\_if\_not
- ranges::find
- ranges::find\_if
- ranges::find\_if\_not

```

1 #include <algorithm>
2 #include <iostream>
3 #include <ranges>
4 #include <vector>
5
6 int main() {
7     std::vector<int> numbers = {1, 2, 3, 4, 5, 6, 7, 8, 9, 10};
8
9     // Use std::find to find the first occurrence of 5
10    auto it = std::find(numbers.begin(), numbers.end(), 5);
11
12    // find the first even number
13    it = std::find_if(numbers.begin(), numbers.end(), [](int n) {
14        return n % 2 == 0; });
15    // find the first odd number
16    it = std::find_if_not(numbers.begin(), numbers.end(), [](int n
17        ) { return n % 2 == 0; });
18    // find the first occurrence of 5
19    auto range_it = std::ranges::find(numbers, 5);
20    // find the first even number
21    range_it = std::ranges::find_if(numbers, [](int n) { return n
22        % 2 == 0; });
23    // find the first odd number
24    range_it = std::ranges::find_if_not(numbers, [](int n) {
25        return n % 2 == 0; });
26 }

```

- find\_last
- find\_last\_if
- find\_last\_if\_not
- find\_end
- ranges::find\_end

```

1 #include <algorithm>
2 #include <iostream>
3 #include <ranges>
4 #include <vector>
5

```

```

6  std::vector<int> numbers = {1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 5, 6,
7    7};
8  // find the last occurrence of 5
9  auto lastFive = std::ranges::find_last(numbers, 5);
10 // find the last even number
11 auto lastEven = std::ranges::find_last_if(numbers, [](int n) {
12     return n % 2 == 0; });
13 // find the last odd number
14 auto lastOdd = std::ranges::find_last_if_not(numbers, [](int n) {
15     return n % 2 == 0; });
16 // Define a subrange to find
17 std::vector<int> subrange = {5, 6, 7};
18 // find the last occurrence of the subrange
19 auto lastSubrange = std::find_end(numbers.begin(), numbers.end(),
20     subrange.begin(), subrange.end());
21 // find the last occurrence of the subrange
22 auto lastSubrangeRange = std::ranges::find_end(numbers, subrange);

```

- find\_end
- ranges::find\_end
- find\_first\_of
- ranges::find\_first\_of
- adjacent\_find
- ranges::adjacent\_find

```

1  std::vector<int> numbers = {1, 2, 3, 4, 5, 3, 4, 5, 6, 7};
2  std::vector<int> pattern = {3, 4, 5};
3
4  // Using std::find_end to find the last occurrence of a pattern
5  auto it_end = std::find_end(numbers.begin(), numbers.end(),
6     pattern.begin(), pattern.end());
7  // Result: it_end points to the first element of the last
8     occurrence of {3, 4, 5}
9
10 // Using std::find_first_of to find the first occurrence of any
11    element from another range
12 std::vector<int> search_elements = {4, 5, 6};
13 auto it_first_of = std::find_first_of(numbers.begin(), numbers.end(),
14    search_elements.begin(), search_elements.end());
15 // Result: it_first_of points to the first occurrence of any
16    element from {4, 5, 6}, which is 4
17
18 // Using std::adjacent_find to find the first occurrence of two
19    consecutive equal elements
20 std::vector<int> numbers_with_adjacent = {1, 2, 3, 3, 4, 5};
21 auto it_adjacent = std::adjacent_find(numbers_with_adjacent.begin(),
22    numbers_with_adjacent.end());
23 // Result: it_adjacent points to the first element of the first
24    pair of adjacent equal elements, which is 3

```

- count
- count\_if
- ranges::count

- `ranges::count_if`

```
1 std::vector<int> numbers = {1, 2, 3, 4, 5, 6, 7, 8, 9, 10};
2
3 // Using std::count to count occurrences of the number 5
4 int count_5 = std::count(numbers.begin(), numbers.end(), 5);
5 // Result: count_5 = 1
6
7 // Using std::count_if to count numbers greater than 5
8 int count_greater_than_5 = std::count_if(numbers.begin(), numbers.
    end(), [](int n) { return n > 5; });
9 // Result: count_greater_than_5 = 5
10
11 // Using std::ranges::count to count occurrences of the number 5
12 int ranges_count_5 = std::ranges::count(numbers, 5);
13 // Result: ranges_count_5 = 1
14
15 // Using std::ranges::count_if to count numbers greater than 5
16 int ranges_count_greater_than_5 = std::ranges::count_if(numbers,
    [](int n) { return n > 5; });
17 // Result: ranges_count_greater_than_5 = 5
```

- `mismatch`

- `ranges::mismatch`

```
1 std::vector<int> vec1 = {1, 2, 3, 4, 5};
2 std::vector<int> vec2 = {1, 2, 0, 4, 5};
3
4 // Using std::mismatch to find the first position where vec1 and
    vec2 differ
5 auto mismatch_pair = std::mismatch(vec1.begin(), vec1.end(), vec2.
    begin());
6 // Result: mismatch_pair.first points to 3 in vec1, mismatch_pair.
    second points to 0 in vec2
7
8 // Using std::ranges::mismatch to find the first position where
    vec1 and vec2 differ
9 auto ranges_mismatch_pair = std::ranges::mismatch(vec1, vec2);
10 // Result: ranges_mismatch_pair.in1 points to 3 in vec1,
    ranges_mismatch_pair.in2 points to 0 in vec2
```

- `equal`

- `ranges::equal`

```
1 std::vector<int> vec1 = {1, 2, 3, 4, 5};
2 std::vector<int> vec2 = {1, 2, 3, 4, 5};
3 std::vector<int> vec3 = {1, 2, 3, 0, 5};
4
5 // Using std::equal to check if vec1 and vec2 are equal
6 bool are_equal_1_2 = std::equal(vec1.begin(), vec1.end(), vec2.
    begin());
7 // Result: are_equal_1_2 = true
8
9 // Using std::equal to check if vec1 and vec3 are equal
10 bool are_equal_1_3 = std::equal(vec1.begin(), vec1.end(), vec3.
    begin());
11 // Result: are_equal_1_3 = false
12
13 // Using std::ranges::equal to check if vec1 and vec2 are equal
14 bool ranges_are_equal_1_2 = std::ranges::equal(vec1, vec2);
15 // Result: ranges_are_equal_1_2 = true
16
```

```

17 // Using std::ranges::equal to check if vec1 and vec3 are equal
18 bool ranges_are_equal_1_3 = std::ranges::equal(vec1, vec3);
19 // Result: ranges_are_equal_1_3 = false

```

- search
- search\_n
- ranges::search
- ranges::search\_n

```

1 std::vector<int> numbers = {1, 2, 3, 4, 5, 3, 4, 5, 6, 7};
2 std::vector<int> pattern = {3, 4, 5};
3
4 // Using std::search to find the first occurrence of a subsequence
5 auto it_search = std::search(numbers.begin(), numbers.end(),
6                               pattern.begin(), pattern.end());
7 // Result: it_search points to the first element of the first
8 // occurrence of {3, 4, 5}
9
10 // Using std::search_n to find the first occurrence of three
11 // consecutive 4s
12 auto it_search_n = std::search_n(numbers.begin(), numbers.end(),
13                                   3, 4);
14 // Result: it_search_n points to numbers.end() as there are no
15 // three consecutive 4s
16
17 // Using std::ranges::search to find the first occurrence of a
18 // subsequence
19 auto ranges_it_search = std::ranges::search(numbers, pattern);
20 // Result: ranges_it_search.begin() points to the first element of
21 // the first occurrence of {3, 4, 5}
22
23 // Using std::ranges::search_n to find the first occurrence of two
24 // consecutive 5s
25 auto ranges_it_search_n = std::ranges::search_n(numbers, 2, 5);
26 // Result: ranges_it_search_n.begin() points to numbers.end() as
27 // there are no two consecutive 5s

```

- ranges::starts\_with
- ranges::ends\_with

```

1 std::vector<int> numbers = {1, 2, 3, 4, 5};
2 std::vector<int> prefix = {1, 2};
3 std::vector<int> suffix = {4, 5};
4 std::vector<int> non_prefix = {2, 3};
5 std::vector<int> non_suffix = {3, 4};
6
7 // Using std::ranges::starts_with to check if numbers starts with
8 // prefix
9 bool starts_with_prefix = std::ranges::starts_with(numbers, prefix);
10 // Result: starts_with_prefix = true
11
12 // Using std::ranges::starts_with to check if numbers starts with
13 // non_prefix
14 bool starts_with_non_prefix = std::ranges::starts_with(numbers,
15                                                         non_prefix);
16 // Result: starts_with_non_prefix = false
17
18 // Using std::ranges::ends_with to check if numbers ends with
19 // suffix

```

```

16 bool ends_with_suffix = std::ranges::ends_with(numbers, suffix);
17 // Result: ends_with_suffix = true
18
19 // Using std::ranges::ends_with to check if numbers ends with
    non_suffix
20 bool ends_with_non_suffix = std::ranges::ends_with(numbers,
    non_suffix);
21 // Result: ends_with_non_suffix = false

```

### 3 Fold Operations

- `ranges::fold_left`
- `ranges::_fold_left_first`
- `ranges::fold_left_with_iter`
- `ranges::fold_left_first_with_iter`
- `ranges::fold_right`
- `ranges::fold_right_last`

### 4 Copy Operations

- `copy`: Copies all elements from numbers to result
- `copy_if`: Copies only even numbers from numbers to result
- `ranges::copy`
- `ranges::copy_if`
- `copy_n`: Copies the first 5 elements from numbers to result
- `ranges::copy_n`: Copies elements from numbers to result in reverse order.
- `copy_backwards`
- `ranges::copy_backwards`

```

1 std::vector<int> numbers = {1, 2, 3, 4, 5, 6, 7, 8, 9, 10};
2 std::vector<int> result(10);
3
4 // Using std::copy to copy all elements
5 std::copy(numbers.begin(), numbers.end(), result.begin());
6 // Result: result = {1, 2, 3, 4, 5, 6, 7, 8, 9, 10}
7
8 // Using std::copy_if to copy only even numbers
9 auto it = std::copy_if(numbers.begin(), numbers.end(), result.
    begin(), [](int n) { return n % 2 == 0; });
10 // Result: result = {2, 4, 6, 8, 10, ?, ?, ?, ?, ?} (remaining
    elements are unspecified)
11
12 // Using std::ranges::copy to copy all elements
13 std::ranges::copy(numbers, result.begin());
14 // Result: result = {1, 2, 3, 4, 5, 6, 7, 8, 9, 10}
15
16 // Using std::ranges::copy_if to copy only even numbers
17 it = std::ranges::copy_if(numbers, result.begin(), [](int n) {
    return n % 2 == 0; });
18 // Result: result = {2, 4, 6, 8, 10, ?, ?, ?, ?, ?} (remaining
    elements are unspecified)
19

```

```

20 // Using std::copy_n to copy the first 5 elements
21 std::copy_n(numbers.begin(), 5, result.begin());
22 // Result: result = {1, 2, 3, 4, 5, ?, ?, ?, ?, ?} (remaining
    elements are unspecified)
23
24 // Using std::ranges::copy_n to copy the first 5 elements
25 std::ranges::copy_n(numbers.begin(), 5, result.begin());
26 // Result: result = {1, 2, 3, 4, 5, ?, ?, ?, ?, ?} (remaining
    elements are unspecified)
27
28 // Using std::copy_backward to copy elements in reverse order
29 std::copy_backward(numbers.begin(), numbers.end(), result.end());
30 // Result: result = {1, 2, 3, 4, 5, 6, 7, 8, 9, 10}
31
32 // Using std::ranges::copy_backward to copy elements in reverse
    order
33 std::ranges::copy_backward(numbers, result.end());
34 // Result: result = {1, 2, 3, 4, 5, 6, 7, 8, 9, 10}

```

- move
- ranges::move
- move\_backward
- ranges::move\_backward

```

1 std::vector<int> source = {1, 2, 3, 4, 5};
2 std::vector<int> destination(5);
3
4 // Using std::move to transfer elements from source to destination
5 std::move(source.begin(), source.end(), destination.begin());
6 // Result: destination = {1, 2, 3, 4, 5}
7 // Result: source = {?, ?, ?, ?, ?} (unspecified, but valid state)
8
9 // Reset source for the next example
10 source = {6, 7, 8, 9, 10};
11
12 // Using std::move_backward to transfer elements from source to
    destination in reverse order
13 std::move_backward(source.begin(), source.end(), destination.end()
    );
14 // Result: destination = {6, 7, 8, 9, 10}
15 // Result: source = {?, ?, ?, ?, ?} (unspecified, but valid state)

```

## 5 Swap Operations

- swap
- swap\_ranges
- ranges::swap\_ranges
- iter\_swap

```

1 // Demonstrate std::swap
2 int a = 10, b = 20;
3 // Before swap: a = 10, b = 20
4 std::swap(a, b);
5 // After swap: a = 20, b = 10
6
7 // Demonstrate std::swap_ranges
8 std::vector<int> vec1 = {1, 2, 3, 4, 5};

```



```

9  std::vector<int> vec2 = {6, 7, 8, 9, 10};
10 // Before swap_ranges: vec1 = 1 2 3 4 5, vec2 = 6 7 8 9 10
11
12 std::swap_ranges(vec1.begin(), vec1.end(), vec2.begin());
13 // After swap_ranges: vec1 = 6 7 8 9 10, vec2 = 1 2 3 4 5
14
15 // Demonstrate std::ranges::swap_ranges
16 std::vector<int> vec3 = {11, 12, 13, 14, 15};
17 std::vector<int> vec4 = {16, 17, 18, 19, 20};
18 // Before ranges::swap_ranges: vec3 = 11 12 13 14 15, vec4 = 16 17
    18 19 20
19
20 std::ranges::swap_ranges(vec3, vec4);
21 // After ranges::swap_ranges: vec3 = 16 17 18 19 20, vec4 = 11 12
    13 14 15
22
23 // Demonstrate std::iter_swap
24 std::vector<int> vec5 = {21, 22, 23, 24, 25};
25 // Before iter_swap: vec5 = 21 22 23 24 25
26
27 std::iter_swap(vec5.begin(), vec5.begin() + 4);
28 // After iter_swap: vec5 = 25 22 23 24 21

```

## 6 Transform Operations

- transform
- ranges::transform

```

1  #include <algorithm>
2  #include <execution>
3  #include <iostream>
4  #include <vector>
5
6  int main() {
7      // Original vector
8      std::vector<int> l1 = {1, 2, 3, 4, 5};
9      std::vector<int> l2 = std::vector<int>(l1.size(), 0);
10     std::vector<int> l3 = std::vector<int>(l1.size(), 0);
11
12     // simple transform (1 input, 1 output)
13     std::transform(l1.begin(), l1.end(), l2.begin(), [](int a) {
14         return a * 10; });
15
16     // transform (2 inputs, 1 output)
17     int multiplier = 2;
18     std::transform(std::execution::par_unseq, l1.begin(), l1.end(),
19         , l2.begin(), l3.begin(),
20         [multiplier](int a, int b) { return (multiplier
21             * a) + b; });
22
23     return 0;
24 }

```

- replace
- replace\_if
- ranges::replace
- ranges::replace\_if

```

1  std::vector<int> numbers = {1, 2, 3, 4, 5, 6, 7, 8, 9, 10};
2
3  // Using std::replace to replace all occurrences of 5 with 50
4  std::replace(numbers.begin(), numbers.end(), 5, 50);
5  // Result: numbers = {1, 2, 3, 4, 50, 6, 7, 8, 9, 10}
6
7  // Using std::replace_if to replace all even numbers with 0
8  std::replace_if(numbers.begin(), numbers.end(), [](int n) { return
    n % 2 == 0; }, 0);
9  // Result: numbers = {1, 0, 3, 0, 0, 0, 7, 0, 9, 0}
10
11 // Reset the numbers vector for ranges example
12 numbers = {1, 2, 3, 4, 5, 6, 7, 8, 9, 10};
13
14 // Using std::ranges::replace to replace all occurrences of 5 with
    50
15 std::ranges::replace(numbers, 5, 50);
16 // Result: numbers = {1, 2, 3, 4, 50, 6, 7, 8, 9, 10}
17
18 // Using std::ranges::replace_if to replace all even numbers with
    0
19 std::ranges::replace_if(numbers, [](int n) { return n % 2 == 0; },
    0);
20 // Result: numbers = {1, 0, 3, 0, 0, 0, 7, 0, 9, 0}

```

- replace\_copy
- ranges::replace\_copy
- replace\_copy\_if
- ranges::replace\_copy\_if

```

1  std::vector<int> numbers = {1, 2, 3, 4, 5, 6, 7, 8, 9, 10};
2  std::vector<int> result(numbers.size());
3
4  // Using std::replace_copy to copy elements and replace 5 with 50
5  std::replace_copy(numbers.begin(), numbers.end(), result.begin(),
    5, 50);
6  // Result: result = {1, 2, 3, 4, 50, 6, 7, 8, 9, 10}
7
8  // Using std::replace_copy_if to copy elements and replace even
    numbers with 0
9  std::replace_copy_if(numbers.begin(), numbers.end(), result.begin
    (), [](int n) { return n % 2 == 0; }, 0);
10 // Result: result = {1, 0, 3, 0, 5, 0, 7, 0, 9, 0}
11
12 // Using std::ranges::replace_copy to copy elements and replace 5
    with 50
13 std::ranges::replace_copy(numbers, result.begin(), 5, 50);
14 // Result: result = {1, 2, 3, 4, 50, 6, 7, 8, 9, 10}
15
16 // Using std::ranges::replace_copy_if to copy elements and replace
    even numbers with 0
17 std::ranges::replace_copy_if(numbers, result.begin(), [](int n) {
    return n % 2 == 0; }, 0);
18 // Result: result = {1, 0, 3, 0, 5, 0, 7, 0, 9, 0}

```

## 7 Generation Operations

- fill

- fill\_n
- ranges::fill
- ranges::fill\_n

```

1 std::vector<int> numbers(10);
2
3 // Using std::fill to fill the entire vector with 5
4 std::fill(numbers.begin(), numbers.end(), 5);
5 // Result: numbers = {5, 5, 5, 5, 5, 5, 5, 5, 5, 5}
6
7 // Using std::fill_n to fill the first 5 elements with 3
8 std::fill_n(numbers.begin(), 5, 3);
9 // Result: numbers = {3, 3, 3, 3, 3, 5, 5, 5, 5, 5}
10
11 // Using std::ranges::fill to fill the entire vector with 7
12 std::ranges::fill(numbers, 7);
13 // Result: numbers = {7, 7, 7, 7, 7, 7, 7, 7, 7, 7}
14
15 // Using std::ranges::fill_n to fill the first 5 elements with 9
16 std::ranges::fill_n(numbers.begin(), 5, 9);
17 // Result: numbers = {9, 9, 9, 9, 9, 7, 7, 7, 7, 7}

```

- generate
- generate\_n
- ranges::generate
- ranges::generate\_n

```

1 std::vector<int> numbers(10);
2 int value = 0;
3
4 // Using std::generate to fill the vector with incrementing values
  // starting from 1
5 std::generate(numbers.begin(), numbers.end(), [&value]() { return
  ++value; });
6 // Result: numbers = {1, 2, 3, 4, 5, 6, 7, 8, 9, 10}
7
8 // Reset value for the next example
9 value = 0;
10
11 // Using std::generate_n to fill the first 5 elements with
  // incrementing values starting from 1
12 std::generate_n(numbers.begin(), 5, [&value]() { return ++value;
  });
13 // Result: numbers = {1, 2, 3, 4, 5, 6, 7, 8, 9, 10}
14
15 // Reset value for the next example
16 value = 0;
17
18 // Using std::ranges::generate to fill the vector with
  // incrementing values starting from 1
19 std::ranges::generate(numbers, [&value]() { return ++value; });
20 // Result: numbers = {1, 2, 3, 4, 5, 6, 7, 8, 9, 10}
21
22 // Reset value for the next example
23 value = 0;
24
25 // Using std::ranges::generate_n to fill the first 5 elements with
  // incrementing values starting from 1
26 std::ranges::generate_n(numbers.begin(), 5, [&value]() { return ++
  value; });

```

```
27 | // Result: numbers = {1, 2, 3, 4, 5, 6, 7, 8, 9, 10}
```

## 8 Removing Operations

- `remove`
- `remove_if`
- `ranges::remove`
- `ranges::remove_if`
- `remove_copy`
- `remove_copy_if`
- `ranges::remove_copy`
- `ranges::remove_copy_if`
- `unique`
- `unique_copy`
- `ranges::unique`
- `ranges::unique_copy`

## 9 Order-Changing Operations

- `reverse`
- `ranges::reverse`
- `reverse_copy`
- `ranges::reverse_copy`
- `rotate`
- `rotate_copy`
- `ranges::rotate`
- `ranges::rotate_copy`
- `shift_left`
- `shift_right`
- `ranges::shift_left`
- `ranges::shift_right`
- `shuffle`
- `random_shuffle`
- `ranges::shuffle`

## 10 Sampling Operations

- `sample`
- `ranges::sample`

## 11 Random Number Generation

- `ranges::generate_random`

## 12 Partitioning Operations

- `is_partitioned`
- `ranges::is_partitioned`
- `partition`
- `ranges::partition`
- `partition_copy`
- `ranges::partition_copy`
- `stable_partition`
- `ranges::stable_partition`
- `partition_point`
- `ranges::partition_point`

## 13 Sorting Operations

- `sort`
- `ranges::sort`
- `stable_sort`
- `ranges::stable_sort`
- `partial_sort`
- `ranges::partial_sort`
- `partial_sort_copy`
- `ranges::partial_sort_copy`
- `is_sorted`
- `ranges::is_sorted`
- `is_sorted_until`
- `ranges::is_sorted_until`
- `nth_element`
- `ranges::nth_element`

## 14 Binary Search Operations (on partitioned ranges)

- `lower_bound`
- `ranges::lower_bound`
- `upper_bound`
- `ranges::upper_bound`
- `equal_range`
- `ranges::equal_range`
- `binary_search`
- `ranges::binary_search`

## 15 Set Operation (on sorted ranges)

- `includes`
- `ranges::includes`
- `set_union`
- `ranges::set_union`
- `set_intersection`
- `ranges::set_intersection`
- `set_difference`
- `ranges::set_difference`
- `set_symmetric_difference`
- `ranges::set_symmetric_difference`

## 16 Merge Operations (on sorted ranges)

- `merge`
- `ranges::merge`
- `inplace_merge`
- `ranges::inplace_merge`

```
1  std::vector<int> vec1 = {1, 3, 5, 7};
2  std::vector<int> vec2 = {2, 4, 6, 8};
3  std::vector<int> merged(vec1.size() + vec2.size());
4
5  // Using std::merge to merge two sorted ranges into a new range
6  std::merge(vec1.begin(), vec1.end(), vec2.begin(), vec2.end(),
7             merged.begin());
8  // Result: merged = {1, 2, 3, 4, 5, 6, 7, 8}
9
10 // Using std::ranges::merge to merge two sorted ranges into a new
11 //    range
12 std::vector<int> mergedRanges(vec1.size() + vec2.size());
13 std::ranges::merge(vec1, vec2, mergedRanges.begin());
14 // Result: mergedRanges = {1, 2, 3, 4, 5, 6, 7, 8}
```

```

14 // Using std::inplace_merge to merge two consecutive sorted ranges
    within a single range
15 std::vector<int> inplaceVec = {1, 3, 5, 7, 2, 4, 6, 8};
16 std::inplace_merge(inplaceVec.begin(), inplaceVec.begin() + 4,
    inplaceVec.end());
17 // Result: inplaceVec = {1, 2, 3, 4, 5, 6, 7, 8}
18
19 // Using std::ranges::inplace_merge to merge two consecutive
    sorted ranges within a single range
20 std::vector<int> inplaceVecRanges = {1, 3, 5, 7, 2, 4, 6, 8};
21 std::ranges::inplace_merge(inplaceVecRanges, inplaceVecRanges.
    begin() + 4);
22 // Result: inplaceVecRanges = {1, 2, 3, 4, 5, 6, 7, 8}

```

## 17 Heap Operations

- push\_heap
- ranges::push\_heap
- pop\_heap
- ranges::pop\_heap

```

1 std::vector<int> heap = {3, 1, 4, 1, 5, 9, 2, 6};
2
3 // Convert the vector into a heap
4 std::make_heap(heap.begin(), heap.end());
5 // Result: heap = {9, 6, 4, 1, 5, 3, 2, 1}
6
7 // Using std::push_heap to add a new element and maintain heap
    property
8 heap.push_back(7);
9 std::push_heap(heap.begin(), heap.end());
10 // Result: heap = {9, 7, 4, 6, 5, 3, 2, 1, 1}
11
12 // Using std::pop_heap to remove the largest element and maintain
    heap property
13 std::pop_heap(heap.begin(), heap.end());
14 heap.pop_back();
15 // Result: heap = {7, 6, 4, 1, 5, 3, 2, 1}
16
17 // Using std::ranges::push_heap to add a new element and maintain
    heap property
18 heap.push_back(8);
19 std::ranges::push_heap(heap);
20 // Result: heap = {8, 7, 4, 6, 5, 3, 2, 1, 1}
21
22 // Using std::ranges::pop_heap to remove the largest element and
    maintain heap property
23 std::ranges::pop_heap(heap);
24 heap.pop_back();
25 // Result: heap = {7, 6, 4, 1, 5, 3, 2, 1}

```

- make\_heap
- ranges::make\_heap
- sort\_heap
- ranges::sort\_heap

```

1  std::vector<int> numbers = {3, 1, 4, 1, 5, 9, 2, 6};
2
3  // Using std::make_heap to create a max-heap from the numbers
   vector
4  std::make_heap(numbers.begin(), numbers.end());
5  // Result: numbers = {9, 6, 4, 1, 5, 1, 2, 3}
6
7  // Using std::sort_heap to sort the heap
8  std::sort_heap(numbers.begin(), numbers.end());
9  // Result: numbers = {1, 1, 2, 3, 4, 5, 6, 9}
10
11 // Reset the numbers vector for ranges example
12 numbers = {3, 1, 4, 1, 5, 9, 2, 6};
13
14 // Using std::ranges::make_heap to create a max-heap from the
   numbers vector
15 std::ranges::make_heap(numbers);
16 // Result: numbers = {9, 6, 4, 1, 5, 1, 2, 3}
17
18 // Using std::ranges::sort_heap to sort the heap
19 std::ranges::sort_heap(numbers);
20 // Result: numbers = {1, 1, 2, 3, 4, 5, 6, 9}

```

- `is_heap`
- `ranges::is_heap`
- `is_heap_until`
- `ranges::is_heap_until`

```

1  std::vector<int> numbers = {9, 6, 4, 1, 5, 1, 2, 3};
2
3  // Using std::is_heap to check if the numbers vector is a heap
4  bool isHeap = std::is_heap(numbers.begin(), numbers.end());
5  // Result: isHeap = true
6
7  // Using std::is_heap_until to find the first position where the
   heap property is violated
8  auto heapEnd = std::is_heap_until(numbers.begin(), numbers.end());
9  // Result: heapEnd points to numbers.end(), indicating the entire
   range is a heap
10
11 // Using std::ranges::is_heap to check if the numbers vector is a
   heap
12 bool isHeapRanges = std::ranges::is_heap(numbers);
13 // Result: isHeapRanges = true
14
15 // Using std::ranges::is_heap_until to find the first position
   where the heap property is violated
16 auto heapEndRanges = std::ranges::is_heap_until(numbers);
17 // Result: heapEndRanges points to numbers.end(), indicating the
   entire range is a heap
18
19 // Modify the vector to violate the heap property
20 numbers = {9, 6, 4, 10, 5, 1, 2, 3};
21
22 // Re-check using std::is_heap
23 isHeap = std::is_heap(numbers.begin(), numbers.end());
24 // Result: isHeap = false
25
26 // Re-check using std::is_heap_until
27 heapEnd = std::is_heap_until(numbers.begin(), numbers.end());

```



```

28 // Result: heapEnd points to numbers.begin() + 3, where the value
    10 violates the heap property
29
30 // Re-check using std::ranges::is_heap
31 isHeapRanges = std::ranges::is_heap(numbers);
32 // Result: isHeapRanges = false
33
34 // Re-check using std::ranges::is_heap_until
35 heapEndRanges = std::ranges::is_heap_until(numbers);
36 // Result: heapEndRanges points to numbers.begin() + 3, where the
    value 10 violates the heap property

```

## 18 Min/Max Operations

- max
- min
- ranges::max
- ranges::min

```

1  int a = 10;
2  int b = 20;
3
4  // Using std::max to find the maximum of two values
5  int maxVal = std::max(a, b);
6  // Result: maxVal = 20
7
8  // Using std::min to find the minimum of two values
9  int minVal = std::min(a, b);
10 // Result: minVal = 10
11
12 std::vector<int> numbers = {3, 1, 4, 1, 5, 9, 2, 6, 5, 3, 5};
13
14 // Using std::ranges::max to find the maximum value in a range
15 int maxInRange = std::ranges::max(numbers);
16 // Result: maxInRange = 9
17
18 // Using std::ranges::min to find the minimum value in a range
19 int minInRange = std::ranges::min(numbers);
20 // Result: minInRange = 1

```

- max\_element
- min\_element
- ranges::max\_element
- ranges::min\_element

```

1  std::vector<int> numbers = {3, 1, 4, 1, 5, 9, 2, 6, 5, 3, 5};
2
3  // Using std::max_element to find the maximum element in a range
4  auto maxElement = std::max_element(numbers.begin(), numbers.end())
    ;
5  // Result: *maxElement = 9
6
7  // Using std::min_element to find the minimum element in a range
8  auto minElement = std::min_element(numbers.begin(), numbers.end())
    ;
9  // Result: *minElement = 1
10

```

```

11 // Using std::ranges::max_element to find the maximum element in a
    range
12 auto maxElementRanges = std::ranges::max_element(numbers);
13 // Result: *maxElementRanges = 9
14
15 // Using std::ranges::min_element to find the minimum element in a
    range
16 auto minElementRanges = std::ranges::min_element(numbers);
17 // Result: *minElementRanges = 1

```

- minmax
- ranges::minmax
- minmax\_element
- ranges::minmax\_element

```

1  int a = 10;
2  int b = 20;
3
4  // Using std::minmax to find the minimum and maximum of two values
5  auto minmaxPair = std::minmax(a, b);
6  // Result: minmaxPair.first = 10, minmaxPair.second = 20
7
8  std::vector<int> numbers = {3, 1, 4, 1, 5, 9, 2, 6, 5, 3, 5};
9
10 // Using std::minmax_element to find the minimum and maximum
    elements in a range
11 auto minmaxElements = std::minmax_element(numbers.begin(), numbers
    .end());
12 // Result: *minmaxElements.first = 1, *minmaxElements.second = 9
13
14 // Using std::ranges::minmax to find the minimum and maximum in a
    range
15 auto minmaxRange = std::ranges::minmax(numbers);
16 // Result: minmaxRange.min = 1, minmaxRange.max = 9
17
18 // Using std::ranges::minmax_element to find the minimum and
    maximum elements in a range
19 auto minmaxRangeElements = std::ranges::minmax_element(numbers);
20 // Result: *minmaxRangeElements.min = 1, *minmaxRangeElements.max
    = 9
21 //
22 // TODO (ksolomon): make sure usage is correct. why does minmax
    return a pair, whereas ranges::minmax return a tuple?
23 //

```

- clamp
- ranges::clamp

```

1  int value = 15;
2  int lowerBound = 10;
3  int upperBound = 20;
4
5  // Using std::clamp to constrain the value within the range [
    lowerBound, upperBound]
6  int clampedValue = std::clamp(value, lowerBound, upperBound);
7  // Result: clampedValue = 15
8
9  // Using std::clamp to constrain a value below the lower bound
10 int belowLower = 5;
11 int clampedBelow = std::clamp(belowLower, lowerBound, upperBound);

```

```

12 // Result: clampedBelow = 10
13
14 // Using std::clamp to constrain a value above the upper bound
15 int aboveUpper = 25;
16 int clampedAbove = std::clamp(aboveUpper, lowerBound, upperBound);
17 // Result: clampedAbove = 20
18
19 // Using std::ranges::clamp to constrain the value within the
    range [lowerBound, upperBound]
20 int clampedValueRanges = std::ranges::clamp(value, lowerBound,
    upperBound);
21 // Result: clampedValueRanges = 15
22
23 // Using std::ranges::clamp to constrain a value below the lower
    bound
24 int clampedBelowRanges = std::ranges::clamp(belowLower, lowerBound
    , upperBound);
25 // Result: clampedBelowRanges = 10
26
27 // Using std::ranges::clamp to constrain a value above the upper
    bound
28 int clampedAboveRanges = std::ranges::clamp(aboveUpper, lowerBound
    , upperBound);
29 // Result: clampedAboveRanges = 20

```

## 19 Lexicographical Operations

- `lexicographical_compare`
- `ranges::lexicographical_compare`
- `lexicographical_compare_three_way`

## 20 Permutation Operations

- `next_permutation`
- `ranges::next_permutation`
- `previous_permutation`
- `ranges::previous_permutation`
- `is_permutation`
- `ranges::is_permutation`

```

1 std::vector<int> numbers = {1, 2, 3};
2 std::vector<int> otherNumbers = {3, 2, 1};
3
4 // Using std::next_permutation to get the next lexicographical
    permutation
5 std::next_permutation(numbers.begin(), numbers.end());
6 // Result: {1, 3, 2}
7
8 // Using std::ranges::next_permutation to get the next
    lexicographical permutation
9 std::ranges::next_permutation(numbers);
10 // Result: {2, 1, 3}
11
12 // Using std::previous_permutation to get the previous
    lexicographical permutation
13 std::previous_permutation(numbers.begin(), numbers.end());

```

```

14 // Result: {1, 3, 2}
15
16 // Using std::ranges::previous_permutation to get the previous
    lexicographical permutation
17 std::ranges::previous_permutation(numbers);
18 // Result: {1, 2, 3}
19
20 // Using std::is_permutation to check if two sequences are
    permutations of each other
21 bool isPermutation = std::is_permutation(numbers.begin(), numbers.
    end(), otherNumbers.begin());
22 // Result: true
23
24 // Using std::ranges::is_permutation to check if two sequences are
    permutations of each other
25 bool isPermutationRanges = std::ranges::is_permutation(numbers,
    otherNumbers);
26 // Result: true

```

## 21 Numeric Operations

- `iota`
- `ranges::iota`

```

1 // Using std::iota to fill a vector with sequential values
2 std::vector<int> numbers(10);
3 std::iota(numbers.begin(), numbers.end(), 1); // Fills with
    values starting from 1
4
5 // Using std::ranges::iota to fill another vector with sequential
    values
6 std::vector<int> moreNumbers(10);
7 std::ranges::iota(moreNumbers, 11); // Fills with values starting
    from 11

```

- `accumulate`
- `reduce`
- `transform_reduce`

```

1 std::vector<int> numbers = {1, 2, 3, 4, 5};
2
3 // Using std::accumulate to sum the elements
4 int sum = std::accumulate(numbers.begin(), numbers.end(), 0);
5
6 // Using std::reduce to sum the elements (C++17)
7 int sumReduce = std::reduce(std::execution::seq, numbers.begin(),
    numbers.end(), 0);
8
9 // Using std::transform_reduce to compute the sum of squares
10 int sumOfSquares = std::transform_reduce(numbers.begin(), numbers.
    end(), 0, std::plus<>(), [](int n) { return n * n; });

```

- `inner_product`

```

1 std::vector<int> vector1 = {1, 2, 3};
2 std::vector<int> vector2 = {4, 5, 6};
3
4 // Using std::inner_product to compute the inner product of
    vector1 and vector2

```

```

5 int result = std::inner_product(vector1.begin(), vector1.end(),
  vector2.begin(), 0);
6 // result = 32

```

- adjacent\_difference

```

1 std::vector<int> numbers = {1, 2, 3, 4, 5};
2 std::vector<int> partialSums(numbers.size());
3
4 // Using std::partial_sum to compute the partial sums of the
  numbers vector
5 std::partial_sum(numbers.begin(), numbers.end(), partialSums.begin
  ());
6 // partialSums: [1, 3, 6, 10, 15]

```

- partial\_sum

```

1 std::vector<int> numbers = {1, 2, 3, 4, 5};
2 std::vector<int> partialSums(numbers.size());
3
4 // Using std::partial_sum to compute the partial sums of the
  numbers vector
5 std::partial_sum(numbers.begin(), numbers.end(), partialSums.begin
  ());
6 // partialSums = [1, 3, 6, 10, 15]

```

- exclusive\_scan

- inclusive\_scan

- transform\_exclusive\_scan

- transform\_inclusive\_scan

```

1 std::vector<int> numbers = {1, 2, 3, 4, 5};
2 std::vector<int> exclusiveScanResult(numbers.size());
3 std::vector<int> inclusiveScanResult(numbers.size());
4 std::vector<int> transformExclusiveScanResult(numbers.size());
5 std::vector<int> transformInclusiveScanResult(numbers.size());
6
7 // Using std::exclusive_scan to compute exclusive prefix sums
8 std::exclusive_scan(numbers.begin(), numbers.end(),
  exclusiveScanResult.begin(), 0);
9 // Result: {0, 1, 3, 6, 10}
10
11 // Using std::inclusive_scan to compute inclusive prefix sums
12 std::inclusive_scan(numbers.begin(), numbers.end(),
  inclusiveScanResult.begin());
13 // Result: {1, 3, 6, 10, 15}
14
15 // Using std::transform_exclusive_scan to compute exclusive prefix
  sums of squares
16 std::transform_exclusive_scan(numbers.begin(), numbers.end(),
  transformExclusiveScanResult.begin(), 0, std::plus<>(),
  [](int n) { return n * n; });
17 // Result: {0, 1, 5, 14, 30}
18
19
20 // Using std::transform_inclusive_scan to compute inclusive prefix
  sums of squares
21 std::transform_inclusive_scan(numbers.begin(), numbers.end(),
  transformInclusiveScanResult.begin(), std::plus<>(),
  [](int n) { return n * n; });
22 // Result: {1, 5, 14, 30, 55}
23

```

## 22 Uninitialized Memory Operations