

DIR-6
INDUSTRIAL ROBOT
ELECTRICAL CABINET



THE INTRODUCTION AND FEATURES OF ELECTRICAL CABINET

- The electric cabinet is specially customized for 4-axis robot, which has the characteristics of compact structure, smaller volume, easy installation, lightweight and multiple functions.
- Built-in control system software independently developed by DIR can meet the requirements of high speed, exact performance of motion control and high reliability of robots. Besides, it can achieve more accurate trajectory control and faster beat in applications with smaller size and multiple functions

FUNCTIONAL FEATURES

- Adopt split design to effectively keep dust out and improve stability
- Adopt quick plug to achieve wiring more convenient;
- Well-knit design makes the robot more convenient in small space.
- With multiple installations, G6 electric cabinet has more flexible layout;
- With multiple interfaces, G6 electrical cabinet supports diversiform communication protocols
- High power density and efficient heat dissipation
- High integration and small size

CABINET TECHNICAL INDEX

Teaching pendant	8-inch TFT-LCD, keyboard + touch screen, mode selection switch, safety switch, emergency stop button
Controlled Axes	4
Interface	Digital I/O interface,24 input/output(expandable COM)
	2-way 0~10V analog output, 12-bit accuracy(expandable COM)
	Encoder signal interface(position tracking)
	Ethernet communication interface,2 USB interface
Operation mode	Communication interface: RS484,RS232,CAN,Expandable: Profinet,cclink
	Teach, Reproduction, Remote
Coordinate system	Point-to-point, straight line, circle
	Motion, Logic, Process, Operation
IP level	IP20
Input Power (including length)	Single-phase AC220V±15% 50/60Hz, PE ground cable
Interconnecting Cable	5M
Dimension	485.8X387.4X155.5mm
Weight	20KG
Installation environment	Indoor (avoid direct sunlight), no corrosive gas, ambient temperature: 0-55°;Storage temperature (-20-65°), 0-99% (no condensation);
Safety	External emergency stop, anti-collision ,safety bolt interface, etc.
Ground Resistance	<0.1Ω
Insulation Resistance	>100MΩ
Vibration Resistance	10<f<58.1HZ Amplitude:0.15mm
Impact-Resistance Strength	Max strength:15g Duration:11ms
EMC Testing Standard	IEC 61000-6-2
Abnormal detection	Abnormal stop, abnormal servo, abnormal user coordinates, abnormal tool coordinates, safety maintenance,etc.
Others	Built-in PLC, power off regeneration, encoder interface (support synchronous belt), arc tracking and accessories (optional), visual software (optional), laser tracking software (optional), etc.
Reserved Interfaces	Arc Welding Interface, Vision Interface, Remote interface, Station Interface
Software Packag	Welding/Handling/Vision/Tracking/Palletizing /Bending/Stamping/ Communication/Spraying

CABINET DIMENSIONAL DRAWING

