



Sigurnost računala i podataka (Lab 3)

Message authentication and integrity.

Message Authentication Code (MAC)

IZAZOV 1

Stvorimo virtualno okruženje.

```
C:\Users\A507\kz>python -m venv ka
C:\Users\A507\kz>cd ka
C:\Users\A507\kz\ka>cd Scripts
C:\Users\A507\kz\ka\Scripts>activate
(ka) C:\Users\A507\kz\ka\Scripts>cd ..
(ka) C:\Users\A507\kz\ka\Scripts>pip install cryptography
```

U lokalnom direktoriju kreiramo tekstualnu datoteku odgovarajućeg sadržaja čiji integritet želimo zaštititi te učitamo sadržaj datoteke u memoriju.

```
with open(filename, "rb") as file:
    content = file.read()
```

Kreiramo funkciju za izračun MAC vrijednosti.

```
from cryptography.hazmat.primitives import hashes, hmac

def generate_MAC(key, message):
    if not isinstance(message, bytes):
        message = message.encode()
    h = hmac.HMAC(key, hashes.SHA256())
    h.update(message)
    signature = h.finalize()
    return signature

if name == "main":
    pass
```

Dobijemo MAC vrijednost.

```
if name == "main":
    key=b"tajna"
    with open("message.txt", "rb") as file:
        content=file.read()

    mac= generate_MAC(key, content)

    with open("message.sig", "wb") as file:
        file.write(mac)
```

Zapisujemo generirani MAC u novi file message.sig.

```
with open("./message.sig", "wb") as file:
    file.write(mac)
```

Funkcija za provjeru validnosti MAC-a za danu poruku.

```
from cryptography.hazmat.primitives import hashes, hmac
from cryptography.exceptions import InvalidSignature

def verify_MAC(key, signature, message):
    if not isinstance(message, bytes):
        message = message.encode()

    h = hmac.HMAC(key, hashes.SHA256())
    h.update(message)
```

```

try:
    h.verify(signature)
except InvalidSignature:
    return False
else:
    return True

```

Nadogradimo kod te završen glasi ovako.

```

from cryptography.hazmat.primitives import hashes, hmac
from cryptography.exceptions import InvalidSignature

def verify_MAC(key, signature, message):
    if not isinstance(message, bytes):
        message = message.encode()
    h = hmac.HMAC(key, hashes.SHA256())
    h.update(message)
    try:
        h.verify(signature)
    except InvalidSignature:
        return False
    else:
        return True

def generate_MAC(key, message):
    if not isinstance(message, bytes):
        message = message.encode()
    h = hmac.HMAC(key, hashes.SHA256())
    h.update(message)
    signature = h.finalize()
    return signature

if name == "main":
    key=b"tajna"
    with open("message.txt", "rb") as file:
        content=file.read()

    with open("message.sig", "rb") as file:
        signature=file.read()

    is_valid = verify_MAC(key, signature, content)
    print(is_valid)



```

Poziv i rezultat funkcije.

```

(ka) C:\Users\A507\kz\ka>python .\message_int.py
True

```



Za kraj smo mijenjali poruke i potpis te gledali kako se rezultat funkcije mijenja bez obzira što promijenili.

IZAZOV 2

U ovom izazovu **želite utvrditi vremenski ispravnu sekvencu transakcija (ispravan redosljed transakcija) sa odgovarajućim dionicama**. Digitalno potpisani (primjenom MAC-a) nalozi za pojedine transakcije nalaze se na lokalnom web poslužitelju.

Sa servera preuzimamo personalizirane izazove (direktorij zupanovic_karmen/mac_challenge).

Preuzmemo sve izazove sa servera prema uputama.

1. Preuzmemo program `wget` dostupan na [wget download](http://a507-server.local/challenges/<zupanovic_karmen>/).
2. Pohranimo ga u direktorij gdje ćemo pisati Python skriptu rješavanje ovog izazova.
3. Osobne izazove preuzimamo izvršavanjem sljedeće naredbe u terminalu:

```
wget.exe -r -nH -np --reject "index.html*" http://a507-server.local/challenges/<zupanovic_karmen>/
```

Tajna vrijednost koja se koristi kao ključ u MAC algoritmu.

```
key = "<prezime_ime>".encode()
```

Ispis poruke i statusa integriteta 10 poruka.

```
from cryptography.hazmat.primitives import hashes, hmac
from cryptography.exceptions import InvalidSignature
import os

def verify_MAC(key, mac, message):
    if not isinstance(message, bytes):
        message = message.encode()
    h = hmac.HMAC(key, hashes.SHA256())
    h.update(message)
    try:
        h.verify(mac)
    except InvalidSignature:
        return False
    else:
        return True

if __name__ == "__main__":

    key="zupanovic_karmen".encode()

    path = os.path.join("challenge", "milicevic_mario", "mac_challenge")
```

```

print(path)

for ctr in range(1, 11):
    msg_filename = f"order_{ctr}.txt"
    sig_filename = f"order_{ctr}.sig"
    print(msg_filename)
    print(sig_filename)

    path_msg = os.path.join(path, msg_filename)
    path_sig = os.path.join(path, sig_filename)

    with open(path + "\\" + msg_filename, "rb") as file:
        content_file = file.read()

    with open(path + "\\" + sig_filename, "rb") as file:
        signature = file.read()

    is_authentic = verify_MAC(key, signature, content_file)

    print(f'Message {content_file.decode():>45} {"OK" if is_authentic else "NOK":<6}')
```

Digital signatures using public-key cryptography

U ovom izazovu trebate odrediti autentičnu sliku (između dvije ponuđene) koju je profesor potpisao svojim privatnim ključem.

Provjera koja je slika autentična korištenjem javnog ključa. U funkciju `verify_signature_rsa` šaljemo potpis za određenu sliku i sliku.

```

from cryptography.hazmat.primitives.asymmetric import padding
from cryptography.hazmat.primitives import hashes
from cryptography.exceptions import InvalidSignature
from cryptography.hazmat.primitives import serialization
from cryptography.hazmat.backends import default_backend

def load_public_key():
    with open("public.pem", "rb") as f:
        PUBLIC_KEY = serialization.load_pem_public_key(
            f.read(),
            backend=default_backend()
        )
    return PUBLIC_KEY

def verify_signature_rsa(signature, message):
    PUBLIC_KEY = load_public_key()
    try:
        PUBLIC_KEY.verify(
            signature,
            message,
```

```
padding.PSS(
    mgf=padding.MGF1(hashes.SHA256()),
    salt_length=padding.PSS.MAX_LENGTH
),
hashes.SHA256()
)
except InvalidSignature:
    return False
else:
    return True

#Reading from a file
with open("image_1.png", "rb") as file:
    image= file.read()
#Reading from a file
with open("image_1.sig", "rb") as file:
    signature= file.read()

is_authentic=verify_signature_rsa(signature, image)
print(is_authentic)
```

```
(ka) C:\Users\A507\ka>python .\digital_signature.py
<cryptography.hazmat.backends.openssl.rsa._RSAPublicKey object at 0x00000259685C0D30>
```

Provjerimo za prvu sliku i dobijemo False.

```
(ka) C:\Users\A507\ka>python .\digital_signature.py
False
```

Kod prepravimo za drugu sliku i stavimo potpis za drugu.

```
(ka) C:\Users\A507\ka>python .\digital_signature.py
True
```