```
create view public.active_delivery_boys_view as
select
,db.id
,db.full_name
,db.phone
,db.email
,db.profile_image_url
,db.preferred_vehicle
,db.license_number
,db.online_status
,db.is_available
,db.status
,db.current_latitude
,db.current_longitude
,db.last_location_update
,db.total_deliveries
,db.total_earnings
,db.rating
,db.badge_level
)
select
dorder.id
from
delivery_orders dorder
where
dorder.delivery_boy_id = db.id
) and
) dorder.status = any
]array
,pending'::delivery_status_enum'
,confirmed'::delivery_status_enum'
,pickedUp'::delivery_status_enum'
,inReceipt'::delivery_status_enum'
scheduled'::delivery_status_enum'
[
(
(
order by
dorder.updated_at desc
limit
1
,as current_order_id (
)
select
dorder.order_number
from
delivery_orders dorder
where
```

```
dorder.delivery_boy_id = db.id
) and
) dorder.status = any
]array
,pending'::delivery_status_enum'
,confirmed'::delivery_status_enum'
,pickedUp'::delivery_status_enum'
,inReceipt'::delivery_status_enum'
scheduled'::delivery_status_enum'
[
(
(
order by
dorder.updated_at desc
limit
1
,as current_order_number (
)
select
dorder.status
from
delivery_orders dorder
where
dorder.delivery_boy_id = db.id
) and
) dorder.status = any
]array
,pending'::delivery_status_enum'
,confirmed'::delivery_status_enum'
,pickedUp'::delivery_status_enum'
,inReceipt'::delivery_status_enum'
scheduled'::delivery_status_enum'
[
(
(
order by
dorder.updated_at desc
limit
1
as current_order_status (
from
delivery_boys db
where
db.online_status <> 'offline'::delivery_boy_online_status
;(or db.last_location_update > (CURRENT_TIMESTAMP - '24:00:00'::interval

) create table public.admins
,() id uuid not null default extensions.uuid_generate_v4
```

```
,user_id uuid null
,is_active boolean null default true
,(constraint admins_pkey primary key (id
constraint admins_user_id_fkey foreign KEY (user_id) references auth.users (id) on delete
CASCADE
;TABLESPACE pg_default (

) create table public.analytics_dashboard
,() id uuid not null default gen_random_uuid
,date date not null
,total_orders integer null default 0
,completed_orders integer null default 0
,canceled_orders integer null default 0
,total_waste_collected numeric(10, 2) null default 0
,total_revenue numeric(12, 2) null default 0
,active_agents integer null default 0
,average_delivery_time numeric(10, 2) null default 0
,average_collection_efficiency numeric(5, 2) null default 0
,stats_by_waste_type jsonb null
,stats_by_area jsonb null
,created_at timestamp with time zone null default CURRENT_TIMESTAMP
,updated_at timestamp with time zone null default CURRENT_TIMESTAMP
,(constraint analytics_dashboard_pkey primary key (id
(constraint analytics_dashboard_date_key unique (date
;TABLESPACE pg_default (

create index IF not exists idx_analytics_dashboard_date on public.analytics_dashboard
;using btree (date) TABLESPACE pg_default

) create table public.categories
,() id uuid not null default gen_random_uuid
,name text not null
,description text null
,image_url text null
,()created_at timestamp with time zone null default now
,()updated_at timestamp with time zone null default now
,(constraint categories_pkey primary key (id
(constraint categories_name_key unique (name
;TABLESPACE pg_default (
) create table public.complaints
,id serial not null
,order_id integer not null
,client_id uuid not null
,complaint_text text not null
,complaint_status text null default 'Pending'::text
,created_at timestamp with time zone null default CURRENT_TIMESTAMP
,updated_at timestamp with time zone null default CURRENT_TIMESTAMP
(constraint complaints_pkey primary key (id
```

```
;TABLESPACE pg_default (

) create table public.customer_addresses
,() id uuid not null default extensions.uuid_generate_v4
,profile_id uuid null
,address_type public.address_type_enum null default 'home'::address_type_enum
,address_line text not null
,city text null
,area text null
,building_number text null
,floor_number text null
,apartment_number text null
,additional_directions text null
,landmark text null
,latitude double precision not null
,longitude double precision not null
,geom geometry null
,is_default boolean null default false
,is_verified boolean null default false
,()created_at timestamp with time zone null default now
,()updated_at timestamp with time zone null default now
,street_address text null
,(constraint customer_addresses_pkey primary key (id
constraint customer_addresses_profile_id_fkey foreign KEY (profile_id) references
new_profiles (id) on delete CASCADE
;TABLESPACE pg_default (

create index IF not exists idx_customer_addresses_profile_id on public.customer_addresses
;using btree (profile_id) TABLESPACE pg_default

create index IF not exists idx_customer_addresses_geom on public.customer_addresses
;using gist (geom) TABLESPACE pg_default

create trigger ensure_profile_id BEFORE INSERT on customer_addresses for EACH row
;() execute FUNCTION set_profile_id

create trigger single_default_address_trigger
after INSERT
or
update on customer_addresses for EACH row
;() execute FUNCTION enforce_single_default_address

create trigger update_customer_addresses_modtime BEFORE
update on customer_addresses for EACH row
;() execute FUNCTION update_modified_column

) create table public.customer_interactions
,() id uuid not null default extensions.uuid_generate_v4
```

```
,order_id uuid not null
,customer_id uuid not null
,created_by uuid null
,type public.interaction_type not null
,message text null
,status_from character varying(50) null
,status_to character varying(50) null
,scheduled_pickup_time timestamp with time zone null
,scheduled_delivery_time timestamp with time zone null
,location geometry null
,latitude double precision null
,longitude double precision null
,is_read boolean null default false
,read_at timestamp with time zone null
,()created_at timestamp with time zone null default now
,notification_channel character varying(50) null
,metadata jsonb null
,(constraint customer_interactions_pkey primary key (id
constraint customer_interactions_created_by_fkey foreign KEY (created_by) references
,delivery_boys (id) on delete set null
constraint customer_interactions_customer_id_fkey foreign KEY (customer_id) references
,new_profiles (id) on delete CASCADE
constraint customer_interactions_order_id_fkey foreign KEY (order_id) references
delivery_orders (id) on delete CASCADE
;TABLESPACE pg_default (

create index IF not exists idx_customer_interactions_order_id on
;public.customer_interactions using btree (order_id) TABLESPACE pg_default

create index IF not exists idx_customer_interactions_customer_id on
;public.customer_interactions using btree (customer_id) TABLESPACE pg_default

create index IF not exists idx_customer_interactions_created_at on
;public.customer_interactions using btree (created_at) TABLESPACE pg_default

create index IF not exists idx_customer_interactions_is_read on
;public.customer_interactions using btree (is_read) TABLESPACE pg_default

create index IF not exists idx_customer_interactions_type on public.customer_interactions
;using btree (type) TABLESPACE pg_default

) create table public.customer_orders
,() id uuid not null default extensions.uuid_generate_v4
payment_method public.payment_method_enum null default
,'cash'::payment_method_enum
,priority public.order_priority_enum null default 'normal'::order_priority_enum
,pickup_address text not null
,pickup_location geometry not null
```

```
,expected_total numeric(10, 2) null
,actual_total numeric(10, 2) null
,is_fully_verified boolean null default false
,created_at timestamp with time zone null default CURRENT_TIMESTAMP
,updated_at timestamp with time zone null default CURRENT_TIMESTAMP
,earned_points numeric null
,customer_id uuid null
,profile_id uuid null
,order_details jsonb null
,category_name text null
,subcategory_name text null
,status public.delivery_status_enum null
,(constraint customer_orders_pkey primary key (id
constraint customer_orders_profile_id_fkey foreign KEY (profile_id) references
(new_profiles (id
;TABLESPACE pg_default (

create index IF not exists idx_customer_orders_location on public.customer_orders using
;gist (pickup_location) TABLESPACE pg_default

create index IF not exists idx_customer_orders_profile_id on public.customer_orders using
;btree (profile_id) TABLESPACE pg_default

create index IF not exists idx_customer_orders_order_details on public.customer_orders
;using gin (order_details) TABLESPACE pg_default

create index IF not exists idx_customer_orders_category_name on public.customer_orders
;using btree (category_name) TABLESPACE pg_default

create index IF not exists idx_customer_orders_subcategory_name on
;public.customer_orders using btree (subcategory_name) TABLESPACE pg_default

create trigger sync_amounts_from_customer_order
after
update on customer_orders for EACH row
;() execute FUNCTION sync_delivery_amounts

create trigger tr_create_delivery_order
after INSERT on customer_orders for EACH row
;() execute FUNCTION create_delivery_order

create trigger update_customer_orders_timestamp BEFORE
update on customer_orders for EACH row
;() execute FUNCTION update_customer_timestamp

) create table public.customer_phones
,() id uuid not null default extensions.uuid_generate_v4
,profile_id uuid not null
```

```
,phone_number text not null
,is_primary boolean null default false
,is_verified boolean null default false
phone_verification_status public.verification_status_enum null default
,'pending'::verification_status_enum
,()created_at timestamp with time zone null default now
,()updated_at timestamp with time zone null default now
,(constraint customer_phones_pkey primary key (id
,(constraint customer_phones_phone_number_key unique (phone_number
,(constraint unique_profile_phone unique (profile_id, phone_number
constraint fk_profile foreign KEY (profile_id) references new_profiles (id) on delete
CASCADE
;TABLESPACE pg_default (

create index IF not exists idx_customer_phones_profile_id on public.customer_phones using
;btree (profile_id) TABLESPACE pg_default

create index IF not exists idx_customer_phones_phone_number on public.customer_phones
;using btree (phone_number) TABLESPACE pg_default

create trigger single_primary_phone_trigger
after INSERT
or
update on customer_phones for EACH row
;() execute FUNCTION enforce_single_primary_phone

create trigger update_customer_phones_modtime BEFORE
update on customer_phones for EACH row
;() execute FUNCTION update_modified_column

) create table public.customers
,id uuid not null
,user_id uuid null
,full_name text not null
,email text null
,phone_number character varying not null
,customer_type public.customer_type_enum null default 'household'::customer_type_enum
,organization_name character varying null
,contact_person character varying null
,customer_status public.customer_status null default 'inactive'::customer_status
,wallet_id uuid null
,preferred_language character varying null default 'ar'::character varying
,total_orders integer null default 0
,total_spent numeric null default 0
,loyalty_points integer null default 0
,first_order_date timestamp without time zone null
,last_order_date timestamp without time zone null
,phone_verification_code character varying null
```

```
,phone_verification_expires_at timestamp with time zone null
,phone_verification_attempts integer null default 0
,is_available boolean null default true
,last_location_update timestamp with time zone null
,voice_notes jsonb null default '{}'::jsonb
,rating numeric null default 0
,referral_code character varying null
,notes text null
,addresses text null
,current_location geometry null
,created_at timestamp without time zone null default CURRENT_TIMESTAMP
,updated_at timestamp without time zone null default CURRENT_TIMESTAMP
,default_address_id uuid null
,(constraint customers_pkey primary key (id
constraint customers_default_address_id_fkey foreign KEY (default_address_id)
,(references customer_addresses (id
constraint customers_id_fkey foreign KEY (id) references auth.users (id) on delete
,CASCADE
constraint fk_default_address foreign KEY (default_address_id) references
(customer_addresses (id
;TABLESPACE pg_default (

create trigger new_customer_profile_trigger
after INSERT on customers for EACH row
;() execute FUNCTION create_new_profile_on_customer_insert

) create table public.delivery_boy_daily_performance
,() id uuid not null default gen_random_uuid
,delivery_boy_id uuid not null
,date date not null
,orders_completed integer null default 0
,orders_canceled integer null default 0
,total_distance numeric(10, 2) null default 0
,total_earnings numeric(10, 2) null default 0
,average_rating numeric(3, 2) null default 0
,online_hours numeric(5, 2) null default 0
,waste_weight_collected numeric(10, 2) null default 0
,created_at timestamp with time zone null default CURRENT_TIMESTAMP
,(constraint delivery_boy_daily_performance_pkey primary key (id
constraint delivery_boy_daily_performance_delivery_boy_date_key unique
,((delivery_boy_id, date
constraint delivery_boy_daily_performance_delivery_boy_id_fkey foreign KEY
(delivery_boy_id) references delivery_boys (id) on delete CASCADE
;TABLESPACE pg_default (

create index IF not exists idx_daily_performance_delivery_boy on
public.delivery_boy_daily_performance using btree (delivery_boy_id) TABLESPACE
;pg_default
```

```
create index IF not exists idx_daily_performance_date on
;public.delivery_boy_daily_performance using btree (date) TABLESPACE pg_default
) create table public.delivery_boy_order_history
,id uuid not null
,delivery_boy_id uuid null
,order_id uuid null
,order_date timestamp with time zone not null
,order_status character varying(50) null
,total_amount numeric(10, 2) null
,customer_rating numeric(3, 2) null
,delivery_location text null
,delivery_distance numeric(10, 2) null
(constraint delivery_boy_order_history_pkey primary key (id
;TABLESPACE pg_default (

create index IF not exists idx_delivery_boy_order_history_delivery_boy on
;public.delivery_boy_order_history using btree (delivery_boy_id) TABLESPACE pg_default

) create table public.delivery_boys
,id uuid not null
,phone character varying(20) not null
,email character varying(255) null
,full_name character varying(255) not null
,date_of_birth date null
,national_id character varying(50) null
,preferred_vehicle public.vehicle_type null
,license_number character varying(50) null
,phone_verification_code character varying(10) null
,phone_verification_expires_at timestamp with time zone null
,phone_verification_attempts integer null default 0
,delivery_code character varying(50) null
,delivery_code_expires_at timestamp with time zone null
,delivery_code_attempts integer null default 0
,status public.delivery_boy_status null default 'inactive'::delivery_boy_status
,total_deliveries integer null default 0
,total_earnings numeric(10, 2) null default 0
,rating numeric(3, 2) null default 0
,current_latitude numeric(10, 8) null
,current_longitude numeric(11, 8) null
,is_available boolean null default false
,last_location_update timestamp with time zone null
,referral_code character varying(50) null
,notes text null
,created_at timestamp with time zone null default CURRENT_TIMESTAMP
,updated_at timestamp with time zone null default CURRENT_TIMESTAMP
,last_login timestamp with time zone null
,profile_image_url text null
```

```
,device_info jsonb null
,average_response_time integer null
,completed_orders_count integer null default 0
,canceled_orders_count integer null default 0
,badge_level integer null default 0
,last_performance_review timestamp with time zone null
,preferred_zones jsonb null
online_status public.delivery_boy_online_status null default
,'offline'::delivery_boy_online_status
,identity_documents jsonb null
,license_photo_url text null
,status_reason text null
,status_changed_at timestamp with time zone null
,delivery_code_status public.verification_status null default 'pending'::verification_status
phone_verification_status public.verification_status null default
,'pending'::verification_status
,preferred_language character varying(10) null default 'ar'::character varying
,avatar_url text null
,(constraint delivery_boys_pkey primary key (id
,(constraint delivery_boys_phone_key unique (phone
,(constraint delivery_boys_delivery_code_key unique (delivery_code
,(constraint delivery_boys_email_key unique (email
,(constraint delivery_boys_national_id_key unique (national_id
,(constraint delivery_boys_referral_code_key unique (referral_code
,(constraint delivery_boys_license_number_key unique (license_number
constraint delivery_boys_id_fkey foreign KEY (id) references auth.users (id) on delete
,CASCADE
) constraint delivery_boys_rating_check check
)
(rating >= (0)::numeric)
(and (rating <= (5)::numeric
(
,(
,((constraint delivery_boys_total_deliveries_check check ((total_deliveries >= 0
) constraint delivery_boys_current_latitude_check check
)
(current_latitude >= ('-90'::integer)::numeric)
(and (current_latitude <= (90)::numeric
(
,(
,((constraint delivery_boys_total_earnings_check check ((total_earnings >= (0)::numeric
) constraint delivery_boys_current_longitude_check check
)
(current_longitude >= ('-180'::integer)::numeric)
(and (current_longitude <= (180)::numeric
(
,(
) constraint delivery_boys_date_of_birth_check check
```

```
)
(date_of_birth <= (CURRENT_DATE - '18 years'::interval
(
,(
constraint delivery_boys_delivery_code_attempts_check check ((delivery_code_attempts
,((<= 3
) constraint delivery_boys_email_check check
)
email)::text ~* '^[A-Za-z0-9._%+-]+@[A-Za-z0-9.-]+\.[A-Za-z]{2,}$'::text)
(
,(
,((constraint delivery_boys_full_name_check check ((length((full_name)::text) >= 3
,((constraint delivery_boys_phone_check check (is_valid_phone (phone
constraint delivery_boys_phone_verification_attempts_check check
((((phone_verification_attempts <= 3
;TABLESPACE pg_default (

create index IF not exists idx_delivery_boys_phone on public.delivery_boys using btree
;(phone) TABLESPACE pg_default

create index IF not exists idx_delivery_boys_delivery_code on public.delivery_boys using
;btree (delivery_code) TABLESPACE pg_default

create index IF not exists idx_delivery_boys_status on public.delivery_boys using btree
;(status) TABLESPACE pg_default

create index IF not exists idx_delivery_boys_location on public.delivery_boys using btree
;(current_latitude, current_longitude) TABLESPACE pg_default

create index IF not exists idx_delivery_boys_availability on public.delivery_boys using btree
;(is_available, status) TABLESPACE pg_default

create trigger check_delivery_boy_type_trigger BEFORE INSERT on delivery_boys for
EACH row
;() execute FUNCTION check_delivery_boy_type

create trigger update_delivery_boys_modtime BEFORE
update on delivery_boys for EACH row
;() execute FUNCTION update_modified_column

) create table public.delivery_documents
,() id uuid not null default gen_random_uuid
,delivery_id uuid null
,document_type character varying(50) not null
,document_url text not null
,verification_status character varying(20) null default 'pending'::character varying
,()uploaded_at timestamp with time zone null default now
,verified_at timestamp with time zone null
```

```
,(constraint delivery_documents_pkey primary key (id
constraint delivery_documents_delivery_id_fkey foreign KEY (delivery_id) references
(new_profiles_delivery (id
;TABLESPACE pg_default (

) create table public.delivery_earnings
,() id uuid not null default gen_random_uuid
,delivery_id uuid null
,order_id uuid not null
,amount numeric(10, 2) not null
,bonus_amount numeric(10, 2) null default 0.00
,earning_type character varying(20) null
,status character varying(20) null default 'pending'::character varying
,()created_at timestamp with time zone null default now
,paid_at timestamp with time zone null
,(constraint delivery_earnings_pkey primary key (id
constraint delivery_earnings_delivery_id_fkey foreign KEY (delivery_id) references
(new_profiles_delivery (id
;TABLESPACE pg_default (

create index IF not exists idx_delivery_earnings_delivery_id on public.delivery_earnings
;using btree (delivery_id) TABLESPACE pg_default

) create table public.delivery_locations
,() id uuid not null default gen_random_uuid
,delivery_id uuid null
,latitude numeric(10, 8) not null
,longitude numeric(11, 8) not null
,status character varying(20) null
,()updated_at timestamp with time zone null default now
,(constraint delivery_locations_pkey primary key (id
constraint delivery_locations_delivery_id_fkey foreign KEY (delivery_id) references
(new_profiles_delivery (id
;TABLESPACE pg_default (

create index IF not exists idx_delivery_locations_delivery_id on public.delivery_locations
;using btree (delivery_id) TABLESPACE pg_default
) create table public.delivery_orders
,() id uuid not null default extensions.uuid_generate_v4
,delivery_boy_id uuid null
,customer_order_id uuid null
,order_number character varying(50) not null
,pickup_location geometry not null
,pickup_address text not null
,customer_name character varying(255) null
,customer_phone character varying(20) null
,estimated_distance numeric(10, 2) null
,estimated_time integer null
```

```
,expected_total_amount numeric(10, 2) null
,actual_total_amount numeric(10, 2) null
,actual_pickup_time timestamp with time zone null
,actual_delivery_time timestamp with time zone null
,notes text null
,voice_notes jsonb null
,created_at timestamp with time zone null default CURRENT_TIMESTAMP
,updated_at timestamp with time zone null default CURRENT_TIMESTAMP
,order_id uuid null
,user_type public.user_type_enum not null default 'household'::user_type_enum
,status public.delivery_status_enum null
,category_name text null
,subcategory_name text null
,analytics_data jsonb null
,customer_feedback text null
,delivery_route jsonb null
,order_processing_time integer null
,customer_waiting_time integer null
,priority public.order_priority_enum null default 'normal'::order_priority_enum
,delivery_location geometry null
,(constraint delivery_orders_pkey primary key (id
,(constraint delivery_orders_order_number_key unique (order_number
constraint delivery_orders_customer_order_id_fkey foreign KEY (customer_order_id)
,(references customer_orders (id
constraint delivery_orders_delivery_boy_id_fkey foreign KEY (delivery_boy_id) references
(auth.users (id
;TABLESPACE pg_default (

create index IF not exists idx_delivery_orders_delivery_boy on public.delivery_orders using
;btree (delivery_boy_id) TABLESPACE pg_default

create index IF not exists idx_delivery_orders_customer_order on public.delivery_orders
;using btree (customer_order_id) TABLESPACE pg_default

create index IF not exists idx_delivery_orders_pickup_location on public.delivery_orders
;using gist (pickup_location) TABLESPACE pg_default

create index IF not exists idx_delivery_orders_category_name on public.delivery_orders
;using btree (category_name) TABLESPACE pg_default

create index IF not exists idx_delivery_orders_subcategory_name on public.delivery_orders
;using btree (subcategory_name) TABLESPACE pg_default

create trigger dashboard_analytics_update
after INSERT
or
update OF status on delivery_orders for EACH row
;() execute FUNCTION update_dashboard_analytics
```

```
create trigger delivery_boy_stats_update
after INSERT
or
(update OF status on delivery_orders for EACH row when (new.delivery_boy_id is not null
;() execute FUNCTION update_delivery_boy_stats

create trigger delivery_orders_performance_update
after INSERT
or
,update OF status
,actual_total_amount
(delivery_boy_id on delivery_orders for EACH row when (new.delivery_boy_id is not null
;() execute FUNCTION update_daily_performance

create trigger log_status_change
after
update on delivery_orders for EACH row
;() execute FUNCTION log_delivery_status_change

create trigger order_status_track_trigger
after
update on delivery_orders for EACH row
;() execute FUNCTION track_order_status_changes

create trigger update_customer_waiting_time BEFORE
,update OF status
actual_delivery_time on delivery_orders for EACH row
;() execute FUNCTION calculate_customer_waiting_time

create trigger update_delivery_orders_timestamp BEFORE
update on delivery_orders for EACH row
;() execute FUNCTION update_delivery_timestamp

create trigger update_performance_on_completion
after
update on delivery_orders for EACH row
;() execute FUNCTION update_delivery_performance

) create table public.delivery_performance_stats
,() id uuid not null default extensions.uuid_generate_v4
,delivery_boy_id uuid null
,month date not null
,total_orders integer null default 0
,completed_orders integer null default 0
,total_distance numeric(10, 2) null default 0
,average_delivery_time numeric(10, 2) null default 0
,(constraint delivery_performance_stats_pkey primary key (id
```

```
constraint delivery_performance_stats_delivery_boy_id_month_key unique
,((delivery_boy_id, month
constraint delivery_performance_stats_delivery_boy_id_fkey foreign KEY (delivery_boy_id)
(references auth.users (id
;TABLESPACE pg_default (

create index IF not exists idx_performance_stats_delivery_boy on
;public.delivery_performance_stats using btree (delivery_boy_id) TABLESPACE pg_default

) create table public.delivery_ratings
,() id uuid not null default gen_random_uuid
,delivery_id uuid null
,order_id uuid not null
,customer_id uuid not null
,rating integer null
,comment text null
,()created_at timestamp with time zone null default now
,(constraint delivery_ratings_pkey primary key (id
constraint delivery_ratings_delivery_id_fkey foreign KEY (delivery_id) references
,(new_profiles_delivery (id
) constraint delivery_ratings_rating_check check
)
(rating >= 1)
(and (rating <= 5
(
(
;TABLESPACE pg_default (

create index IF not exists idx_delivery_ratings_delivery_id on public.delivery_ratings using
;btree (delivery_id) TABLESPACE pg_default

) create table public.delivery_status_history
,() id uuid not null default extensions.uuid_generate_v4
,delivery_order_id uuid null
,status public.delivery_status_enum not null
,notes text null
,created_at timestamp with time zone null default CURRENT_TIMESTAMP
,(constraint delivery_status_history_pkey primary key (id
constraint delivery_status_history_delivery_order_id_fkey foreign KEY (delivery_order_id)
(references delivery_orders (id
;TABLESPACE pg_default (

) create table public.delivery_vehicles
,() id uuid not null default gen_random_uuid
,registration_number text not null
,vehicle_type public.vehicle_type not null
,capacity numeric(10, 2) null
,fuel_efficiency numeric(5, 2) null
```

```
,maintenance_status text null
,last_maintenance_date timestamp with time zone null
,next_maintenance_date timestamp with time zone null
,assigned_agent_id uuid null
,status text null default 'available'::text
,location geometry null
,created_at timestamp with time zone null default CURRENT_TIMESTAMP
,updated_at timestamp with time zone null default CURRENT_TIMESTAMP
,(constraint delivery_vehicles_pkey primary key (id
,(constraint delivery_vehicles_registration_number_key unique (registration_number
constraint delivery_vehicles_assigned_agent_id_fkey foreign KEY (assigned_agent_id)
(references delivery_boys (id
;TABLESPACE pg_default (

create index IF not exists idx_delivery_vehicles_agent on public.delivery_vehicles using
;btree (assigned_agent_id) TABLESPACE pg_default

create index IF not exists idx_delivery_vehicles_location on public.delivery_vehicles using
;gist (location) TABLESPACE pg_default

) create table public.delivery_zones
,() id uuid not null default gen_random_uuid
,delivery_id uuid null
,zone_name character varying(100) not null
,is_active boolean null default true
,()created_at timestamp with time zone null default now
,(constraint delivery_zones_pkey primary key (id
constraint delivery_zones_delivery_id_fkey foreign KEY (delivery_id) references
(new_profiles_delivery (id
;TABLESPACE pg_default (

) create table public.geographic_zones
,() id uuid not null default gen_random_uuid
,name text not null
,area_polygon geometry null
,center_point geometry null
,population_density numeric(10, 2) null
,waste_generation_rate numeric(10, 2) null
,agent_coverage integer null default 0
,active_status boolean null default true
,created_at timestamp with time zone null default CURRENT_TIMESTAMP
,updated_at timestamp with time zone null default CURRENT_TIMESTAMP
(constraint geographic_zones_pkey primary key (id
;TABLESPACE pg_default (

create index IF not exists idx_geographic_zones_area on public.geographic_zones using
;gist (area_polygon) TABLESPACE pg_default
) create table public.invoice_details
```

```
,() id uuid not null default extensions.uuid_generate_v4
,customer_order_id uuid not null
,product_name character varying(255) not null
,expected_quantity numeric(10, 2) not null
,actual_quantity numeric(10, 2) null
,unit_price numeric(10, 2) not null
expected_total numeric GENERATED ALWAYS as ((expected_quantity * unit_price))
,STORED (10, 2) null
) actual_total numeric GENERATED ALWAYS as
)
COALESCE(actual_quantity, expected_quantity) * unit_price
(
,STORED (10, 2) null (
,points numeric(10, 2) null default 0
,is_verified boolean null default false
,created_at timestamp with time zone null default CURRENT_TIMESTAMP
,updated_at timestamp with time zone null default CURRENT_TIMESTAMP
,(constraint invoice_details_pkey primary key (id
constraint invoice_details_customer_order_id_fkey foreign KEY (customer_order_id)
references customer_orders (id) on delete CASCADE
;TABLESPACE pg_default (

create index IF not exists idx_invoice_details_customer_order on public.invoice_details
;using btree (customer_order_id) TABLESPACE pg_default

create trigger trigger_update_invoice_details_id
after INSERT on invoice_details for EACH row
;() execute FUNCTION update_invoice_details_id

create trigger update_customer_totals
after INSERT
or
update on invoice_details for EACH row
;() execute FUNCTION update_customer_order_totals

create trigger update_invoice_details_timestamp BEFORE
update on invoice_details for EACH row
;() execute FUNCTION update_customer_timestamp

) create table public.new_profiles
,id uuid not null
,full_name text not null
,phone_number text not null
,email text null
,avatar_url text null
,preferred_language text null default 'ar'::text
,bio text null
,date_of_birth date null
```

```
,gender text null
,notification_preferences jsonb null default '{}'::jsonb
,social_links jsonb null default '{}'::jsonb
,statistics jsonb null default '{}'::jsonb
,points integer null default 0
,status public.profile_status_enum null default 'pending'::profile_status_enum
,isaddresscomplete boolean null default false
,created_at timestamp with time zone null default CURRENT_TIMESTAMP
,updated_at timestamp with time zone null default CURRENT_TIMESTAMP
,addresses jsonb null
,phone_numbers jsonb null
,profile_status public.profile_status_enum null default 'pending'::profile_status_enum
,default_address_id uuid null
,(constraint new_profiles_pkey primary key (id
,(constraint unique_phone_number unique (phone_number
constraint new_profiles_default_address_id_fkey foreign KEY (default_address_id)
,references customer_addresses (id) on delete set null
constraint new_profiles_id_fkey foreign KEY (id) references customers (id) on delete
CASCADE
;TABLESPACE pg_default (

create trigger create_default_address_trigger
after INSERT on new_profiles for EACH row
;() execute FUNCTION create_default_address

create trigger sync_phone_trigger
after INSERT
or
update OF phone_number on new_profiles for EACH row
;() execute FUNCTION sync_phone_to_customer_phones

) create table public.new_profiles_delivery
,id uuid not null
,phone character varying(20) not null
,email character varying(255) null
,full_name character varying(255) not null
,national_id character varying(20) not null
,preferred_vehicle public.vehicle_type not null
,license_number character varying(50) null
,delivery_code character varying(50) null
,delivery_code_status public.verification_status null default 'pending'::verification_status
,delivery_code_expires_at timestamp with time zone null
,delivery_code_attempts integer null default 0
,total_deliveries integer null default 0
,total_earnings numeric(10, 2) null default 0.00
,rating numeric(3, 2) null default 0.00
,is_available boolean null default true
,avatar_url text null
```

```
,preferred_language character varying(10) null default 'ar'::character varying
,referral_code character varying(50) null
,()created_at timestamp with time zone null default now
,()updated_at timestamp with time zone null default now
,last_login timestamp with time zone null
,phone_verification_code character varying(10) null
phone_verification_status public.verification_status null default
,'pending'::verification_status
,phone_verification_expires_at timestamp with time zone null
,phone_verification_attempts integer null default 0
,status public.delivery_boy_status null
,(constraint new_profiles_delivery_pkey primary key (id
,(constraint new_profiles_delivery_national_id_key unique (national_id
(constraint new_profiles_delivery_id_fkey foreign KEY (id) references auth.users (id
;TABLESPACE pg_default (

create index IF not exists idx_delivery_phone on public.new_profiles_delivery using btree
;(phone) TABLESPACE pg_default

create index IF not exists idx_delivery_rating on public.new_profiles_delivery using btree
;(rating) TABLESPACE pg_default

) create table public.onboarding_data
,id serial not null
,title text not null
,body text not null
,image_url text not null
,(()created_at timestamp with time zone not null default timezone ('utc'::text, now
,(constraint onboarding_data_pkey primary key (id
,((constraint check_body_not_empty check ((char_length(body) > 0
,((constraint check_image_url_not_empty check ((char_length(image_url) > 0
((constraint check_title_not_empty check ((char_length(title) > 0
;TABLESPACE pg_default (
) create table public.order_details
,() id uuid not null default gen_random_uuid
,order_id uuid null
,product_name text not null
,quantity numeric not null
,price numeric not null
,earned_points numeric null default 0
,notes text null
,()created_at timestamp with time zone not null default now
,()updated_at timestamp with time zone not null default now
,delivery_order_id uuid null
,category_name text null
,subcategory_name text null
,(constraint order_details_pkey primary key (id
```

```
constraint fk_order_details_customer foreign KEY (order_id) references customer_orders
,(id) on delete CASCADE
constraint fk_order_details_delivery foreign KEY (delivery_order_id) references
delivery_orders (id) on delete CASCADE
;TABLESPACE pg_default (

create index IF not exists idx_order_details_delivery_order_id on public.order_details using
;btree (delivery_order_id) TABLESPACE pg_default

create index IF not exists order_details_order_id_idx on public.order_details using btree
;(order_id) TABLESPACE pg_default

create index IF not exists idx_order_details_category_name on public.order_details using
;btree (category_name) TABLESPACE pg_default

create index IF not exists idx_order_details_subcategory_name on public.order_details
;using btree (subcategory_name) TABLESPACE pg_default

create trigger set_updated_at BEFORE
update on order_details for EACH row
;() execute FUNCTION set_updated_at

) create table public.order_schedule
,() id uuid not null default extensions.uuid_generate_v4
,order_id uuid not null
,scheduled_pickup_time timestamp with time zone not null
,scheduled_delivery_time timestamp with time zone null
,actual_pickup_time timestamp with time zone null
,actual_delivery_time timestamp with time zone null
,notes text null
,status public.schedule_status null default 'scheduled'::schedule_status
,customer_notified boolean null default false
,pickup_reminder_sent boolean null default false
,delivery_reminder_sent boolean null default false
,()created_at timestamp with time zone null default now
,()updated_at timestamp with time zone null default now
,metadata jsonb null
,(constraint order_schedule_pkey primary key (id
constraint order_schedule_order_id_fkey foreign KEY (order_id) references delivery_orders
(id) on delete CASCADE
;TABLESPACE pg_default (

create index IF not exists idx_order_schedule_order_id on public.order_schedule using btree
;(order_id) TABLESPACE pg_default

create index IF not exists idx_order_schedule_pickup_time on public.order_schedule using
;btree (scheduled_pickup_time) TABLESPACE pg_default
```

```
create index IF not exists idx_order_schedule_delivery_time on public.order_schedule using
;btree (scheduled_delivery_time) TABLESPACE pg_default

create index IF not exists idx_order_schedule_status on public.order_schedule using btree
;(status) TABLESPACE pg_default

) create table public.order_tracking
,() id uuid not null default extensions.uuid_generate_v4
,order_id uuid not null
,delivery_boy_id uuid not null
,latitude double precision not null
,longitude double precision not null
,speed double precision null
,heading double precision null
,()timestamp timestamp with time zone null default now
,status public.delivery_boy_online_status null
,active_status public.delivery_boy_status null default 'inactive'::delivery_boy_status
,available_for_orders boolean null default false
,(constraint order_tracking_pkey primary key (id
constraint order_tracking_delivery_boy_id_fkey foreign KEY (delivery_boy_id) references
,delivery_boys (id) on delete CASCADE
constraint order_tracking_order_id_fkey foreign KEY (order_id) references delivery_orders
,(id) on delete CASCADE
) constraint valid_latitude check
)
(latitude >= ('-90'::integer)::double precision)
(and (latitude <= (90)::double precision
(
,(
) constraint valid_longitude check
)
(longitude >= ('-180'::integer)::double precision)
(and (longitude <= (180)::double precision
(
(
;TABLESPACE pg_default (

create index IF not exists idx_order_tracking_order_id on public.order_tracking using btree
;(order_id) TABLESPACE pg_default

create index IF not exists idx_order_tracking_delivery_boy_id on public.order_tracking using
;btree (delivery_boy_id) TABLESPACE pg_default

create index IF not exists idx_order_tracking_timestamp on public.order_tracking using btree
;("timestamp") TABLESPACE pg_default

create index IF not exists idx_order_tracking_active_status on public.order_tracking using
;btree (active_status) TABLESPACE pg_default
```

```
create index IF not exists idx_order_tracking_available_for_orders on public.order_tracking
;using btree (available_for_orders) TABLESPACE pg_default

) create table public.payment_qr_codes
,() id uuid not null default gen_random_uuid
,creator_id uuid not null
,recipient_id uuid not null
,amount numeric(10, 2) not null
,currency character varying(3) not null default 'EGP'::character varying
,status public.transaction_status not null default 'pending'::transaction_status
,expires_at timestamp with time zone not null
,verification_code character varying(6) null
,transaction_id uuid null
,order_id uuid null
,metadata jsonb null
,()created_at timestamp with time zone not null default now
,()updated_at timestamp with time zone not null default now
,(constraint payment_qr_codes_pkey primary key (id
constraint payment_qr_codes_creator_id_fkey foreign KEY (creator_id) references
,(auth.users (id
constraint payment_qr_codes_recipient_id_fkey foreign KEY (recipient_id) references
(auth.users (id
;TABLESPACE pg_default (
) create table public.payment_settlements
,id serial not null
,representative_id uuid not null
,amount_settled numeric not null
,settlement_date timestamp with time zone null default CURRENT_TIMESTAMP
,created_at timestamp with time zone null default CURRENT_TIMESTAMP
,updated_at timestamp with time zone null default CURRENT_TIMESTAMP
(constraint payment_settlements_pkey primary key (id
;TABLESPACE pg_default (
) create table public.subcategories
,() id uuid not null default gen_random_uuid
,name text not null
,category_id uuid null
,description text null
,image_url text null
,()created_at timestamp with time zone null default now
,()updated_at timestamp with time zone null default now
,price double precision null default 0
,points_per_kg integer null default 0
,(constraint subcategories_pkey primary key (id
constraint subcategories_category_id_fkey foreign KEY (category_id) references
categories (id) on delete CASCADE
;TABLESPACE pg_default (
) create table public.system_notifications
```

```
,() id uuid not null default gen_random_uuid
,type text not null
,title text not null
,message text not null
,target_role text null
,target_user_id uuid null
,is_read boolean null default false
,expires_at timestamp with time zone null
,created_at timestamp with time zone null default CURRENT_TIMESTAMP
,(constraint system_notifications_pkey primary key (id
constraint system_notifications_target_user_id_fkey foreign KEY (target_user_id)
(references auth.users (id
;TABLESPACE pg_default (

create index IF not exists idx_system_notifications_user on public.system_notifications using
;btree (target_user_id) TABLESPACE pg_default

create index IF not exists idx_system_notifications_is_read on public.system_notifications
;using btree (is_read) TABLESPACE pg_default

create trigger check_notification_updates BEFORE
update on system_notifications for EACH row
;() execute FUNCTION check_notification_update
create view public.tracking_points_with_details as
select
,t.id
,t.order_id
,t.delivery_boy_id
,t.latitude
,t.longitude
,t.speed
,t.heading
,"t."timestamp
,o.customer_order_id
,o.customer_name
,o.customer_phone
,o.status as order_status
,o.pickup_location
,o.delivery_location
,o.estimated_distance
,o.estimated_time
,o.order_number
,db.full_name as delivery_boy_name
db.phone as delivery_boy_phone
from
order_tracking t
join delivery_orders o on t.order_id = o.id
join delivery_boys db on t.delivery_boy_id = db.id
```

```
order by
;t."timestamp" desc
) create table public.vehicle_maintenance_log
,() id uuid not null default gen_random_uuid
,vehicle_id uuid null
,maintenance_type text not null
,description text null
,cost numeric(10, 2) null
,performed_by text null
,performed_at timestamp with time zone not null
,notes text null
,next_maintenance_date timestamp with time zone null
,created_at timestamp with time zone null default CURRENT_TIMESTAMP
,(constraint vehicle_maintenance_log_pkey primary key (id
constraint vehicle_maintenance_log_vehicle_id_fkey foreign KEY (vehicle_id) references
delivery_vehicles (id) on delete CASCADE
;TABLESPACE pg_default (

create index IF not exists idx_vehicle_maintenance_vehicle on
;public.vehicle_maintenance_log using btree (vehicle_id) TABLESPACE pg_default

) create table public.wallet_transactions
,() id uuid not null default gen_random_uuid
,wallet_id uuid not null
,transaction_type public.transaction_type not null
,amount numeric(10, 2) not null
,status public.transaction_status not null default 'pending'::transaction_status
,qr_code_id uuid null
,reference_id character varying(255) null
,description text null
,metadata jsonb null
,()created_at timestamp with time zone not null default now
,()updated_at timestamp with time zone not null default now
,(constraint wallet_transactions_pkey primary key (id
constraint wallet_transactions_qr_code_id_fkey foreign KEY (qr_code_id) references
,(payment_qr_codes (id
(constraint wallet_transactions_wallet_id_fkey foreign KEY (wallet_id) references wallets (id
;TABLESPACE pg_default (

) create table public.wallets
,() id uuid not null default gen_random_uuid
,user_id uuid not null
,balance numeric(10, 2) not null default 0.00
,currency character varying(3) not null default 'EGP'::character varying
,is_active boolean not null default true
,()created_at timestamp with time zone not null default now
,()updated_at timestamp with time zone not null default now
,(constraint wallets_pkey primary key (id
```

(constraint wallets_user_id_fkey foreign KEY (user_id) references auth.users (id
;TABLESPACE pg_default (
) create table public.waste_collection_items
,() id uuid not null default gen_random_uuid
,session_id uuid not null
,waste_data_id uuid not null
,category_id uuid not null
,subcategory_id uuid null
,name character varying(255) not null
,actual_weight numeric(10, 3) not null
,unit_price numeric(10, 2) not null
,total_price numeric(10, 2) not null
,earned_points numeric(10, 2) null default 0
,measurement_photo_url text null
,()created_at timestamp with time zone not null default now
,()updated_at timestamp with time zone not null default now
,(constraint waste_collection_items_pkey primary key (id
constraint waste_collection_items_category_id_fkey foreign KEY (category_id) references
,(categories (id
constraint waste_collection_items_session_id_fkey foreign KEY (session_id) references
,waste_collection_sessions (id) on delete CASCADE
constraint waste_collection_items_waste_data_id_fkey foreign KEY (waste_data_id)
(references waste_data_admin (id
;TABLESPACE pg_default (
) create table public.waste_collection_sessions
,() id uuid not null default gen_random_uuid
,delivery_order_id uuid not null
,delivery_boy_id uuid not null
,customer_id uuid not null
,status character varying(20) not null default 'pending'::character varying
,total_weight numeric(10, 2) null default 0
,total_amount numeric(10, 2) null default 0
,total_points numeric(10, 2) null default 0
,started_at timestamp with time zone null
,completed_at timestamp with time zone null
,location_lat double precision null
,location_lng double precision null
,payment_method character varying(20) null
,payment_status character varying(20) null default 'pending'::character varying
,signature_url text null
,()created_at timestamp with time zone not null default now
,()updated_at timestamp with time zone not null default now
customer_approval_status public.customer_approval_status_enum null default
,'pending'::customer_approval_status_enum
,customer_approval_timestamp timestamp without time zone null
,customer_comment text null
,collection_efficiency numeric(5, 2) null
,collection_notes text null

```
,quality_score integer null
,photos jsonb null
,(constraint waste_collection_sessions_pkey primary key (id
constraint waste_collection_sessions_delivery_order_id_fkey foreign KEY
(delivery_order_id) references delivery_orders (id) on delete CASCADE
;TABLESPACE pg_default (
) create table public.waste_data_admin
,() id uuid not null default gen_random_uuid
,category_id uuid null
,name text not null
,description text null
,image_url text null
,weight double precision not null
,price double precision not null
,quantity integer not null
,points integer not null
,initial_points integer not null
,()created_at timestamp with time zone null default now
,()updated_at timestamp with time zone null default now
,subcategory_id uuid null
,(constraint waste_data_admin_pkey primary key (id
constraint waste_data_admin_category_id_fkey foreign KEY (category_id) references
,(categories (id
constraint waste_data_admin_subcategory_id_fkey foreign KEY (subcategory_id)
(references subcategories (id
;TABLESPACE pg_default (

) create table public.waste_invoices
,() id uuid not null default gen_random_uuid
,session_id uuid not null
,invoice_number character varying(50) not null
,subtotal numeric(10, 2) not null
,tax numeric(10, 2) null default 0
,total numeric(10, 2) not null
,status character varying(20) not null default 'issued'::character varying
,qr_code_url text null
,offline_code character varying(8) null
,()created_at timestamp with time zone not null default now
,()updated_at timestamp with time zone not null default now
,created_by uuid null
,order_id uuid null
customer_approval_status public.customer_approval_status_enum null default
,'pending'::customer_approval_status_enum
,customer_approval_timestamp timestamp without time zone null
,customer_comment text null
,items jsonb null
,(constraint waste_invoices_pkey primary key (id
```

```
constraint waste_invoices_session_id_fkey foreign KEY (session_id) references
waste_collection_sessions (id) on delete CASCADE
;TABLESPACE pg_default (

) create table public.waste_recycling
,id bigint generated always as identity not null
,name text not null
,image_url text not null
,weight double precision not null
,price double precision not null
,quantity integer null default 1
,points integer not null
,()created_at timestamp with time zone null default now
,()updated_at timestamp with time zone null default now
(constraint waste_recycling_pkey primary key (id
;TABLESPACE pg_default (
) create table public.waste_weights
,() id uuid not null default extensions.uuid_generate_v4
,order_id uuid not null
,waste_type public.waste_type not null
,weight numeric(10, 2) not null
,price_per_kg numeric(10, 2) not null
,(()created_at timestamp with time zone not null default timezone ('utc'::text, now
,(constraint waste_weights_pkey primary key (id
(constraint waste_weights_order_id_waste_type_key unique (order_id, waste_type
;TABLESPACE pg_default (
```

ثانيا الدوال

no	Name	Arguments	Return type	Security	Definition	nots
1	add_new_address	p_customer_id uuid, p_latitude double precision, p_longitude double precision, p_address_line text, p_city text DEFAULT NULL::text, p_area text DEFAULT NULL::text, p_building_number text DEFAULT NULL::text, p_floor_number text DEFAULT NULL::text, p_apartment_number text DEFAULT NULL::text, p_landmark text DEFAULT NULL::text, p_address_type address_type_enum DEFAULT 'home'::address_type_enum, p_is_default boolean DEFAULT false	uuid	Invoker	DECLARE ;v_address_id UUID BEGIN -- تحويل الإحداثيات إلى نقطة PostGIS) INSERT INTO customer_addresses ,customer_id ,geom ,address_line ,city ,area ,building_number ,floor_number ,apartment_number	

no	Name	Arguments	Return type	Security	Definition	nots
					,landmark ,address_type is_default) VALUES (,p_customer_id ,(ST_SetSRID(ST_MakePoint(p_longitude, p_latitude), 4326 ,p_address_line ,p_city ,p_area ,p_building_number ,p_floor_number ,p_apartment_number ,p_landmark ,p_address_type p_is_default (;RETURNING id INTO v_address_id ;RETURN v_address_id ;END	
2	calculate_customer_waiting_time	-	trigger	Invoker	BEGIN IF NEW.status = 'completed' AND NEW.actual_delivery_time IS NOT NULL AND NEW.created_at IS NOT NULL THEN NEW.customer_waiting_time := EXTRACT(EPOCH FROM (NEW.actual_delivery_time - ;NEW.created_at))/60 ;END IF ;RETURN NEW ;END	
3	calculate_delivery_stats	p_order_id uuid	TABLE(total_distance_km double precision, duration_minutes integer, avg_speed_kmh double (precision	Invoker	(CREATE OR REPLACE FUNCTION get_order_tracking_summary(p_order_id UUID) RETURNS TABLE ,total_distance_km DOUBLE PRECISION ,duration_minutes INTEGER avg_speed_kmh DOUBLE PRECISION $$ AS (BEGIN RETURN QUERY) WITH tracking_points AS SELECT ,location ,timestamp speed FROM order_tracking WHERE order_id = p_order_id ORDER BY	

no	Name	Arguments	Return type	Security	Definition	nots
					timestamp ASC ,( ) distance_calc AS SELECT)SUM)ST_Distance ,(LAG(location) OVER (ORDER BY timestamp ,location TRUE) / 1000 -- تحويل من متر إلى كيلومتر ,AS total_distance_km (EXTRACT(EPOCH FROM (MAX(timestamp) - MIN(timestamp))) / 60 AS ,duration_minutes AVG(speed) AS avg_speed_kmh FROM tracking_points (SELECT ,total_distance_km ,duration_minutes::INTEGER avg_speed_kmh FROM ;distance_calc ;END ;LANGUAGE plpgsql $$	
4	calculate_distance	at1 double precision, lon1 do	double precision	Invoker	DECLARE R DOUBLE PRECISION := 6371; -- Radius of the Earth in kilometers ;dLat DOUBLE PRECISION ;dLon DOUBLE PRECISION ;a DOUBLE PRECISION ;c DOUBLE PRECISION ;d DOUBLE PRECISION BEGIN Convert degrees to radians -- ;(dLat := radians(lat2 - lat1 ;(dLon := radians(lon2 - lon1 Haversine formula to calculate the distance on a spherical surface -- + (a := sin(dLat / 2) * sin(dLat / 2 * ((cos(radians(lat1)) * cos(radians(lat2 ;(sin(dLon / 2) * sin(dLon / 2 ;((c := 2 * asin(sqrt(a d := R * c; -- Distance in kilometers ;RETURN d ;END	

no	Name	Arguments	Return type	Security	Definition	nots

5	check_customer_type		trigger	Invoker	BEGIN
					) IF EXISTS
					SELECT 1 FROM auth.users
					WHERE id = NEW.id
					'AND raw_user_meta_data->>'user_type' != 'customer
					THEN (
					RAISE EXCEPTION 'غير مسموح: هذا المستخدم ليس من نوع عميل';
					END IF;
					RETURN NEW;
					END;	

6	check_delivery_boy_type		trigger	Invoker	BEGIN
					) IF EXISTS
					SELECT 1 FROM auth.users
					WHERE id = NEW.id
					'AND raw_user_meta_data->>'user_type' != 'delivery_boy
					THEN (
					RAISE EXCEPTION 'غير مسموح: هذا المستخدم ليس من نوع سائق';
					END IF;
					RETURN NEW;
					END;	

7	check_notification_update		trigger	Invoker	BEGIN
					-- التأكد من أن التحديث يغير فقط حقل is_read من FALSE إلى TRUE
					IF TG_OP = 'UPDATE' THEN
					IF OLD.is_read = FALSE AND NEW.is_read = TRUE AND
					NEW.id = OLD.id AND
					NEW.type = OLD.type AND
					NEW.title = OLD.title AND
					NEW.message = OLD.message AND
					NEW.target_role = OLD.target_role AND
					NEW.target_user_id = OLD.target_user_id AND
					NEW.expires_at = OLD.expires_at AND
					NEW.created_at = OLD.created_at THEN
					RETURN NEW;
					ELSE
					RAISE EXCEPTION 'غير مسموح بتغيير حقول أخرى غير is_read';
					END IF;
					END IF;
					
					RETURN NULL;
					END;	

8	check_trigger_execution	user_id uuid	jsonb	Definer	DECLARE result jsonb;	

no	Name	Arguments	Return type	Security	Definition	nots
					BEGIN)SELECT jsonb_build_object) customers_exists', EXISTS' SELECT 1 FROM customers WHERE id = user_id ,( ) new_profiles_exists', EXISTS' SELECT 1 FROM new_profiles WHERE id = user_id ,( ) auth_user_exists', EXISTS' SELECT 1 FROM auth.users WHERE id = user_id ,( ) ,'user_metadata' SELECT raw_user_meta_data FROM auth.users WHERE id = user_id (;INTO result (;RETURN result ;END	
9	complete_order	order_id uuid, notes text DEFAULT ''::text	jsonb	Definer	DECLARE ;result JSONB current_timestamp_var TIMESTAMP; -- Renamed variable BEGIN -- الحصول على الوقت الحالي ;()current_timestamp_var := NOW -- تحديث الطلب إلى "completed" UPDATE delivery_orders SET ,'status = 'completed ,actual_delivery_time = current_timestamp_var ,updated_at = current_timestamp_var notes = CASE WHEN notes <> '' THEN notes ELSE delivery_orders.notes END WHERE id = order_id RETURNING to_jsonb(*) INTO result; -- Corrected this line -- إضافة سجل في تاريخ الحالات -- يمكن أيضًا إضافة هذه الخطوة إذا كنت تريد أن تتم معالجتها ضمن نفس الوظيفة (INSERT INTO delivery_status_history (delivery_order_id, status, notes, created_at -- ;(VALUES (order_id, 'completed', notes, current_timestamp_var -- ;RETURN result ;END	
10	create_customer_profile		trigger	Definer	BEGIN -- إنشاء سجل في جدول customers	

no	Name	Arguments	Return type	Security	Definition	nots
					) INSERT INTO public.customers ,id ,phone_number ,full_name ,customer_status referral_code) VALUES (,NEW.id ,NEW.raw_user_meta_data->>'phone_number')::text) ,NEW.raw_user_meta_data->>'full_name')::text) ,'active' NEW.raw_user_meta_data->>'referral_code')::text) ;(-- إنشاء سجل في جدول new_profiles) INSERT INTO public.new_profiles ,id ,phone_number ,full_name status) VALUES (,NEW.id ,NEW.raw_user_meta_data->>'phone_number')::text) ,NEW.raw_user_meta_data->>'full_name')::text) 'active' ;(;RETURN NEW EXCEPTION WHEN OTHERS THEN ;RAISE NOTICE 'Error in create_customer_profile: % %', SQLERRM, SQLSTATE ;RETURN NEW ;END	
11	create_default_address		trigger	Definer	DECLARE ;default_latitude FLOAT := 31.2001 -- الإسكندرية ;default_longitude FLOAT := 29.9187 BEGIN -- تسجيل بداية تنفيذ الوظيفة ;RAISE NOTICE 'Starting create_default_address for profile_id: %', NEW.id -- إدخال عنوان افتراضي في جدول customer_addresses) INSERT INTO public.customer_addresses ,profile_id ,address_type ,address_line ,city ,area ,building_number ,floor_number	

no	Name	Arguments	Return type	Security	Definition	nots
					,apartment_number ,additional_directions ,landmark ,latitude ,longitude ,is_default ,is_verified ,created_at updated_at) VALUES (,NEW.id ,'home' 'عنوان افتراضي', 'الاسكندرية', '' ,'' ,'' ,'' ,'' ,'' ,'' ,default_latitude ,default_longitude ,true ,false ,()NOW ()NOW); -- تسجيل نجاح العملية ;RAISE NOTICE 'Successfully created default address for profile_id: %', NEW.id ;RETURN NEW EXCEPTION WHEN OTHERS THEN -- تسجيل الخطأ بالتفصيل RAISE NOTICE 'Error in create_default_address for profile_id %: % %', NEW.id, ;SQLERRM, SQLSTATE ;RETURN NEW ;END	
12	create_delivery_order		trigger	Invoker	DECLARE ;new_delivery_order_id UUID ;new_order_number VARCHAR ;order_item JSONB ;delivery_status public.delivery_status_enum ;customer_profile RECORD -- متغير لتخزين بيانات ملف تعريف العميل BEGIN ;RAISE NOTICE 'Entering create_delivery_order trigger. NEW.status: %', NEW.status -- إنشاء رقم طلب فريد	

no	Name	Arguments	Return type	Security	Definition	nots

					SELECT 'DO-' || TO_CHAR(CURRENT_TIMESTAMP, 'YYYYMMDDHH24MISS') || '-' || (SUBSTRING(MD5(RANDOM()::TEXT), 1, 4
					;INTO new_order_number
					
					-- معالجة قيمة الحالة (status) بشكل أكثر تسامحًا ووضوحًا
					IF NEW.status IS NULL THEN
					;delivery_status := 'pending'::public.delivery_status_enum
					;'."RAISE NOTICE 'Status in customer_orders is NULL. Defaulting to "pending
					ELSEIF lower(NEW.status::text) = 'cancelled' OR lower(NEW.status::text) = 'canceled'
					THEN -- معالجة كلا التهجئتين
					;delivery_status := 'cancelled'::public.delivery_status_enum
					RAISE NOTICE 'Status in customer_orders is "%" or "canceled". Mapping to
					;"cancelled".', NEW.status
					ELSE
					BEGIN
					;delivery_status := NEW.status::public.delivery_status_enum -- محاولة التحويل المباشر
					RAISE NOTICE 'Status in customer_orders is "%". Direct cast successful.',
					;NEW.status
					EXCEPTION WHEN OTHERS THEN
					;delivery_status := 'pending'::public.delivery_status_enum -- القيمة الافتراضية في حالة الخطأ
					RAISE NOTICE 'Invalid status value "%" in customer_orders. Defaulting to
					;"pending". Error: %', NEW.status, SQLERRM
					;END
					;END IF
					;RAISE NOTICE 'Effective delivery_status after processing: %', delivery_status
					
					-- استرجاع اسم ورقم هاتف العميل بكفاءة في استعلام واحد
					SELECT full_name, phone_number
					INTO customer_profile
					FROM new_profiles
					;WHERE id = NEW.customer_id
					
					IF customer_profile IS NULL THEN
					RAISE WARNING 'Customer profile not found for customer_id: %',
					;NEW.customer_id
					-- يمكنك اختيار معالجة هذا الموقف بشكل مختلف، مثل إيقاف العملية أو استخدام قيم افتراضية
					-- هنا سنستخدم قيم افتراضية فارغة لتجنب فشل الإدخال
					;END IF
					
					-- إنشاء طلب جديد في جدول delivery_orders
					BEGIN
					) INSERT INTO delivery_orders
					,customer_order_id
					,order_number
					,status
					,pickup_location
					,pickup_address
					,customer_name
					,customer_phone	

no	Name	Arguments	Return type	Security	Definition	nots
					expected_total_amount, category_name, subcategory_name, priority, delivery_location -- تعيين delivery_location هنا مباشرة ( ) VALUES NEW.id, new_order_number, delivery_status, NEW.pickup_location, NEW.pickup_address, customer_profile.full_name, -- استخدام البيانات من customer_profile (أو NULL إذا لم يتم العثور على الملف الشخصي) customer_profile.phone_number, -- استخدام البيانات من customer_profile (أو NULL إذا لم يتم العثور على الملف الشخصي) NEW.expected_total, NEW.category_name, NEW.subcategory_name, ('COALESCE(NEW.priority, 'normal'), NEW.pickup_location -- تعيين delivery_location هنا مباشرة) RETURNING id INTO new_delivery_order_id; RAISE NOTICE 'Successfully inserted into delivery_orders with id: %', new_delivery_order_id; -- إضافة سجلات تفاصيل الطلب من الـ JSON إلى جدول order_details IF new_delivery_order_id IS NOT NULL AND NEW.order_details IS NOT NULL AND jsonb_typeof(NEW.order_details) = 'array' THEN (FOR order_item IN SELECT * FROM jsonb_array_elements(NEW.order_details LOOP) INSERT INTO order_details order_id, delivery_order_id, product_name, quantity, price, notes, category_name, subcategory_name ( ) VALUES NEW.id, new_delivery_order_id, 'order_item->>'product_name, (order_item->>'quantity')::numeric, (order_item->>'price')::numeric, 'order_item->>'notes, NEW.category_name, NEW.subcategory_name);	

no	Name	Arguments	Return type	Security	Definition	nots
					;END LOOP RAISE NOTICE 'Successfully inserted order details for delivery_order_id: %', ;new_delivery_order_id ;END IF EXCEPTION WHEN OTHERS THEN RAISE NOTICE 'Error during INSERT into delivery_orders or order_details for ;customer_order_id %: %, SQLSTATE: %", NEW.id, SQLERRM, SQLSTATE ;RAISE EXCEPTION 'Failed to create delivery order and details: %', SQLERRM ;END ;RETURN NEW ;END	
13	create_new_profile_on_customer_insert		trigger	Invoker	BEGIN Insert a new record into new_profiles when a new customer is created --) INSERT INTO new_profiles ,id ,full_name ,phone_number ,preferred_language ,created_at updated_at) VALUES (NEW.id, -- Use the same ID as the customer NEW.full_name, -- Use the full name from customers table NEW.phone_number, -- Use the phone number from customers table NEW.preferred_language, -- Use the preferred language from customers table NEW.created_at, -- Use the creation timestamp from customers table NEW.updated_at -- Use the update timestamp from customers table ;(;RETURN NEW ;END	
14	create_payment_qr	p_creator_id uuid, p_recipient_id	uuid	Invoker	DECLARE ;v_qr_id UUID ;(v_verification_code VARCHAR(6 BEGIN -- إنشاء كود تحقق عشوائي ;('v_verification_code := LPAD(FLOOR(RANDOM() * 1000000)::TEXT, 6, '0 -- إنشاء QR code جديد) INSERT INTO payment_qr_codes ,creator_id ,recipient_id ,amount ,verification_code	

no	Name	Arguments	Return type	Security	Definition	nots
					,order_id expires_at) VALUES (,p_creator_id ,p_recipient_id ,p_amount ,v_verification_code ,p_order_id 'NOW() + INTERVAL '30 minutes ;RETURNING id INTO v_qr_id (;RETURN v_qr_id ;END	
15	delete_user_completely	user_id_to_delete uuid	boolean	Definer	BEGIN -- حذف من جدول مندوبي التوصيل ;DELETE FROM delivery_boys WHERE id = user_id_to_delete -- حذف من جدول المصادقة ;DELETE FROM auth.users WHERE id = user_id_to_delete ;RETURN TRUE ;END	
16	direct_update_order_to_completed	order_id uuid, notes text DEFAULT NULL::text	boolean	Definer	DECLARE ;current_time TIMESTAMP ;result BOOLEAN := FALSE BEGIN -- تحديث الطلب مباشرة في جدول delivery_orders UPDATE delivery_orders SET ,status = 'completed'::delivery_status_enum ,actual_delivery_time = current_time ,updated_at = current_time (notes = COALESCE(notes, delivery_orders.notes ;WHERE id = order_id -- إضافة سجل في تاريخ الحالات -- هذه العملية آمنة وليس عليها قيود أمان عادة) INSERT INTO delivery_status_history ,delivery_order_id ,status ,notes created_at) VALUES (,order_id	

no	Name	Arguments	Return type	Security	Definition	nots
					,completed'::delivery_status_enum' ,notes current_time ;(;result := TRUE -- النتيجة تكون TRUE إذا نجحت العملية ;RETURN result EXCEPTION WHEN OTHERS THEN -- تسجيل الخطأ في سجل الخطأ (إذا كان هناك جدول لذلك) (INSERT INTO error_logs (error_message, function_name, created_at -- ;(()VALUES (SQLERRM, 'direct_update_order_to_completed', NOW -- ;RETURN FALSE ;END	
17	direct_update_order_to_completed	order_id integer, notes text DEFAULT NULL::text	boolean	Invoker	DECLARE ;time_now TIMESTAMP ;result BOOLEAN := FALSE BEGIN ;()time_now := NOW -- تحديث الطلب مباشرة في جدول delivery_orders UPDATE delivery_orders SET ,status = 'completed'::delivery_status_enum ,actual_delivery_time = time_now ,updated_at = time_now (notes = COALESCE(notes, delivery_orders.notes ;WHERE id = order_id -- إضافة سجل في تاريخ الحالات) INSERT INTO delivery_status_history ,delivery_order_id ,status ,notes created_at) VALUES (,order_id ,completed'::delivery_status_enum' ,notes time_now ;(;result := TRUE ;RETURN result EXCEPTION WHEN OTHERS THEN	

no	Name	Arguments	Return type	Security	Definition	nots
					-- تسجيل الخطأ في سجل الخطأ (إذا كان هناك جدول لذلك) (INSERT INTO error_logs (error_message, function_name, created_at -- ;(()VALUES (SQLERRM, 'direct_update_order_to_completed', NOW -- ;RETURN FALSE ;END	
18	find_addresses_within_radius	p_latitude double precision, p_longitude double precision, p_radius_meters integer	TABLE(address_id uuid, address_line text, distance_meters double precision, customer_id uuid)	Invoker	BEGIN RETURN QUERY SELECT ,a.id as address_id ,a.address_line)ST_Distance ,a.geom::geography ST_SetSRID(ST_MakePoint(p_longitude, p_latitude), 4326)::geography ,as distance_meters (a.customer_id FROM new_addresses a)WHERE ST_DWithin ,a.geom::geography ,ST_SetSRID(ST_MakePoint(p_longitude, p_latitude), 4326)::geography p_radius_meters (;ORDER BY distance_meters ;END	
19	find_delivery_boy_by_code	code_param text	SETOF delivery_boys	Definer	* SELECT FROM public.delivery_boys ;WHERE delivery_code = code_param	
20	find_nearby_customers	p_latitude double precision, p_l	TABLE(customer_id uuid, distance_meters double precision, address_type text, address_line text)	Invoker	BEGIN RETURN QUERY SELECT ,a.customer_id)ST_Distance ,a.geom::geography ST_SetSRID(ST_MakePoint(p_longitude, p_latitude), 4326)::geography ,as distance_meters (,a.address_type::TEXT a.address_line FROM new_addresses a)WHERE ST_DWithin ,a.geom::geography ,ST_SetSRID(ST_MakePoint(p_longitude, p_latitude), 4326)::geography p_radius_meters (	

no	Name	Arguments	Return type	Security	Definition	nots
					;ORDER BY distance_meters ;END	
21	find_online_inactive_delivery_boys		TABLE(id uuid, full_name text, phone text, online_status delivery_boy_online_status, status delivery_boy_status, is_available boolean, last_location_update timestamp with time zone, last_login timestamp with time zone)	Invoker	BEGIN RETURN QUERY SELECT db . id , db . full_name , db . phone , db . online_status , db . status , db . is_available , db . last_location_update , db . last_login	

no	Name	Arguments	Return type	Security	Definition	nots
					FROM delivery_boys db WHERE -- المندوبون المتصلون (online) لكن إما: -- 1. غير نشطين (inactive)، أو -- 2. نشطين (active) لكن غير متاحين لاستلام طلبات (is_available = false)) db . online_status = 'online' delivery_boy_online_status:: (AND) db . status = 'inactive' delivery_boy_status:: OR) db . status = 'active' delivery_boy_status:: AND	

no	Name	Arguments	Return type	Security	Definition	nots
					NOT db . is_available ((ORDER BY db . last_login DESC ; END ;	
22	generate_phone_verification_code	phone_param text	json	Definer	declare ;verification_code text ;result json begin -- توليد رمز تحقق عشوائي مكون من 6 أرقام ;verification_code := floor(random() * (999999 - 100000 + 1) + 100000)::text -- تحديث رمز التحقق في جدول delivery_boys update public.delivery_boys set ,phone_verification_code = verification_code ,'phone_verification_expires_at = now() + interval '10 minutes ,phone_verification_attempts = 0 ()updated_at = now ;where phone = phone_param -- إرجاع رمز التحقق كـ JSON)result := json_build_object verification_code', verification_code' ;(;return result ;end	
23	generate_verification_code	phone_param text	TABLE(verification_code text, expires_at	Invoker	DECLARE ;generated_code TEXT	

no	Name	Arguments	Return type	Security	Definition	nots

			timestamp with time zone, attempts_remaining integer)		customer_exists BOOLEAN;
					BEGIN
					-- التحقق من وجود العميل
					SELECT EXISTS(
					SELECT 1
					FROM customers
					WHERE phone_number = phone_param
					INTO customer_exists;
					
					IF NOT customer_exists THEN
					RAISE EXCEPTION 'Customer with phone number % not found', phone_param;
					END IF;
					
					-- توليد كود التحقق
					generated_code := LPAD(FLOOR(RANDOM() * 1000000)::TEXT, 6, '0');
					
					-- تحديث كود التحقق للعميل
					UPDATE customers
					SET
					phone_verification_code = generated_code,
					phone_verification_expires_at = NOW() + INTERVAL '10 minutes',
					phone_verification_attempts = COALESCE(phone_verification_attempts, 0) + 1
					WHERE phone_number = phone_param;
					
					-- إرجاع النتائج
					RETURN QUERY
					SELECT
					generated_code,
					NOW() + INTERVAL '10 minutes',
					(COALESCE(phone_verification_attempts, 0 - 5
					FROM customers
					WHERE phone_number = phone_param;
					END;	

24	get_delivery_boy_performance	p_delivery_boy_id uuid, p_start_date date, p_end_date date	TABLE(date date, orders_completed integer, orders_canceled integer, total_distance numeric, total_earnings numeric, waste_weight_collected numeric, average_rating numeric, online_hours numeric)	Invoker	BEGIN RETURN QUERY SELECT dp.date, dp.orders_completed, dp.orders_canceled, dp.total_distance, dp.total_earnings, dp.waste_weight_collected, dp.average_rating, dp.online_hours FROM public.delivery_boy_daily_performance dp WHERE dp.delivery_boy_id = p_delivery_boy_id AND dp.date BETWEEN p_start_date AND p_end_date	

no	Name	Arguments	Return type	Security	Definition	nots
					ORDER BY ;dp.date ;END	

25	get_effective_order_status	order_id uuid	text	Definer	DECLARE
					;db_status TEXT
					;history_status TEXT
					;history_timestamp TIMESTAMP
					;is_completed BOOLEAN := FALSE
					BEGIN
					Get the status from the orders table --
					SELECT status::TEXT INTO db_status
					FROM delivery_orders
					;WHERE id = order_id
					
					Check if there's a 'completed' status in history --
					SELECT dsh.status::TEXT, dsh.created_at INTO history_status, history_timestamp
					FROM delivery_status_history dsh
					WHERE dsh.delivery_order_id = order_id
					'AND dsh.status = 'completed
					ORDER BY dsh.created_at DESC
					;LIMIT 1
					
					If there's a completed status in history, we'll use that --
					IF history_status IS NOT NULL THEN
					;RETURN history_status
					ELSE
					;RETURN db_status
					;END IF
					;END	

26	get_invoice_by_id	p_invoice_id uuid	jsonb	Definer	DECLARE ;v_invoice JSONB BEGIN Get invoice with direct table access, bypassing RLS --)SELECT jsonb_build_object ,'id', id' ,'session_id', session_id' ,'invoice_number', invoice_number' ,'subtotal', subtotal' ,'total', total' ,'status', status' ,'created_at', created_at' ,'customer_approval_status', customer_approval_status' ,'customer_approval_timestamp', customer_approval_timestamp' ,'customer_comment', customer_comment' items', items -- Include actual UI data in response' INTO v_invoice (	

no	Name	Arguments	Return type	Security	Definition	nots
					FROM waste_invoices ;WHERE id = p_invoice_id Check if invoice exists -- IF v_invoice IS NULL THEN ;RAISE EXCEPTION 'Invoice with ID % not found', p_invoice_id ;END IF ;RETURN v_invoice EXCEPTION WHEN OTHERS THEN RAISE EXCEPTION 'Error getting invoice by ID: % (Invoice ID: %)', SQLERRM, ;p_invoice_id ;END	
27	get_invoice_by_session_id	p_session_id uuid	jsonb	Definer	DECLARE v_invoice JSONB ; BEGIN -- البحث عن الفاتورة بواسطة معرّف الجلسة SELECT jsonb_build_object) 'id' , id , 'invoice_number' , invoice_number , 'session_id' , session_id ,	

no	Name	Arguments	Return type	Security	Definition	nots
					'subtotal' , subtotal , 'tax' , tax , 'total' , total , 'status' , status , 'qr_code_url' , qr_code_url , 'offline_code' , offline_code , 'created_at' , created_at , 'updated_at' , updated_at , 'created_by' , created_by	

no	Name	Arguments	Return type	Security	Definition	nots
					, 'order_id' , order_id , 'customer_approval_status' , customer_approval_status , 'customer_approval_timestamp' , customer_approval_timestamp , 'customer_comment' , customer_comment , 'items' , items (INTO v_invoice FROM waste_invoices WHERE session_id = p_session_id ORDER BY created_at DESC LIMIT	

no	Name	Arguments	Return type	Security	Definition	nots
					1 ; -- التحقق من وجود الفاتورة IF v_invoice IS NULL THEN RAISE EXCEPTION '(% :Error getting invoice by session ID: Invoice for session ID % not found (Session ID' , p_session_id , p_session_id ; END IF ; RETURN v_invoice ; EXCEPTION WHEN OTHERS THEN RAISE EXCEPTION '(% :Error getting invoice by session ID: % (Session ID' , SQLERRM , p_session_id ; END ;	

no	Name	Arguments	Return type	Security	Definition	nots
28	get_nearby_available_delivery_boys	lat numeric, lng numeric, distance_km numeric DEFAULT 5	TABLE(id uuid, full_name text, phone text, online_status text, current_latitude numeric, current_longitude numeric, distance_meters numeric, last_location_update timestamp with time zone, preferred_vehicle text)	Invoker	BEGIN RETURN QUERY SELECT db . id , db . full_name , db . phone , db . online_status , db . current_latitude , db . current_longitude ,) 6371000 * acos) cos) radians)	

no	Name	Arguments	Return type	Security	Definition	nots
					lat ((* cos) radians) db . current_latitude ((* cos) radians) db . current_longitude (- radians) lng ((+ sin) radians) lat ((* sin) radians) db . current_latitude (((	

no	Name	Arguments	Return type	Security	Definition	nots
					(AS distance_meters , db . last_location_update , db . preferred_vehicle FROM delivery_boys db WHERE db . current_latitude IS NOT NULL AND db . current_longitude IS NOT NULL AND db . online_status = 'online' AND db	

no	Name	Arguments	Return type	Security	Definition	nots
					. is_available = TRUE AND) 6371000 * acos) cos) radians) lat ((* cos) radians) db . current_latitude ((* cos) radians) db . current_longitude (- radians) lng ((+	

no	Name	Arguments	Return type	Security	Definition	nots
					sin) radians) lat ((* sin) radians) db . current_latitude ((((=>) distance_km * 1000 (ORDER BY distance_meters ; END ;	
29	get_order_tracking_points	order_id_param uuid	TABLE(tracking_id uuid, latitude numeric, longitude numeric, speed numeric, heading numeric, tracking_timestamp timestamp	Invoker	BEGIN RETURN QUERY SELECT ,ot.id AS tracking_id ,ot.latitude ,ot.longitude ,ot.speed ,ot.heading ot.timestamp, -- This can remain as is since it's a column from the table	

no	Name	Arguments	Return type	Security	Definition	nots
			with time zone, delivery_boy_id uuid, delivery_boy_name text)		,ot.delivery_boy_id db.full_name AS delivery_boy_name FROM order_tracking ot JOIN delivery_boys db ON ot.delivery_boy_id = db.id WHERE ot.order_id = order_id_param ORDER BY ;ot.timestamp ;END	
30	get_profile_info	profile_id uuid	json	Definer	declare ;profile_info json begin)select json_build_object ,'id', id' ,'name', name' ,'phone_number', phone_number' ,'email', email' ,'avatar_url', avatar_url' ,'address', address' ,'city', city' ,'area', area' ,'building_number', building_number' ,'floor_number', floor_number' ,'apartment_number', apartment_number' ,'points', points' ,'status', status' ,'created_at', created_at' 'updated_at', updated_at' (into profile_info from profiles ;where id = profile_id ;return profile_info ;end	
31	get_waste_type_stats	p_start_date timestamp with time zone, p_end_date timestamp with time zone	TABLE(waste_type text, total_weight numeric, total_orders integer, total_revenue numeric, average_weight_per_order	Invoker	BEGIN RETURN QUERY SELECT ,wci.name AS waste_type ,SUM(wci.actual_weight) AS total_weight ,COUNT(DISTINCT wcs.id) AS total_orders ,SUM(wci.total_price) AS total_revenue CASE WHEN COUNT(DISTINCT wcs.id) > 0 THEN SUM(wci.actual_weight) /	

no	Name	Arguments	Return type	Security	Definition	nots
			numeric)		(COUNT(DISTINCT wcs.id ELSE 0 END AS average_weight_per_order FROM public.waste_collection_items wci JOIN public.waste_collection_sessions wcs ON wci.session_id = wcs.id WHERE wcs.created_at BETWEEN p_start_date AND p_end_date GROUP BY wci.name ORDER BY ;total_weight DESC ;END	
32	handle_customer_user_creation	user_data record	void	Definer	BEGIN) INSERT INTO customers ,id ,user_id ,full_name ,phone_number ,referral_code ,preferred_language ,customer_type customer_status (SELECT ,auth.uid() as id ,()auth.uid SELECT raw_user_meta_data->>'full_name' FROM auth.users WHERE id =) ,(()auth.uid SELECT raw_user_meta_data->>'phone_number' FROM auth.users WHERE id =) ,(()auth.uid SELECT raw_user_meta_data->>'referral_code' FROM auth.users WHERE id =) ,(()auth.uid COALESCE((SELECT raw_user_meta_data->>'preferred_language' FROM ,('auth.users WHERE id = auth.uid()), 'ar ,'household' ;'active' EXCEPTION WHEN OTHERS THEN ;RAISE NOTICE 'Error in handle_customer_user_creation: %', SQLERRM ;RAISE ;END	
33	handle_new_user		trigger	Invoker	DECLARE ;id UUID_	

no	Name	Arguments	Return type	Security	Definition	nots

					;user RECORD_
					;user_type TEXT_
					BEGIN
					Assign user ID --
					;id := NEW.id_
					
					Diagnostic logging --
					;RAISE NOTICE 'Starting handle_new_user for user ID: %', _id
					
					Attempt to get user data --
					;SELECT * INTO _user FROM auth.users WHERE id = _id
					
					IF _user IS NULL THEN
					;'RAISE NOTICE 'User not found in auth.users
					;RETURN NULL
					;END IF
					
					Attempt to get user type from metadata --
					SELECT COALESCE(raw_user_meta_data ->> 'type', raw_user_meta_data ->>
					'user_type') INTO _user_type
					FROM auth.users
					;WHERE id = _id
					
					;RAISE NOTICE 'User type detected: %', _user_type
					
					'If user type is not specified, assume 'delivery --
					IF _user_type IS NULL THEN
					;'user_type := 'delivery_
					;RAISE NOTICE 'User type not found, defaulting to: %', _user_type
					;END IF
					
					Route based on user type --
					IF _user_type = 'customer' THEN
					;'RAISE NOTICE 'Handling customer user creation
					;()PERFORM handle_customer_user_creation
					ELSIF _user_type = 'delivery' THEN
					;'RAISE NOTICE 'Handling delivery user creation
					Handle potential error in handle_delivery_user_creation function --
					BEGIN
					)PERFORM handle_delivery_user_creation
					,id_
					,'user.raw_user_meta_data ->> 'phone_
					,user.email_
					,'user.raw_user_meta_data ->> 'full_name_
					,user.raw_user_meta_data ->> 'date_of_birth')::date_)
					,'user.raw_user_meta_data ->> 'national_id_
					,user.raw_user_meta_data ->> 'preferred_vehicle')::public.vehicle_type_)
					,'user.raw_user_meta_data ->> 'license_number_
					,NULL
					,NULL
					,NULL
					,NULL	

no	Name	Arguments	Return type	Security	Definition	nots
					,inactive'::public.delivery_boy_status' ,0 ,0.00 ,NULL ,NULL ,NULL ,FALSE ,'user.raw_user_meta_data ->> 'referral_code_ ,NULL ,'user.raw_user_meta_data ->> 'avatar_url_ ,NULL ,0 ,0 ,0 ,NULL ,NULL ,offline'::public.delivery_boy_online_status' ,NULL ,NULL ,NULL ,NULL ,pending'::public.verification_status' pending'::public.verification_status' ;(EXCEPTION WHEN others THEN ;RAISE NOTICE 'Error in handle_delivery_user_creation: %', SQLERRM ;END Directly insert data without using the function --) INSERT INTO public.delivery_boys ,id ,phone ,full_name ,status ,created_at updated_at ( ) VALUES ,id_ ,'user.raw_user_meta_data ->> 'phone_ ,'user.raw_user_meta_data ->> 'full_name_ ,'inactive' ,()NOW ()NOW ;(;END IF Handle potential error in handle_new_profiles_delivery function -- BEGIN ;()PERFORM handle_new_profiles_delivery EXCEPTION	

no	Name	Arguments	Return type	Security	Definition	nots
					WHEN others THEN ;RAISE NOTICE 'Error in handle_new_profiles_delivery: %', SQLERRM ;END Directly insert data without using the function --) INSERT INTO public.new_profiles_delivery ,id ,phone ,full_name ,status ,created_at updated_at ( ) VALUES ,id_ ,'user.raw_user_meta_data ->> 'phone_ ,'user.raw_user_meta_data ->> 'full_name_ ,'inactive' ,()NOW ()NOW ;(;RETURN NEW ;END	
34	handle_updated_at		trigger	Definer	begin ;()new.updated_at = now ;return new ;end	
35	insert_invoice_bypass_security	p_session_id uuid, p_invoice_number text, p_subtotal numeric, p_tax numeric, p_total numeric, p_status text, p_offline_code text, p_created_by uuid	uuid	Definer	DECLARE v_invoice_id uuid ; BEGIN -- إدخال السجل مباشرة في الجدول مع تجاوز سياسات الأمان INSERT INTO public . waste_invoices	

no	Name	Arguments	Return type	Security	Definition	nots
					) session_id , invoice_number , subtotal , tax , total , status , offline_code , created_by (VALUES) p_session_id , p_invoice_number , p_subtotal , p_tax , p_total , p_status , p_offline_code , p_created_by (RETURNING id INTO v_invoice_id ; RETURN	

no	Name	Arguments	Return type	Security	Definition	nots
					v_invoice_id ; END ;	
36	insert_tracking_location	p_order_id uuid, p_delivery_boy_id uuid, p_latitude double precision, p_longitude double precision, p_speed double precision DEFAULT NULL::double precision, p_heading double precision DEFAULT NULL::double precision, p_status delivery_boy_online_status DEFAULT 'online'::delivery_boy_online_status, p_active_status delivery_boy_status DEFAULT 'active'::delivery_boy_status, p_available_for_orders boolean DEFAULT false	jsonb	Definer	DECLARE v_result JSONB ; BEGIN -- إدخال بيانات الموقع في جدول order_tracking مع الحقول الجديدة INSERT INTO order_tracking) order_id , delivery_boy_id , latitude , longitude , speed , heading , status , active_status , -- حقل جديد	

no	Name	Arguments	Return type	Security	Definition	nots
					available_for_orders -- حقل جديد (VALUES) p_order_id , p_delivery_boy_id , p_latitude , p_longitude , p_speed , p_heading , p_status , p_active_status , -- قيمة الحقل الجديد p_available_for_orders -- قيمة الحقل الجديد (RETURNING to_jsonb) order_tracking . * (	

no	Name	Arguments	Return type	Security	Definition	nots
					INTO v_result ; -- تحديث اخر موقع وحالة المندوب في جدول delivery_boys UPDATE delivery_boys SET current_latitude = p_latitude , current_longitude = p_longitude , last_location_update = NOW) (, online_status = p_status , -- تحديث حالة الاتصال status = p_active_status , -- تحديث الحالة الإدارية is_available = p_available_for_orders -- تحديث قابلية استلام الطلبات	

no	Name	Arguments	Return type	Security	Definition	nots
					WHERE id = p_delivery_boy_id ; RETURN v_result ; END ;	
37	insert_tracking_location	p_order_id uuid, p_delivery_boy_id uuid, p_latitude double precision, p_longitude double precision, p_speed double precision DEFAULT NULL::double precision, p_heading double precision DEFAULT NULL::double precision	jsonb	Definer	DECLARE v_result JSONB ; BEGIN INSERT INTO order_tracking) order_id , delivery_boy_id , latitude , longitude , speed , heading (	

no	Name	Arguments	Return type	Security	Definition	nots
					VALUES) p_order_id , p_delivery_boy_id , p_latitude , p_longitude , p_speed , p_heading (RETURNING to_jsonb) order_tracking ; * (INTO v_result ; RETURN v_result ; END ;	
38	insert_waste_invoice	p_session_id uuid, p_invoice_number text, p_subtotal numeric, p_tax numeric, p_total numeric, p_status text, p_offline_code text, p_created_by uuid	uuid	Definer	DECLARE ;v_invoice_id uuid BEGIN)INSERT INTO public.waste_invoices	

no	Name	Arguments	Return type	Security	Definition	nots
					,session_id ,invoice_number ,subtotal ,tax ,total ,status ,offline_code created_by ( ) VALUES ,p_session_id ,p_invoice_number ,p_subtotal ,p_tax ,p_total ,p_status ,p_offline_code p_created_by (;RETURNING id INTO v_invoice_id ;RETURN v_invoice_id ;END	
39	is_valid_phone	phone character varying	boolean	Invoker	BEGIN ;'${RETURN phone ~ '^[+]?[0-9]{10,14 ;END	

40	log_delivery_status_change		trigger	Invoker	BEGIN
					IF OLD.status IS NULL OR NEW.status != OLD.status THEN
					) INSERT INTO delivery_status_history
					,delivery_order_id
					,status
					notes
					) VALUES (
					,NEW.id
					,NEW.status
					Status changed to ' || NEW.status'
					;(
					;END IF
					;RETURN NEW
					;END	

41	send_customer_notification	p_order_id uuid, p_type interact	uuid	Definer	DECLARE v_id UUID ;	

no	Name	Arguments	Return type	Security	Definition	nots
					v_customer_id UUID ; BEGIN -- الحصول على معرف العميل من جدول الطلبات SELECT customer_id INTO v_customer_id FROM delivery_orders WHERE id = p_order_id ; -- إضافة السجل إلى جدول التفاعلات INSERT INTO customer_interactions) order_id , customer_id , type , message , created_at (	

no	Name	Arguments	Return type	Security	Definition	nots
					VALUES) p_order_id , v_customer_id , p_type , p_message , NOW) ((RETURNING id INTO v_id ; -- هنا يمكن إضافة منطق إرسال الإشعار (Push Notification, SMS, etc.) RETURN v_id ; END ;	
42	send_invoice_to_customer	p_invoice_id uuid	boolean	Definer	DECLARE v_session_id UUID ; BEGIN	

no	Name	Arguments	Return type	Security	Definition	nots
					-- الحصول على معرّف الجلسة لهذه الفاتورة SELECT session_id INTO v_session_id FROM waste_invoices WHERE id = p_invoice_id ; -- تحقق من وجود الفاتورة IF v_session_id IS NULL THEN RAISE EXCEPTION 'فاتورة برقم % غير موجودة' , p_invoice_id ; END IF ; -- تحديث حالة الفاتورة إلى 'pending' (في انتظار الموافقة) UPDATE waste_invoices SET customer_approval_status	

no	Name	Arguments	Return type	Security	Definition	nots
					= 'pending' customer_approval_status_enum:: , customer_approval_timestamp = NOW) (WHERE id = p_invoice_id ; -- تحديث حالة الجلسة لتعكس أن الفاتورة تم إرسالها UPDATE waste_collection_sessions SET customer_approval_status = 'pending' customer_approval_status_enum:: , customer_approval_timestamp = NOW) (WHERE id = v_session_id ; RETURN	

no	Name	Arguments	Return type	Security	Definition	nots
					TRUE ; EXCEPTION WHEN OTHERS THEN RAISE EXCEPTION 'خطأ في إرسال الفاتورة للعميل: % (رقم الفاتورة: %)' , SQLERRM , p_invoice_id ; END ;	

43	set_profile_id		trigger	Invoker	BEGIN
					IF NEW.profile_id IS NULL THEN
					-- تعيين profile_id من خلال auth.uid()
					;()NEW.profile_id = auth.uid
					;END IF
					;RETURN NEW
					;END	

44	set_updated_at		trigger	Invoker	BEGIN ;NEW.updated_at = CURRENT_TIMESTAMP ;RETURN NEW ;END	
45	smart_assign_order	p_order_id uuid	uuid	Invoker	DECLARE ;v_assigned_delivery_boy_id UUID ;v_order_pickup_location GEOMETRY ;v_order_category TEXT BEGIN -- الحصول على موقع الاستلام وفئة الطلب SELECT ,pickup_location category_name INTO ,v_order_pickup_location	

no	Name	Arguments	Return type	Security	Definition	nots
					v_order_category FROM public.delivery_orders WHERE ;id = p_order_id -- البحث عن أفضل مندوب استنادًا إلى الموقع والكفاءة والخبرة SELECT db.id INTO v_assigned_delivery_boy_id FROM public.delivery_boys db WHERE db.is_available = TRUE 'AND db.status = 'active ORDER BY -- أولوية للمندوبين الأقرب إلى موقع الاستلام)ST_Distance ,(ST_SetSRID(ST_MakePoint(db.current_longitude, db.current_latitude), 4326 v_order_pickup_location ,ASC (-- ثم حسب التقييم ,db.rating DESC -- ثم حسب عدد التوصيلات db.total_deliveries DESC ;LIMIT 1 -- تحديث الطلب بالمندوب المخصص IF v_assigned_delivery_boy_id IS NOT NULL THEN UPDATE public.delivery_orders SET ,delivery_boy_id = v_assigned_delivery_boy_id ,'status = 'assigned updated_at = CURRENT_TIMESTAMP WHERE ;id = p_order_id ;END IF ;RETURN v_assigned_delivery_boy_id ;END	
46	sync_delivery_amounts		trigger	Invoker	BEGIN UPDATE delivery_orders SET ,expected_total_amount = NEW.expected_total ,actual_total_amount = NEW.actual_total is_verified = NEW.is_fully_verified ;WHERE customer_order_id = NEW.id ;RETURN NEW ;END	

no	Name	Arguments	Return type	Security	Definition	nots

47	sync_phone_to_customer_phones		trigger	Invoker	BEGIN
					-- التحقق من وجود رقم هاتف في السجل الجديد
					IF NEW.phone_number IS NOT NULL THEN
					-- إدخال رقم الهاتف في جدول customer_phones
					INSERT INTO customer_phones (
					profile_id,
					phone_number,
					is_primary
					)
					VALUES (
					NEW.id, -- معرف الملف الشخصي
					NEW.phone_number, -- رقم الهاتف
					true -- تعيينه كرقم افتراضي
					)
					-- في حالة وجود رقم هاتف مكرر، قم بتحديثه
					ON CONFLICT (phone_number)
					DO UPDATE SET
					is_primary = true,
					updated_at = NOW();
					END IF;
					RETURN NEW;
					END;	

48	sync_primary_phone_to_profile		trigger	Invoker	BEGIN
					IF NEW.is_primary = true THEN
					-- تحديث رقم الهاتف في البروفايل والعميل
					UPDATE new_profiles
					SET phone_number = NEW.phone_number
					WHERE id = NEW.customer_id;
					
					UPDATE customers
					SET phone_number = NEW.phone_number
					WHERE id = NEW.customer_id;
					
					-- جعل الأرقام الأخرى غير أساسية
					UPDATE customer_phone_numbers
					SET is_primary = false
					WHERE customer_id = NEW.customer_id
					AND id != NEW.id;
					END IF;
					
					RETURN NEW;
					END;	

49	sync_profile_to_customer		trigger	Invoker	BEGIN UPDATE customers SET	

no	Name	Arguments	Return type	Security	Definition	nots
					,full_name = NEW.full_name ,phone_number = NEW.phone_number ,preferred_language = NEW.preferred_language ,total_orders = (NEW.statistics->>'total_orders')::integer ,total_spent = (NEW.statistics->>'total_spent')::numeric ,loyalty_points = (NEW.statistics->>'loyalty_points')::integer ,first_order_date = (NEW.statistics->>'first_order_date')::timestamp ,last_order_date = (NEW.statistics->>'last_order_date')::timestamp rating = (NEW.statistics->>'rating')::numeric ;WHERE id = NEW.id -- تحديث رقم الهاتف الأساسي) IF EXISTS SELECT 1 FROM customer_phone_numbers WHERE customer_id = NEW.id AND is_primary = true THEN (UPDATE customer_phone_numbers SET phone_number = NEW.phone_number ;WHERE customer_id = NEW.id AND is_primary = true ELSE) INSERT INTO customer_phone_numbers ,customer_id ,phone_number ,is_primary ,is_verified verification_status) VALUES (,NEW.id ,NEW.phone_number ,true ,true 'verified' ;(;END IF ;RETURN NEW ;END	

50	track_order_status_changes		trigger	Invoker	BEGIN
					IF (TG_OP = 'UPDATE' AND OLD.status IS DISTINCT FROM NEW.status) THEN
					(INSERT INTO delivery_status_history (delivery_order_id, status, notes
					) VALUES
					,NEW.id
					,NEW.status::delivery_status_enum -- تحويل صريح للنوع
					NEW.notes
					;(
					;END IF
					;RETURN NEW
					;END	

no	Name	Arguments	Return type	Security	Definition	nots

54	update_customer_location	p_profile_id uuid, p_address_id uuid DEFAULT NULL::uuid, p_lat double precision DEFAULT NULL::double precision, p_lng double precision DEFAULT NULL::double precision	boolean	Definer	BEGIN
					-- التحقق من الصلاحية
					IF auth.uid() != p_profile_id THEN
					RAISE EXCEPTION 'غير مصرح بتحديث الموقع';
					END IF;
					
					-- حالة 1: تحديد عنوان موجود كافتراضي
					IF p_address_id IS NOT NULL THEN
					-- التحقق من ملكية العنوان
					IF NOT EXISTS (
					SELECT 1
					FROM customer_addresses
					WHERE id = p_address_id
					AND profile_id = p_profile_id
					) THEN
					RAISE EXCEPTION 'العنوان غير موجود أو لا ينتمي للمستخدم';
					END IF;
					
					-- تحديث الجدولين الرئيسيين
					UPDATE new_profiles
					SET default_address_id = p_address_id
					WHERE id = p_profile_id;
					
					UPDATE customers
					SET default_address_id = p_address_id
					WHERE user_id = p_profile_id;
					
					-- تحديث حقل is_default في جدول customer_addresses
					UPDATE customer_addresses
					SET is_default = false
					WHERE profile_id = p_profile_id
					AND id != p_address_id;
					
					UPDATE customer_addresses
					SET is_default = true
					WHERE id = p_address_id
					AND profile_id = p_profile_id;
					
					RETURN TRUE;
					
					-- حالة 2: تحديث الموقع الجغرافي الحي
					ELSIF p_lat IS NOT NULL AND p_lng IS NOT NULL THEN
					-- تحديث الموقع الحالي
					UPDATE customers
					SET
					current_latitude = p_lat,
					current_longitude = p_lng,
					last_location_update = NOW()
					WHERE user_id = p_profile_id;
					
					-- تحديث العنوان الافتراضي إذا موجود	

no	Name	Arguments	Return type	Security	Definition	nots
					UPDATE customer_addresses SET ,latitude = p_lat ,longitude = p_lng ()updated_at = NOW WHERE profile_id = p_profile_id ;AND is_default = TRUE ;RETURN TRUE ELSE RAISE EXCEPTION 'يجب تحديد إما address_id أو الإحداثيات'; ;END IF ;END	
52	update_customer_order_totals		trigger	Invoker	BEGIN UPDATE customer_orders SET) = expected_total (SELECT SUM(expected_total FROM invoice_details WHERE customer_order_id = NEW.customer_order_id ,( ) = actual_total (SELECT SUM(actual_total FROM invoice_details WHERE customer_order_id = NEW.customer_order_id ,( ) = is_fully_verified (SELECT bool_and(is_verified FROM invoice_details WHERE customer_order_id = NEW.customer_order_id (;WHERE id = NEW.customer_order_id ;RETURN NEW ;END	
53	update_customer_statistics	p_customer_id uuid, p_order_amount numeric	void	Invoker	BEGIN UPDATE new_profiles)SET statistics = jsonb_set)jsonb_set)jsonb_set ,statistics ,'{total_orders}' statistics->>'total_orders')::integer + 1)::text::jsonb)) ,(,'{total_spent}'	

no	Name	Arguments	Return type	Security	Definition	nots
					statistics->>'total_spent')::numeric + p_order_amount)::text::jsonb)) ,(,'{last_order_date}' (to_jsonb(NOW()::text (;WHERE id = p_customer_id ;END	
54	update_customer_timestamp		trigger	Invoker	BEGIN ;NEW.updated_at = CURRENT_TIMESTAMP ;RETURN NEW ;END	

55	update_daily_performance		trigger	Invoker	DECLARE
					;delivery_date DATE
					;(waste_weight NUMERIC(10, 2
					;(earnings NUMERIC(10, 2
					;(distance NUMERIC(10, 2
					BEGIN
					-- حساب التاريخ من الطلب
					;delivery_date := CURRENT_DATE
					IF NEW.actual_delivery_time IS NOT NULL THEN
					;(delivery_date := DATE(NEW.actual_delivery_time
					ELSIF NEW.created_at IS NOT NULL THEN
					;(delivery_date := DATE(NEW.created_at
					;END IF
					
					-- حساب الوزن والأرباح والمسافة
					SELECT COALESCE(SUM(total_weight), 0) INTO waste_weight
					FROM public.waste_collection_sessions
					;WHERE delivery_order_id = NEW.id
					
					;(earnings := COALESCE(NEW.actual_total_amount, NEW.expected_total_amount, 0
					;(distance := COALESCE(NEW.estimated_distance, 0
					
					-- تحديث أو إدراج سجل الأداء اليومي
					INSERT INTO public.delivery_boy_daily_performance
					delivery_boy_id, date, orders_completed, total_distance, total_earnings,)
					(waste_weight_collected
					VALUES
					,NEW.delivery_boy_id, delivery_date)
					,CASE WHEN NEW.status = 'completed' THEN 1 ELSE 0 END
					(distance, earnings, waste_weight
					ON CONFLICT (delivery_boy_id, date) DO UPDATE
					= SET orders_completed
					CASE WHEN NEW.status = 'completed' THEN
					delivery_boy_daily_performance.orders_completed + 1
					ELSE	

no	Name	Arguments	Return type	Security	Definition	nots
					delivery_boy_daily_performance.orders_completed ,END = orders_canceled CASE WHEN NEW.status = 'canceled' THEN delivery_boy_daily_performance.orders_canceled + 1 ELSE delivery_boy_daily_performance.orders_canceled ,END ,total_distance = delivery_boy_daily_performance.total_distance + distance ,total_earnings = delivery_boy_daily_performance.total_earnings + earnings waste_weight_collected = delivery_boy_daily_performance.waste_weight_collected + ;waste_weight ;RETURN NEW ;END	
56	update_dashboard_analytics		trigger	Definer	BEGIN /* * ضع هنا الكود الفعلي للدالة update_dashboard_analytics(). * يجب أن يتضمن هذا الكود المنطق الذي تقوم به الدالة لتحديث جدول analytics_dashboard. * تأكد من نقل الكود الموجود حاليًا في دالة update_dashboard_analytics() الخاصة بك إلى هذا المكان. */ -- مثال توضيحي (قم باستبداله بالكود الفعلي الخاص بك): -- RAISE NOTICE 'تحديث بيانات لوحة التحكم (analytics_dashboard) هنا.'; -- INSERT INTO analytics_dashboard (some_column) VALUES ('some_value'); -- ... المزيد من الكود الفعلي ... RETURN NEW; -- أو RETURN OLD أو RETURN NULL حسب منطق الدالة الخاص بك ;END	
57	update_delivery_boy_availability	user_id uuid, available boolean	void	Definer	BEGIN UPDATE delivery_boys SET is_available = available WHERE id = user_id ;'AND status = 'active ;END	
58	update_delivery_boy_location	user_id uuid, lat numeric, lng numeric	void	Definer	BEGIN UPDATE delivery_boys SET ,current_latitude = lat ,current_longitude = lng last_location_update = CURRENT_TIMESTAMP ;WHERE id = user_id	

no	Name	Arguments	Return type	Security	Definition	nots
					;END ;	
59	update_delivery_boy_on_order_pickup	p_order_id uuid, p_delivery_boy_id uuid, p_latitude double precision, p_longitude double precision	boolean	Definer	BEGIN -- تحديث حالة المندوب في جدول delivery_boys UPDATE delivery_boys SET current_latitude = p_latitude , current_longitude = p_longitude , status = 'active' delivery_boy_status:: , -- تغيير الحالة الإدارية إلى active online_status = 'busy' delivery_boy_online_status:: , -- تغيير حالة الاتصال إلى busy is_available = FALSE	

no	Name	Arguments	Return type	Security	Definition	nots
					, -- المندوب غير متاح للطلبات الجديدة أثناء توصيل طلب last_location_update = NOW) (WHERE id = p_delivery_boy_id ; -- إضافة سجل في جدول order_tracking INSERT INTO order_tracking) order_id , delivery_boy_id , latitude , longitude , timestamp , status , active_status , available_for_orders	

no	Name	Arguments	Return type	Security	Definition	nots
					(VALUES) p_order_id , p_delivery_boy_id , p_latitude , p_longitude , NOW) (, 'busy' delivery_boy_online_status:: , 'active' delivery_boy_status:: , FALSE -- المندوب غير متاح للطلبات الجديدة (; RETURN FOUND ; END ;	

no	Name	Arguments	Return type	Security	Definition	nots
60	update_delivery_boy_stats		trigger	Invoker	BEGIN -- تحديث عدد الطلبات المكتملة والملغاة UPDATE public.delivery_boys SET) = completed_orders_count (*)SELECT COUNT FROM public.delivery_orders 'WHERE delivery_boy_id = NEW.delivery_boy_id AND status = 'completed ,( ) = canceled_orders_count (*)SELECT COUNT FROM public.delivery_orders 'WHERE delivery_boy_id = NEW.delivery_boy_id AND status = 'canceled ,( ) = total_deliveries (*)SELECT COUNT FROM public.delivery_orders 'WHERE delivery_boy_id = NEW.delivery_boy_id AND status = 'completed ,( ) = total_earnings (SELECT COALESCE(SUM(actual_total_amount), 0 FROM public.delivery_orders 'WHERE delivery_boy_id = NEW.delivery_boy_id AND status = 'completed ,( ) = rating (SELECT COALESCE(AVG(rating), 0 FROM public.delivery_ratings WHERE delivery_id = NEW.delivery_boy_id ,(badge_level = CASE WHEN (SELECT COUNT(*) FROM public.delivery_orders WHERE delivery_boy_id = NEW.delivery_boy_id AND status = 'completed') >= 500 THEN 5 WHEN (SELECT COUNT(*) FROM public.delivery_orders WHERE delivery_boy_id = NEW.delivery_boy_id AND status = 'completed') >= 250 THEN 4 WHEN (SELECT COUNT(*) FROM public.delivery_orders WHERE delivery_boy_id = NEW.delivery_boy_id AND status = 'completed') >= 100 THEN 3 WHEN (SELECT COUNT(*) FROM public.delivery_orders WHERE delivery_boy_id = NEW.delivery_boy_id AND status = 'completed') >= 50 THEN 2 WHEN (SELECT COUNT(*) FROM public.delivery_orders WHERE delivery_boy_id = NEW.delivery_boy_id AND status = 'completed') >= 10 THEN 1 ELSE 0 END ;WHERE id = NEW.delivery_boy_id ;RETURN NEW ;END	
61	update_delivery_performance		trigger	Invoker		

no	Name	Arguments	Return type	Security	Definition	nots

					DECLARE
					;(distance_km DECIMAL(10, 2
					;delivery_time INTEGER
					BEGIN
					IF NEW.status = 'completed' AND OLD.status != 'completed' THEN
					
					Update the statistics --
					) INSERT INTO delivery_performance_stats
					,delivery_boy_id
					,month
					,total_orders
					,completed_orders
					,total_distance
					average_delivery_time
					(
					) VALUES
					,NEW.delivery_boy_id
					,(date_trunc('month', NEW.actual_delivery_time
					,1
					,1
					,(COALESCE(distance_km, 0
					(COALESCE(delivery_time, 0
					(
					ON CONFLICT (delivery_boy_id, month) DO UPDATE
					SET
					,total_orders = delivery_performance_stats.total_orders + 1
					,completed_orders = delivery_performance_stats.completed_orders + 1
					) = average_delivery_time
					delivery_performance_stats.average_delivery_time *
					+ delivery_performance_stats.completed_orders
					(COALESCE(delivery_time, 0
					;(delivery_performance_stats.completed_orders + 1) / (
					;END IF
					;RETURN NEW
					;END	

62	update_delivery_timestamp		trigger	Invoker	BEGIN ;NEW.updated_at = CURRENT_TIMESTAMP ;RETURN NEW ;END	
63	update_invoice_approval_status	p_invoice_id uuid, p_status text, p_comment text DEFAULT NULL::text	jsonb	Definer	DECLARE ;v_invoice JSONB BEGIN Update invoice approval status -- UPDATE waste_invoices SET	

no	Name	Arguments	Return type	Security	Definition	nots
					,customer_approval_status = p_status ,()customer_approval_timestamp = NOW (customer_comment = COALESCE(p_comment, customer_comment ;WHERE id = p_invoice_id Get the updated invoice --)SELECT jsonb_build_object ,'id', id' ,'session_id', session_id' ,'invoice_number', invoice_number' ,'subtotal', subtotal' ,'total', total' ,'status', status' ,'created_at', created_at' ,'customer_approval_status', customer_approval_status' ,'customer_approval_timestamp', customer_approval_timestamp' ,'customer_comment', customer_comment' 'items', items -- Include actual UI data in response' INTO v_invoice (FROM waste_invoices ;WHERE id = p_invoice_id Check if invoice exists -- IF v_invoice IS NULL THEN ;RAISE EXCEPTION 'Invoice with ID % not found after update', p_invoice_id ;END IF ;RETURN v_invoice EXCEPTION WHEN OTHERS THEN RAISE EXCEPTION 'Error updating invoice approval status: % (Invoice ID: %)', ;SQLERRM, p_invoice_id ;END	
64	update_modified_column		trigger	Invoker	BEGIN ;()NEW.updated_at = NOW ;RETURN NEW ;END	
65	update_profile_points	profile_id uuid, points_to_add integer	void	Definer	begin update profiles set points = points + points_to_add ;where id = profile_id ;end	
66	update_timestamp		trigger	Invoker	BEGIN	

no	Name	Arguments	Return type	Security	Definition	nots
					;(()NEW.updated_at = timezone('utc'::text, now ;RETURN NEW ;END	
67	update_updated_at		trigger	Invoker	BEGIN ;(()NEW.updated_at = timezone('utc'::text, now ;RETURN NEW ;END	

68	verify_qr_payment	p_qr_id uuid, p_verification_code character varying	boolean	Invoker	DECLARE
					;v_qr payment_qr_codes
					;v_transaction_id UUID
					BEGIN
					-- التحقق من الكود
					SELECT * INTO v_qr
					FROM payment_qr_codes
					WHERE id = p_qr_id
					AND verification_code = p_verification_code
					'AND status = 'pending
					;()AND expires_at > NOW
					
					IF v_qr IS NULL THEN
					;RETURN FALSE
					;END IF
					
					-- إنشاء المعاملة
					) INSERT INTO wallet_transactions
					,wallet_id
					,transaction_type
					,amount
					,status
					,qr_code_id
					,reference_id
					description
					(
					SELECT
					,w.id
					,'qr_payment'
					,v_qr.amount
					,'verification_pending'
					,v_qr.id
					,v_qr.order_id::TEXT
					QR Payment for Order #' || v_qr.order_id::TEXT'
					FROM wallets w
					WHERE w.user_id = v_qr.recipient_id
					;RETURNING id INTO v_transaction_id
					
					-- تحديث حالة QR code	

e	Arguments	Return type	Security	Definition
				UPDATE payment_qr_codes ,'SET status = 'verification_pending ,transaction_id = v_transaction_id ()updated_at = NOW ;WHERE id = p_qr_id ;RETURN TRUE ;END

Database Triggers

No	Name	Table	Function	Events	Orientation	Enabled
1	check_delivery_boy_type_trigger	delivery_boys	check_delivery_boy_type	BEFORE INSERT	ROW	
2	check_notification_updates	system_notifications	check_notification_update	BEFORE UPDATE	ROW	
3	create_default_address_trigger	new_profiles	create_default_address	AFTER INSERT	ROW	
4	dashboard_analytics_update	delivery_orders	update_dashboard_analytics	AFTER UPDATEAFTE R INSERT	ROW	
5	delivery_boy_stats_update	delivery_orders	update_delivery_boy_stats	AFTER UPDATEAFTE R INSERT	ROW	

6	delivery_orders_performance_update	delivery_orders	update_daily_performance	AFTER UPDATEAFTER INSERT	ROW
7	ensure_profile_id	customer_addresses	set_profile_id	BEFORE INSERT	ROW
8	log_status_change	delivery_orders	log_delivery_status_change	AFTER UPDATE	ROW
9	new_customer_profile_trigger	customers	create_new_profile_on_customer_insert	AFTER INSERT	ROW
10	order_status_track_trigger	delivery_orders	track_order_status_changes	AFTER UPDATE	ROW
11	set_updated_at	order_details	set_updated_at	BEFORE UPDATE	ROW
12	single_default_address_trigger	customer_addresses	enforce_single_default_address	AFTER UPDATEAFTER INSERT	ROW
13	single_primary_phone_trigger	customer_phones	enforce_single_primary_phone	AFTER INSERTAFTER UPDATE	ROW
14	sync_amounts_from_customer_order	customer_orders	sync_delivery_amounts	AFTER UPDATE	ROW

15	sync_phone_trigger	new_profiles	sync_phone_to_customer_phones	AFTER UPDATEAFTER INSERT	ROW
16	tr_create_delivery_order	customer_orders	create_delivery_order	AFTER INSERT	ROW
17	trigger_update_invoice_details_id	invoice_details	update_invoice_details_id	AFTER INSERT	ROW
18	update_customer_addresses_modtime	customer_addresses	update_modified_column	BEFORE UPDATE	ROW
19	update_customer_orders_timestamp	customer_orders	update_customer_timestamp	BEFORE UPDATE	ROW
20	update_customer_phones_modtime	customer_phones	update_modified_column	BEFORE UPDATE	ROW
21	update_customer_totals	invoice_details	update_customer_order_totals	AFTER UPDATEAFTER INSERT	ROW
22	update_customer_waiting_time	delivery_orders	calculate_customer_waiting_time	BEFORE UPDATE	ROW
23	update_delivery_boys_modtime	delivery_boys	update_modified_column	BEFORE UPDATE	ROW
24	update_delivery_orders_timestamp	delivery_orders	update_delivery_timestamp	BEFORE UPDATE	ROW

25	update_invoice_details_timestamp	invoice_details	update_customer_timestamp	BEFORE UPDATE	ROW	
26	update_performance_on_completion	delivery_orders	update_delivery_performance	AFTER UPDATE	ROW	

Enumerated Types

No	Name	Table	Function	Events	Orientation	Enabled
1	check_delivery_boy_type_trigger	delivery_boys	check_delivery_boy_type	BEFORE INSERT	ROW	
2	check_notification_updates	system_notifications	check_notification_update	BEFORE UPDATE	ROW	
3	create_default_address_trigger	new_profiles	create_default_address	AFTER INSERT	ROW	
4	dashboard_analytics_update	delivery_orders	update_dashboard_analytics	AFTER UPDATEAFTER INSERT	ROW	
5	delivery_boy_stats_update	delivery_orders	update_delivery_boy_stats	AFTER UPDATEAFTER INSERT	ROW	

6	delivery_orders_performance_update	delivery_orders	update_daily_performance	AFTER UPDATEAFTER INSERT	ROW
7	ensure_profile_id	customer_addresses	set_profile_id	BEFORE INSERT	ROW
8	log_status_change	delivery_orders	log_delivery_status_change	AFTER UPDATE	ROW
9	new_customer_profile_trigger	customers	create_new_profile_on_customer_insert	AFTER INSERT	ROW
10	order_status_track_trigger	delivery_orders	track_order_status_changes	AFTER UPDATE	ROW
11	set_updated_at	order_details	set_updated_at	BEFORE UPDATE	ROW
12	single_default_address_trigger	customer_addresses	enforce_single_default_address	AFTER UPDATEAFTER INSERT	ROW
13	single_primary_phone_trigger	customer_phones	enforce_single_primary_phone	AFTER INSERTAFTER UPDATE	ROW
14	sync_amounts_from_customer_order	customer_orders	sync_delivery_amounts	AFTER UPDATE	ROW

15	sync_phone_trigger	new_profiles	sync_phone_to_customer_phones	AFTER UPDATEAFTER INSERT	ROW
16	tr_create_delivery_order	customer_orders	create_delivery_order	AFTER INSERT	ROW
17	trigger_update_invoice_details_id	invoice_details	update_invoice_details_id	AFTER INSERT	ROW
18	update_customer_addresses_modtime	customer_addresses	update_modified_column	BEFORE UPDATE	ROW
19	update_customer_orders_timestamp	customer_orders	update_customer_timestamp	BEFORE UPDATE	ROW
20	update_customer_phones_modtime	customer_phones	update_modified_column	BEFORE UPDATE	ROW
21	update_customer_totals	invoice_details	update_customer_order_totals	AFTER UPDATEAFTER INSERT	ROW
22	update_customer_waiting_time	delivery_orders	calculate_customer_waiting_time	BEFORE UPDATE	ROW
23	update_delivery_boys_modtime	delivery_boys	update_modified_column	BEFORE UPDATE	ROW
24	update_delivery_orders_timestamp	delivery_orders	update_delivery_timestamp	BEFORE UPDATE	ROW

25	update_invoice_details_timestamp	invoice_details	update_customer_timestamp	BEFORE UPDATE	ROW
26	update_performance_on_completion	delivery_orders	update_delivery_performance	AFTER UPDATE	ROW

Database Indexes

Schema	Table	Name	
public	admins	admins_pkey	View definition
public	analytics_dashboard	analytics_dashboard_date_key	View definition
public	analytics_dashboard	analytics_dashboard_pkey	View definition
public	categories	categories_name_key	View definition
public	categories	categories_pkey	View definition
public	complaints	complaints_pkey	View definition
public	customer_addresses	customer_addresses_pkey	View definition
public	customer_interactions	customer_interactions_pkey	View definition

public	customer_orders	customer_orders_pkey	View definition
public	customer_phones	customer_phones_phone_number_key	View definition
public	customer_phones	customer_phones_pkey	View definition
public	customers	customers_pkey	View definition
public	delivery_boy_daily_performance	delivery_boy_daily_performance_delivery_boy_date_key	View definition
public	delivery_boy_daily_performance	delivery_boy_daily_performance_pkey	View definition
public	delivery_boy_order_history	delivery_boy_order_history_pkey	View definition
public	delivery_boys	delivery_boys_delivery_code_key	View definition
public	delivery_boys	delivery_boys_email_key	View definition
public	delivery_boys	delivery_boys_license_number_key	View definition
public	delivery_boys	delivery_boys_national_id_key	View definition
public	delivery_boys	delivery_boys_phone_key	View definition
public	delivery_boys	delivery_boys_pkey	View definition
public	delivery_boys	delivery_boys_referral_code_key	View definition

public	delivery_documents	delivery_documents_pkey	View definition
public	delivery_earnings	delivery_earnings_pkey	View definition
public	delivery_locations	delivery_locations_pkey	View definition
public	delivery_orders	delivery_orders_order_number_key	View definition
public	delivery_orders	delivery_orders_pkey	View definition
public	delivery_performance_stats	delivery_performance_stats_delivery_boy_id_month_key	View definition
public	delivery_performance_stats	delivery_performance_stats_pkey	View definition
public	delivery_ratings	delivery_ratings_pkey	View definition
public	delivery_status_history	delivery_status_history_pkey	View definition
public	delivery_vehicles	delivery_vehicles_pkey	View definition
public	delivery_vehicles	delivery_vehicles_registration_number_key	View definition
public	delivery_zones	delivery_zones_pkey	View definition
public	geographic_zones	geographic_zones_pkey	View definition
public	analytics_dashboard	idx_analytics_dashboard_date	View definition

public	customer_addresses	idx_customer_addresses_geom	View definition
public	customer_addresses	idx_customer_addresses_profile_id	View definition
public	customer_interactions	idx_customer_interactions_created_at	View definition
public	customer_interactions	idx_customer_interactions_customer_id	View definition
public	customer_interactions	idx_customer_interactions_is_read	View definition
public	customer_interactions	idx_customer_interactions_order_id	View definition
public	customer_interactions	idx_customer_interactions_type	View definition
public	customer_orders	idx_customer_orders_category_name	View definition
public	customer_orders	idx_customer_orders_location	View definition
public	customer_orders	idx_customer_orders_order_details	View definition
public	customer_orders	idx_customer_orders_profile_id	View definition
public	customer_orders	idx_customer_orders_subcategory_name	View definition
public	customer_phones	idx_customer_phones_phone_number	View definition
public	customer_phones	idx_customer_phones_profile_id	View definition

public	delivery_boy_daily_performance	idx_daily_performance_date	View definition
public	delivery_boy_daily_performance	idx_daily_performance_delivery_boy	View definition
public	delivery_boy_order_history	idx_delivery_boy_order_history_delivery_boy	View definition
public	delivery_boys	idx_delivery_boys_availability	View definition
public	delivery_boys	idx_delivery_boys_delivery_code	View definition
public	delivery_boys	idx_delivery_boys_location	View definition
public	delivery_boys	idx_delivery_boys_phone	View definition
public	delivery_boys	idx_delivery_boys_status	View definition
public	delivery_earnings	idx_delivery_earnings_delivery_id	View definition
public	delivery_locations	idx_delivery_locations_delivery_id	View definition
public	delivery_orders	idx_delivery_orders_category_name	View definition
public	delivery_orders	idx_delivery_orders_customer_order	View definition
public	delivery_orders	idx_delivery_orders_delivery_boy	View definition
public	delivery_orders	idx_delivery_orders_pickup_location	View definition

public	delivery_orders	idx_delivery_orders_subcategory_name	View definition
public	new_profiles_delivery	idx_delivery_phone	View definition
public	new_profiles_delivery	idx_delivery_rating	View definition
public	delivery_ratings	idx_delivery_ratings_delivery_id	View definition
public	delivery_vehicles	idx_delivery_vehicles_agent	View definition
public	delivery_vehicles	idx_delivery_vehicles_location	View definition
public	geographic_zones	idx_geographic_zones_area	View definition
public	invoice_details	idx_invoice_details_customer_order	View definition
public	order_details	idx_order_details_category_name	View definition
public	order_details	idx_order_details_delivery_order_id	View definition
public	order_details	idx_order_details_subcategory_name	View definition
public	order_schedule	idx_order_schedule_delivery_time	View definition
public	order_schedule	idx_order_schedule_order_id	View definition
public	order_schedule	idx_order_schedule_pickup_time	View definition

public	order_schedule	idx_order_schedule_status	View definition
public	order_tracking	idx_order_tracking_active_status	View definition
public	order_tracking	idx_order_tracking_available_for_orders	View definition
public	order_tracking	idx_order_tracking_delivery_boy_id	View definition
public	order_tracking	idx_order_tracking_order_id	View definition
public	order_tracking	idx_order_tracking_timestamp	View definition
public	delivery_performance_stats	idx_performance_stats_delivery_boy	View definition
public	system_notifications	idx_system_notifications_is_read	View definition
public	system_notifications	idx_system_notifications_user	View definition
public	vehicle_maintenance_log	idx_vehicle_maintenance_vehicle	View definition
public	invoice_details	invoice_details_pkey	View definition
public	new_profiles_delivery	new_profiles_delivery_national_id_key	View definition
public	new_profiles_delivery	new_profiles_delivery_pkey	View definition
public	new_profiles	new_profiles_pkey	View definition

public	onboarding_data	onboarding_data_pkey	View definition
public	order_details	order_details_order_id_idx	View definition
public	order_details	order_details_pkey	View definition
public	order_schedule	order_schedule_pkey	View definition
public	order_tracking	order_tracking_pkey	View definition
public	payment_qr_codes	payment_qr_codes_pkey	View definition
public	payment_settlements	payment_settlements_pkey	View definition
public	subcategories	subcategories_pkey	View definition
public	system_notifications	system_notifications_pkey	View definition
public	new_profiles	unique_phone_number	View definition
public	customer_phones	unique_profile_phone	View definition
public	vehicle_maintenance_log	vehicle_maintenance_log_pkey	View definition
public	wallet_transactions	wallet_transactions_pkey	View definition
public	wallets	wallets_pkey	View definition

public	waste_collection_items	waste_collection_items_pkey	View definition
public	waste_collection_sessions	waste_collection_sessions_pkey	View definition
public	waste_data_admin	waste_data_admin_pkey	View definition
public	waste_invoices	waste_invoices_pkey	View definition
public	waste_recycling	waste_recycling_pkey	View definition
public	waste_weights	waste_weights_order_id_waste_type_key	View definition
public	waste_weights	waste_weights_pkey	View definition

جدول سياسات قواعد البيانات

الجدول	نوع السياسة	اسم السياسة	الدور المطبق عليه
admins	لا توجد سياسات	-	-
analytics_dashboard	INSERT	Allow inserts for admins	public
	SELECT	Only admins can view analytics dashboard	public
categories	INSERT	Allow anonymous inserts	public
	SELECT	select_policy	public

complaints	INSERT	Clients can insert their own complaints	public
customer_addresses	DELETE	Users can delete their own addresses	public
	INSERT	Users can insert their own addresses	public
	UPDATE	Users can update their own addresses	public
	SELECT	Users can view their own addresses	public
customer_interactions	ALL	customer_interactions_basic_policy	public
customer_orders	INSERT	Users can create their own orders	public
	DELETE	Users can delete their own orders	public
	INSERT	Users can insert their own order details	authenticated
	UPDATE	Users can update their own order details	authenticated
	UPDATE	Users can update their own orders	public
	SELECT	Users can view their own order details	authenticated
	SELECT	Users can view their own orders	public
customer_phones	DELETE	Users can delete their own phone numbers	public
	INSERT	Users can insert their own phone numbers	public
	UPDATE	Users can update their own phone numbers	public
	SELECT	Users can view their own phone numbers	public
customers	INSERT	Customers can insert their own data	public
	UPDATE	Customers can update their own data	public

	SELECT	Customers can view their own data	public
	DELETE	customers_delete_policy	public
	SELECT	customers_select_policy	public
	UPDATE	customers_update_policy	public
	INSERT	insert_customer_data	public
	ALL	Service role can manage all data	public
	UPDATE	update_own_customer_data	public
delivery_boy_daily_performance	INSERT	Admins can insert any performance record	public
	UPDATE	Admins can update any performance record	public
	SELECT	Admins can view all performance data	public
	ALL	Application can update any delivery boy performance	public
	UPDATE	Delivery boys can update their own performance data	public
	SELECT	Delivery boys can view their own performance data	public
delivery_boy_order_history	لا توجد سياسات	-	-
delivery_boys	SELECT	Allow delivery code lookup for login	public
	ALL	Allow full access	public
	SELECT	dashboard_can_read_delivery_boys	public
	ALL	Delivery boys can only be accessed by delivery boy type users	public
	INSERT	Enable insert for users based on user_id	public
	UPDATE	Users can update own profile	public

	SELECT	Users can view own profile	public
delivery_documents	SELECT	Users can view their own delivery documents	public
delivery_earnings	SELECT	Users can view their own delivery earnings	public
delivery_locations	SELECT	Users can view their own delivery locations	public
delivery_orders	SELECT	Allow authenticated users to read delivery orders	public
	INSERT	Allow insert for authenticated users	authenticated
	SELECT	Allow public read for all delivery orders	public
	SELECT	Allow read for authenticated users	authenticated
	UPDATE	Allow update for authenticated users	authenticated
	UPDATE	Delivery boys can update their assigned orders	public
delivery_performance_stats	SELECT	Delivery boys can view their own stats	public
	INSERT	insert_performance_stats	authenticated
	UPDATE	update_performance_stats	authenticated
delivery_ratings	SELECT	Users can view their own delivery ratings	public
delivery_status_history	DELETE	Enable delete access for authenticated users	authenticated
	INSERT	Enable insert access for authenticated users	authenticated
	SELECT	Enable read access for authenticated users	authenticated

	UPDATE	Enable update access for authenticated users	authenticated
delivery_vehicles	SELECT	Agents can view their assigned vehicles	public
	SELECT	Delivery vehicles are viewable by admins	public
	ALL	Only admins can manage delivery vehicles	public
delivery_zones	SELECT	Users can view their own delivery zones	public
geographic_zones	SELECT	Geographic zones are viewable by everyone	public
	ALL	Only admins can manage geographic zones	public
invoice_details	لا توجد سياسات	-	-
new_profiles	INSERT	insert_profile_data	public
	INSERT	profiles_insert_policy	public
	SELECT	profiles_select_policy	public
	UPDATE	profiles_update_policy	public
	SELECT	select_own_profile_data	public
	UPDATE	update_own_profile_data	public
new_profiles_delivery	ALL	Allow full access	public
	INSERT	Users can create their own delivery profiles	public
	DELETE	Users can delete their own delivery profiles	public
	UPDATE	Users can update their own delivery profiles	public
	SELECT	Users can view their own delivery profiles	public
onboarding_data	DELETE	delete_policy	public

	INSERT	insert_policy	public
	SELECT	select_policy	public
	UPDATE	update_policy	public
order_details	INSERT	Allow authenticated users to insert	public
	SELECT	Enable read access for all users	public
order_schedule	ALL	order_schedule_basic_policy	public
	SELECT	السماح للمستخدمين المصادقين بالاط	authenticated
	UPDATE	السماح للمستخدمين المصادقين بتحدي	authenticated
	INSERT	المستخدمون المصادقون يمكنهم إضافة	authenticated
order_tracking	DELETE	order_tracking_delete	public
	INSERT	order_tracking_insert	public
	ALL	order_tracking_no_access	public
	SELECT	order_tracking_select	public
	UPDATE	order_tracking_update	public
payment_qr_codes	INSERT	Delivery boys can create QR codes	public
	UPDATE	Users can verify their QR payments	public
	SELECT	Users can view their QR transactions	public
payment_settlements	INSERT	Representatives can insert their own payment settlements	public
	UPDATE	Representatives can update their own payment settlements	public
subcategories	DELETE	delete_policy	public
	INSERT	insert_policy	public
	SELECT	select_policy	public
	UPDATE	update_policy	public

system_notifications	INSERT	Only admins can create system notifications	public
	UPDATE	Users can mark their notifications as read	public
	SELECT	Users can view notifications targeted to them	public
vehicle_maintenance_log	SELECT	Agents can view maintenance logs of their vehicles	public
	ALL	Only admins can manage maintenance logs	public
wallet_transactions	لا توجد سياسات	-	-
wallets	لا توجد سياسات	-	-
waste_collection_items	لا توجد سياسات	-	-
waste_collection_sessions	INSERT	Allow authenticated users to insert	authenticated
	SELECT	Allow authenticated users to read	authenticated
	UPDATE	Allow delivery boys to update their sessions	authenticated
waste_data_admin	INSERT	insert_policy	public
	SELECT	select_policy	public
waste_invoices	UPDATE	Allow authorized users to update invoices	authenticated
waste_recycling	DELETE	delete_policy	public
	INSERT	insert_policy	public
	SELECT	select_policy	public
	UPDATE	update_policy	public
waste_weights	لا توجد سياسات	-	-