

imageRUNNER 2224N/2224



Main Unit



Machine Type	A3 Monochrome Laser Multifunctional
Core Functions	iR2224N: Print, Copy, Scan, and Send iR2224: Print, Copy, and Scan
Control Panel	88.9-mm monochrome touch panel
Memory	1.0 GB RAM
Storage	eMMC: 2 GB
Interface Connection	NETWORK* ¹ Standard: 100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n) OTHERS Standard: USB 2.0 (Device) x1

Paper Supply Capacity (A4, 80 g/m2 (gsm))	Standard: 350 sheets (Paper Drawer: 250 sheets, MPT Tray: 100 sheets) Maximum: 600 sheets (with Cassette Feeding Module-AK1)
Paper Output Capacity (A4, 80 g/m2 (gsm))	Standard: 250 sheets Maximum: 250 sheets
Supported Media Types	Multi-purpose Tray: Thin, Plain, Recycled, Thick, Colour, Bond, Label, Pre-punched, Envelope Paper Cassette: Plain, Recycled, Colour, Pre-punched
Supported Media Sizes	Multi-purpose tray: A3, A4, A4R, A5, A5R, B4, B5, B5R, Envelope (COM10, Monarch, DL, ISO-C5), Custom size min. 95.0 x 148.0 mm up to 297.0 x 431.0 mm Paper Cassette: Standard size: A3, A4, A4R, A5R, B4, B5, B5R
Supported Media Weights	Multi-purpose tray: 60 to 157 g/m2 (gsm) Paper cassettes: 64 to 90 g/m2 (gsm) Duplex: 60 to 90 g/m2 (gsm)
Warm-up Time	From Power On: 13 seconds or less ^{*2*3} From Sleep Mode: 4.3 seconds or less
Dimensions (W x D x H)	iR2224N (with DADF): 627 x 607 x 606 mm iR2224/2224N (with Platen cover): 627 x 589 x 502 mm iR2224N (with DADF and cassette): 627 x 607 x 698 mm iR2224N (with Platen cover and cassette): 627 x 589 x 594 mm
Installation Space (W x D)	1065 x 1285 mm
Weight	iR2224N: Approx. 30.3 kg without toner and Platen cover iR2224: Approx. 31.6 kg without toner and including Platen cover

Print



Print Speed (BW)

1-sided: Up to 24 pages/min (A4), Up to 12 pages/min (A3), Up to 11 pages/min (A4R)

	2-sided: Up to 16.7 pages/min (A4), Up to 7.5 pages/min (A3), Up to 7.8 pages/min (A4R)
Print Resolution (dpi)	600 × 600
Page Description Languages	Standard: UFR II Optional (iR2224N only): PCL6 (Optional)/PCL5 (Optional)
Printing From Mobile and Cloud Application	Apple AirPrint, Canon PRINT Business, Mopria, Canon Print Service
Fonts	PCL (Optional) fonts: 45 Roman, 10 Bitmap fonts
Operating System	UFR II: Windows® 8.1 / Windows® 10 / Windows® 11 / Windows® Server 2012 / Windows® Server 2012 R2 / Windows® Server 2016 / Windows® Server 2019 / Windows® Server 2022 / macOS (10.12 or later) PCL (Optional): Windows® 8.1 / Windows® 10 / Windows® 11 / Windows® Server 2012 / Windows® Server 2012 R2 / Windows® Server 2016 / Windows® Server 2019 / Windows® Server 2022

Copy



Copy Speed	1-sided: Up to 24 pages/min (A4), Up to 12 pages/min (A3), Up to 11 pages/min (A4R) 2-sided: Up to 16.7 pages/min (A4), Up to 7.5 pages/min (A3), Up to 7.8 pages/min (A4R)
First-Copy-Out Time (BW)	Platen: Approx. 7.4 seconds or less (A4)
Copy Resolution (dpi)	600 x 600
Multiple Copies	Up to 999 copies
Copy Density	Automatic or Manual (9 Levels)
Magnification	25% - 400% (1% Increments) Preset reduction/enlargement: 25%, 50%, 70%, 100%, 141%, 200%, 400%

Scan



Document Feeder Paper Capacity	50 Sheets (80 g/m2 (gsm))
Acceptable Originals and Weights	Platen: Sheet, Book Document Feeder sheet media weight:

	1-sided/2-sided continuous scanning: 52 to 105 g/m2 (gsm) (BW/CL) Only 1-sheet feeding is supported in 37-52 and 105-128 g/m2 (gsm)
Supported Media Sizes	Platen: Max. scanning size: 297.0 x 431.8 mm Document Feeder media size: A3, A4, A4R, A5, A5R, B4, B5, B5R Custom size: 128.0 x 148.0 mm to 297.0 x 431.8 mm
Scan Speed (ipm: BW/CL, A4)	DADF: 1-sided Scanning: 35/25 (300 dpi, send), 25 (600 dpi, copy) 2-sided Scanning: 12/8 (300 dpi, send), 8 (600 dpi, copy)
Scan Resolution (dpi)	Scan for Copy: up to 600 x 600 Scan for Send: (Push) up to 300 x 600, (Pull) up to 600 x 600
Pull Scan Specifications	ScanGear MF For both TWAIN and WIA Windows® 8.1/ Windows® 10/ Windows® 11 macOS (10.12 or later)

Send

Destination	iR2224N: Email (SMTP), SMB3.0
Address Book / Speed Dials	iR2224N: LDAP (50) / Local (300) / One-Touch (296)
Send Resolution (dpi)	Push (iR2224N): 300 x 600 (SMB/FTP/Email) Pull: 50 x 50, 75 x 75, 150 x 150, 200 x 200, 300 x 300, 400 x 400, 600 x 600
Communication Protocol	File ^{*1} : SMB3.0 (TCP/IP) Email ^{*1} : SMTP (Send)
File Format	Standard: TIFF, JPEG ^{*4} , PDF (Compact)

Security

Authentication and Access Control	Department ID Authentication (Department ID and PIN Login, Function Level Login)
Document Security	Print Security (SecurePrint, Encrypted SecurePrint), Send Data Security (Restricted E-mail/File send functions, Confirming FAX)

	number, Allow/Restrict Fax Driver Transmissions, Allow/Restrict Sending from History)
Network Security	TLS 1.3 ^{*5} , IPSec, IEEE802.1X authentication, SNMPv3, Firewall Functionality (IP Address Filtering), Enabling/Disabling (Network Applications, Remote UI, USB Interface), G3 FAX separation from LAN, USB Port separation from LAN
Device Security	Standard HDD/SSD Initialize, Job Log Conceal Function, Protecting MFP Software Integrity, Verify System at Startup (NIST SP800-193)
Device Management and Auditing	Administrator Password, Digital Certificate and Key Management ^{*6} , Security Policy Setting ^{*6}
Environmental	
Operating Environment	Temperature: 10 to 30 °C Humidity: 20 to 80% RH (Relative Humidity)
Power Source	Asia: 220-240V 50/60Hz 10A
Power Consumption	Maximum: Approx. 1,500 W Standby: Approx. 15.5 W Sleep mode: Approx. 0.9 W

Consumables

Toner Yield (Estimated Yield @ 6% Coverage)	NPG-59 TONER BK OTH: 10,200 impressions (A4)
--	--

Paper Supply Options

Feeder Options	Cassette Feeding Module-AK1
	Paper Capacity: 250 sheets x 1 (80 g/m2 (gsm)) Paper Type: Plain, Recycled, Colour, Pre-punched Paper Size: A3, A4, A4R, A5, B4, B5, B5R Paper Weight: 64 to 90 g/m2 (gsm) Power Source: Main Unit Dimensions (W x D x H): 581 x 575 x 92 mm Weight: Approx. 5.8 kg

1. iR2224N only.

2. Time from device power-on, until copy ready (not print reservation).
3. Quick start mode N/A.
4. Single page only.
5. STD only, ENT model N/A.

-
- Prices, specifications, availability and terms of offers may change without notice.
 - Products / Services may be manufactured by and/or supplied to us by third party manufacturers / suppliers for distribution / resale (non-Canon brand products).
 - Prices above are maximum retail price (MRP) and may change without prior notice.
-

