



New **Gujarat** SALES & SERVICE

Nr. Honda Show-room, Deesa Highway, Palanpur-385001
Dist. Banaskantha, N.Gujarat, India
Ph. +91 02742 261245, Mob. +91 98250 15702, 98984 87120
Website : www.gujaratpanel.com
E-mail : gujaratpanel@gmail.com



Jaleshwar Multi Print- 9426567480



An ISO 9001:2015 Certified Company

Since 1996 ®
Gujarat
PANEL

We Stand Ahead in Quality



Welcome to Gujarat Panel

We are leading Agriculture control Panel manufacturing from last 20 Years, Gujarat Panel committed to research and development Agriculture Panels. Our company provides high quality Agriculture panels with good service team. Our wide range have been developed in compliance to the diverse needs of various Agriculture and have been well responded by our customers based all over India. This has been possible because of our modern production facilities, engineering excellence and dedicated approach of the professionals working with us.

We are keeping our business principles for "Approaching the first-class management, providing the first class products, providing the first class service". All Gujarat staffs are working hard and constantly innovate. Honest Gujarat welcome to all users to fighting a better tomorrow hand in hand.

"Customer Service
is the cornerstone of our business.
We go to any lengths for our customers"

**ATS Panel
Three Phase
415 volt.
GPS - 501**
Heavy Duty 3 Door

SALIENT FEATURES

- Electronic start / stop auto system
- Electronic overload protection
- High voltage protection above 450 v
- Low voltage protection below 375 v
- Powder coated sheet metal enclosure
- Easy to Operate
- Standard indicator lamp
- Main supply wire as the standards
- Copper transformer
- Inbuilt mccb, volt meter and amp. meter



Applications :

Agriculture / Submersible pumpset in farming, Industries, Hospital, Building

Type	Maximum Submersible Pump Rating	Electronic Relay Range	Coil Voltage
GPS - 501	60 HP	34 Amp. to 110 Amp.	415
	80 HP	34 Amp. to 110 Amp.	415
	100 HP	50 Amp. to 200 Amp.	415
	150 HP	50 Amp. to 200 Amp.	415
	200 HP	50 Amp. to 200 Amp.	415



**MCCB DOL Panel
Three Phase
415 volt.
GPS - 502**
Heavy Duty 3 Door

SALIENT FEATURES

- Electronic start / stop auto system
- Electronic / Thermal overload protection
- High voltage protection above 450 v
- Low voltage protection below 375 v
- Powder coated sheet metal enclosure
- Easy to Operate
- Standard indicator lamp
- Main supply wire as the standards
- Inbuilt mccb, volt meter and amp. meter



Applications :

Agriculture / Submersible pumpset in farming, Industries, Hospital, Building

Type	Maximum Submersible Pump Rating	Electronic / Thermal Relay Range	Coil Voltage
GPS - 502	30 HP	15 Amp. to 50 Amp.	415
	40 HP	34 Amp. to 110 Amp.	415
	50 HP	34 Amp. to 110 Amp.	415
	60 HP	34 Amp. to 110 Amp.	415
	80 HP	34 Amp. to 110 Amp.	415
	100 HP	50 Amp. to 200 Amp.	415
	150 HP	50 Amp. to 200 Amp.	415
	200 HP	50 Amp. to 200 Amp.	415



**DOL Panel
Three Phase
415 volt.
GPS - 503**



SALIENT FEATURES

- Electronic start / stop auto system
- Electronic / Thermal overload protection
- High voltage protection above 450 v
- Low voltage protection below 375 v
- Powder coated sheet metal enclosure
- Easy to Operate
- Standard indicator lamp
- Main supply wire as the standards
- Inbuilt volt meter and amp. meter

Applications :

Agriculture / Submersible pumpset in farming, Industries, Hospital, Building

Type	Maximum Submersible Pump Rating	Electronic / Thermal Relay Range	Coil Voltage
GPS - 503	60 HP	34 Amp. to 110 Amp.	415
	80 HP	34 Amp. to 110 Amp.	415
	100 HP	50 Amp. to 200 Amp.	415
	150 HP	50 Amp. to 200 Amp.	415
	200 HP	50 Amp. to 200 Amp.	415



**DOL GOLD Panel
Three Phase
415 volt.
GPS - 504**



SALIENT FEATURES

- Electronic start / stop auto system
- Electronic / Thermal overload protection
- High voltage protection above 450 v
- Low voltage protection below 375 v
- Powder coated sheet metal enclosure
- Easy to operate
- Standard indicator lamp
- Main supply wire as the standards
- Inbuilt MCB, volt meter and amp. meter

Applications :

Agriculture / Submersible pumpset in farming, Industries, Hospital, Building

Type	Maximum Submersible Pump Rating	Electronic / Thermal Relay Range	Coil Voltage
GPS - 504	10 HP	9 Amp. to 13 Amp.	415
	15 HP	17 Amp. to 25 Amp.	415
	20 HP	23 Amp. to 32 Amp.	415
	30 HP	15 Amp. to 50 Amp.	415
	40 HP	34 Amp. to 110 Amp.	415



**STAR DELTA Panel
Three Phase
415 volt.
GPS - 505**



SALIENT FEATURES

- Electronic start / stop auto system
- Electronic / Thermal overload protection
- High voltage protection above 450 v
- Low voltage protection below 375 v
- Powder coated sheet metal enclosure
- Easy Operate
- Standard indicator lamp
- Main supply wire as the standards
- Inbuilt mccb, volt meter and amp. meter
- With MCCB, MCB & without MCCB, MCB

Applications :

Agriculture / Submersible pumpset in farming, Industries, Hospital, Building

Type	Maximum Submersible Pump Rating	Electronic / Thermal Relay Range	Coil Voltage
GPS - 505	10 HP	9 Amp. to 13 Amp.	415
	15 HP	12 AMP. to 18 Amp.	415
	20 HP	12 Amp. to 18 Amp.	415
	25 HP	17 Amp. to 25 Amp.	415
	40 HP	23 Amp. to 32 Amp.	415
	60 HP	37 Amp. to 50 Amp.	415
	80 HP	48 Amp. to 65 Amp.	415
	100 HP	63 Amp. to 80 Amp.	415



**STAR DELTA MCCB Panel
Three Phase
415 volt.
GPS - 506**
Heavy Duty 3 Door

SALIENT FEATURES

- Electronic start / stop auto system
- Electronic / Thermal overload protection
- High voltage protection above 450 v
- Low voltage protection below 375 v
- Powder coated sheet metal enclosure
- Easy to operate
- Standard indicator lamp
- Main supply wire as the standards
- Inbuilt mccb, volt meter and amp. meter



Applications :

Agriculture / Submersible pumpset in farming, Industries, Hospital, Building

Type	Maximum Submersible Pump Rating	Electonic / Thermal Relay Range	Coil Valtage
GPS - 506	40 HP	23 Amp. to 32 Amp.	415
	60 HP	37 Amp. to 50 Amp.	415
	80 HP	48 Amp. to 65 Amp.	415
	100 HP	63 Amp. to 80 Amp.	415
	150 HP	63 Amp. to 80 Amp.	415



**STAR DELTA
MCCB Panel
Three Phase
415 volt.
GPS - 507**



SALIENT FEATURES

- Electronic start / stop auto system
- Electronic / Thermal overload protection
- High voltage protection above 220 v
- Low voltage protection below 175 v
- Powder coated sheet metal enclosure
- Easy to operate
- Standard indicator lamp
- Main supply wire as the standards
- Inbuilt volt meter, amp. meter

Applications :

Agriculture / Submersible pumpset in farming, Industries, Hospital, Building

Type	Maximum Submersible Pump Rating	Electronic / Thermal Relay Range	Coil Voltage
GPS - 507	40 HP	23 AMP. to 32 Amp.	415
	60 HP	37 Amp. to 50 Amp.	415
	80 HP	48 Amp. to 65 Amp.	415
	100 HP	63 Amp. to 80 Amp.	415



**SINGAL PHASE
Panel
220 volt.
GPS - 508**



SALIENT FEATURES

- Thermal overload protection
- High voltage protection above 220 v
- Low voltage protection below 175 v
- Powder coated sheet metal enclosure
- Easy to operate
- Standard indicator lamp
- Main supply wire as the standards
- Inbuilt volt meter, amp. meter and Standard Capacitor

Applications :

Agriculture / Submersible pumpset in farming, Industries, Hospital, Building

Type	Maximum Submersible Pump Rating	Thermal Relay Range	Coil Voltage
GPS - 508	2 HP	17 Amp. to 25 Amp.	220
	3 HP	23 AMP. to 32 Amp.	220
	5 HP	37 Amp. to 50 Amp.	220
	7.5 HP	48 Amp. to 65 Amp.	220
	10 HP	48 Amp. to 65 Amp.	220

