Slip 4

Create a webpage containing a heading and a button. When the button is clicked, change the heading text from “Hello! Welcome” to “Text Changed Successfully!”.

HTML

Wrap linesCopiedPreview

```
<!DOCTYPE html>
<html>
<body>
<h1 id="h">Hello! Welcome</h1>
<button onclick="document.getElementById('h').innerText='Text
Changed Successfully!'">Click Me</button>
</body>
</html>
```

Copied

Slip 6

Create a webpage containing a button and link. Change their appearance when the mouse pointer moves over them. (Use :hover Pseudo-Class)

```
<!DOCTYPE html>
<html>
<head>
<style>
button:hover {
  background: blue;
  color: white;
}
a:hover {
  color: red;
  font-size: 20px;
}
</style>
</head>
<body>
<button>Click Me</button>
<br><br>
<a href="#">Visit Link</a>
</body>
</html>
```

Slip 7

Create an unordered list of Programming Language names and apply different styles to the first and last list items.(Use :first-child and :lastchild)

```
<!DOCTYPE html>

<html>

<head>

<style>

li:first-child { color: red; }

li:last-child { color: blue; }

</style>

</head>

<body>

<h2>Programming Languages</h2>

<ul>

<li>C</li>

<li>Java</li>

<li>Python</li>

<li>JavaScript</li>

</ul>

</body>

</html>
```

Slip 9

HTML
Wrap linesCopy codePreview

```
<!DOCTYPE html>
<html>
<body>
<script>
let a = 10, b = 5;
let add = (a,b) => a+b;
let sub = (a,b) => a-b;
let mul = (a,b) => a*b;
let div = (a,b) => a/b;

document.write("Addition: "+add(a,b)+"<br>");
document.write("Subtraction: "+sub(a,b)+"<br>");
document.write("Multiplication: "+mul(a,b)+"<br>");
document.write("Division: "+div(a,b));
</script>
</body>
</html>
```

Slip 10

```
<!DOCTYPE html>
<html>
<body>
<script>
let name = "Rahul", roll = 101, marks = 85;

let report = `
Student Report
Name: ${name}
Roll No: ${roll}
Marks: ${marks}`;

document.write(`<pre>${report}</pre>`);
</script>
</body>
</html>
```

Slip 11

```
<!DOCTYPE html>
<html>
<body>
<script>
let a = 80, b = 90, c = 70;
let total = (a,b,c) => a+b+c;
let avg = (a,b,c) => (a+b+c)/3;

document.write(`Total: ${total(a,b,c)}<br>
Average: ${avg(a,b,c)}`);
</script>
</body>
</html>
```

Slip 12

```
<!DOCTYPE html>
<html>
<body>
<script>
let name = "Pen", price = 10, qty = 5;
let total = (p, q) => p * q;

document.write(`Product: ${name}<br>
Price: ₹${price}<br>
Quantity: ${qty}<br>
Total Bill: ₹${total(price, qty)}`);
</script>
</body>
</html>
```

Slip 13

```
<!DOCTYPE html>
<html>
<body>
<script>
let a = 10, b = 20;
[a, b] = [b, a];
document.write(`a = ${a}<br>b = ${b}`);
</script>
</body>
</html>
```

Slip 19

```
<!DOCTYPE html>
<html>
<body>
<script>
async function login(user, pass) {
  try {
    if (user == "admin" && pass == "1234")
      return "Login Successful!";
    throw "Invalid username or password";
  } catch (e) {
    return e;
  }
}

login("admin", "1234").then(msg => document.write(msg));
</script>
</body>
</html>
```

Slip 21(Node js)

javascript

```
const path = require('path');

console.log("Join:", path.join('folder', 'file.txt'));
console.log("Resolve:", path.resolve('folder', 'file.txt'));
console.log("Directory:", path.dirname('/home/user/file.txt'));
console.log("Filename:", path.basename('/home/user/file.txt'));
console.log("Extension:", path.extname('file.txt'));
```

Slip 24(node js)

javascript

```
const fs = require('fs');

console.log("Synchronous Operation");
fs.writeFileSync('test.txt', 'Hello');
console.log(fs.readFileSync('test.txt', 'utf8'));

console.log("Asynchronous Operation");
fs.writeFile('test.txt', 'Welcome', err => {
  if (err) throw err;
  fs.readFile('test.txt', 'utf8', (err, data) => {
    if (err) throw err;
    console.log(data);
  });
});

console.log("Program End");
```

Comparison: Synchronous operations block execution; asynchronous operations allow other code to run while waiting.

Slip 1 Java

```
import java.util.*;
class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int[] a = new int[5];
        int sum = 0;

        for (int i = 0; i < 5; i++) {
            a[i] = sc.nextInt();
            sum += a[i];
        }

        Arrays.sort(a);
        System.out.println("Sum = " + sum);
        System.out.println("Ascending Order: " +
Arrays.toString(a));
        sc.close();
    }
}
```

Slip 2(java)

java

```
import java.util.Scanner;

class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        System.out.print("Enter range: ");
        int start = sc.nextInt(), end = sc.nextInt();

        for (int i = start; i <= end; i++) {
            int n = i, sum = 0, digits =
String.valueOf(i).length();

            while (n > 0) {
```

```
                int d = n % 10;
                sum += Math.pow(d, digits);
                n /= 10;
            }

            if (sum == i) System.out.println(i);
        }
        sc.close();
    }
}
```

Input: `1 500`

Output:

text

```
1
2
3
4
5
6
7
8
9
153
370
371
407
```