# CAS 741: Unit Verification and Validation Report

Dynamical Systems: MPSim

Karol Serkis serkiskj@mcmaster.ca GitHub: karolserkis

December 19, 2018

# 1 Revision History

Date	Version	Notes
Dec. 18, 2018	1.0	First full draft for submission

# 2 Symbols, Abbreviations and Acronyms

See SRS Documentation at:

 $\verb|https://github.com/karolserkis/CAS-741-Pendula/blob/master/docs/SRS/SRS.pdf| The symbols are listed in alphabetical order.$ 

symbol	description	
A	Assumption	
DD	Data Definition	
FT	Functional Test	
GD	General Definition	
GS	Goal Statement	
IM	Instance Model	
LC	Likely Change	
MG	Module Guide	
MIS	Module Interface Specification	
NF	Non-Functional Requirement	
R	Requirement	
SRS	Software Requirements Specification	
Τ	Test	
VnV	Verification and Validation	

# Contents

1	Revision History	i
2	Symbols, Abbreviations and Acronyms	ii
3	Functional Requirements Evaluation	1
4	Nonfunctional Requirements Evaluation 4.1 Usability	1 2 2
5	Comparison to Existing Implementation	2
6	Unit Testing	2
7	Changes Due to Testing	2
8	Automated Testing	2
9	Trace to Requirements	2
10	Trace to Modules	3
11	Code Coverage Metrics	3

# List of Tables

# List of Figures

This document is a review of the system tests that have been performed on MPSim . This report is a partner to the Unit VnV Report that is located in the docs/VnVReport/U-nitVnVReport directory.

# 3 Functional Requirements Evaluation

FR1 was: MPSim program should be rendered with 3D Cartesian coordinates. This requirement has been successfully met.

FR2 was: MPSim program will take the following inputs:

- 1. The number of pendulum rods in the simulation.
- 2. Toggle the ground plane to introduce friction to the pendulum rod initial moment of inertia
- 3. Toggle the plot of Potential & Kinetic Energy

This requirement has been successfully met.

FR3 was: MPSim program will calculate the kinetic and potential energy after the user has set the initialization parameters of input from the user have been entered. This requirement has been successfully met.

FR4 was: MPSim program will calculate the Lagrangian after the user has set the initialization parameters of input have been entered and the kinetic and potential energy of the system as whole has been calculated. This requirement has been somewhat met. A generic use of OpenGL and GLUT has allowed for other ways around this.

FR5 was: MPSim program will ensure that the inputs do not violate the constraints specified in the Data Constraints section:

- 1. MPSim program will generate diagrams with and plot lines and time-line of logged movement.
- 2. The time-line of swings of the pendulum will be logged and eventually return to a resting state in equilibrium

This requirement has been somewhat successfully met.

# 4 Nonfunctional Requirements Evaluation

NFR1 and subsequent requirements for the software to be portable have been met. The simulation software can run on any computer system and is contained in one Python file for convenience.

### 4.1 Usability

To make the program easy to use, the interaction with the GUI is minimal.

The user can provide a variety of input types, but because of exception handling the program will still run or provide feedback to let the user try the correct input parameters into the command-line.

#### 4.2 Performance

The performance bottleneck is most likely the running of the program on a local computer. The simulation requires some relative graphics card for calculations. Performance otherwise is not a focus of the program.

### 5 Comparison to Existing Implementation

Comparing Existing Implementation resulted in very comparable results thus the simulation was quite capable and true to life.

## 6 Unit Testing

The unit testing will be covered in more details in the UnitVnVReport. The actual implementation of the unit tests can be found in the src/ or test/ directory on the github repohttps://github.com/karolserkis/CAS-741-Pendula.

### 7 Changes Due to Testing

The actual System VnV Plan tests will be discussed henceforth. All the functional and most of the non-functional requirements have been meet.

### 8 Automated Testing

Unit-based scripts can be created for testing the modules in MPSim and be tested automatically with scripts written in pytest. The test scripts using pytest will cycle through an array of data and check an assert statement. See section on verification tools for more information.

### 9 Trace to Requirements

This section will be covered in the Unit VnV Report. All functional requirements met.

## 10 Trace to Modules

This section will be covered in the Unit VnV Report. Not enough tests have been performed to assess the proper behaviour of the modules in MPSim .

# 11 Code Coverage Metrics

Current code coverage metrics can be found in the test scripts using pytest will cycle through an array of data and check an assert statement. See section on verification tools for more information.

Name	Cover				
src/MPSim.py	1/3 tests				
src/MPSim_inputargparse_test.py	7/8 tests				
test/sim_inputargparse_test.py	7/8 tests				
\$ pytest-3					
platform linux — Python 3 6 7 pytest	$z = 3 \ 3 \ 2  \text{pv} = 1 \ 5 \ 2  \text{pluggy} = 0 \ 6 \ 0$				
platform linux — Python 3.6.7, pytest -3.3.2, py-1.5.2, pluggy-0.6.0 rootdir: /mnt/c/Users/Karol/CAS-741-Pendula/src, inifile: collected 8 items					
MPSim_inputargparse_test.pyx [100%]					
======================================	.19 seconds ======				