
Intelligent Agents

From Decision Theory to Modern Agentic AI

Kumar Arpit

Gisma
University
of Applied
Sciences



Gisma University of Applied Sciences

The Next 45 Minutes

Eight parts. One running example: **3 days in Lisbon on a 600 € budget**. Opening: 0–3 min.

1	**What Is an Agent?** Definition, the agent cycle, history	**3–9′**
2	**Deciding Under Uncertainty** How to choose when you can't be sure	**9–16′**
3	**Learning to Decide** Repeated choices and choices that shape the future	**16–21′**
4	**Learning From Feedback** What really changes when an agent "learns"	**21–26′**
5	**Modern Agentic Architectures** LLMs, tools, memory, many agents	**26–30′**
6	**Building Reliable Agents** Design rules, then my n8n + Ollama workspace	**30–40′**
7	**Evaluation and Impact** Does it work, and for whom?	**40–43′**
8	**Future of AI** Where agents are heading, then your questions	**43–45′**

Our Running Example

"Plan me a three-day trip to Lisbon. My budget is 600 euros. I love museums and good food, I hate early mornings, and here's a hotel I liked."

hotel_screenshot.png

Every idea today = something this agent needs to get right.



LLM + tools + memory, running in a loop, is how agents are **built**. It is not what makes them **good**.

The loop is the body.
The decisions are the intelligence.

Know · Decide · Learn · Verify



Gisma
University
of Applied
Sciences

PART 1 · 3–9 MIN

What Is an Agent?

1

What turns a language model into an agent?

- Definition
- The agent cycle
- Three kinds of AI
- Classical designs
- History
- The formal model

Gisma
University
of Applied
Sciences

What Is an Intelligent Agent?

- **An agent pursues a goal in a loop**
  - Perceives its environment through observations
  - Keeps a picture of the situation, with uncertainty
  - Acts, then observes the consequences
- **The loop defines it, not the technology**
  - Thermostats, chess programs and LLM planners are all agents
  - They differ in how good their decisions are
- **"Agent" describes how a system is organised**
  - Not a guarantee that it is reliable or intelligent
  - A bad agent can loop forever or invent facts confidently

Thermostat

Perceives: Senses temperature

Acts: Switches heating

Chess program

Perceives: Sees the board

Acts: Moves a piece

Self-driving car

Perceives: Cameras, radar

Acts: Steers, brakes

Travel planner


Perceives: Messages, search results

Acts: Searches, plans, asks

Same loop. Very different decision quality.

The Agent Cycle

An agent perceives, decides under uncertainty, acts, and learns from what happens.



From Chatbot to Agent

A chatbot

> You: “Where should I go for 3 days?”
>
> **Bot: “You should visit Lisbon!”**

× Produces text

× Takes no actions

× Never sees a consequence

An agent

1. Searches hotels
2. Adds up the cost: **680 €**
3. Notices: over budget
4. Swaps to a cheaper hotel
5. New total: **590 €** ✓

An agent acts, observes the result, and changes what it does next.

Same Model, Three Kinds of System

Traditional AI

Predicts or classifies

"Will this hotel get more expensive next month?"

Generative AI

Creates content

"Write me a guide to Lisbon's museums."

Agentic AI

Acts, observes, adapts

Searches, checks the budget, revises the plan, knows when to stop.

"Agentic" describes the system around the model, not the model.

Classical Agent Architectures

- **Simple reflex agents**
  - Fixed condition–action rules on the current input only
  - "If the user says 'cheap', show hostels." No memory
- **Model-based reflex agents**
  - Keep an internal state about what they can't see now
  - Remember the user said "vegetarian" three messages ago
- **Goal-based agents**
  - Have an explicit goal and plan steps to reach it
  - Ask: "What will happen if I do this?"

+ Rules

React to what is in front of you

+ Memory

Track what you can no longer see

+ Goals and planning

Look ahead to reach a target

Classical Agent Architectures

- **Utility-based agents**
  - Score how good each outcome is, not just “goal met?”
  - Trade off: cheap but far, or central but pricey?
- **Learning agents**
  - A critic judges performance; a learner changes behaviour
  - Improve from feedback across many trips
- **Modern LLM agents mix all five**
  - Guardrails are reflex rules; chat state is model-based
  - Finishing the task is goal-based; trade-offs are utility-based

+ Utility

Weigh competing outcomes

+ Learning

Get better with experience

LLM agents

A mix of all of the above

Five Classical Agent Designs

Each step up the stairs decides more cleverly.

☆ **Modern LLM agents mix all five**

Simple reflex

Rule: “cheap” → hostels

Model-based

Remembers: user is vegetarian

Goal-based

Plans steps to finish 3 days

Utility-based

Trades price against location

Learning

Improves from feedback over many trips

A Bit of Agent History

1950s–80s

Rules and logic

Shakey and STRIPS, expert systems like MYCIN

Transparent, but brittle

1990s

Rational agents

Expected utility, belief-desire-intention agents

Model uncertainty explicitly

1990s–2010s

Learning from reward

TD-Gammon, DQN on Atari, AlphaGo

Superhuman when the reward is clear

2022 →

LLM agents


ReAct, tool calling, MCP, A2A, coding agents

Broad, but weak at checking themselves

The newest era didn’t replace the old ideas. It needs them.


A Bit of Agent History

- **Era 1: rules and logic (1950s–80s)**
  - Shakey the robot (SRI, 1966–72) planned with STRIPS
  - Expert systems like MYCIN: specialist if–then rules
  - **Lesson:** transparent and explainable, but brittle
- **Era 2: rational agents (1990s)**
  - Choose the action with the best expected outcome
  - Belief–desire–intention (BDI): beliefs, goals, plans
  - **Lesson:** represent uncertainty and preferences explicitly



A Bit of Agent History

- **Era 3: learning from reward (1990s–2010s)**
  - TD-Gammon (1992): expert-level backgammon
  - DQN (2013–15) learned Atari from pixels; AlphaGo (2016)
  - **Lesson:** superhuman when reward is clear and practice cheap
- **Era 4: LLM agents (2022 →)**
  - ReAct (2022): interleave reasoning and actions
  - Tool calling (2023), MCP (2024), A2A (2025)
  - **Lesson:** broad skills, but poorly calibrated, weak self-checks



An Agent Acts on Beliefs

[Murphy 2023, §34.5.2, p. 1117]

POMDP element	In our travel agent
True state	Real prices, opening hours, what the user truly wants
Observation	The message, search results, the screenshot
Belief	“Hotel probably 95–110 €; user probably prefers central”
Action	Search, calculate, ask, revise, stop
Reward	User satisfaction minus money, time and interruptions
Policy	The LLM plus its workflow code

Context + memory = belief · LLM + workflow = policy

PART 2 · 9–16 MIN

Deciding Under Uncertainty

How should an agent choose when it can’t be sure what will happen?

2

Beliefs | Expected utility | Constraints | Value of information | Explore vs exploit | Regret | Fairness | Test and roll | Empirical Bayes



Gisma University of Applied Sciences

Beliefs With Confidence

[Murphy 2023, §3.2, pp. 65–72]

Good agents hold beliefs, not facts

- Every estimate carries a degree of confidence
- Stating a guess as a fact is a classic agent failure

Bayes: update beliefs with evidence

- **Prior:** what you believed before
- **Evidence:** what you just observed
- **Posterior:** the updated belief

Uncertainty tells the agent what to do

- A wide range says: check the live price first
- It also warns the user the figure is an estimate

⚠ **Sounds certain**

"The hotel costs 90 € a night."

✓ **Honest belief**

"Probably about 90 €, from last year's listing. Could be 80–120 €."



Gisma University of Applied Sciences

Utility and Rational Choice

[Murphy 2023, §34.1, pp. 1093–1098]

- **Utility: how good an outcome is**
  - Measured for the person the agent serves
  - Lets very different outcomes be compared
- **Rational agents maximise expected utility**
  - Weigh each outcome by its probability
  - Pick the best average (Bayesian decision theory, §34.1.3)
- **Neither optimist nor pessimist**
  - Don’t chase the best case
  - Don’t just play it safe either

THE RECIPE

1. List the possible actions
2. List the outcomes and how likely each is
3. Score each outcome: its utility
4. Average the scores, weighted by probability
5. Pick the action with the best average

Gisma University of Applied Sciences

Weigh Outcomes by Likelihood

[Murphy 2023, §34.1, pp. 1093–1098]

Day 2: coastal hike or museum? The forecast says **60% sun, 40% rain**.

Coastal hike

Sunny (60%) → 10 · Rainy (40%) → 2

$0.6 \times 10 + 0.4 \times 2$

6.8 **Best average**

Museum

Sunny → 6 · Rainy → 6

$0.6 \times 6 + 0.4 \times 6$

6.0

Not the best case. Not the safest. The best average: expected utility.

Rules Are Not Wishes

Must: hard constraints

- Total cost at most 600 €
- Step-free routes, if needed
- Vegetarian meals, if needed

Valid or invalid. Never traded off.

Would like: preferences

- Lots of museums
- Good food
- No early mornings


Better or worse. Traded off against cost.

⚠ A 680 € plan isn't "better". It's invalid.

Value of Information

[Murphy 2023, §34.2, pp. 1099–1102]

- **Gathering information is an action**
  - Calling a tool, searching, asking the user
  - It costs time, money or patience
- **Worth it only if it could change the decision**
  - Two indoor museums? The forecast changes nothing: worth 0
- **Imagine a perfect forecast**
  - Sun (60%): pick the hike, get 10
  - Rain (40%): pick the museum, get 6
  - Average: $0.6 \times 10 + 0.4 \times 6 = \mathbf{8.4}$



8.4 with the forecast vs 6.8 without

Value of Information

[Murphy 2023, §34.2.3, pp. 1101–1102]

1.6

What a perfect weather forecast is worth here

Without forecast

Pick the hike: average **6.8**

With a perfect forecast

Hike if sunny, museum if rainy: average **8.4**

Value of information

8.4 − 6.8 = **1.6**. Check only if checking costs less.

✓ **Ask:** "Is 600 € a hard limit?"

⚠ **Don't ask:** "What's your shoe size?"

Only ask if the answer could change what you do.

When Should an Agent Ask?

- **Asking the human is information gathering**
  - Same rule: ask only if the answer could change the plan
  - Never asking and always asking both fail
- **In theory: compute each question's value**
  - Needs confidence that matches reality
- **In practice: LLMs are poorly calibrated**
  - Stated confidence ≠ how often they are right
  - So designers turn the principle into rules

Rule 1: always ask when a hard constraint is ambiguous.

Rule 2: always ask before an irreversible action.

OPEN RESEARCH PROBLEM

Closing the gap between the ideal value-of-information rule and what poorly calibrated models can actually compute.

Explore or Exploit?

Every pull of the lever gives a **reward** and some **information**.

Exploit

Use the option that looks best so far

Explore

Try an uncertain option that might be better

Regret

What you lose by not knowing the best option from the start

Your favourite restaurant vs the new place next door




Gisma University of Applied Sciences

Regret: Measuring Decision Quality

[Murphy 2023, §34.4.7, pp. 1114–1115]

- **Regret: what you lost by not knowing the best option**
  - Compare with an agent that knew it from the start
- **Explore too little**
  - Stuck on a mediocre option: regret grows steadily
- **Explore too much**
  - Keep paying for needless experiments: regret grows too
- **Good strategies**
  - Regret grows more and more slowly as they focus




Low regret = learning fast what's best

Fairness in Decision-Making

[Murphy 2023, §34.1.5.6, pp. 1095–1098]

- **The objective decides who is served well**
  - Maximising average satisfaction can fail a minority
  - e.g. travellers who need step-free routes
- **Fairness as constraints on decisions**
  - **Equal opportunity:** among people who truly qualify, "yes" at equal rates across groups
  - **Equalised odds:** correct and wrong "yes" rates equal across groups
- **Definitions can conflict**
  - Often they can't all hold: choosing is a value judgement




Average 8.2 looks great. Ask: for whom?

Optimal Sample Size: Test and Roll

[Murphy 2023, §34.3, pp. 1103–1107]

- **A/B test: try two versions, roll out the winner**
  - PML2 calls this “test and roll”
- **Testing has a price**
  - Test users who get the worse version lose out
  - It is exploration vs exploitation again
- **There is an optimal test size**
  - Bigger when outcomes are noisy
  - Smaller when you expect a big difference




Test enough to choose well. Not more.

Test and Roll: A Worked Example

[Murphy 2023, §34.3.1, pp. 1103–1106]

- **Setting**
  - 10,000 requests next term; current agent succeeds ~60%
  - New versions usually differ by a few points
- **Test and roll**
  - Test each version on **~423** requests (~850 total)
  - Roll the winner out to the other ~9,150
- **Classical power analysis**
  - 80% sure of spotting a 5-point gap: **~1,500** per version
- **Ask the right question**
  - Not “is the gap real?” but “what helps users most overall?”



Empirical Bayes: Borrowing Strength

[Murphy 2023, §3.7, pp. 115–118]

- **Little data → unreliable estimates**
  - New restaurant: two reviews, both 5★
  - Established one: 500 reviews, 4.4★ on average
- **Learn the prior from many similar cases**
  - What scores are typical, and how much they vary
  - "Empirical": the prior is estimated from data
- **Shrink each estimate toward typical**
  - Few reviews: pulled strongly; many: barely move
  - $(2 \times 5 + 10 \times 4.0) \div 12 \approx \mathbf{4.17}$



Recap: Three Tools From the Book

[Murphy 2023, §34.1.5.6, §34.3.1, §3.7]

How to judge a decision rule, and how to estimate from little data.

Fairness

Average ≠ everyone

Maximising average satisfaction can keep failing a minority. Fairness definitions can conflict.

Optimal sample size

~423 vs ~1,500

Test size per version in our example: optimise total benefit (test and roll), not certainty (classic power analysis).

Empirical Bayes

4.17, not 5

Two 5-star reviews get pulled toward the 4.0 average of similar places.

Criteria and estimation methods, not agent architectures.

PML2 §34.1.5.6 · §34.3.1, pp. 1103–1106 · §3.7, pp. 115–118

PART 3 · 16–21 MIN

Learning to Decide

3

What if choices repeat, or change what happens next?

Bandits | UCB and Thompson sampling | Contextual bandits | MDPs | Long-term reward | Planning | Active learning

Gisma University of Applied Sciences

Multi-Armed Bandits

[Murphy 2023, §34.4, pp. 1107–1115]

- **Slot machines with unknown payouts**
  - Each round: pull one arm, see the reward
  - Goal: the most total reward
- **The purest explore–exploit problem**
  - Every pull gives a reward and information
  - Your choice does not change the machines
- **In our travel agent**
  - Which source should research trust today?
  - Each source's reliability is unknown




Each "arm" = one information source

Learn which arm is best while still winning.

Two Bandit Strategies

- **UCB: optimism in the face of uncertainty**
  - Imagine each option's plausible best value
  - Pick the highest: rarely tried options get a chance
- **Thompson sampling: the Bayesian way**
  - Draw one imagined value per option from beliefs
  - Pick the best draw, observe, update
  - Each option is chosen as often as it's likely to be best
- **Both keep regret growing slowly**
  - PML2 §34.4.7, pp. 1114–1115



Two Smart Ways to Explore


Multi-armed bandit: which of three price sources should the agent trust today?

UCB: optimism

Give rarely tried options the benefit of the doubt. Try what could plausibly be best.

Thompson sampling


Imagine each option's value from your beliefs, pick the winner, then update.




Contextual Bandits

[Murphy 2023, §34.4, from p. 1107]

- **The best choice depends on the situation**
  - Observe the context first, then choose
- **Same request, different travellers**
  - Family with small children vs solo backpacker
  - Different hotels are best for each
- **Behind most recommender systems**
  - Recommendations, online ads, personalised content
  - Still assumes today's choice doesn't change tomorrow





Observe → choose → learn, one decision at a time.

Choices That Change Tomorrow

A **Markov decision process** (MDP): every move reshapes the next position.


States **Actions** **Transitions** **Rewards**

Markov property

The 6 a.m. flight

Saves 40 € today. Costs the traveller day one. Judge choices by the **total return**.


Bandit: choose well now. MDP: plan for what comes next.



Markov Decision Processes

[Murphy 2023, §34.5, pp. 1116–1119]

- **When today's action changes tomorrow**
  - A hotel in Belém changes every later travel time
- **Five ingredients**
  - **States:** where, when, budget left
  - **Actions:** what the agent can do in each state
  - **Transitions:** what happens next, with probabilities
  - **Rewards:** how good each step is
- **The Markov property**
  - The current state holds all that matters from the past



Transition probabilities (illustrative)

Gisma University of Applied Sciences

Short-Term vs Long-Term Reward

[Murphy 2023, §34.5.3–34.5.5, pp. 1117–1119]

- **The return: total reward over time**
  - Not just the next step
  - Future rewards are often discounted a little
- **Greedy agents only see the next step**
  - The 6 a.m. flight saves 40 € today…
  - …and costs the traveller most of day one
- **Value function**
  - "How good is this state, counting all that follows?"
  - Compare situations by long-term prospects

06:00 flight

+40 € now

Exhausted, day one lost

Total return: worse

10:30 flight

−40 € now


Fresh for day one

Total return: better

Planning and Feedback Loops

[Murphy 2023, §34.6, pp. 1120–1123]


- **Planning: look ahead before acting**
  - Simulate action sequences and their consequences
  - Value iteration: start with rough guesses of each state's value…
  - …improve them until they stop changing
- **Feedback: correct after acting**
  - See what actually happened and adjust
- **Good agents do both**
  - Plan with current beliefs, then act, observe, update, replan



Active Learning

[Murphy 2023, §34.7, from p. 1124]

- **Choose which data to collect next**
  - Don’t label thousands of random examples…
  - …ask where the model is most unsure
- **Value of information, applied to learning**
  - A label is worth asking for if it changes the model
- **Humans in the loop**
  - People correct outputs, approve decisions, give labels
  - In our system: a human approves the final plan



PART 4 · 21–26 MIN

Learning From Feedback

4

When an agent “learns”, what actually changes?

Reinforcement learning | Reward design | Reward hacking | RLHF | Continual learning | Memory vs learning | Hallucination




Gisma University of Applied Sciences

Reinforcement Learning

[Murphy 2023, §35.1, pp. 1133–1137]

- **Learn a policy from rewards, by trial and error**
  - Nobody tells the agent the correct action
  - It discovers what leads to high reward
- **The loop**
  - Agent sees a state and takes an action
  - Environment returns a reward and a new state
- **Explore vs exploit, in full sequential form**
  - §35.1.5, pp. 1136–1137



Three Families of RL Methods

[Murphy 2023, §35.2–35.4, pp. 1138–1158]

§35.2

Value-based

Learn how good each action is in each state, then pick the best.

Q-learning · DQN on Atari

§35.3

Policy-based

Directly make high-reward actions more likely.

PPO (§35.3.4)

§35.4

Model-based


Learn how the world works, then plan with it.

Plan in your head first

Imitation learning (§35.6.3): copy an expert's demonstrations instead of learning from reward.

Reward Design

- **Agents optimise exactly what is rewarded**
  - Not necessarily what the designer meant
- **A reward is usually a proxy for the goal**
  - When proxy and goal diverge, a strong optimiser finds the gap
  - This is reward hacking
- **Design lessons**
  - Check anything checkable directly, not via a proxy
  - An evaluator's score ≠ the user's satisfaction



↑ reward hacking lives here

Reward Hacking

Agents optimise what you measure, not what you mean.

Essays graded on word count	⚡	**Long essays, not good ones**
Judge rewards many sources	⚡	**Padded source lists**
Coding agent rewarded for passing tests	⚡	**Code that special-cases the tests**

Defence: check outcomes directly, and read real samples.

Gisma University of Applied Sciences

How Assistants Learn What We Prefer

[Murphy 2023, §22.4.1, pp. 815–816]

RLHF: reinforcement learning from human feedback, in three steps.

1 • Humans rank

Raters compare two itineraries and pick the better one.

2 • Learn a scorer

A reward model learns to predict which answer people prefer.

3 • Tune the model

RL fine-tuning makes the LLM score highly with that scorer.

⚠ **Can be hacked too:** models learn to be verbose, agreeable or overconfident because raters liked it.

This is how the model was **trained**, not what happens when the agent **runs**.

RLHF: Learning From Preferences

[Murphy 2023, §22.4.1, pp. 815–816]

- **People compare better than they score**
  - "Which of these two is better?" is easy
  - "Rate this from 1 to 10" is noisy
- **Preference learning**
  - The reward model learns a score from comparisons
- **RL fine-tuning, on a leash**
  - e.g. PPO (§35.3.4) pushes toward high scores…
  - …while staying close to the original model
- **Trained once, not while running**
  - At run time the weights are fixed

Itinerary A

3 museums/day, rushed, 598 €

Itinerary B

2 museums/day, long lunches, 560 €


👍 **Rater prefers B**

⚠ **LLM agents are not automatically RL agents.**

Online vs Continual Learning

[Murphy 2023, §19.7, pp. 750–755]

- **Online learning (§19.7.5)**
  - Update the model as data arrives, bit by bit
- **Continual learning**
  - Gain new skills over time without losing old ones
- **Catastrophic forgetting (§19.7.4)**
  - Training on new data overwrites what was learned
- **Drift**
  - **Domain drift:** the data changes
  - **Concept drift:** what the task means changes



Still an open problem.

Remembering Is Not Learning

[Murphy 2023, §19.7, pp. 750–755]

"The agent learned." Three very different things can change.

MEMORY

The sticky note

"Guest is vegetarian" is saved and read next time.

Model unchanged

WORKFLOW

The recipe book

A designer adds a rule: always check museum opening days.

Model unchanged

WEIGHTS

The chef goes to school

The model is fine-tuned on thousands of rated itineraries.

Model changed

When an assistant "remembers you", it usually wrote a sticky note.

Hallucination and Overclaiming

- **Hallucination**
  - Fluent but false: prices, opening hours, sources
- **Overclaiming**
  - More confidence than the evidence supports
- **Phantom actions**
  - “I have booked your hotel” when nothing was booked
  - Dangerous: agent actions have real consequences
- **Defence**
  - Check the actual tool result, not the model’s story about it

> **“Done! I’ve booked Hotel Alfama for 3 nights.” ✔**

WHAT THE LOGS SAY

```
booking_api.calls = 0
reservation_id = null
status = NOT BOOKED
```

Trust the log, not the message.

PART 5 · 26–30 MIN

Modern Agentic Architectures

What turns a language model into a working agentic system?

5

Reasoning loops | Tools | Skills and memory | Multimodal | Multi-agent | MCP and A2A | Failure modes



Gisma University of Applied Sciences

LLM-Based Agents

- **The LLM is the decision-maker**
  - Reads its context: task, chat, tool results, notes
  - Proposes one action: answer, call a tool, delegate, ask, stop
- **The system executes it**
  - Adds the result to the context, asks again
- **Reason, act, observe, repeat**
  - Interleaving reasoning and actions (ReAct)
  - The basic pattern of modern agents

A TRACE (ILLUSTRATIVE)

```
Thought: I need live prices first.
Action: search_hotels("Lisbon", 3)
Observe: Casa Alfama, 110 €/night
Thought: 330 € on hotel, 270 € left.
Action: get_museum_prices(...)
Observe: 3 museums, 42 € total
Thought: within budget. Draft plan.
```

Tools, Skills and Memory

- **Tools observe and act**
  - **Observe:** search, prices, maps, weather
  - **Act:** send messages, write files, book
- **A tool call is only a proposal**
  - The model writes a structured request; the system runs it
  - Check permissions; validate inputs and results
- **Skills and memory**
  - **Skills:** packaged know-how, loaded when needed
  - **Working memory:** this task only
  - **Long-term memory:** across sessions, with privacy care


PROPOSED TOOL CALL

```
{
"tool": "search_hotels",
"city": "Lisbon",
"nights": 3,
"max_price": 120
}
```

- ✓ **Research Agent may call this tool**
- ✓ **Inputs valid · result plausible**

Inside a Modern Agent

The LLM proposes one action at a time: answer, call a tool, delegate, ask, stop.



MCP

Connects an agent to **tools and data**


A2A

Connects agents to **other agents**

⚠ **More agents ≠ better:** more calls, more cost, shared blind spots.


Multimodal Agents

- **Agents that work beyond text**
  - Images, audio, voice, or combinations
- **A separate perception step**
  - One model turns an image or speech into structured data
  - Text-focused agents then use that data
- **A property of the pipeline, not a given**
  - Voice usually needs its own speech-to-text step



Multi-Agent Systems

- **Divide the work among specialists**
  - Specialists: research, budget, planning, evaluation
  - A supervisor delegates and combines results
- **Agents talk, and may disagree**
  - They exchange structured messages
  - Conflicting conclusions must be resolved
- **More agents ≠ better**
  - More calls, latency, cost, coordination
  - Same underlying model → shared blind spots



⚠ **Add an agent only when it earns its cost.**


Interoperability: MCP and A2A

- **MCP: Model Context Protocol (2024)**
  - Standard way to connect an agent to tools and data
  - A tool exposes an MCP server; any MCP agent can use it
- **A2A: Agent2Agent (2025)**
  - Standard way for agents to talk to and delegate to agents
  - Even across companies and frameworks
- **Complementary, not competing**
  - MCP: agent ↔ tools · A2A: agent ↔ agent



Reliability: How Agents Fail

- **Hallucination**
  - Invented facts, prices, opening hours, sources
- **Prompt injection**
  - Text in a web page or image that gives orders
  - LLMs read instructions and data the same way
- **Unverified tool results**
  - Trusting a tool, or its summary, without checking
- **Poor calibration**
  - Confidence does not match accuracy



↑ **hidden text: prompt injection**

Retrieved content is data, never instructions.

PART 6 · 30–40 MIN

Building Reliable Agents

6

How do you design an agent you can actually trust?


- Do you need an agent?
- Supervisor–worker
- Judges and bounded loops
- Code checks
- Guardrails
- Escalation
- Then: live in n8n + Ollama



Gisma
University
of Applied
Sciences


Do You Need an Agent?

- **Use an agent when the task needs**
  - Multiple steps
  - Decisions under uncertainty
  - Feedback: adapt to what you find, then revise
- **Otherwise, a fixed workflow wins**
  - Simpler, cheaper, more reliable
  - A workflow with an LLM inside is not automatically an agent
- **Give each agent a narrow job**
  - Clear task, defined inputs and output, only the tools it needs



Supervisor–Worker Pattern

- **The supervisor**
  - Breaks the request into subtasks
  - Delegates and routes feedback to the right specialist
  - Decides when to stop
- **Shared state**
  - One versioned record everyone works from
  - Without it, agents hold diverging copies of the truth
- **Parallel vs sequential**
  - Independent tasks run side by side
  - Dependent tasks wait for their inputs



Shared state: request · facts + sources · plan versions · verdicts

Judge Agents and Bounded Loops

- **A judge checks against explicit criteria**
  - Returns structured feedback: what failed, evidence, who fixes it
- **The loop must be bounded**
  - e.g. one draft plus two revisions
  - Plus time and cost limits
- **A judge is a second opinion, not an oracle**
  - Same model → may share the same mistakes
  - Test it against careful human judgements

STRUCTURED JUDGE FEEDBACK

```
verdict: "revise"
failed: "budget"
evidence: "680 € > 600 €"
overrun: 80 €
responsible: ["Budget", "Planner"]
iteration: 1 of 3
```

No infinite loops: cap it, then hand to a human.

Code Checks and Guardrails

[Murphy 2023, §34.1.1–34.1.3, pp. 1093–1095]

- **If code can check it, code should**
  - Sum costs, date clashes, opening hours, required fields
  - Code doesn't hallucinate arithmetic
- **Least privilege**
  - Each agent gets only the access it needs
- **Limits and validation**
  - Allow-lists for tools; validate inputs and outputs
  - Caps on steps, time, cost: at the cap, stop and escalate
- **Humans approve consequential actions**
  - A wrong museum is easy to fix; a wrong payment isn't

Agent	Read	Edit plan	Book
Research	✓	×	×
Budget	✓	×	×
Planner	✓	✓	×
Judge	✓	×	×
Human	✓	✓	✓


Permissions in our system

The LLM proposes. Code and humans dispose.

Knowing When to Stop or Escalate

[Murphy 2023, §19.3.2–19.3.3, pp. 733–736]

- **Selective prediction (§19.3.3)**
  - Decline when too uncertain; hand over to a human
- **Out-of-distribution inputs (§19.3.2)**
  - Spot requests unlike anything the system was built for
- **Observability: show the trace**
  - Which agent did what; every tool call, in and out
  - Every revision, its reason, and why the run stopped
- **A lucky good answer is not evidence**



Same agent, three different right moves

PART 7 · 40–43 MIN

Evaluation and Impact

7

It worked in the demo. Does it actually help, and for whom?

- Two causal questions
- Demos vs evidence
- Randomised trials
- Applications
- Risks
- Case study



Gisma
University
of Applied
Sciences

Two Different Causal Questions

[Murphy 2023, Ch. 36, from p. 1171]

INSIDE THE TASK

Can the agent reason about causes?

"The plan failed because the museum is closed on Mondays. Moving it to Tuesday will fix it."

OUT IN THE WORLD

Does deploying the agent change outcomes?

Satisfaction, time saved, error rates, compared with not having the agent.

An agent can reason well and still not help. Or the reverse.

A Demo Is Not Evidence

⚠ Beware confounders

Agent users were happier. But the agent went mostly to frequent travellers, who are happier anyway.

Fix: randomise who gets the agent, like a drug trial.

Design compared	Question it answers
Single LLM	The baseline
Multi-agent, one pass	Does specialisation help?
Multi-agent + judge loop	Does feedback help, and at what cost?


A demo shows what is possible, not how often it works, or for whom.

Measure on many requests, not one:

- Task success
- Accuracy and evidence
- Constraint compliance
- Latency and cost
- Tool reliability
- Escalation rate

Measuring the Effect

- **Randomised controlled trial (§36.3)**
  - Randomly assign who gets the agent
  - Groups match on average, except for the agent
  - A/B testing is exactly this
- **When you can't randomise**
  - Adjust for confounders (§36.4)
  - Staggered rollout: difference-in-differences (§36.6)
- **Check robustness (§36.7)**
  - Placebo tests and sensitivity analyses



Random assignment: ● agent vs ● no agent

Randomise, then compare.

Applications and Risks

Where agents are used

- **Healthcare:** documentation, triage support
- **Finance:** research, compliance checks
- **Education:** tutoring, feedback
- **Logistics:** routing, scheduling
- **Software:** coding agents: most mature
- **Science:** literature, experiment planning

What can go wrong

- ⚠ Hallucinations
- ⚠ Bias and fairness
- ⚠ Privacy and security
- ⚠ Prompt injection: unsolved
- ⚠ Cost, latency, coordination
- ⚠ Accountability: who is responsible?

Very different domains, very different readiness and risk.

Two AI Steps, Zero Verification

[CNN, 18 Sep 2026, anonymous sources]

Case study · as reported by CNN, citing anonymous sources



The report falsely claimed the ship carried nuclear-weapons components. One source said it "almost started a war." No on-record official confirmation was reported.

The failure was the system design, not just the model.

PART 8 · 43–45 MIN

Future of AI

Bigger models, or systems that learn and improve themselves?

8

Long-horizon autonomy | Verifiable rewards | Continual learning | World models | Discussion

Gisma University of Applied Sciences

Where Agents Are Heading

Long-horizon autonomy

The length of task agents finish reliably has doubled about every 7 months since 2019 (METR).

Links to Part 3

Verifiable rewards

Train agents with RL on outcomes a computer can check: tests that pass, proofs that verify.

Links to Part 4

Continual learning

The open problem: improve on the job without forgetting what you already know.

PML2 §19.7


Better judgment, not just bigger loops.

Gisma University of Applied Sciences

Why Long Tasks Are Hard

[Murphy 2023, §34.5.3, pp. 1117–1118]

- **Long tasks = many decisions in a row**
  - Small errors compound over the steps
- **At 99% reliability per step**
  - 10 steps: about 90% success
  - 100 steps: only about 37%
- **So each step must be reliable**
  - Verification and recovery matter more as tasks grow
- **Task length keeps growing**
  - Doubled about every 7 months since 2019 (METR)



Beyond Today's Agents

[Murphy 2023, §19.7, §34.7, §35.4]

Continual learning §19.7

Improve on the job without forgetting

World models §35.4

Predict consequences before acting

Agents that experiment §34.7

Choose the next experiment by active learning

Neural + symbolic Our budget check


A model proposes; a rule verifies

Today agents take notes. Next: agents that truly learn.

DISCUSSION

Will the next breakthrough come from bigger models, or from systems that learn, reason, experiment and improve themselves?

Thank you! Questions?



Gisma University of Applied Sciences

Photos: Unsplash · Timur Seyfelmlyukov, Daniel van den Berg, Cindy F, Tono Graphy, Annamaria Kupo