Olho 3 sata-	761294 MHT 180. TUESDAY
Ostos of Leaphdudy	94/115 Midachhi ma October
OTHER SERVICE MANER	986445 Hydroctatic non October 186445 19445 25
. 6	) Telchandler:
	fooklifts MAT: 790-med
and the second of the	
5 Mantau and	Manlift. MT 629 already
Mantau and	@ Boon can be extended
	Boon up (hughe)
+	Machine police verall up from
W. Priston	tening who right come - bland spot .
way would be	
and the papers Air	
the said of the	300 mm above ground.
y Epinc with	dow travel who wan extended.
- Floor with	Nervyee: load serior this angle
	sever plus boom yterder
	machine limited to 3 buller
to	Missay What are Blinno handling
10	Person in cays: Machine but an
	a beauch. (note: Josekon machine
	to fullhor lusin)
	· Insugrated cage control.
16	- pallet: furth tilked brank for load
	to here against back net .
- 3	Paty + load knowledge is contral
(	E) Forklifts: drum broken fuglerostates
	toque courter.
	Application must be checked
• 10.40	1 1/4 con 1 d
- 0	Store: Mondiff can: hard
5 T 1	types a there . more as

	MHT-X 790
Lifting	10000000
Max. capacity at 600 mm LC	9 000 kg
Max, lifting height	6.84 m
Max. outreach	3.72 m
Unladen time	
Lifting	925
Lowering	7.8 \$
Protension	665
Retraction	615
Tyres	445/66 R22.5
Braking	
Service brake	Multiple-disc brake with oil bath on front and rear axles
Parking brake	Automatic negative parking brake
Engine	John Deere Stage III a
Type	4045 PWX
Displacement	45
Power	127 HP / 102 WW
Max. torque	545 Nm / 1500 rpm
Injection	Direct
Laden drawbar pull	10905 daN
Gradeability (laden)	49%
Transmission	Hydrostatic
Reversing shift	electroly/draulic control
Number of gears (forward/reverse)	3/2
Max. travel speed (mayvary according to applicable regulations)	30 kph
научау эссония по аррисаем педалиния; Амія	DANA
Actio	CONTRACTOR OF CO
Steering mode	4Wheel Steer - 3 steering modes
Controls	JSM* Joystick multi-function - Load limiter cut off system - EN 15000 Norm
Hydraulics	Axial piston variable displacement pump (LS)
Load Sensing Pump	180 V min - 270 bar
Capacities	
Hydraulic oil	1511
Fuel	1501
Unladen weight (with forks)	13 020 kg
Dimensions	
Overall length to carriage	5.27 m
Ground clearance	0.41 m
Overall width	2.47 m
Overall height	2.48 m
Standard forks	1200 x 200 x 60 mm
	****
Turning radius overtyres (V2)	4.88 m
Carriage Rotation (crowd / dump) Noise and vibration	137 °
	20.70
Noise at driving position (LpA)	79.7 dB
Environmental noise (LwA)	103 dB


## Rough turnia load clart (3) (40) Annua 6 il | 100 Annua 7 | 100 Annua 7

Actor discrete/severemen and comparation options for Marinius productive thin may be interested supported in the interestent may be distincted or not a sale below productive enter the productive of the interestent may be distincted and except of oreign and except of the interestent may be distincted and except of the interested and except of the interestent intere


co cony. U BF SA - <mark>U</mark>erited company with board of directors - Share capital: 28,507,804 curss - 857 803 508 RCS Number.


Manitou Page 1

## MHT 860 | 780




## MHT 860 | 780






Manitou Page 2

## MANITOU SIGHT LINE DIAGRAMME






PLAN VIEW

DRIVERS CLEAR VISION

NO VISION



Manitou Page 3