

BIOCLAD white & Pastels EXTRUDED PVC SHEET

PROPERTIES PHYSICAL DATA

The world's first antimicrobial PVC wall cladding containing BioCote® technology

	PROPERTY	TEST METHOD	UNITS	AVERAGE VALUE	
Physical	Specific Gravity	ASTM D792	g/cm ³	1.4	
Characteristics	Rockwell Hardness	ASTM D785	R-SCALE	R115	
Mechanical	Tensile Strength	ASTM D638	Kgf/cm ²	600	
Properties	Elongation	ASTM D638	%	100	
	Bending Strength Youngs Modulus of	ASTM D790	kgf/cm ²	1,000	
	Elasticity	ASTM D790	kgf/cm ²	34,000	
	Impact Resistance (Izod)	ASTM D256	kgfcm/cm ²	5.0	
Thermal	Heat Distortion				
Properties	Temperature Coefficient of Linear	ASTM D648	°C	60	
	Expansion	ASTM D696	cm/cm ⁰ C	7.0 ×10-5	
Electrical	Dielectric Breakdown				
Properties	Voltage	ASTM D149	kv/mm	22-35	
	40. Tel Sport of 100. Tel Paris of 100.				

CHEMICAL RESISTANT PROPERTIES

NAME OF CHEMICAL TEMP C		<u>IP</u>	NAME OF CHEMICAL		TEMP C			
Hydrochloric Acid 35%	20	40	60	Petrol	20	40	60	
Sulphuric Acid 60%	V	٧	V	Glycerine Nitric Acid	V	V	V	
Nitric Acid 70%	V	V	V	Solution of Spraying Paint	P	P	P	
Formic Acid 100%	V	G	P	Chlorine Gas	P	P	P	
Lactic Acid	V	V	V	Ammonia/Other Waste Gases	V	V	G	
Caustic Soda	V	٧	V	Natural Gas	V	V		
Ammonia Water	V	٧	V	Coal Gas	G	G		
Sodium Disulphide	V	٧	P	Bleaching Solution	V	V	-	
Acetone	P	P	P	Electro-Plating	V	V	G	
Ethyl Alcohol	V	٧	G	Developing (Fixing Liquid for Photography)	V	V	-	
Butyl Alcohol	V	G	G	Sea Water/Salt Water	V	V	V	
Benzene	P	P		Fermented Alcohol	V	G		
Formalin	V	V	G	Starch (carbohydrate) Solution	V	V	V	
Carbon Disulphide	P	P	-	Brewing Water	٧	٧	٧	
REMARKS	٧			Denotes Safely applicable (absolutely corrosion resistant)				
	G			Denotes applicable (corrosion resistant)				
	Р			Denotes inapplicable				

BIOCLAD PVC

BIOCLAD/ADVANCED EXTRUDED PVC SHEET in conjunction with **BioCote Ltd** (§) has been tested for antimicrobial efficacy according to ISO 22196: 2011 and exhibited a minimum of 95% and up to 99.99% reduction in bacterial population, classified as 'microbiological results satisfactory'. Testing by Biocote Ltd (§) is carried out by an independent laboratory.

BIOCLAD/ADVANCED PVC is suitable for cladding in food preparation areas such as kitchens, diaries, abattoirs and bakeries. Hospitals and clinics This has been confirmed by the Ministry of Food, Fisheries and Agriculture and also local Health Authorities.

BIOCLAD/ADVANCED PVC meets the following regulations:

STATUTORY INSTRUMENTS 1172 - 1970 - Food Hygiene (General) Regulations 1920

STATUTORY INSTRUMENTS 2037 - 1992 - Fresh Meat Regulations 1992

Milk and Dairies Regulations 1959 No 277

ISO 22196:2011

ASTM E84, EN 13501-1:2007+A1:2009 C-S1-d0,BS 476 part 6 class 'O' (when attached to a non-combustible substrate), part 7 class '1', AS/NZS 3837:1998

This material should be cleaned by using warm soapy water, or stubborn stains and marks may be cleaned with proprietary milk cleaner such as Cif (Jif).

PVC Cream or Solvent cleaners are also available, if require















