

CS342301: Operating System
MP2: Multi-Programming
Deadline: 2020/11/15 23:59

I.Goal

1. Understand how memory management works in NachOS
2. Understand how to implement page table mechanism

II. Assignment

1. Trace code
 - Starting from “threads/kernel.cc **Kernel::ExecAll()**”, “threads/thread.cc **thread::Sleep**” until “machine/mipssim.cc **Machine::Run()**” is called for executing the first instruction from the user program.
2. Implement page table in NachOS
 - Working item: Modify its memory management code to make NachOS support multi-programming.
 - Verification:
 - Wrong results without multi-programming

```
[ta@lsalab ~/2020/riya/MP2_test/code/test]$ ../build.linux/nachos -e consoleIO_test1 -e consoleIO_test2
consoleIO_test1
consoleIO_test2
9
16
15
18
19
1return value:0
7
return value:0
```

- Correct results with multi-programming

```
[ta@lsalab ~/2020/riya/MP2_sol/code/test]$ ../build.linux/nachos -e consoleIO_test1 -e consoleIO_test2
consoleIO_test1
consoleIO_test2
9
8
7
6
1return value:0
5
16
17
18
19
return value:0
```

- **Note:**

- Be careful that program size might exceed a pagesize

- You must put the data structure recording used physical memory in kernel.h / kernel.cc
- You must set up “valid, readOnly, use, and dirty” field for your page table, which is defined under “translate.h TranslationEntry class”
- The size of your page table must be able to contain the whole physical memory
- Hint: The following files “may” be modified...
 - userprog/addrspace.*
 - threads/kernel.*

3. Report

- Cover page, including team members, Team member contribution.
- Explain your implementation as requested in Part II-2.
- Explain how NachOS creates a thread(process), load it into memory and place it into scheduling queue as requested in Part II-1. Your explanation on the functions along the code path should **at least** cover answer for the questions below:
 - How Nachos allocates the memory space for new thread(process)?
 - How Nachos initializes the memory content of a thread(process), including loading the user binary code in the memory?
 - How Nachos creates and manages the page table?
 - How Nachos translates address?
 - How Nachos initializes the machine status (registers, etc) before running a thread(process)
 - Which **object** in Nachos acts the role of **process control block**
 - When and how does a thread get added into the ReadyToRun queue of Nachos CPU scheduler?

III. Instruction

1. Copy your code for MP1 to a new folder
 - `cp -r NachOS-4.0_MP1 NachOS-4.0_MP2`
2. Copy test file
 - `cp /home/os2020/share/consoleIO_test* NachOS-4.0_MP2/code/test/`
3. Test your program
 - `cd NachOS-4.0_MP2/code/test`
 - `../build.linux/nachos -e consoleIO_test1 -e consoleIO_test2`

IV. Grading

1. Implementation correctness – 60%

- Execute “../build.linux/nachos -e consoleIO_test1 -e consoleIO_test2” correctly
2. Report – 20%
 - Upload it to iLMS with the Filename:
MP2_report_[GroupNumber].pdf.
 3. Demo– 20%
 - Answer questions during demo.
 - Demo will take place on our server, so you are responsible to make sure your code works on our server.

***Refer to syllabus for late submission penalty.**