

Question Description	Correct Answer Choice
1.What is the output of this program? <pre> class Main { public static void main(String args[]) { int ascii[] = { 65, 66, 67, 68}; String s = new String(ascii, 1, 3); System.out.println(s); } } </pre>	BCD
2.What is the output of the following code? <pre> class Main { public static void main(String args[]) { String s1 = "Hello i love java"; String s2 = new String(s1); System.out.println((s1 == s2) + " " + s1.equals(s2)); } } </pre>	false true
3.In the below code, which code fragment should be inserted at line 3 so that the output will be: "123abc 123abc"? <pre> class Main { public static void main(String args[]) { StringBuilder sb1 = new StringBuilder("123"); String s1 = "123"; //insert statements here System.out.println(sb1 + " " + s1); } } </pre>	end("abc"); s1 = s1.concat("abc");

4.What is the output of this program? <pre> class Main { public static void main(String args[]) { String s1 = "Hello World"; String s2 = s1.substring(0 , 4); System.out.println(s2); } } </pre>	Hell
5.What is the output of the following code? <pre> class Book<T> { private static T book; // Line 1 } class Main{ public static void main(String... str){ // Line 2 Book<Integer> bookInt = new Book<Integer>(); // Line 3 Book<Boolean> bookBool = new Book<Boolean> (); // Line 4 System.out.println("Objects Created Successfully"); } } </pre>	Compile Time Error At Line 1

6.What is the output of the following code? <pre> class Book<T> { //Line 1 } public class InstanceTester{ public static void main(String... str){ Book<int> bookInt = new Book<int>();//Line 2 Book<Boolean> bookBool = new Book<Boolean> (); //Line 3 System.out.println("Objects Created Successfully"); } } </pre>	
7.Which of these types cannot be used to initiate a generic type	Compile Time Error At Line 2 Primitive Types

7.What will be the output of the following program?

```
class Main {  
    public static void main(String args[]){  
        MyGen<Integer> m = new MyGen<Integer>();  
        m.set("merit");  
        System.out.println(m.get());  
    }  
}  
class MyGen<T>  
{  
    T var;  
    void set(T var)  
    {  
        this.var = var;  
    }  
    T get()  
    {  
        return var;  
    }  
}
```

Compile Time Error

What will be the output of the following program?

```
class Main {
    public static void main(String args[])
    {
        BoundedType1<Integer> obj1 = new
BoundedType1<Integer>();
        obj1.addSum(5);
        obj1.addSum(11);
        System.out.println("Value 2 :" + obj1.getSum());
        BoundedType1<Float> obj2 = new
BoundedType1<Float>();
        obj2.addSum(new Float(11.5));
        obj2.addSum(new Float(18.5));
        System.out.println("Value 1 :" + obj2.getSum());
    }
}

class BoundedType1<T extends Number> {
    double sum = 0.0;
    void addSum(T item)
    {
        sum+= item.doubleValue();
    }
    double getSum()
    {
        return sum;
    }
}
```

Value 2 :16.0

Value 1 :30.0

What is the output of the following code?

```
public class GenericsDemo{
    public static void main(String[] args) {
        A b = new A(20);
        int sum = 10;
        sum += b.ob;
        System.out.println("Sum = " + sum);
    }
}
class A<T> {
    T ob;
    public A(T ob) {
        this.ob = ob;
    }
    public void print(T ob) {
        System.out.println("Obj = " + ob);
    }
}
```

Compilation Error or Runtime Error

What will be the output of the following program?

```
class Main {  
    public static void main(String[] args) {  
        A b = new A(20);  
        b.print(b.ob);  
        int sum = 10;  
        sum += (Integer) b.ob;  
        System.out.println("Sum = " + sum);  
    }  
}  
class A<T> {  
    T ob;  
    public A(T ob) {  
        this.ob = ob;  
    }  
    public void print(T ob) {  
        System.out.println("Obj = " + ob);  
    }  
}
```

Obj = 20
Sum = 30

12. What will be the output of the following program?

```
class Main {  
    public static void main(String args[]) {  
        Gen obj = new Gen(100);  
        obj.print();  
    }  
}  
class Gen {  
    private double value;  
    <T extends Number> Gen(T value) {  
        this.value = value.doubleValue();  
    }  
    void print(){  
        System.out.println(value);  
    }  
}
```

100.0

13. Select correct option based on below code.

```
class GenericsType<MC> {
    private MC t;
    public MC get() {
        return this.t;
    }
    public void set(MC t1) {
        this.t = t1;
    }
    public static void main(String args[]) {
        GenericsType<String> type = new GenericsType<String>();
        type.set("Merit");
        GenericsType type1 = new GenericsType();// LINE A
        type1.set("Campus");
        type1.set(10);// LINE B
    }
}
```

program compile successfully.

14. A thread can acquire a lock by using which reserved keyword

synchronized

What is true about acquiring object lock before calling wait(), n

all

16.What will be the output of the following code? StringBuilder

A

How can you ensure all threads that started from main must en

join() method

What is the output of this program? <pre> class newthread extends Thread{ Thread t1,t2; newthread() { t1 = new Thread(this,"Thread_1"); t2 = new Thread(this,"Thread_2"); t1.start(); t2.start(); } public void run(){ t2.setPriority(Thread.MAX_PRIORITY); System.out.print(t1.equals(t2)); } } class multithreaded_programing{ public static void main(String args[]){ new newthread(); } } </pre>	falsefalse
19 .What is the correct syntax for creating a generic method in	a
20.What will be the output of the following code? StringBuffer	C

21.What is the output of the following code? <pre> class Main { public static void main(String args[]) { try { throw 50; } catch(int e) { System.out.println("Exception handled " + e); } } } </pre>	Compilation Error
22.What will happen if a thread is started more than once using	D
What is the output of this program? <pre> class Main { public static void main(String args[]) { try { System.out.print("Coding" + " " + 1 / 0); } catch(ArithmeticException e) { System.out.print("Blocks"); } } } </pre>	Blocks

24. What is the output of this program?

```
class Main
{
    public static void main(String args[])
    {
        try
        {
            int p, q;
            p = 0;
            q = 5 / p;
            System.out.print("P");
        }
        catch(ArithmeticException e)
        {
            System.out.print("Q");
        }
        finally
        {
            System.out.print("R");
        }
    }
}
```

QR

What is the output of the following code? <pre>class Main { public static void main(String[] args) { try { int arr[] = {5, 6, 7, 8}; for (int i = 1; i <= 4; i++) { System.out.println ("arr[" + i + "]=" + arr[i] + "n"); } } catch (Exception e) { System.out.println ("error = " + e); } catch (ArrayIndexOutOfBoundsException e) { System.out.println ("ArrayIndexOutOfBoundsException"); } } }</pre>	Compile time error
---	---------------------------

What is the output of the following code?

```
class Main {  
    public static void main(String args[]) throws IOException {  
        //write your code here  
        try  
        {  
            return;  
        }  
        finally  
        {  
            System.out.println("Finally" );  
        }  
    }  
}
```

Finally

27. Consider the following program and predict the output:

```
class Test
{
    public static void main (String[] args)
    {
        try
        {
            int a = 0;
            System.out.println ("a = " + a);
            int b = 20 / a;
            System.out.println ("b = " + b);
        }
        catch(ArithmeticException e)
        {
            System.out.println ("Divide by zero error");
        }
        finally
        {
            System.out.println ("inside the finally block");
        }
    }
}
```

a

28. Output of the following code?

```
class Main{  
    public static void main(String[] args){  
        try {  
            throw 10;  
        } catch (int e) {  
            System.out.println("Got the Exception" + e);  
        }  
    }  
}
```

D

29. What is the Output of the Code?

```
class Test<T>{
    T obj;
    Test(T obj){
        this.obj=obj;
    }
    public T getObj(){
        return this.obj;
    }
}
class Main{
    public static void main (String[] args){
        Test<Integer> iObj= new Test<Integer>(15);
        System.out.println(iObj.getObj());

        Test<String> sObj = new Test<String>("Coding
Blocks");
        System.out.printl(sObj.getObj());
    }
}
```

A

30. Consider the following program and predict the output: <pre> class MyThread extends Thread { @Override public void run() { System.out.println("In run method; thread name is: " + Thread.currentThread().getName()); } } public class ThreadTest { public static void main(String args[]) { Thread myThread = new MyThread(); myThread.run(); #1 System.out.println("In main method; thread name is: " + Thread.currentThread().getName()); } } </pre>	A
31. What is the Output of the Code? <pre> class Main{ public static void main(String args[]){ int x=0; int y=10; int z= y/x; } } </pre>	D

32. What is the Output of the Code?

```
class Box(T){  
    private T value;  
  
    public void set(T value){  
        this.value=value;  
    }  
  
    public T get(){  
        return value;  
    }  
  
    public static void main(String args[]){  
        Box<Integer> box = new Box<>();  
        box.set(100)  
        Box<String> box1 = new Box<>();  
        box1.set("Hello");  
        System.out.println(box.get());  
        System.out.println(box1.get());  
    }  
}
```

D

33.What will be the output of the following code?

```
class newthread extends Thread
{
    newthread()
    {
        super("My Thread");
        start();
    }
    public void run()
    {
        System.out.println(this);
    }
}
public class multithreaded_programing
{
    public static void main(String args[])
    {
        new newthread();
    }
}
```

B

What will be the output of the following code? <pre> public class ExceptionTest { public static void main(String[] args) { try { throw new NullPointerException("Exception thrown"); } catch (RuntimeException e) { System.out.println("Caught RuntimeException"); } catch (NullPointerException e) { System.out.println("Caught NullPointerException"); } finally { System.out.println("Finally block executed"); } } } </pre>	a
35. What is the result of the following code snippet? <pre> class GenericBox<T> { private T value; public GenericBox(T value) { this.value = value; } public T getValue() { return value; } } public class GenericTest { public static void main(String[] args) { GenericBox<Integer> box = new GenericBox<>(10); System.out.println(box.getValue()); } } </pre>	a