Experiment-13

customize switch with network modules using cisco packet tracer

Aim:

To add network modules to a cisco switch and configure advanced feature including VLANs, port security

Procedure

1) open packet tracer and add a catalyst
2) click switch -> lab -> all -> drag
3) power on the switch and verify new interface
4) create VLANs: switch (config)# vlan 10 / name sales
5) Assign port to vlans: interface fa 0/1
6) config trunk port: interface fa0/24
7) enable port security on fa0/1
8) set violation mode: switch port security
9) use sticky MAC: switch port

commands / code

```
switch > enable
switch # configure terminal
switch (config) # vlan 10
switch (config-vlan) # name sales
switch (config-vlan) # vlan 20
switch (config-vlan) # name HR
switch (config-vlan) # exit
switch (config) # interface fastethernet 0/1
switch (config-if) # switch port mode access
switch (config-if) # switch port vlan access
switch (config-if) # switch port security max
switch (config-if) # switch port security violati
switch (config-if) # exit
switch (config) # interface fastethernet 0/24
switch (config-if) # switch port mode trunk
switch # show vlan brief
switch # show port-security interface fa 0/1
```

10) verify with: show vlan brief, show interfaces trunk, show port-security

11) Test by connecting devices to connect vlans and verifying isolation

Result: 13/X 10/10

network modules were successfully added to the switch. vlan were created and assigned to ports. Trunk links and port security were configured and verified