Rajalakshmi Engineering College

Name: karthieswaran L
Email: 241801117@rajalakshmi.edu.in
Roll no: 241801117
Phone: 9840695531
Branch: REC
Department: I AI & DS FB
Batch: 2028
Degree: B.E - AI & DS

Scan to verify results

NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 2_COD_Question 4

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Ravi is developing a student registration system for a college. To efficiently store and manage the student IDs, he decides to implement a doubly linked list where each node represents a student's ID.

In this system, each student's ID is stored sequentially, and the system needs to display all registered student IDs in the order they were entered.

Implement a program that creates a doubly linked list, inserts student IDs, and displays them in the same order.

Input Format

The first line contains an integer N the number of student IDs.

The second line contains N space-separated integers representing the student IDs.

Output Format

The output should display the single line containing N space-separated integers representing the student IDs stored in the doubly linked list.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5
10 20 30 40 50
Output: 10 20 30 40 50

Answer

```
// You are using GCC
#include<stdio.h>
#include<stdlib.h>
typedef struct node
{
   int data;
   struct node*next;
   struct node*prev;
}Node;
void insertAtend(Node**head,int data)
{
   Node*newNode=(Node*)malloc(sizeof(Node));
   newNode->data=data;
   newNode->next=NULL;
   newNode->prev=NULL;
   if(*head==NULL)
   {
      *head=newNode;
      return;
   }
   Node*temp=*head;
   while(temp->next!=NULL)
   {
      temp=temp->next;
```

```
    }
    temp->next=newNode;
    newNode->prev=temp;
}
void traverse(Node*head)
{
    Node*temp=head;
    while(temp!=NULL)
    {
        printf("%d",temp->data);
        temp=temp->next;
    }
}
int main()
{
    int n,e;
    Node*head=NULL;
    scanf("%d",&n);
    for(int i =0;i<n;i++)
    {
        scanf("%d",&e);
        insertAtend(&head,e);
    }
    traverse(head);
}
```

Status : Correct **Marks : 10/10**