

Voice Orchestrator — Complete API Reference

All mobile-facing endpoints: identity, enrollments, devices & search, favorites, scene mappings, automation trigger, voice enable, VAPI. July 2026 · v1.0 · everything verified in production

Basics

Item	Value
Base URL (\$BASE)	https://voiceorchestrator.homeadapt.us/api/v1/voice-auth
Auth	Authorization: Bearer <login token (JWT) or static platform key>
Login token	from POST /auth/login; 30-day expiry; identifies the USER; sending a foreign user_ref or home_id → 403
Static keys	sk_ios/_sk_and/_sk_web_ — identify only the platform; legacy, still work during the transition
Error envelope	{ "error": "<message>", "code": "<CODE>" } on every non-2xx

Session model: login once with email+password → get a signed token → send it as the bearer on every call → any 401 means re-login. Logout = delete the stored token. Passwords are never stored on the device or re-sent.

Endpoint index

Group	Endpoints
Identity	POST /auth/signup · POST /auth/login · GET /me · POST /auth/change-password
Enrollments (voice-gate)	POST/GET /enrollments · GET/DELETE /enrollments/{id} · PATCH /enrollments/{id}/status · GET /check · GET /challenges · GET /challenges/{id}
Devices & search	GET /devices/discover · GET /items/search · GET /automations/discover
Favorites	POST/GET /favorites · DELETE /favorites/{ref} · PATCH /favorites/reorder · POST /favorites/{id}/fire
Scene mappings	POST/GET /scene-mappings · GET/PATCH/DELETE /scene-mappings/{id}
Automation trigger	POST /automations/trigger
Voice enable (VAPI)	POST/GET/DELETE /voice-enable
Phone mappings (server/VAPI internal)	POST/GET /phone-mappings · DELETE /phone-mappings/{id} · GET /phone-lookup

1 · Identity

POST /auth/signup — create account (pending approval)

```
curl -s -X POST "$BASE/auth/signup" -H "Content-Type: application/json" \
  -d '{"email":"new@example.com","password":"min-8-chars","full_name":"New User"}'
```

201 pending_approval (admin activates + attaches home before login works) · 409 EMAIL_EXISTS · 400 VALIDATION · 429 RATE_LIMITED (5/15 min/IP). Login before activation → 403 PENDING_APPROVAL.

POST /auth/login — get token + identity in one call

```
curl -s -X POST "$BASE/auth/login" -H "Content-Type: application/json" \
  -d '{"email":"scott@example.com","password":"*****"}'
```

```
200: { "token": "eyJ...", "token_type": "Bearer", "expires_in": 2592000,
      "user_ref": "scott_mobile", "user_id": "scott_mobile",
      "username": "scottmeyers", "email": "smeyersne@gmail.com",
      "full_name": "scott meyers",
      "homes": [ { "home_id": "scott_home", "name": "scott_home" } ],
      "default_home_id": "scott_home" }
```

Cache user_ref + default_home_id — use them everywhere the app previously hardcoded scott_mobile/scott_home. user_id + email are for feedback reports. 401 wrong credentials · 403 PENDING_APPROVAL · 429 after 5 failures (15-min lock).

GET /me — refresh identity on startup

```
curl -s "$BASE/me" -H "Authorization: Bearer $TOKEN"
```

Same payload minus token fields. 401 → token expired → login screen. Requires a login token (static keys are rejected — they carry no identity).

POST /auth/change-password

```
curl -s -X POST "$BASE/auth/change-password" -H "Authorization: Bearer $TOKEN" \
  -H "Content-Type: application/json" -d '{
    "user_ref": "scott_mobile", "home_id": "scott_home",
    "automation_name": "Main Lights On",
    "ha_service": "script", "ha_entity": "main_lights_on" }'
```

204 changed (token stays valid) · 403 wrong current password · 400 policy · 429 lockout. Forgotten password: admin reset only (for now).

2 · Voice-auth enrollments (gate an automation behind a spoken phrase)

POST /enrollments — enable “Voice Protect” on an automation

```
curl -s -X POST "$BASE/enrollments" -H "Authorization: Bearer $TOKEN" \
  -H "Content-Type: application/json" -d '{
    "user_ref": "scott_mobile", "home_id": "scott_home",
    "automation_name": "Main Lights On",
    "ha_service": "script", "ha_entity": "main_lights_on" }'
```

ha_service ∈ scene/script/switch/light/lock/cover/media_player/climate/input_boolean/fan; ha_entity is the suffix only (main_lights_on, not script.main_lights_on). 201 with id, status ACTIVE, max_attempts 3, cooldown 30s. Idempotent on (user_ref, automation_id).

The rest of the group

Call	What it does
GET /enrollments?user_ref=...[&status=...]	list a user's enrollments → {count, items}
GET /enrollments/{id}	one enrollment's detail
PATCH /enrollments/{id}/status { "status": "PAUSED" "ACTIVE" }	pause / resume
DELETE /enrollments/{id}	revoke permanently → 204
GET /check?user_ref=...&automation_id=...	pre-flight before a VAPI session → exists, status, attempts_remaining, cooldown_remaining_seconds
GET /challenges?user_ref=...&limit=10	audit log of attempts (PASS/FAIL/TIMEOUT + vapi_call_id)
GET /challenges/{log_id}	one attempt's detail

3 · Devices & search

GET /devices/discover?home_id=... — physical devices

One row per HA device: device_id, name, manufacturer, model, area, primary_entity_id (the controllable surface), is_controllable, all_entities. Cached 60s server-side. Sensor-only devices have is_controllable:false and cannot be favorited.

GET /items/search — the “Add favorite” picker (devices + scenes + scripts + automations)

```
curl -s -G "$BASE/items/search" -H "Authorization: Bearer $TOKEN" \
  --data-urlencode "home_id=$HOME" --data-urlencode "q=bat" \
  --data-urlencode "user_ref=$USER"
```

Param	Req	Notes
home_id	yes	which home to search
q	no	case-insensitive substring on name + entity_id + device_id
kind	no	comma-filter: device,scene,script,automation,entity
user_ref	no	populates is_favorited + favorite_id per row
limit	no	default 200, max 500

GET /automations/discover?home_id=... — HA scene/script/automation candidates for the Voice-Protect enrollment picker.

4 · Favorites (home-screen tiles)

POST /favorites — add by device OR entity

```
# by device (server resolves entity, domain, friendly_name from HA):
curl -s -X POST "$BASE/favorites" -H "Authorization: Bearer $TOKEN" \
  -H "Content-Type: application/json" \
  -d '{"user_ref": "$USER", "home_id": "$HOME", "device_id": "6b86cd8c..."}'

# by entity (scenes/scripts/automations; friendly_name recommended):
-d '{"user_ref": "$USER", "home_id": "$HOME",
    "entity_id": "scene.good_morning", "friendly_name": "Good Morning"}'
```

Exactly ONE of device_id / entity_id (both or neither → 400). 201 returns the favorite incl. its id (UUID — store it). Duplicates → 400. Sensor-only device → 400 NO_CONTROLLABLE_ENTITY. **Locks auto-enroll**: lock.* favorites return voice_auth_required:true + voice_auth_enrollment_id — firing them always requires the voice challenge.

GET /favorites?user_ref=...&home_id=... — ordered list; each row carries voice_auth_required for the lock badge.

DELETE /favorites/{ref} — two forms

```
# by favorite id (from create response / list):
curl -s -X DELETE -H "Authorization: Bearer $TOKEN" "$BASE/favorites/<uuid>" # 204

# ONE-STEP by device_id or entity_id (no lookup):
curl -s -X DELETE -H "Authorization: Bearer $TOKEN" \
  "$BASE/favorites/6b86cd8c...?home_id=$HOME" # 204
# user_ref inferred from token; static-key callers add &user_ref=$USER
```

PATCH /favorites/reorder — drag-and-drop

```
curl -s -X PATCH "$BASE/favorites/reorder" -H "Authorization: Bearer $TOKEN" \
  -H "Content-Type: application/json" \
  -d '{"items":[{"id": "<id-1>", "position": 0}, {"id": "<id-2>", "position": 1}]}'
```

POST /favorites/{id}/fire — one-tap activation

Server picks the HA action by domain: scene/script/light/switch → turn_on; automation → trigger; lock → unlock. 200 {success, latency_ms}. **409 ENROLLMENT_REQUIRED** when voice-gated (always for locks) — launch the VAPI session with the returned automation_id + home_id instead of retrying.

5 · Scene mappings (spoken name → HA webhook)

```
curl -s -X POST "$BASE/scene-mappings" -H "Authorization: Bearer $TOKEN" \
  -H "Content-Type: application/json" -d '{
    "home_id": "scott_home", "scene_name": "Movie Night",
    "webhook_id": "movie_night_1751404299018" }'
```

Call	What it does
POST /scene-mappings	create (names normalized to lowercase) → 201
GET /scene-mappings?home_id=...	list a home's scenes

Call	What it does
GET /scene-mappings/{id}	detail
PATCH /scene-mappings/{id}	update scene_name / webhook_id / is_active (all optional)
DELETE /scene-mappings/{id}	remove → 204

6 · Automation trigger (direct fire, voice-gate aware)

```
curl -s -X POST "$BASE/automations/trigger" -H "Authorization: Bearer $TOKEN" \
  -H "Content-Type: application/json" -d '{
    "home_id": "scott_home", "ha_service": "scene", "ha_entity": "movie_night",
    "user_ref": "scott_mobile", "automation_id": "movie_night" }'
```

200 {success:true, latency_ms} · **409 ENROLLMENT_REQUIRED** if the automation is voice-gated (route to VAPI) · 502 HA unreachable · 400 validation. user_ref + automation_id are required for the gate check — omitting them bypasses it (only for clearly unprotected items).

7 · Voice enable (provision a VAPI phone number)

```
curl -s -X POST "$BASE/voice-enable" -H "Authorization: Bearer $TOKEN" \
  -H "Content-Type: application/json" \
  -d '{"user_ref":"scott_mobile","home_id":"scott_home","area_code":"415"}'
```

201 {phone_e164, vapi_phone_number_id, is_active}. Idempotent per (user_ref, home_id) — no double purchase; first call is billable on VAPI. GET /voice-enable?user_ref=... → {enabled, is_dry_run, mapping}. DELETE /voice-enable?user_ref=... releases the number → 204.

Phone mappings (server/VAPI internal): POST/GET /phone-mappings, DELETE /phone-mappings/{id}, GET /phone-lookup — used by the inbound VAPI webhook to resolve caller → (user_ref, home_id). The app normally doesn't call these.

8 · VAPI SDK — the spoken challenge

On 409 ENROLLMENT_REQUIRED (from trigger or favorite-fire), launch the VAPI SDK (iOS: github.com/VapiAI/ios, Android: /android, Web: /web) with the **VAPI public key** (not the API key):

```
assistantId: "1a2904b1-61cf-49da-a804-199d8d39fb9f"
assistantOverrides.variableValues:
  home_id:      "scott_home"
  user_ref:     "scott_mobile"
  automation_id: "main_lights_on"
  automation_name: "Main Lights On"
  initiated_by:  "MOBILE_IOS" | "MOBILE_ANDROID"
```

Assistant prompts the security phrase; on pass, HA fires. Subscribe to the call-end event, then refresh with GET /check.

9 · Error reference (all endpoints)

HTTP	Code	Meaning	App action
400	VALIDATION	bad body/params	fix input, inline error
400	NO_CONTROLLABLE_ENTITY	sensor-only device	exclude from picker
401	UNAUTHORIZED	missing/expired token or bad key	re-login (token) / config bug (key)
403	FORBIDDEN	foreign user_ref or home_id with a token	app bug — use own identity
403	PENDING_APPROVAL	account awaiting activation	show “awaiting activation”
404	NOT_FOUND	unknown id/ref	varies; delete-by-ref hint included
409	ENROLLMENT_REQUIRED	voice-gated (always locks)	launch VAPI session
409	EMAIL_EXISTS	signup email taken	offer login

HTTP	Code	Meaning	App action
429	RATE_LIMITED	login/signup lockout (15 min)	"try later", no auto-retry
502	— / VAPI_ERROR	HA or VAPI upstream failure	retry once with backoff
503	HOME_UNREACHABLE	home's HA down or token lapsed	"home offline, retry later"
503	NOT_CONFIGURED	feature not wired	report to backend

Support: send user_ref, the HTTP request+response (curl -i), and a vapi_call_id from GET /challenges for voice flows. Companion docs: identity_api_guide.pdf (deep dive on login/sign-up) · mobile_handoff.md (narrative walkthroughs).