Exp No: 1

Date:

# IMPLEMENT CODE TO RECOGNIZE TOKENS IN C

# AIM:

To implement the program to identify C keywords, identifiers, operators, end statements like [], {} using C tool.

### **ALGORITHM:**

- 1. Start
- 2. Define functions to check if a character is a delimiter, operator, or a valid identifier.
- 3. Define functions to check if a given string is a keyword, integer, real number, or a valid identifier based on certain conditions.
- 4. Define a function to extract substrings from the input string based on delimiter positions.
- 5. Define a parsing function that iterates through the input string character by character and identify substrings delimited by spaces or operators.
- 6. Check each substring for being a keyword, integer, real number, or a valid identifier and print the corresponding message.
- 7. Define the main function.
- 8. Initialize a string with the input expression.
- 9. Call the parsing function with the input string.
- 10. Print the results of the parsing, indicating whether substrings are keywords, integers, real numbers, or valid identifiers.

## **PROGRAM:**

```
#include <stdbool.h>

#include <stdio.h>

#include <stdio.h>

#include <stdlib.h> bool

isDelimiter(char ch)

{

if (ch == '' || ch == '+' || ch == '-' || ch == '*' ||

ch == '/' || ch == ',' || ch == ',' || ch == '>' ||

ch == '<' || ch == '=' || ch == '(' || ch == ')' ||

ch == '[' || ch == ']' || ch == '{' || ch == '}')

return (true);

return (false);
```

Roll Number: 210701107

```
}
bool isOperator(char ch)
           if (ch == '+' || ch == '-' || ch == '*' ||
          ch == \text{'/'} \parallel ch == \text{'>'} \parallel ch == \text{'<'} \parallel
           ch == '=')
                                           return (true);
           return (false);
}
bool validIdentifier(char* str)
           if (str[0] == '0' \parallel str[0] == '1' \parallel str[0] == '2' \parallel
str[0] == \text{'3'} \parallel str[0] == \text{'4'} \parallel str[0] == \text{'5'} \parallel
\operatorname{str}[0] == \text{'}6\text{'} \parallel \operatorname{str}[0] == \text{'}7\text{'} \parallel \operatorname{str}[0] == \text{'}8\text{'} \parallel
str[0] == '9' \parallel isDelimiter(str[0]) == true)
                     return (false);
return (true);
bool isKeyword(char* str)
{ if (!strcmp(str, "if") || !strcmp(str, "else") ||
                      !strcmp(str, "while") || !strcmp(str, "do") ||
                      !strcmp(str, "break") ||
                      !strcmp(str, "continue") || !strcmp(str, "int")
                     | !strcmp(str, "double") | !strcmp(str, "float")
                     | !strcmp(str, "return") | !strcmp(str, "char")
                     | !strcmp(str, "case") | !strcmp(str, "char")
                     | !strcmp(str, "sizeof") | !strcmp(str, "long")
                     | !strcmp(str, "short") | !strcmp(str, "typedef")
                     | !strcmp(str, "switch") | !strcmp(str, "unsigned")
                     | !strcmp(str, "void") | !strcmp(str, "static")
           | !strcmp(str, "struct") | !strcmp(str, "goto"))
                     return (true);
           return (false);
```

Name: S.Karthic

Roll Number: 210701107

```
}
bool isInteger(char* str)
         int i, len = strlen(str);
if (len == 0) return (false);
         for (i = 0; i < len; i++) {
                 if (str[i] != '0' && str[i] != '1' && str[i] != '2'
                          && str[i] != '3' && str[i] != '4' && str[i] != '5'
                          && str[i] != '6' && str[i] != '7' && str[i] != '8'
                          && str[i] != '9' \parallel (str[i] == '-' && i > 0))
                 return (false);
         }
        return (true);
}
bool isRealNumber(char* str)
         int i, len = strlen(str);
bool hasDecimal = false;
if (len == 0) return (false);
         for (i = 0; i < len; i++)
                 if (str[i] != '0' && str[i] != '1' && str[i] != '2'
                          && str[i] != '3' && str[i] != '4' && str[i] != '5'
                          && str[i] != '6' && str[i] != '7' && str[i] != '8'
                          && str[i] != '9' && str[i] != '.' ||
                          (str[i] == '-' \&\& i > 0))
                 return (false);
                                            if
(str[i] == '.')
                          hasDecimal = true;
         return (hasDecimal);
char* subString(char* str, int left, int right)
Roll Number: 210701107
```

```
{
        int i;
        char* subStr = (char*)malloc(
                                  sizeof(char) * (right - left + 2));
        for (i = left; i \le right; i++)
                 subStr[i - left] = str[i];
subStr[right - left + 1] = '\0'; return
(subStr);
} void parse(char* str){
int left = 0, right = 0;
len = strlen(str);
        while (right <= len && left <= right) {
if (isDelimiter(str[right]) == false)
                         right++;
                 if (isDelimiter(str[right]) == true && left == right) {
        if (isOperator(str[right]) == true)
printf(""%c' IS AN OPERATOR\n", str[right]);
                         right++;
                         left = right;
                 } else if (isDelimiter(str[right]) == true && left != right
                                  || (right == len && left != right)) {
                         char* subStr = subString(str, left, right - 1);
                         if (isKeyword(subStr) == true)
printf(""%s' IS A KEYWORD\n", subStr);
                         else if (isInteger(subStr) == true)
        printf(""%s' IS AN INTEGER\n", subStr);
Roll Number: 210701107
```

```
else if (isRealNumber(subStr) == true)
                                                  printf(""%s' IS A REAL
NUMBER\n", subStr);
                                       else if (validIdentifier(subStr) == true
                                       && isDelimiter(str[right - 1]) == false)
        printf(""%s' IS A VALID IDENTIFIER\n", subStr);
                       else if (validIdentifier(subStr) == false
   && isDelimiter(str[right - 1]) == false)
                                                    printf(""%s' IS NOT A VALID
IDENTIFIER\n", subStr); left = right;}} return;}
int main(){
       // maximum length of string is 100 here
printf("The expression is: float b=0.5 * b;\n"); char
str[100] = "float b = 0.5 * b; ";
        parse(str); // calling the parse function
        return (0);
}
```

# **OUTPUT:**

```
(kali@kali)-[~/Documents/cdlab]
$ vi exp1.c

(kali@kali)-[~/Documents/cdlab]
$ gcc exp1.c

(kali@kali)-[~/Documents/cdlab]
$ ./a.out
The expression is: float b= 0.5 * b;'float' IS A KEYWORD
'b' IS A VALID IDENTIFIER
'=' IS AN OPERATOR
'0.5' IS A REAL NUMBER
'*' IS AN OPERATOR
'b' IS A VALID IDENTIFIER
```

### **RESULT:**

Thus, a C program is implemented to identify C keywords, identifiers, operators and end statements.

Roll Number: 210701107