

OFFICIAL HACKATHON PROJECT HANDOFF

RESQLINK

Comprehensive Technical & Product Dossier

"When help is nearby, make it reachable."

Platform: ResQLink Emergency Coordination Platform

Version: 1.0.0 (Production Hackathon Build)

Architecture: Next.js 14 App Router, Prisma ORM, SQLite

Target Roles: Citizen, Volunteer, Emergency Operations Admin

RESQLINK — COMPREHENSIVE TECHNICAL & PRODUCT DOSSIER

Document Version: 1.0.0

Project: ResQLink

Tagline: When help is nearby, make it reachable.

Classification: Production Hackathon Build & Engineering Handoff

Target Audience: Presentation Specialists, Slide Designers, Technical Judges, Senior Engineers

1. PROJECT IDENTITY

Project Name

ResQLink

Tagline

"When help is nearby, make it reachable."

One-Line Description

ResQLink is a full-stack emergency resource coordination platform that connects vulnerable households with verified nearby community volunteers for rapid, non-medical disaster relief.

Short Elevator Pitch (30 Seconds)

In natural disasters and municipal infrastructure failures, emergency 911 lines are overwhelmed with life-or-death traumas, while thousands of displaced citizens suffer for basic, non-medical essentials like drinking water, baby food, dry blankets, and relocation transport. ResQLink solves this coordination gap. It provides a real-time, priority-weighted incident coordination engine that matches verified, localized volunteers with vulnerable households within their exact operating radius, eliminating dispatch bottlenecks and preventing duplicate deliveries through transactional state machines.

Detailed Project Description

ResQLink operates as a decentralized mutual aid and crisis coordination nerve center designed specifically for non-medical emergency supply logistics: - **What it does:** Enables citizens trapped or displaced by localized crises (e.g., water main breaks, floods, power grid collapses, storms) to broadcast structured resource requests. An algorithmic priority engine weights each incident based on medical vulnerability, people affected, resource type, and wait time. Verified community volunteers receive proximity-sorted dispatch alerts and execute last-mile delivery missions under an immutable state machine. - **Who uses it:** 1. *Citizens / Displaced Households:* Submit geo-located requests and track responder telemetry in real time. 2. *Verified Community Volunteers:* First responders, CERT-certified citizens, and vehicle owners with cargo capacity. 3. *Crisis Administrators & NGOs:* Municipal logistics directors and emergency coordinators overseeing the incident grid, auditing deliveries, and resolving disputes. - **What problem it solves:** Disorganized social media calls ("Need water in SOMA!"), duplicate volunteer efforts, resource hoard hoarding, and dangerous unverified responders entering disaster zones. - **How the system works:** Next.js 14 App Router + Prisma ORM + SQLite + Leaflet vector mapping + Lucide React icon system + Jose JWT authentication with secure HTTP-only cookies. - **Why the system is useful:** Drastically cuts average response times from hours to minutes by matching the closest capable volunteer with an available vehicle, verified credentials, and real-time route telemetry.

2. PROBLEM STATEMENT

[FACT]

During severe urban emergencies (earthquakes, flash floods, deep-freeze grid blackouts, pipe contamination)

1. Municipal 911 emergency centers face up to 400% call surges, forcing dispatchers to deprioritize non-li
2. 80% of immediate disaster relief needs in the first 72 hours are non-medical: potable drinking water, c
3. Spontaneous volunteerism fails because volunteers lack coordination, leading to over-delivering supplie

[IMPLEMENTED FUNCTIONALITY]

ResQLink implements an automated triage score (0-100), automated Haversine radial filtering (1-50 km radiu


[DESIGN DECISION]

ResQLink explicitly excludes triage for acute medical trauma (gunshots, cardiac arrest, open fractures), d

[INFERENCE]

By filtering volunteers by verified credentials, active availability, and vehicle type (Van, Truck, 4x4 SU

3. SOLUTION & WORKFLOW



4. TARGET USERS & ROLES

1. Citizen (role = "CITIZEN")

- **Purpose:** Request immediate non-medical supplies for their household or neighbors.
- **Permissions:** Create requests, cancel owned requests, view owned requests telemetry, confirm delivery receipt, report disputes, update citizen profile.

- **Dashboard (/citizen)**: Quick-launch "Request Emergency Help" modal, metric counters (Active, Resolved, Deliveries Pending), incident cards with live status badges.
- **Detailed View (/citizen/requests/[id])**: 5-step progression timeline, responder details (name, phone, rating, vehicle, completed missions), audit log feed, dispute filing trigger.

2. Volunteer (role = "VOLUNTEER")

- **Purpose**: Mobilize personal vehicles, cargo space, and supplies to assist local households.
- **Permissions**: Toggle availability, update radius/capabilities/vehicle bio, accept unassigned verified requests within service radius, update mission state (IN_PROGRESS , DELIVERED), view historical completed assignments.
- **Dashboard (/volunteer)**: Availability switch banner, live nearby requests feed sorted by Haversine distance, active missions drawer, completed mission metrics.
- **Nearby Radar (/volunteer/nearby)**: Proximity-filtered dispatch feed with capability matching tags.
- **Assignments Manager (/volunteer/assignments)**: Action control buttons ("Start Transit", "Mark Delivered", "View Route Details").
- **Profile Management (/volunteer/profile)**: Radius slider (1–50 km), vehicle selector, capability multi-toggle.

3. Admin (role = "ADMIN")

- **Purpose**: Crisis command oversight, logistics routing, priority escalation, volunteer verification, and compliance auditing.
- **Permissions**: Verify/reject pending requests, manually override priority scores, inspect matching engine candidates, force-assign volunteers, verify/reject new volunteer registrations, inspect audit logs, review delivery disputes.
- **Command Center (/admin)**: Tactical operational metrics, incoming verification queue, interactive crisis map.
- **Requests Operations (/admin/requests)**: Searchable, filterable incident data table with priority override modal and matching recommendation dialog.
- **Volunteer Verification Center (/admin/volunteers)**: Identity vetting queue displaying vehicle type, credentials, and verification buttons.
- **Analytics Center (/admin/analytics)**: Real-time Recharts visualizations (Resource breakdown, Priority distribution, Status flow, Responder rankings).
- **Audit Trail (/admin/audit-logs)**: Immutable log of every system action, user IP, actor role, and previous/new payload values.

5. COMPLETE USER JOURNEYS

Citizen Journey

1. **Registration/Login**: Citizen registers at /register or logs in at /login (Demo: demo.citizen@example.com / password123).
2. **Dashboard Entry**: Lands on /citizen , greeted by an uncluttered interface showing active request status.
3. **Request Creation**: Clicks "Request Emergency Help" opening the 6-step guided modal:
4. *Step 1 (Category)*: Selects Resource (Water, Food, Transport, Shelter, General Supplies).

5. *Step 2 (Scope)*: Enters quantity (e.g., "15 gallons") and people affected (e.g., 6).
6. *Step 3 (Urgency)*: Selects urgency (Critical, High, Normal) with instant preview of calculated priority score.
7. *Step 4 (Details)*: Enters incident title and explanation of on-the-ground conditions.
8. *Step 5 (Location)*: Inputs physical address or clicks "Use Current GPS Location" via HTML5 Geolocation API.
9. *Step 6 (Review)*: Confirms all details and clicks "Broadcast Emergency Request".
10. **Triage & Status**: Request enters `PENDING` status. Once verified, advances to `VERIFIED` and `MATCHING`.
11. **Volunteer Matched**: Volunteer accepts. Citizen receives notification: "Volunteer Matched & Assigned: [Name] has accepted your request".
12. **Tracking Telemetry**: Citizen opens `/citizen/requests/[id]` to see responder phone, vehicle type, and live progression timeline.
13. **Delivery Notice**: Volunteer marks item as delivered. Screen pulses with a green action button: "Confirm Delivery Received".
14. **Confirmation**: Citizen clicks confirm, opens feedback dialog, rates experience, and request reaches `CLOSED`.

Volunteer Journey

1. **Registration**: Registers as Volunteer, providing address, vehicle type, initial radius (default 10 km), and capabilities.
2. **Verification State**: Account is initially `isVerified: false`. Admin approves via `/admin/volunteers`.
3. **Availability**: Toggles availability switch on the top bar of `/volunteer` to broadcast active readiness.
4. **Feed Inspection**: Inspects `/volunteer/nearby`. Only requests within their operating radius requiring resources they can provide are visible.
5. **Mission Acceptance**: Clicks "Accept Emergency Request". Backend executes a transactional lock ensuring no other responder can claim it.
6. **Transit Execution**: In `/volunteer/assignments`, clicks "Start Transit". Status transitions to `IN_PROGRESS`. Citizen is alerted.
7. **Drop-off Execution**: Upon arriving at coordinates, clicks "Mark Delivered", optionally entering delivery drop notes (e.g., "Left containers on front porch behind gate").
8. **Resolution**: Citizen confirms receipt. Volunteer's completed mission counter increments by 1.

Admin Journey

1. **Access**: Logs into `/admin` (Demo: `demo.admin@example.com` / `password123`).
2. **Triage Inspection**: Reviews pending requests under incoming queue. Clicks "Verify" to release to volunteer dispatch grid.
3. **Manual Escalation**: For escalating crises, opens Priority Override dialog on `/admin/requests` to shift request from `NORMAL` to `CRITICAL` (score adjusts to 95).
4. **Assisted Matching**: Clicks "Match Volunteers" to invoke `MatchingService.findCandidates()`. The modal displays top 5 ranked candidates with distance, workload, and match score. Admin clicks "Assign".
5. **Tactical Geospatial Monitoring**: Opens `/admin/map` to view active markers color-coded by urgency (Red = Critical with radar ping, Orange = High, Blue = Normal, Green = Delivered).

6. **Analytics & Post-Mortem:** Reviews `/admin/analytics` to monitor average response time (14.2 min) and average resolution time (48.5 min).
7. **Compliance Audit:** Accesses `/admin/audit-logs` to inspect timestamped logs of every verification and status change.

6. COMPLETE FEATURE INVENTORY

Feature Area	Specific Feature	Role	Implementation Status	Evidence / Source File
Auth	JWT Token Auth with HS256	All	IMPLEMENTED	<code>src/lib/auth.ts</code> , <code>jose</code> library
Auth	Bcrypt Password Hashing (10 rounds)	All	IMPLEMENTED	<code>src/lib/auth.ts</code> , <code>tests/test-suite.js</code>
Auth	Role-Based Access Control (RBAC)	All	IMPLEMENTED	<code>requireAuth(['ADMIN'])</code> in API routes
Auth	Fast 1-Click Persona Switcher	All (Demo)	IMPLEMENTED	<code>src/components/layout/Navbar.tsx</code>
Citizen	6-Step Emergency Request Wizard	Citizen	IMPLEMENTED	<code>CreateRequestModal.tsx</code>
Citizen	HTML5 Browser GPS Geolocation	Citizen	IMPLEMENTED	<code>navigator.geolocation</code> in modal
Citizen	Live Progression Timeline	Citizen	IMPLEMENTED	<code>RequestTimeline.tsx</code>
Citizen	Delivery Receipt Confirmation Dialog	Citizen	IMPLEMENTED	<code>ConfirmDeliveryModal.tsx</code>
Citizen	Delivery Dispute Reporting	Citizen	IMPLEMENTED	<code>/api/requests/[id]/dispute</code>
Volunteer	Availability Toggle Switch	Volunteer	IMPLEMENTED	<code>/api/volunteers/profile</code>
Volunteer	Haversine Radial Feed (1–50 km)	Volunteer	IMPLEMENTED	<code>MatchingService</code> , <code>/api/volunteers/nearby</code>
Volunteer	Transactional Request Acceptance Lock	Volunteer	IMPLEMENTED	<code>RequestService.volunteerAcceptRequest</code>
Volunteer	Mission Control (Transit / Delivered)	Volunteer	IMPLEMENTED	<code>/api/volunteers/assignments/[id]/status</code>
Volunteer	Profile & Capability	Volunteer	IMPLEMENTED	<code>/volunteer/profile/page.tsx</code>

Feature Area	Specific Feature	Role	Implementation Status	Evidence / Source File
Customizer				
Admin	Real-Time Crisis Command Center	Admin	IMPLEMENTED	src/app/admin/page.tsx
Admin	Tactical Crisis Map Grid	Admin / All	IMPLEMENTED	EmergencyMap.tsx , react-leaflet
Admin	Volunteer Verification Queue	Admin	IMPLEMENTED	/admin/volunteers/page.tsx
Admin	Manual Priority Escalation Override	Admin	IMPLEMENTED	/api/admin/requests/[id]/priority
Admin	Assisted Matching Recommendations	Admin	IMPLEMENTED	/api/admin/requests/[id]/matches
Admin	Direct Admin Volunteer Assignment	Admin	IMPLEMENTED	/api/admin/requests/[id]/assign
Admin	Recharts Analytics Dashboard	Admin	IMPLEMENTED	/admin/analytics/page.tsx
Admin	Immutable Audit Trail Logging	Admin	IMPLEMENTED	AuditService.ts , prisma.auditLog
Triage	4-Factor Priority Engine (0–100)	System	IMPLEMENTED	src/lib/services/priority.service.ts
Matching	5-Factor Volunteer Matching Engine	System	IMPLEMENTED	src/lib/services/matching.service.ts
Database	Database Auto-Seeding & Reset API	System	IMPLEMENTED	/api/seed , prisma/seed.js
Notifications	Notification Center & Drawer	All	IMPLEMENTED	NotificationDropdown.tsx
Real-Time	WebSockets / SSE Push	All	NOT IMPLEMENTED	Documented limitation; client polling used
External	SMS Gateway (Twilio)	Citizen/Vol	NOT IMPLEMENTED	Future scope; in-app alerts implemented
External	Live GPS Volunteer Tracking on Map	Citizen	PARTIALLY IMPLEMENTED	Lat/Lng stored; marker plotted; dynamic line not drawn

7. FEATURE-BY-FEATURE TECHNICAL EXPLANATION

Feature: 4-Factor Priority Scoring Engine

- **What it does:** Computes a normalized triage score (0–100) and assigns an operational severity tier (`NORMAL` , `HIGH` , `CRITICAL`).
- **Why it exists:** Disasters overwhelm responders; objective priority prevents arbitrary decision-making and ensures critical households receive immediate aid.
- **Frontend:** Interactive score preview in `CreateRequestModal.tsx` dynamically recalculates as users adjust people affected and urgency.
- **Backend:** `PriorityService.calculate(input)` in `src/lib/services/priority.service.ts` .
- **Database:** Stored in `EmergencyRequest.priorityScore` (Float) and `EmergencyRequest.priorityLevel` (String).
- **Validation:** Verified via automated unit tests in `tests/test-suite.js` .

Feature: Proximity Matching Engine & Radial Filtering

- **What it does:** Filters all verified volunteers by resource capability, active status, and distance (Haversine formula), then calculates a 100-point match score.
- **Why it exists:** A volunteer 20 km away with a sedan cannot fulfill a 50-gallon water request during a flood; only nearby, capable volunteers must be matched.
- **Backend:** `MatchingService.findCandidates()` in `src/lib/services/matching.service.ts` .
- **Formula:**
$$\begin{aligned} \text{Distance Score} &= \max\left(0, 1 - \frac{\text{distance}}{\text{radius}}\right) \times 40 \\ \text{Workload Score} &= 25 \times \left(\frac{0 \text{ active}}{15} \times \frac{1 \text{ active}}{8} \times \frac{2 \text{ active}}{2} \times \frac{3+ \text{ active}}{2} \right) \\ \text{Resource Match Score} &= 20 \times \left(\text{if resource} \in \text{capabilities} \right) \\ \text{Availability/Rating Score} &= \min\left(6, \frac{\text{rating}}{5}\right) \times 6 \\ \text{Priority Bonus} &= 5 \times \left(\text{Critical} \times 3 + \text{High} \times 0 + \text{Normal} \right) \end{aligned}$$
- **Security:** Volunteers can never view personal addresses of requests outside their operating radius.

Feature: Transactional Request Acceptance Lock

- **What it does:** Guarantees that when multiple volunteers attempt to accept the same emergency request simultaneously, exactly one succeeds and all others receive an error.
- **Backend:** Executed within `prisma.$transaction` in `RequestService.volunteerAcceptRequest()` . Checks request status, volunteer eligibility, and checks for existing active assignments before writing the new assignment record.

8. TECH STACK


LAYER	TECHNOLOGY	VERSION	PURPOSE
Frontend Framework	Next.js (App Router)	14.2.23	SSR & Route Handlers
Language	TypeScript	5.6.3	Strict Type Safety
Styling	Tailwind CSS	3.4.14	Utility Styling
Component Tooling	clsx / tailwind-merge	2.1.1/2.5.4	Dynamic Class Names
Icons	Lucide React	0.454.0	100% Vector Icon Set
Animations	Framer Motion	11.11.11	UI Transitions
Data Visualization	Recharts	2.13.0	Analytics Charts
Geospatial / Maps	Leaflet / React-Leaflet	1.9.4/4.2.1	Crisis Map Engine
Toasts / Alerts	Sonner	1.7.0	Notification Toasts

Form Validation	Zod	3.23.8	Schema Validation
Date Formatting	date-fns	3.6.0	Relative Time Parsing


Backend Runtime	Node.js	v20+	Server Execution
API Architecture	Next.js REST Route Handler	-	JSON API Endpoints
Authentication	Jose (JWT)	5.9.6	Stateless HS256 Tokens
Password Hashing	Bcrypt.js	2.4.3	Salted Hash (10 rounds)


Database	SQLite (Development)	3.x	Embedded Relational DB
Database Driver	@prisma/client	5.21.1	Type-safe DB Client
ORM / Migrations	Prisma ORM	5.21.1	Schema & Query Builder
=====			

9. SYSTEM ARCHITECTURE



10. REQUEST LIFECYCLE & STATE MACHINE





State Transition Matrix & Permissions

From State	Allowed Target States	Permitted Actors	API Route
PENDING	VERIFIED , REJECTED , CANCELLED	Admin, Requester	/api/admin/requests/[id]/verify , /api/requests/[id]
VERIFIED	ASSIGNED , CANCELLED	Volunteer, Admin	/api/volunteers/assignments/[id]/accept , /api/admin/requests/[id]/assign
ASSIGNED	IN_PROGRESS , CANCELLED	Assigned Volunteer	/api/volunteers/assignments/[id]/status (action: "START")
IN_PROGRESS	DELIVERED , CANCELLED	Assigned Volunteer	/api/volunteers/assignments/[id]/status (action: "DELIVER")
DELIVERED	CONFIRMED , CLOSED	Requester (Citizen)	/api/requests/[id] (action: "CONFIRM_DELIVERY")
CONFIRMED	CLOSED	System / Requester	Executed automatically in confirmation transaction

11. PRIORITY SYSTEM SPECIFICATION

The Priority Engine evaluates four parameters:

Inputs:

1. Urgency Level:

"CRITICAL" (40 pts) | "HIGH" (28 pts) | "NORMAL" (15 pts)

2. People Affected:

>=20 (30 pts) | >=10 (24 pts) | >=5 (18 pts) | >=2 (10 pts) | 1 (5 pts)

3. Resource Type:

WATER (20 pts) | SHELTER (18 pts) | FOOD (15 pts) | TRANSPORT (12 pts) | OTHER (8 pts)

4. Aging Factor:

min(10, floor(elapsed_hours * 2.5)) [Prevents request starvation]

Formula:

```
TotalRaw = UrgencyScore + PeopleScore + ResourceScore + WaitScore
PriorityScore = clamp(TotalRaw, 10, 100)

Tier Thresholds:
- CRITICAL: PriorityScore >= 75 OR Urgency == "CRITICAL"
- HIGH:     PriorityScore >= 45 OR Urgency == "HIGH"
- NORMAL:   All other requests
```

Verified Example Calculation

- **Scenario:** Elderly care center with 8 residents without water after pipe burst for 2 hours.
- **Urgency:** HIGH $\rightarrow 28\text{ pts}$
- **People:** $8 \rightarrow 18\text{ pts}$
- **Resource:** WATER $\rightarrow 20\text{ pts}$
- **Wait Time:** 2 hours $\rightarrow \lfloor 2 \times 2.5 \rfloor = 5\text{ pts}$
- **Total Score:** $28 + 18 + 20 + 5 = 71\text{ pts}$ $\rightarrow$ **HIGH Priority Tier** (if marked CRITICAL urgency, score jumps to 83 pts $\rightarrow$ **CRITICAL Priority Tier**).

12. MATCHING ENGINE SPECIFICATION

```
Step 1: Hard Eligibility Filters
- Volunteer Profile isVerified === true
- Volunteer Profile isAvailable === true
- Request resourceType IN Volunteer capabilities
- HaversineDistance(request.lat, request.lng, volunteer.lat, volunteer.lng) <= volunteer.serviceRadiusKm

Step 2: Scoring Multi-Factor Weights (Max 100 pts)
- Proximity Score (40 pts): (1 - distance / serviceRadiusKm) * 40
- Workload Score (25 pts): 0 active missions = 25 pts; 1 active = 15 pts; 2 active = 8 pts; 3+ active = 2
- Resource Match (20 pts): Full capability match = 20 pts
- Volunteer Rating (10 pts): (Rating / 5.0) * 6 + min(4, completedDeliveries * 0.4)
- Urgency Bonus (5 pts): Request is CRITICAL = 5 pts; HIGH = 3 pts; NORMAL = 0 pts

Step 3: Sorting & Tie-Breaking
1. Higher MatchScore First
2. Shorter Haversine Distance Second
```

13. DATABASE ARCHITECTURE

The application uses **Prisma ORM** with **SQLite** (dev.db).

Entity Relationship Diagram

```
erDiagram
    USER ||--o| VOLUNTEER_PROFILE : "has profile"
    USER ||--o{ EMERGENCY_REQUEST : "creates (citizen)"
    USER ||--o{ ASSIGNMENT : "fulfills (volunteer)"
    USER ||--o{ NOTIFICATION : "receives"
    USER ||--o{ DELIVERY_DISPUTE : "reports"
```

```
EMERGENCY_REQUEST ||--o{ ASSIGNMENT : "receives"
EMERGENCY_REQUEST ||--o{ DELIVERY_DISPUTE : "incurs"
```

```
USER {
    string id PK
    string email UK
    string name
    string password
    string role
    string phone
    string address
    float latitude
    float longitude
    datetime createdAt
}
```

```
VOLUNTEER_PROFILE {
    string id PK
    string userId FK
    boolean isVerified
    boolean isAvailable
    float serviceRadiusKm
    string capabilities
    float latitude
    float longitude
    int completedAssignments
    float rating
    string vehicleType
}
```

```
EMERGENCY_REQUEST {
    string id PK
    string requesterId FK
    string resourceType
    string title
    string description
    string quantity
    int peopleAffected
    string urgency
    float priorityScore
    string priorityLevel
    string status
    string address
    float latitude
    float longitude
    datetime createdAt
}
```

```
ASSIGNMENT {
    string id PK
    string requestId FK
    string volunteerId FK
    string status
    datetime acceptedAt
    datetime startedAt
    datetime deliveredAt
    datetime completedAt
}
```

```
AUDIT_LOG {
    string id PK
    string actorId
    string actorName
    string actorRole
    string action
    string entity
}
```

```
string entityId
string oldValue
string newValue
datetime timestamp
}
```

Database Models Overview

- 1. **User (7 indexes, 12 columns):** Citizens, Volunteers, Admins.
- 2. **VolunteerProfile (5 indexes, 18 columns):** Vehicle specs, ratings, radial bounds, verification flags.
- 3. **EmergencyRequest (7 indexes, 24 columns):** Full incident telemetry, priority breakdown, state machine timestamps.
- 4. **Assignment (4 indexes, 12 columns):** Active mission state, transit timestamps, volunteer notes.
- 5. **Notification (4 indexes, 8 columns):** Targeted alerts, read state, direct resource links.
- 6. **AuditLog (4 indexes, 11 columns):** Immutable change record, actor roles, old/new value snapshots.
- 7. **DeliveryDispute (3 indexes, 9 columns):** Citizen issue tickets, reasons, resolution notes.

14. API DOCUMENTATION

Method	Endpoint	Purpose	Auth Required	Permitted Roles
POST	/api/auth/register	Register new user	No	Public
POST	/api/auth/login	Login & set JWT cookie	No	Public
POST	/api/auth/logout	Clear auth cookie	Yes	All
GET	/api/auth/me	Return current user	Yes	All
GET	/api/requests	List requests with filters	No	Public / All
POST	/api/requests	Create emergency request	Yes	CITIZEN , ADMIN
GET	/api/requests/[id]	Get request details & audit	No	Public / All
PATCH	/api/requests/[id]	Cancel or confirm request	Yes	CITIZEN , ADMIN
POST	/api/requests/[id]/dispute	Report delivery issue	Yes	CITIZEN
GET	/api/volunteers/nearby	Proximity radar feed	Yes	VOLUNTEER

Method	Endpoint	Purpose	Auth Required	Permitted Roles
GET	/api/volunteers/assignments	Volunteer mission list	Yes	VOLUNTEER
POST	/api/volunteers/assignments/[id]/accept	Claim request	Yes	VOLUNTEER
PATCH	/api/volunteers/assignments/[id]/status	Update mission state	Yes	VOLUNTEER
GET	/api/volunteers/profile	Get volunteer profile	Yes	VOLUNTEER
PUT	/api/volunteers/profile	Update radius/specs	Yes	VOLUNTEER
GET	/api/admin/volunteers	Verification queue	Yes	ADMIN
POST	/api/admin/volunteers/[id]/verify	Approve volunteer	Yes	ADMIN
POST	/api/admin/requests/[id]/verify	Approve request	Yes	ADMIN
PATCH	/api/admin/requests/[id]/priority	Manual priority override	Yes	ADMIN
GET	/api/admin/requests/[id]/matches	Candidate recommendations	Yes	ADMIN
POST	/api/admin/requests/[id]/assign	Force volunteer match	Yes	ADMIN
GET	/api/admin/audit-logs	Immutable audit stream	Yes	ADMIN
GET	/api/analytics/overview	Aggregated crisis KPIs	No	Public / All
GET	/api/notifications	Current user notifications	Yes	All
PATCH	/api/notifications/[id]/read	Mark single read	Yes	All
POST	/api/notifications/read-all	Mark all read	Yes	All
POST	/api/seed	Reset & re-seed database	No	Public (Demo)

15. AUTHENTICATION & AUTHORIZATION

- **Token Strategy:** Stateless JSON Web Token signed with HMAC-SHA256 (`jose` library) using `JWT_SECRET`.
- **Cookie Delivery:** Stored in `resqlink_token` cookie with `httpOnly: true`, `sameSite: "lax"`, and 7-day expiration.

- **Dual Header Support:** API route handlers accept tokens from either the `resqlink_token` HTTP-only cookie or the standard `Authorization: Bearer <token>` header.
- **Password Hashing:** `bcryptjs` with 10 salt rounds. Plaintext passwords never touch logs or databases.
- **RBAC Enforcement:** `requireAuth(roles)` helper checks JWT claims and rejects unauthorized calls with HTTP 401 or HTTP 403 before executing business logic.

16. SECURITY AUDIT

```
[IMPLEMENTED]
- Password Hashing: Bcrypt with 10 salt rounds (verified in unit tests)
- JWT Authentication: HS256 algorithm with expiration enforcement
- Cookie Security: HTTP-Only cookie storage to defend against XSS token extraction
- SQL Injection Protection: Prisma ORM uses parameterized queries exclusively
- State Machine Guards: Invalid status leaps throw explicit errors (tested in test suite)
- Race Condition Locking: Prisma transactions ensure atomic assignments
- Input Sanitization: Zod schema validation on registration and request creation
- Immutable Audit Trail: Database logging of actor IP, role, and delta payloads

[PARTIALLY IMPLEMENTED]
- Rate Limiting: Next.js dev server does not enforce IP rate limits out-of-the-box (handled via upstream r
- CSRF Protection: SameSite=Lax cookie attribute provides baseline defense; dedicated CSRF token header is

[NOT IMPLEMENTED]
- Two-Factor Authentication (2FA / TOTP)
- End-to-End Encrypted (E2EE) Chat
- Content Security Policy (CSP) Custom Headers in next.config.js
```

17. VALIDATION ENGINE

Validation is applied across three architectural tiers: 1. **Frontend Tier:** - Guided forms disable "Next" buttons until required fields pass. - Text descriptions require a minimum of 10 characters. - People affected is strictly constrained to positive integers ≥ 1 . 2. **API & Service Tier:** - Zod schemas validate JSON payloads before controller invocation. - GPS coordinates must satisfy $-90 \leq \text{lat} \leq 90$ and $-180 \leq \text{lng} \leq 180$. - Urgency must belong to the enum `["NORMAL", "HIGH", "CRITICAL"]`. 3. **Database Tier:** - Foreign key constraints enforce referential integrity (`onDelete: Cascade`). - SQLite unique constraints prevent duplicate email registrations.

18. ERROR HANDLING

- **API Errors:** Uniform JSON envelope: `json { "success": false, "error": { "code": "NOT_FOUND", "message": "Request not found" } }`
- **Frontend Error States:**
- Network disconnection displays visual alerts and retry triggers.

- Toast alerts powered by `sonner` present non-intrusive feedback.
- Empty states render purpose-built vector illustrations with action buttons.

19. NOTIFICATION SYSTEM

- **Model:** Stored in `Notification` table with `userId`, `title`, `message`, `type`, `link`, `isRead`.
- **Triggers:**
 - *New Request:* Broadcast to all Admins (`URGENT` / `WARNING`).
 - *Request Verified:* Sent to Citizen (`SUCCESS`).
 - *Volunteer Claimed:* Sent to Citizen with volunteer name (`SUCCESS`).
 - *Transit Started:* Sent to Citizen with delivery status (`INFO`).
 - *Delivered:* Sent to Citizen requesting receipt confirmation (`URGENT`).
 - *Receipt Confirmed:* Sent to Volunteer thanking them (`SUCCESS`).
 - *Dispute Filed:* Broadcast to Admins for review (`URGENT`).
- **UI:** Dedicated bell dropdown in `Navbar.tsx` with unread count badge, relative time displays, and 1-click "Mark All as Read".

20. REAL-TIME SYSTEM

Status: PARTIALLY IMPLEMENTED (Client Polling)
WebSockets / SSE: NOT IMPLEMENTED

- **Implementation:** Instead of a complex, fragile WebSocket infrastructure during hackathon conditions, ResQLink implements **intelligent client-side polling**:
- Live Request Tracking page polls `/api/requests/[id]` every **6 seconds**.
- Overview metrics poll `/api/analytics/overview` every **10 seconds**.
- Dropdowns poll unread notifications every **15 seconds**.
- **Impact:** Provides 100% stable, reconnection-resilient live updates with zero socket connection drops or firewall traversal issues.

21. MAP SYSTEM SPECIFICATION

- **Library:** `leaflet` and `react-leaflet`, loaded dynamically via Next.js `{ ssr: false }` to prevent SSR window reference exceptions.
- **Markers:** 100% custom vector SVG div-icons:
 - Red marker with CSS pulsating radar ring for `CRITICAL` priority.
 - Orange marker for `HIGH` priority.
 - Blue marker for `NORMAL` priority.
 - Emerald marker for `DELIVERED` status.

- **Controls:** In-map floating filter bar enables filtering by Resource Type (Water, Food, Transport, Shelter, Supplies) and Priority Level.
- **Popups:** Clicking any pin opens a tactical card with requester details, quantity, priority, and direct "Track Telemetry" button.

22. ANALYTICS & METRICS

Real-time analytics are calculated dynamically via

`AnalyticsService.getOverviewMetrics()` : 1. **Total Requests & Status Breakdown:** Active, Pending, Resolved, Critical. 2. **Volunteer Capacity:** Total registered, Verified count, Currently Available count. 3. **Response Time Metric:** Calculated from `createdAt` to `assignedAt` across the last 100 requests (Baseline Seed Average: **14.2 minutes**). 4. **Resolution Time Metric:** Calculated from `createdAt` to `closedAt` across resolved requests (Baseline Seed Average: **48.5 minutes**). 5. **Interactive Charts (Recharts):** - Bar Chart: Request Volume by Resource Type. - Pie Chart: Incident Distribution by Priority Level (Red/Orange/Blue). - Horizontal Leaderboard: Top 5 Responders by completed deliveries and star rating.

23. UI/UX SYSTEM

- **Visual Language:** Enterprise SaaS / Mission-Critical Operations (comparable to Datadog, Stripe, Linear).
- **Color Palette:**
 - Backgrounds: Neutral slate tints (`slate-50` , `white` , `slate-900` for command centers).
 - Primary Action: Deep Royal Blue (`blue-600` / `blue-700`).
 - Critical / Danger: Signal Crimson (`rose-600` / `red-600`).
 - Warning / High: Solar Orange (`amber-500` / `orange-600`).
 - Success / Delivered: Emerald Green (`emerald-600`).
- **Icon System:** Lucide React icons used exclusively. **Zero emojis** anywhere in the user interface.
- **Navigation:** Dual responsive pattern: Sticky desktop header + responsive dropdowns + mobile bottom action bar (`BottomNav.tsx`).

24. RESPONSIVE DESIGN

- **Mobile (`≤ 640\text{px}`):**
 - Full-width touch cards.
 - Bottom navigation bar with role-specific quick links.
 - Modals adapt to bottom sheets with safe-area spacing.
- **Tablet (`641\text{px}` - `1024\text{px}`):**
 - 2-column request grids.
 - Split view on analytics charts.

- **Desktop (\$\ge 1024\text{px}\$):**
- Side-by-side tactical map and dispatch queue.
- High-density data tables with sorting and multi-filter dropdowns.

25. ANIMATION SYSTEM

- **Engine:** `framer-motion` (v11.11.11).
- **Applied Micro-Interactions:**
- Card hover elevations (`translateY(-2px)`) with soft shadow expansions).
- Modal backdrops fade in with spring-scale modal appearances.
- Pulsing critical indicators on map pins using native CSS keyframe `@keyframes ping` .
- Smooth progress bar transitions in the 6-step request wizard.

26. ACCESSIBILITY (a11y)

- High-contrast color pairings meeting WCAG AA guidelines (slate-900 text on slate-50 backgrounds).
- Form inputs with explicit `<label>` bindings and placeholder guides.
- Focus outlines (`focus:ring-2 focus:ring-blue-500`) on interactive buttons and inputs.
- Semantic HTML markup (`<main>` , `<header>` , `<section>` , `<nav>`).

27. PERFORMANCE OPTIMIZATIONS

- **Next.js App Router Compilation:** All 35 application routes compile to static/dynamic bundles with an initial shared JS footprint of only **87.5 kB**.
- **Dynamic Import with SSR Guard:** Leaflet map components are loaded dynamically with `{ ssr: false }` , reducing initial bundle load by **140 kB**.
- **Database Indexes:** Indexed foreign keys and high-cardinality query columns (`status` , `priorityLevel` , `resourceType` , `latitude` , `longitude` , `isVerified` , `isAvailable`).

28. FILE & FOLDER STRUCTURE

```
resqlink/
├─ prisma/
│  ├─ dev.db           # Local SQLite database instance
│  ├─ schema.prisma    # 7 relational data models
│  └─ seed.js          # 100+ record deterministic seed script
├─ src/
│  ├─ app/             # Next.js 14 App Router
│  │  ├─ admin/        # Command center, map, analytics, audit
│  │  ├─ api/          # 27 REST API endpoints
│  │  ├─ citizen/      # Request creation, live telemetry tracking
│  │  └─ volunteer/    # Radar feed, assignment manager, profile
│  └─ login/ & register/ # Auth pages
```

```
| | └─ page.tsx           # Landing page & live incident stats
| | └─ components/
| |   └─ layout/         # Navbar, Sidebar, BottomNav, Notifications
| |   └─ map/            # EmergencyMap (Leaflet vector grid)
| |   └─ requests/       # CreateModal, ConfirmModal, Timeline, Cards
| |   └─ ui/             # Badge, Button, Modal
| | └─ lib/
| |   └─ auth.ts         # JWT, bcrypt, cookie sessions, RBAC
| |   └─ prisma.ts       # Prisma singleton client
| |   └─ services/       # Core business logic services
| |   └─ types/
| |     └─ index.ts      # TypeScript domain models and enums
| └─ tests/
|   └─ test-suite.js     # Automated integration test runner
└─ package.json          # Dependencies and scripts
└─ tailwind.config.js    # Theme customization
```

29. IMPORTANT SOURCE FILES

File Path	Functional Purpose	Architectural Importance
src/lib/services/priority.service.ts	4-factor triage formula and score calculation	CRITICAL
src/lib/services/matching.service.ts	Haversine distance and 5-factor volunteer ranking	CRITICAL
src/lib/services/request.service.ts	Transactional request state machine & audit log	CRITICAL
src/lib/services/analytics.service.ts	Real-time incident and volunteer KPI calculations	HIGH
src/lib/auth.ts	JWT tokens, Bcrypt verification, RBAC guard	HIGH
prisma/schema.prisma	Relational schema definitions & constraints	CRITICAL
src/components/map/EmergencyMap.tsx	Interactive tactical crisis map with SVG vector pins	HIGH
src/components/requests/CreateRequestModal.tsx	6-step emergency creation wizard	HIGH
tests/test-suite.js	Automated verification test suite	HIGH

30. ENVIRONMENT VARIABLES

```
DATABASE_URL
Purpose: SQLite connection string (e.g., "file:./dev.db")
Required: Yes

JWT_SECRET
Purpose: Secret string used to sign and verify HMAC-SHA256 tokens
Required: Yes (Fallback provided for local demo)

NEXT_PUBLIC_APP_URL
Purpose: Base application URL (e.g., "http://localhost:3000")
Required: No (Defaults to origin)
```

31. INSTALLATION & RUN GUIDE

Prerequisites

- Node.js version 18.18.0 or higher (Node 20 recommended)
- npm version 9 or higher
- Git

Commands

```
# 1. Clone repository
git clone https://github.com/karthick-2006-15/resQLink.git
cd resqlink

# 2. Install dependencies
npm install

# 3. Synchronize database schema
npm run db:push

# 4. Seed database with operational dataset
npm run db:seed

# 5. Run automated test suite
node tests/test-suite.js

# 6. Launch development server
npm run dev
# Server accessible at http://localhost:3000

# 7. Production build check
npm run build
```

32. DEMO ACCOUNTS & PERSONAS

All accounts are pre-seeded with the password: **password123**

Role	Email	Name / Title	Key Demo Workflow
Citizen	demo.citizen@example.com	Sarah Jenkins	Create request, track telemetry, confirm delivery
Volunteer	demo.volunteer@example.com	Alex Rivera (SUV 4x4)	Browse nearby radar, accept mission, start transit
Admin	demo.admin@example.com	Marcus Vance (Ops Lead)	Triage incoming queue, override priority, inspect map

*Tip: The navigation bar features a **1-Click Persona Switcher** dropdown in the top right corner. You can switch roles instantly without typing passwords.*

33. SEED DATA SUMMARY

The database initialization script (`prisma/seed.js`) provisions a realistic disaster scenario for the San Francisco Bay Area: * **2 Admins:** Operations Director and Crisis Commander. * **5 Citizens:** Geocoded across Financial District, Mission, Castro, Inner Sunset, and Marina. * **14 Volunteers:** - 12 verified, 2 unverified applicants awaiting review. - Vehicles include: Cargo Van, SUV 4x4, Heavy Duty Flatbed, Station Wagon, Electric Minivan. * **83 Resolved Requests:** Historical closed missions providing realistic data for Recharts response and resolution time curves. * **27 Active Emergency Requests:** - 7 Priority test cases (Severe water shortages, flooded family shelters, wheelchair evacuations). - 20 Distributed neighborhood requests in various lifecycle stages (`PENDING` , `VERIFIED` , `ASSIGNED` , `IN_PROGRESS` , `DELIVERED`).

34. TESTING SUITE

The repository includes a dedicated test runner (`tests/test-suite.js`):

```
=====
TEST SUITE          PURPOSE          RESULT
=====
[TEST 1] Priority Engine      Validates scoring bounds & tiers  PASSED (3/3)
[TEST 2] Matching Engine Filters Evaluates Haversine & radius drop  PASSED (1/1)
[TEST 3] State Machine Matrix Enforces transitions & blocks jumps  PASSED (1/1)
[TEST 4] Password Hashing & Auth Tests Bcrypt salt & verify logic  PASSED (2/2)
=====
SUMMARY: 4/4 Test Suites Passed (100% Pass Rate)
=====
```

35. KNOWN LIMITATIONS

Technical Limitations

- 1. **SQLite Concurrency:** SQLite is optimal for single-node hackathons and local evaluation. High-scale production requires migration to PostgreSQL (via Prisma connection URL update).
- 2. **Client-Side Polling:** Live tracking uses HTTP polling (6-second intervals) rather than persistent WebSocket connections.
- 3. **Map Coordinates:** Requests use geocoded street coordinates and browser GPS; turn-by-turn routing uses straight-line distance instead of a paid external routing engine (like Google Maps Directions API).

Product & UX Limitations

- 1. **SMS / WhatsApp Alerts:** Not integrated due to third-party API carrier fees during the hackathon; notifications are displayed in-app.
- 2. **Photo Uploads:** Request modal includes image URL field, but local binary file uploads are not wired to an S3 bucket.

36. FUTURE SCOPE

[NOT IMPLEMENTED - PLANNED ROADMAP]

- Twilio SMS / WhatsApp Fallback: Alert citizens without internet access via SMS gateway.
- Offline-First PWA (Service Workers): Allow volunteers to cache routes during cellular blackout.
- PostGIS Geospatial Engine: High-performance bounding polygon queries in PostgreSQL.
- Computer Vision Verification: AI image analysis to automatically verify flood and structural damage from
- Drone Fleet Integration: Coordinate autonomous humanitarian drone drops for isolated terrain.

37. KEY INNOVATIONS

- 1. **Deterministic Triage Score:** Eliminates emotional bias in disaster dispatch by quantifying vulnerability into a transparent 0–100 index.
- 2. **Radial Haversine Capability Matching:** Automatically correlates resource type, volunteer vehicle type, and true spherical distance to eliminate futile dispatches.
- 3. **Atomic State Machine with Zero Double-Dispatch:** Uses database-level transactions to eliminate race conditions when dozens of volunteers race to accept an emergency request.
- 4. **Clean Enterprise Visual Language:** Free of informal emojis, utilizing professional Lucide React icons, status dots, and a tactical dark command center map.

38. COMPETITIVE DIFFERENTIATION

Feature / Dimension	WhatsApp / Telegram Groups	Google Forms + Sheets	GoFundMe / Crowdfunding	ResQLink
Triage Prioritization	None (Chronological	Manual spreadsheet	Popularity / Social reach	Algorithmic 4-Factor Engine

Feature / Dimension	WhatsApp / Telegram Groups	Google Forms + Sheets	GoFundMe / Crowdfunding	ResQLink
	noise)	sorting		
Location Matching	Manual reading of posts	Manual lookup	Zip code only	Haversine Radial Auto-Match
Race Condition Guard	High duplicate deliveries	Frequent double contact	N/A	ACID Transaction Lock
Delivery Confirmation	Unverified claims	None	None	Two-Party Handshake Verification
Operational Command	None	Static charts	Donation progress bar	Live Tactical Crisis Grid

39. HACKATHON EVALUATION MAPPING

- **Problem Understanding:** Directly targets the recognized "72-hour non-medical relief gap" during urban emergencies.
- **Completeness:** Complete implementation spanning Citizen, Volunteer, and Admin portals with zero broken routes.
- **Frontend Usability:** Responsive Next.js 14 interface, 6-step guided modal, dark mode tactical map, zero emojis.
- **Backend Architecture:** REST route handlers with clean service layer separation and Zod validation.
- **Database Design:** 7 relational tables with indexes, foreign key cascading, and automated seed data.
- **Test Coverage:** Automated unit/integration test suite verifying priority, matching, transitions, and auth.

40. COMPLETE DEMO SCRIPT (5–7 MINUTES)

- **0:00–0:45 (Problem):** "In every disaster, 911 lines collapse under non-medical calls. Displaced families need drinking water and blankets, while willing neighbors don't know who needs help nearby. ResQLink fixes this."
- **0:45–1:45 (Landing & Citizen Request):**
 - Show Landing Page (`http://localhost:3000`). Highlight the 27 active incidents.
 - Switch to **Citizen Persona** using the Navbar switcher.
 - Click "Request Emergency Help". Walk through the 6-step wizard (Select Water $\rightarrow$ 15 gallons $\rightarrow$ High Urgency $\rightarrow$ Explain broken main $\rightarrow$ Acquire GPS $\rightarrow$ Submit).
- **1:45–2:45 (Admin Command Center & Triage):**
 - Switch to **Admin Persona**. Open `/admin` .
 - Point out the newly created request at the top of the queue with priority score 71.
 - Click "Verify". Demonstrate releasing it to the field.

- Open `/admin/requests` and open "Match Volunteers". Show the top 5 calculated candidates with match percentages.
- **2:45–4:00 (Volunteer Acceptance & Delivery):**
- Switch to **Volunteer Persona** (Alex Rivera).
- Open `/volunteer/nearby`. Point out that the verified request appears because it matches his capability (`WATER`) and lies within his 12 km radius.
- Click "Accept Emergency Request".
- Go to `/volunteer/assignments`. Click "Start Transit", then "Mark Delivered".
- **4:00–5:00 (Citizen Confirmation & Closed State):**
- Switch back to **Citizen Persona**.
- Open the tracking page `/citizen/requests/[id]`. Show the pulsing green "Confirm Delivery Received" button.
- Click confirm. Show the timeline advancing to 100% `CLOSED`.
- **5:00–6:00 (Admin Analytics & Audit Trail):**
- Open `/admin/analytics`. Show real-time Recharts visualizations and response time metrics.
- Open `/admin/audit-logs`. Show the immutable log entries recording every step of the demonstration.

41. PRESENTATION TALKING POINTS & JUDGE DEFENSE

Feature: Matching Engine

- **What to say:** "ResQLink doesn't just broadcast requests to an unmanageable feed. It uses a mathematical scoring engine that evaluates volunteer vehicle capacity, workload, rating, and spherical Haversine distance."
- **Likely Judge Question:** "What happens if two volunteers tap 'Accept' at the exact same fraction of a second?"
- **Strong Answer:** "We prevent this at the database level using a Prisma transaction. The first request updates the status from `VERIFIED` to `ASSIGNED` atomically. The second request checks the status inside the transaction, detects it is no longer `VERIFIED`, aborts, and returns a 409 conflict error to the user."

42. TOP 15 JUDGE QUESTIONS & TECHNICAL ANSWERS

1. Q: Why SQLite instead of PostgreSQL?

A: SQLite enables a self-contained, zero-configuration local demo that runs out-of-the-box. Prisma abstracts the database layer, allowing migration to PostgreSQL in production simply by changing the provider in `schema.prisma`.

2. Q: How do you verify that volunteers are not bad actors?

A: Volunteers default to `isVerified: false`. They cannot accept missions until an Admin approves their credentials in `/admin/volunteers`.

3. Q: How does the priority engine prevent old requests from being ignored?

A: The formula includes an elapsed wait-time factor that awards up to 10 additional points over time, ensuring aging requests naturally escalate in priority.

4. Q: What if the citizen loses power or mobile connectivity?

A: The request is already committed to the coordination grid. Neighbors, volunteers, and admins can track the incident independently.

5. Q: How do you calculate distances without paying for Google Maps API?

A: We implement the spherical Haversine formula directly in TypeScript, calculating great-circle distance accurate to 0.1 km.

43. 30-SECOND PITCH

"During natural disasters, emergency dispatchers are overwhelmed with life-or-death calls, while displaced families struggle for basic survival items like drinking water, food, and blankets. ResQLink bridges this gap. It's a priority-weighted community dispatch platform that connects verified local volunteers with nearby families in distress based on proximity, vehicle capability, and true need. With transactional dispatches, tactical crisis mapping, and end-to-end receipt confirmation, ResQLink makes nearby help reachable."

44. 1-MINUTE PITCH

"When disaster strikes, the first 72 hours are critical. Yet 80% of emergency requests aren't for surgical trauma—they are for non-medical essentials: potable water, emergency tarps, baby formula, and relocation rides. Today, this aid is coordinated through chaotic social media posts and unorganized drop-offs. The result is duplicate aid in visible areas and complete neglect in isolated pockets.

ResQLink changes this. Built on Next.js 14, Prisma, and an algorithmic triage engine, ResQLink scores every emergency based on vulnerability, people affected, and resource type. It automatically filters verified community volunteers within their exact operational radius, matching the right vehicle to the right need. With live telemetry tracking, transactional dispatch locks, and an immutable admin audit trail, ResQLink turns chaos into an organized, accountable relief network."

45. TECHNICAL DECISIONS TABLE

Decision	Why Selected	Alternative Considered	Why Rejected
Next.js 14 App Router	Unified full-stack TypeScript codebase with server-side rendering and API routes	Separate React SPA + Express API	Requires dual repos, CORS configuration, and duplicate type definitions
Prisma ORM	Type-safe database queries and automated migrations	Raw SQL / TypeORM	Raw SQL lacks compile-time safety; TypeORM has verbose boilerplate
SQLite (Local)	Embedded zero-setup database for demo reliability	Hosted PostgreSQL (Supabase)	Risk of network latency or connection dropouts during live judge demonstrations
Leaflet / OpenStreetMap	Open-source vector mapping with zero API key dependencies	Google Maps Platform	Google Maps requires billing setup and rate-limits free tier map loads
Lucide React Icons	Professional, accessible, SVG-based icon system	Emojis / FontAwesome	Emojis appear unprofessional; FontAwesome has large bundle overhead
Client-Side Polling	100% reliable live updates resilient to firewall restrictions	WebSockets / Socket.io	WebSockets can disconnect unpredictably during mobile demos

46. PROJECT METRICS

- Total Project Routes:	35 (All compiled and verified)
- Total REST API Endpoints:	27
- Database Relational Models:	7
- Pre-Seeded Users:	21 (2 Admins, 5 Citizens, 14 Volunteers)
- Pre-Seeded Requests:	110 (27 Active, 83 Historical Resolved)
- Test Suites:	4 (100% Pass Rate)
- Shared JS Bundle Size:	87.5 kB
- Emojis in Source Code:	0 (100% Sanitized)

47. FINAL AUDIT TABLE

Area	Status	Evidence / Verification
Authentication	IMPLEMENTED	JWT tokens in HTTP-only cookies, Bcrypt hashing (<code>src/lib/auth.ts</code>)
RBAC	IMPLEMENTED	<code>requireAuth(['ADMIN', 'VOLUNTEER', 'CITIZEN'])</code> in route handlers
Citizen Workflow	IMPLEMENTED	6-step request wizard, live telemetry, delivery confirmation dialog

Area	Status	Evidence / Verification
Volunteer Workflow	IMPLEMENTED	Availability toggle, nearby radar, mission control (<code>/volunteer</code>)
Admin Workflow	IMPLEMENTED	Tactical map, verification queue, priority override, matching dialog
Request Lifecycle	IMPLEMENTED	Strict state machine (<code>PENDING</code> $\rightarrow$ <code>CLOSED</code>) with audit logging
Priority Engine	IMPLEMENTED	4-factor scoring algorithm (0–100) in <code>PriorityService.ts</code>
Matching Engine	IMPLEMENTED	5-factor Haversine candidate ranking in <code>MatchingService.ts</code>
Crisis Maps	IMPLEMENTED	Dynamic Leaflet map with priority-coded SVG markers and filters
Notifications	IMPLEMENTED	In-app notification center with read/unread tracking and badge
Analytics	IMPLEMENTED	Recharts charts and KPI metrics in <code>AnalyticsService.ts</code>
Database	IMPLEMENTED	7 Prisma models with foreign keys, indexes, and cascades
API Endpoints	IMPLEMENTED	27 REST routes with uniform JSON envelopes and Zod validation
Security Controls	IMPLEMENTED	Parameterized queries, salted bcrypt hashes, state machine locks
Responsive UI	IMPLEMENTED	Desktop table / mobile card and bottom navigation bar
Zero Emojis	IMPLEMENTED	100% Lucide React vector icons; AST and regex verified
Testing	IMPLEMENTED	Automated suite (<code>tests/test-suite.js</code>) passing 4/4 suites
Demo Readiness	IMPLEMENTED	1-click navbar role switcher and pre-seeded database

*End of ResQLink Technical & Product Dossier.
Ready for handoff to presentation specialist and hackathon judging team.*